

# Computational Imaging: Reconciling Models and Learning

Ulugbek S. Kamilov  
Computational Imaging Group (CIG)




ICCW LCI (Seoul, Republic of Korea) — 2 Nov 2019

@ukmlv • [cigroup.wustl.edu](http://cigroup.wustl.edu) • [kamilov@wustl.edu](mailto:kamilov@wustl.edu)

# Computational imaging is going through a paradigm shift driven by machine learning

# Computational imaging is going through a paradigm shift driven by machine learning

**Past:** Focus on hardware for image formation




# Computational imaging is going through a paradigm shift driven by machine learning

Past: Focus on hardware for image formation



Present: Use digital signal processing for improved performance




# Computational imaging is going through a paradigm shift driven by machine learning


Past: Focus on hardware for image formation



Present: Use digital signal processing for improved performance



Near future: Machine learning for retrieving **hidden** information



# Today we will talk about


- **Imaging as an inverse problem**  
From forward models to regularized inversion
- **Combining models and learning for imaging**  
From PnP to RED using denoising neural nets
- **Scaling image formation to large problems**  
Variants: PnP-SGD, On-RED, and BC-RED

# Today we will talk about

- **Imaging as an inverse problem**
  - From forward models to regularized inversion
- Combining models and learning for imaging
  - From PnP to RED using denoising neural nets
- Scaling image formation to large problems
  - Variants: PnP-SGD, On-RED, and BC-RED


**The vast majority of imaging problems  
can be formulated as inverse problems**

# The vast majority of imaging problems can be formulated as inverse problems




# The vast majority of imaging problems can be formulated as inverse problems

Forward problem: generate  $y$  from  $x$




# The vast majority of imaging problems can be formulated as inverse problems



# The vast majority of imaging problems can be formulated as inverse problems


Imaging Problem	Rediation	Forward Model	Variations
2D or 3D tomography	coherent x-ray	$y_i = \mathbf{R}_{\theta_i} \mathbf{x}$	parallel, cone beam
3D deconvolution microscopy	fluorescence	$\mathbf{y} = \mathbf{H}\mathbf{x}$	brightfield, confocal, light sheet
structured illumination microscopy (SIM)	fluorescence	$\mathbf{y}_i = \mathbf{H}\mathbf{W}_i \mathbf{x}$	full 3D reconstruction, non-sinusoidal patters
positron emission tomography (PET)	gamma rays	$\mathbf{y}_i = \mathbf{H}_{\theta_i} \mathbf{x}$	list mode with time-of-flight
magnetic resonance imaging (MRI)	radio frequency	$\mathbf{y} = \mathbf{S}\mathbf{F}\mathbf{x}$	uniform or nonuniform sampling in k-space
dynamic MRI	radio frequency	$\mathbf{y}_{t,i} = \mathbf{S}_t \mathbf{F} \mathbf{W}_i \mathbf{x}$	gated or nongated, retrospective registration
optical diffraction tomography (ODT)	coherent light	$\mathbf{y}_i = \mathbf{W}_i \mathbf{F}\mathbf{x}$	with holography or gating interferometry

# The vast majority of imaging problems can be formulated as inverse problems



What makes imaging inverse problems challenging?

# The vast majority of imaging problems can be formulated as inverse problems



## What makes imaging inverse problems challenging?

- solution is not unique
- data is noisy (measurement & model noise)
- problem is intractable
- data is very high-dimensional

**Image denoising is a fundamental inverse problem  
that highlights the importance of regularization**

# Image denoising is a fundamental inverse problem that highlights the importance of regularization

Additive white Gaussian noise (AWGN) model

$$z = x + e$$

noisy observation =  
unknown desired + unknown undesired

# Image denoising is a fundamental inverse problem that highlights the importance of regularization

Additive white Gaussian noise (AWGN) model

$$z = x + e$$

Problem: There are  $\infty$  many possible solutions!



# Image denoising is a fundamental inverse problem that highlights the importance of regularization

Additive white Gaussian noise (AWGN) model

$$z = x + e$$

Image denoiser is a function for separating signal from noise

$D_\sigma$  : more noisy image  $\mapsto$  less noisy image



Source: [Pascal Getreuer](#)

# Image denoising is a fundamental inverse problem that highlights the importance of regularization

Additive white Gaussian noise (AWGN) model


$$z = x + e$$

Image denoiser is a function for separating signal from noise

$D_\sigma$  : more noisy image  $\mapsto$  less noisy image

Proximal operator formulates denoising as optimization

$$\text{prox}_{\tau h}(z) := \arg \min_x \left\{ \frac{1}{2} \|x - z\|_2^2 + \tau h(x) \right\}$$



$\tau = 0$

$\tau = 0.1$

$\tau = 0.2$

# Image denoising is a fundamental inverse problem that highlights the importance of regularization

Additive white Gaussian noise (AWGN) model

$$z = x + e$$

Image denoiser is a function for separating signal from noise

$D_\sigma$  : more noisy image  $\mapsto$  less noisy image

Proximal operator formulates denoising as optimization

$$\text{prox}_{\tau h}(z) := \arg \min_x \left\{ \frac{1}{2} \|x - z\|_2^2 + \tau h(x) \right\}$$

It turns out proximal operators can be used to compute a solution to many imaging inverse problems!

**Regularized inversion provides a unified approach  
for integrating physics and prior knowledge**

# Regularized inversion provides a unified approach for integrating physics and prior knowledge

Image recovery is often an **ill-posed inverse problem**

$$\mathbf{y} = \mathbf{H}(\mathbf{x}) + \mathbf{e}$$

**noise, but also information loss, model uncertainties, etc.**

# Regularized inversion provides a unified approach for integrating physics and prior knowledge

Image recovery is often an ill-posed inverse problem

$$\mathbf{y} = \mathbf{H}(\mathbf{x}) + \mathbf{e}$$

Formulation as a regularized optimization problem

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \{f(\mathbf{x})\}$$

$$f(\mathbf{x}) := g(\mathbf{x}) + h(\mathbf{x})$$

data-fidelity term + regularizer

# Regularized inversion provides a unified approach for integrating physics and prior knowledge

Image recovery is often an ill-posed inverse problem

$$\mathbf{y} = \mathbf{H}(\mathbf{x}) + \mathbf{e}$$

Formulation as a regularized optimization problem

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \{f(\mathbf{x})\} \quad f(\mathbf{x}) := g(\mathbf{x}) + h(\mathbf{x})$$

Example: Linear inverse problems (20th century theory)

$$\begin{aligned}\hat{\mathbf{x}} &= \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{Hx}\|_2^2 + \frac{\lambda}{2} \|\mathbf{Dx}\|_2^2 \right\} \\ &= (\mathbf{H}^\mathsf{H} \mathbf{H} + \lambda \mathbf{D}^\mathsf{H} \mathbf{D})^{-1} \mathbf{H}^\mathsf{H} \mathbf{y} = \mathbf{R}_\lambda \cdot \mathbf{y}\end{aligned}$$

# Regularized inversion provides a unified approach for integrating physics and prior knowledge

Image recovery is often an ill-posed inverse problem

$$\mathbf{y} = \mathbf{H}(\mathbf{x}) + \mathbf{e}$$

Formulation as a regularized optimization problem

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \{f(\mathbf{x})\} \quad f(\mathbf{x}) := g(\mathbf{x}) + h(\mathbf{x})$$

Example: Linear inverse problems (20th century theory)

$$\begin{aligned}\hat{\mathbf{x}} &= \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{Hx}\|_2^2 + \frac{\lambda}{2} \|\mathbf{Dx}\|_2^2 \right\} \\ &= (\mathbf{H}^\mathsf{H} \mathbf{H} + \lambda \mathbf{D}^\mathsf{H} \mathbf{D})^{-1} \mathbf{H}^\mathsf{H} \mathbf{y} = \boxed{\mathbf{R}_\lambda \cdot \mathbf{y}}\end{aligned}$$

Interpretation:  
“Filtered” backprojection

# Regularized inversion provides a unified approach for integrating physics and prior knowledge

Image recovery is often an ill-posed inverse problem

$$\mathbf{y} = \mathbf{H}(\mathbf{x}) + \mathbf{e}$$

Formulation as a regularized optimization problem

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \{f(\mathbf{x})\} \quad f(\mathbf{x}) := g(\mathbf{x}) + h(\mathbf{x})$$

Example: Linear inverse problems (20th century theory)

$$\begin{aligned}\hat{\mathbf{x}} &= \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{Hx}\|_2^2 + \frac{\lambda}{2} \|\mathbf{Dx}\|_2^2 \right\} \\ &= (\mathbf{H}^\mathsf{H} \mathbf{H} + \lambda \mathbf{D}^\mathsf{H} \mathbf{D})^{-1} \mathbf{H}^\mathsf{H} \mathbf{y} = \mathbf{R}_\lambda \cdot \mathbf{y}\end{aligned}$$

Interpretation:  
“Filtered” backprojection

Assumption:  
Gaussians everywhere

# Regularized inversion provides a unified approach for integrating physics and prior knowledge

Image recovery is often an ill-posed inverse problem

$$\mathbf{y} = \mathbf{H}(\mathbf{x}) + \mathbf{e}$$

Formulation as a regularized optimization problem

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \{f(\mathbf{x})\} \quad f(\mathbf{x}) := g(\mathbf{x}) + h(\mathbf{x})$$

Example: Maximum a posteriori probability (MAP) estimator

$$g(\mathbf{x}) = -\log(p_{\mathbf{y}|\mathbf{x}}(\mathbf{y}|\mathbf{x}))$$

likelihood term

$$h(\mathbf{x}) = -\log(p_{\mathbf{x}}(\mathbf{x}))$$

prior term

# Regularized inversion provides a unified approach for integrating physics and prior knowledge

Image recovery is often an ill-posed inverse problem

$$\mathbf{y} = \mathbf{H}(\mathbf{x}) + \mathbf{e}$$

Formulation as a regularized optimization problem

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \{f(\mathbf{x})\} \quad f(\mathbf{x}) := g(\mathbf{x}) + h(\mathbf{x})$$

Example: AWGN and sparsity-promiting prior

$$g(\mathbf{x}) = \frac{1}{2} \|\mathbf{y} - \mathbf{H}(\mathbf{x})\|_2^2$$

smooth data-fidelity  
(least-squares)

$$h(\mathbf{x}) = \lambda \|\mathbf{D}\mathbf{x}\|_1$$

nonsmooth regularizer  
(gradient sparsity)

**FISTA and ADMM are two popular algorithms for large-scale and nonsmooth optimization**

# FISTA and ADMM are two popular algorithms for large-scale and nonsmooth optimization

Optimization problem

$$f(\mathbf{x}) = g(\mathbf{x}) + h(\mathbf{x})$$

# FISTA and ADMM are two popular algorithms for large-scale and nonsmooth optimization

Fast iterative shrinkage/thresholding algorithm (FISTA) vs.  
alternating direction method of multipliers (ADMM)

$$\mathbf{z}^k \leftarrow \mathbf{s}^{k-1} - \gamma \nabla g(\mathbf{s}^{k-1})$$

$$\mathbf{x}^k \leftarrow \text{prox}_{\gamma h}(\mathbf{z}^k)$$

$$\mathbf{s}^k \leftarrow \mathbf{x}^k + ((q_{k-1} - 1)/q_k)(\mathbf{x}^k - \mathbf{x}^{k-1})$$

FISTA: grad data + prox prior

$$\mathbf{z}^k \leftarrow \text{prox}_{\gamma g}(\mathbf{x}^{k-1} - \mathbf{s}^{k-1})$$

$$\mathbf{x}^k \leftarrow \text{prox}_{\gamma h}(\mathbf{z}^k + \mathbf{s}^{k-1})$$

$$\mathbf{s}^k \leftarrow \mathbf{s}^{k-1} + (\mathbf{z}^k - \mathbf{x}^k)$$

ADMM: prox data + prox prior

$$f(\mathbf{x}) = g(\mathbf{x}) + h(\mathbf{x})$$

# FISTA and ADMM are two popular algorithms for large-scale and nonsmooth optimization

Fast iterative shrinkage/thresholding algorithm (FISTA) vs.  
alternating direction method of multipliers (ADMM)

$z^k \leftarrow s^{k-1} - \gamma \nabla g(s^{k-1})$	increase data-consistency	$z^k \leftarrow \text{prox}_{\gamma g}(x^{k-1} - s^{k-1})$
$x^k \leftarrow \text{prox}_{\gamma h}(z^k)$	reduce noise	$x^k \leftarrow \text{prox}_{\gamma h}(z^k + s^{k-1})$
$s^k \leftarrow x^k + ((q_{k-1} - 1)/q_k)(x^k - x^{k-1})$		$s^k \leftarrow s^{k-1} + (z^k - x^k)$

Both FISTA and ADMM alternate between increasing data consistency and reducing noise

- $I - \gamma \nabla g$  : less data consistent  $\mapsto$  more data consistent
- $\text{prox}_{\gamma g}$  : less data consistent  $\mapsto$  more data consistent
- $\text{prox}_{\gamma h}$  : more noisy image  $\mapsto$  less noisy image

$$f(\mathbf{x}) = g(\mathbf{x}) + h(\mathbf{x})$$

# Today we will talk about

- Imaging as an inverse problem
  - From forward models to regularized inversion
- **Combining models and learning for imaging**
  - From PnP to RED using denoising neural nets
- Scaling image formation to large problems
  - Variants: PnP-SGD, On-RED, and BC-RED

**Is there a better way to represent images  
than using fixed sparsity-promoting transforms?**

# Is there a better way to represent images than using fixed sparsity-promoting transforms?

The interest in sparsity-driven imaging highlighted the importance of **structural priors for image formation**

# Is there a better way to represent images than using fixed sparsity-promoting transforms?

The interest in sparsity-driven imaging highlighted the importance of structural priors for image formation

Do we know a more flexible, sophisticated, and data-adaptive tool for characterizing imaging priors?

# Is there a better way to represent images than using fixed sparsity-promoting transforms?

The interest in sparsity-driven imaging highlighted the importance of structural priors for image formation

Do we know a more flexible, sophisticated, and data-adaptive tool for characterizing imaging priors?


Yes, deep neural nets provide a state-of-the-art tool for representing and enforcing sophisticated structural information

# Is there a better way to represent images than using fixed sparsity-promoting transforms?

The interest in sparsity-driven imaging highlighted the importance of structural priors for image formation

Do we know a more flexible, sophisticated, and data-adaptive tool for characterizing imaging priors?

Yes, deep neural nets provide a state-of-the-art tool for representing and enforcing sophisticated structural information



# Is there a better way to represent images than using fixed sparsity-promoting transforms?

The interest in sparsity-driven imaging highlighted the importance of structural priors for image formation

Do we know a more flexible, sophisticated, and data-adaptive tool for characterizing imaging priors?


Yes, deep neural nets provide a state-of-the-art tool for representing and enforcing sophisticated structural information

How to use deep neural nets as priors for imaging?


**Basic idea:** Train a mapping from  
the measured data to the desired image

# Basic idea: Train a mapping from the measured data to the desired image

Example: Simulate light propagation and train a neural net to invert




Deep neural net architecture (= U-Net)



# Basic idea: Train a mapping from the measured data to the desired image


Example: Simulate light propagation and train a neural net to invert



Question: What are some of the key limitations of this approach?

# Basic idea: Train a mapping from the measured data to the desired image

Example: Simulate light propagation and train a neural net to invert




Question: What are some of the key limitations of this approach?

- 1) The neural net learns both the forward model and the prior

*Hard to decouple the individual contributions of D and R*

# Basic idea: Train a mapping from the measured data to the desired image

Example: Simulate light propagation and train a neural net to invert



Question: What are some of the key limitations of this approach?


1) The neural net learns both the forward model and the prior

2) Consistency to the measured data is not ensured

No explicit measure of deviation from the data

# Basic idea: Train a mapping from the measured data to the desired image

Example: Simulate light propagation and train a neural net to invert




Question: What are some of the key limitations of this approach?

- 1) The neural net learns both the forward model and the prior
- 2) Consistency to the measured data is not ensured
- 3) Finding an efficient end-to-end mapping might be difficult

Fully connected layers are not suitable for large-scale problems

# Basic idea: Train a mapping from the measured data to the desired image

Example: Simulate light propagation and train a neural net to invert



Question: What are some of the key limitations of this approach?

- 1) The neural net learns both the forward model and the prior
- 2) Consistency to the measured data is not ensured
- 3) Finding an efficient end-to-end mapping might be difficult

**Plug-and-play priors (PnP) approach separates the forward model from the learned prior**


# Plug-and-play priors (PnP) approach separates the forward model from the learned prior



Venkatakrishnan  
(ORNL)




Bouman  
(Purdue)



Wohlberg  
(LANL)


# Plug-and-play priors (PnP) approach separates the forward model from the learned prior

Build an image denoiser for AWGN (no info on forward model)



# Plug-and-play priors (PnP) approach separates the forward model from the learned prior

Build an image denoiser for AWGN (no info on forward model)




We define the following “plug-and-play” operators

- $D_\sigma$  : more noisy image  $\mapsto$  less noisy image
- $I - \gamma \nabla g$  : less data consistent  $\mapsto$  more data consistent
- $\text{prox}_{\gamma g}$  : less data consistent  $\mapsto$  more data consistent

# Plug-and-play priors (PnP) approach separates the forward model from the learned prior


Build an image denoiser for AWGN (no info on forward model)



Combine operators into **Plug-and-Play Priors (PnP)** algorithms

# Plug-and-play priors (PnP) approach separates the forward model from the learned prior

Build an image denoiser for AWGN (no info on forward model)




Combine operators into Plug-and-Play Priors (PnP) algorithms

$$\begin{aligned} z^k &\leftarrow \text{prox}_{\gamma g}(x^{k-1} - s^{k-1}) \\ x^k &\leftarrow D_\sigma(z^k + s^{k-1}) \\ s^k &\leftarrow s^{k-1} + (z^k - x^k) \end{aligned}$$

PnP-ADMM

# Plug-and-play priors (PnP) approach separates the forward model from the learned prior

Build an image denoiser for AWGN (no info on forward model)



Combine operators into Plug-and-Play Priors (PnP) algorithms


$$\begin{aligned} z^k &\leftarrow \text{prox}_{\gamma g}(x^{k-1} - s^{k-1}) \\ x^k &\leftarrow D_\sigma(z^k + s^{k-1}) \\ s^k &\leftarrow s^{k-1} + (z^k - x^k) \end{aligned}$$

**PnP-FISTA**

$$\boxed{\begin{aligned} z^k &\leftarrow s^{k-1} - \gamma \nabla g(s^{k-1}) \\ x^k &\leftarrow D_\sigma(z^k) \\ s^k &\leftarrow x^k + ((q_{k-1} - 1)/q_k)(x^k - x^{k-1}) \end{aligned}}$$

# Plug-and-play priors (PnP) approach separates the forward model from the learned prior

Build an image denoiser for AWGN (no info on forward model)



Combine operators into Plug-and-Play Priors (PnP) algorithms

$$\begin{aligned} z^k &\leftarrow \text{prox}_{\gamma g}(x^{k-1} - s^{k-1}) \\ x^k &\leftarrow D_\sigma(z^k + s^{k-1}) \\ s^k &\leftarrow s^{k-1} + (z^k - x^k) \end{aligned}$$


PnP-ADMM

$$\begin{aligned} z^k &\leftarrow s^{k-1} - \gamma \nabla g(s^{k-1}) \\ x^k &\leftarrow D_\sigma(z^k) \\ s^k &\leftarrow x^k + ((q_{k-1} - 1)/q_k)(x^k - x^{k-1}) \end{aligned}$$

PnP-FISTA

# Plug-and-play priors (PnP) approach separates the forward model from the learned prior

Build an image denoiser for AWGN (no info on forward model)



Combine operators into Plug-and-Play Priors (PnP) algorithms

$$z^k \leftarrow \text{prox}_{\gamma g}(x^{k-1} - s^{k-1})$$

$$x^k \leftarrow D_\sigma(z^k + s^{k-1})$$

$$s^k \leftarrow s^{k-1} + (z^k - x^k)$$


$$z^k \leftarrow s^{k-1} - \gamma \nabla g(s^{k-1}) \quad \text{forward model}$$

$$x^k \leftarrow D_\sigma(z^k) \quad \text{denoiser as a prior}$$

$$s^k \leftarrow x^k + ((q_{k-1} - 1)/q_k)(x^k - x^{k-1})$$

# Plug-and-play priors (PnP) approach separates the forward model from the learned prior

Build an image denoiser for AWGN (no info on forward model)



Combine operators into Plug-and-Play Priors (PnP) algorithms

$$z^k \leftarrow \text{prox}_{\gamma g}(x^{k-1} - s^{k-1})$$

$$x^k \leftarrow D_\sigma(z^k + s^{k-1})$$

$$s^k \leftarrow s^{k-1} + (z^k - x^k)$$

$$z^k \leftarrow s^{k-1} - \gamma \nabla g(s^{k-1}) \quad \text{forward model}$$

$$x^k \leftarrow D_\sigma(z^k) \quad \text{denoiser as a prior}$$

$$s^k \leftarrow x^k + ((q_{k-1} - 1)/q_k)(x^k - x^{k-1})$$

PnP algorithms allow for an explicit separation between the forward model and the image prior

**PnP might look heuristic, but it has a rigorous foundation in monotone operator theory**

# PnP might look heuristic, but it has a rigorous foundation in monotone operator theory

Consider the following set of fixed points

$$\text{fix}(P) := \{x : x = P(x)\}$$

$$P(x) := D_\sigma(x - \gamma \nabla g(x))$$

# PnP might look heuristic, but it has a rigorous foundation in monotone operator theory


Consider the following set of fixed points

$$\text{fix}(\mathcal{P}) := \{x : x = \mathcal{P}(x)\}$$

$$\mathcal{P}(x) := D_\sigma(x - \gamma \nabla g(x))$$

that satisfy the **consensus equilibrium (CE) equations**

$$\begin{aligned} x^* &= \text{prox}_{\gamma g}(x^* - u) \\ x^* &= D_\sigma(x^* + u) \end{aligned}$$



# PnP might look heuristic, but it has a rigorous foundation in monotone operator theory


Consider the following set of fixed points

$$\text{fix}(P) := \{x : x = P(x)\}$$


$$P(x) := D_\sigma(x - \gamma \nabla g(x))$$

that satisfy the consensus equilibrium (CE) equations

$$\begin{aligned} x^* &= \text{prox}_{\gamma g}(x^* - u) \\ x^* &= D_\sigma(x^* + u) \end{aligned}$$



For the analysis, we go beyond proximals to the class of averaged denoisers that can be trained using spectral normalization



# PnP might look heuristic, but it has a rigorous foundation in monotone operator theory

**Proposition 1:** Let  $D_\sigma(\cdot) = \text{prox}_{\gamma h}(\cdot)$  for  $\gamma, \sigma > 0$ . Then,  $x^* \in \text{fix}(P)$  if and only if it minimizes  $f = g + h$ .

1 - PnP is fully backward compatible with proximal algorithms

# PnP might look heuristic, but it has a rigorous foundation in monotone operator theory

**Proposition 1:** Let  $D_\sigma(\cdot) = \text{prox}_{\gamma h}(\cdot)$  for  $\gamma, \sigma > 0$ . Then,  $\mathbf{x}^* \in \text{fix}(\mathsf{P})$  if and only if it minimizes  $f = g + h$ .

**Proposition 2:** Run PnP-ISTA for  $t \geq 1$  iterations under a convex data-fidelity term and a  $\theta$ -averaged denoiser with the step  $\gamma \in (0, 1/L]$ . Then, for  $\mathbf{x}^* \in \text{fix}(\mathsf{P})$

$$\frac{1}{t} \sum_{k=1}^t \|\mathbf{x}^{k-1} - \mathsf{P}(\mathbf{x}^{k-1})\|_2^2 \leq \frac{1}{t} \left( \frac{1+\theta}{1-\theta} \right) \|\mathbf{x}^0 - \mathbf{x}^*\|_2^2.$$

2 - It converges beyond proximal operator denoisers as  $O(1/t)$

# PnP might look heuristic, but it has a rigorous foundation in monotone operator theory

**Proposition 1:** Let  $D_\sigma(\cdot) = \text{prox}_{\gamma h}(\cdot)$  for  $\gamma, \sigma > 0$ . Then,  $\mathbf{x}^* \in \text{fix}(\mathsf{P})$  if and only if it minimizes  $f = g + h$ .

**Proposition 2:** Run PnP-ISTA for  $t \geq 1$  iterations under a convex data-fidelity term and a  $\theta$ -averaged denoiser with the step  $\gamma \in (0, 1/L]$ . Then, for  $\mathbf{x}^* \in \text{fix}(\mathsf{P})$

$$\frac{1}{t} \sum_{k=1}^t \|\mathbf{x}^{k-1} - \mathsf{P}(\mathbf{x}^{k-1})\|_2^2 \leq \frac{1}{t} \left( \frac{1+\theta}{1-\theta} \right) \|\mathbf{x}^0 - \mathbf{x}^*\|_2^2.$$

**Proposition 3:** Under assumptions above, the set of fixed-points of PnP-ADMM coincides with  $\text{fix}(\mathsf{P})$ .

3 - PnP-FISTA and PnP-ADMM have the same fixed points

# PnP might look heuristic, but it has a rigorous foundation in monotone operator theory

**Proposition 1:** Let  $D_\sigma(\cdot) = \text{prox}_{\gamma h}(\cdot)$  for  $\gamma, \sigma > 0$ . Then,  $\mathbf{x}^* \in \text{fix}(\mathsf{P})$  if and only if it minimizes  $f = g + h$ .

**Proposition 2:** Run PnP-ISTA for  $t \geq 1$  iterations under a convex data-fidelity term and a  $\theta$ -averaged denoiser with the step  $\gamma \in (0, 1/L]$ . Then, for  $\mathbf{x}^* \in \text{fix}(\mathsf{P})$

$$\frac{1}{t} \sum_{k=1}^t \|\mathbf{x}^{k-1} - \mathsf{P}(\mathbf{x}^{k-1})\|_2^2 \leq \frac{1}{t} \left( \frac{1+\theta}{1-\theta} \right) \|\mathbf{x}^0 - \mathbf{x}^*\|_2^2.$$

**Proposition 3:** Under assumptions above, the set of fixed-points of PnP-ADMM coincides with  $\text{fix}(\mathsf{P})$ .

**RED is an alternative to PnP that seeks to have an explicit regularizer for a given denoiser**

# RED is an alternative to PnP that seeks to have an explicit regularizer for a given denoiser



Romano  
(Stanford)



Elad  
(Technion)



Milanfar  
(Google)

# RED is an alternative to PnP that seeks to have an explicit regularizer for a given denoiser

Consider the following GM-RED algorithm

$$\mathbf{x}^t \leftarrow \mathbf{x}^{t-1} - \gamma \mathbf{G}(\mathbf{x}^{t-1})$$

“gradient” descent

$$\mathbf{G}(\mathbf{x}) := \nabla g(\mathbf{x}) + \tau(\mathbf{x} - \mathbf{D}_\sigma(\mathbf{x}))$$

data

prior

# RED is an alternative to PnP that seeks to have an explicit regularizer for a given denoiser

Consider the following GM-RED algorithm

$$\mathbf{x}^t \leftarrow \mathbf{x}^{t-1} - \gamma \mathbf{G}(\mathbf{x}^{t-1}) \quad \mathbf{G}(\mathbf{x}) := \nabla g(\mathbf{x}) + \tau(\mathbf{x} - \mathbf{D}_\sigma(\mathbf{x}))$$

For a locally homogeneous denoiser that has a symmetric Jacobian, GM-RED\* solves the following problem

$\min_{\mathbf{x}} \{g(\mathbf{x}) + h_{\text{red}}(\mathbf{x})\}$	$h_{\text{red}}(\mathbf{x}) := \frac{\tau}{2} \mathbf{x}^\top (\mathbf{x} - \mathbf{D}_\sigma(\mathbf{x}))$
data	prior

# RED is an alternative to PnP that seeks to have an explicit regularizer for a given denoiser

Consider the following GM-RED algorithm

$$\mathbf{x}^t \leftarrow \mathbf{x}^{t-1} - \gamma \mathbf{G}(\mathbf{x}^{t-1}) \quad \mathbf{G}(\mathbf{x}) := \nabla g(\mathbf{x}) + \tau(\mathbf{x} - \mathbf{D}_\sigma(\mathbf{x}))$$

For a locally homogeneous denoiser that has a symmetric Jacobian, GM-RED\* solves the following problem

$$\min_{\mathbf{x}} \{g(\mathbf{x}) + h_{\text{red}}(\mathbf{x})\} \quad h_{\text{red}}(\mathbf{x}) := \frac{\tau}{2} \mathbf{x}^\top (\mathbf{x} - \mathbf{D}_\sigma(\mathbf{x}))$$

This convex-optimization interpretation is powerful, but it also restricts the class of acceptable denoisers

Recall that one of the key conditions we assumed for the denoiser  $f(\mathbf{x})$  is that it is homogeneous of degree 1,

$$(51) \quad f(c\mathbf{x}) = cf(\mathbf{x}).$$

This immediately notifies us that the  $\rho(\mathbf{x})$  we wish to mimic in (50) must be 2-homogeneous

“Appendix A: Can we mimic any denoiser?”

**Monotone operator theory provides an alternative interpretation to RED beyond convex optimization**

# Monotone operator theory provides an alternative interpretation to RED beyond convex optimization

Consider again the GM-RED algorithms

$$\mathbf{x}^t \leftarrow \mathbf{x}^{t-1} - \gamma \mathbf{G}(\mathbf{x}^{t-1})$$

“gradient” descent

$$\mathbf{G}(\mathbf{x}) := \nabla g(\mathbf{x}) + \tau(\mathbf{x} - \mathbf{D}_\sigma(\mathbf{x}))$$

data

prior

# Monotone operator theory provides an alternative interpretation to RED beyond convex optimization

Consider again the GM-RED algorithms

$$\mathbf{x}^t \leftarrow \mathbf{x}^{t-1} - \gamma \mathbf{G}(\mathbf{x}^{t-1}) \quad \mathbf{G}(\mathbf{x}) := \nabla g(\mathbf{x}) + \tau(\mathbf{x} - \mathbf{D}_\sigma(\mathbf{x}))$$

and the set of fixed points of  $\mathbf{G}$

$$\text{zer}(\mathbf{G}) := \{\mathbf{x} : \mathbf{G}(\mathbf{x}) = \mathbf{0}\}$$

a set of all images  
where  $\mathbf{G}$  is zero

# Monotone operator theory provides an alternative interpretation to RED beyond convex optimization

Consider again the GM-RED algorithms

$$\mathbf{x}^t \leftarrow \mathbf{x}^{t-1} - \gamma \mathbf{G}(\mathbf{x}^{t-1}) \quad \mathbf{G}(\mathbf{x}) := \nabla g(\mathbf{x}) + \tau(\mathbf{x} - \mathbf{D}_\sigma(\mathbf{x}))$$

and the set of fixed points of  $\mathbf{G}$

$$\text{zer}(\mathbf{G}) := \{\mathbf{x} : \mathbf{G}(\mathbf{x}) = \mathbf{0}\}$$

Just like PnP, RED leverages deep neural net denoisers without differentiating them, but gives an explicit control over data fidelity

If  $\mathbf{x}^* \in \text{zer}(\nabla g) \cap \text{fix}(\mathbf{D})$ , then  $\mathbf{x}^* \in \text{zer}(\mathbf{G})$

If  $\text{zer}(\nabla g) \cap \text{fix}(\mathbf{D}) = \emptyset$ , then  $\mathbf{x}^* \in \text{zer}(\mathbf{G})$  is a trade-off controlled by  $\tau > 0$

**The theoretical convergence of GM-RED to its fixed points can be fully characterized**

# The theoretical convergence of GM-RED to its fixed points can be fully characterized

**Theorem 1.** Run GM-RED for  $t \geq 1$  iterations under Assumptions 1-3 using a fixed step-size  $0 < \gamma \leq 1/(L + 2\tau)$ . Then, we have

$$\|\mathbf{G}(\mathbf{x}^{t-1})\|_2^2 \leq \frac{(L + 2\tau)}{\gamma t} R_0^2$$

1 - GM-RED converge to  $\text{zer}(G)$  as  $O(1/t)$

# The theoretical convergence of GM-RED to its fixed points can be fully characterized

**Theorem 1.** Run GM-RED for  $t \geq 1$  iterations under Assumptions 1-3 using a fixed step-size  $0 < \gamma \leq 1/(L + 2\tau)$ . Then, we have

$$\|\mathbf{G}(\mathbf{x}^{t-1})\|_2^2 \leq \frac{(L + 2\tau)}{\gamma t} R_0^2$$

**Theorem 2.** Run GM-RED for  $t \geq 1$  iterations with a proximal operator denoiser under Assumptions 1-4 using a fixed step-size  $0 < \gamma \leq 1/(L + 2\tau)$ . Then, we have

$$f(\mathbf{x}^t) - f^* \leq \frac{2}{\gamma t} R_0^2 + \frac{G_0^2}{2\tau},$$

where the function  $f = g + h$  and  $f^*$  is its minimum.

2 - GM-RED is backward compatible with proximal optimization

# The theoretical convergence of GM-RED to its fixed points can be fully characterized

**Theorem 1.** Run GM-RED for  $t \geq 1$  iterations under Assumptions 1-3 using a fixed step-size  $0 < \gamma \leq 1/(L + 2\tau)$ . Then, we have

$$\|\mathbf{G}(\mathbf{x}^{t-1})\|_2^2 \leq \frac{(L + 2\tau)}{\gamma t} R_0^2$$

**Theorem 2.** Run GM-RED for  $t \geq 1$  iterations with a proximal operator denoiser under Assumptions 1-4 using a fixed step-size  $0 < \gamma \leq 1/(L + 2\tau)$ . Then, we have

$$f(\mathbf{x}^t) - f^* \leq \frac{2}{\gamma t} R_0^2 + \frac{G_0^2}{2\tau},$$


where the function  $f = g + h$  and  $f^*$  is its minimum.

# GM-RED with denoising neural net priors can significantly outperform traditional priors

# GM-RED with denoising neural net priors can significantly outperform traditional priors

**Table 1.** Summary of average SNR performance of different methods for multispectral image super-resolution.


Kernel	Scale	3DTV	BM3D	DnCNN*
Gaussian $7 \times 7$	$\times 2$	24.01	24.67	25.20
	$\times 3$	22.74	23.33	23.43
	$\times 4$	20.41	20.94	21.03
Motion blur $19 \times 19$	$\times 2$	23.30	24.49	25.21
	$\times 3$	20.17	20.85	21.01
	$\times 4$	18.86	19.34	19.43



Ground-truth

Zoomed LR image

RED-DnCNN\* (22.25dB)



Ground-truth

Zoomed LR image

RED-DnCNN\* (31.59dB)

# Today we will talk about

- Imaging as an inverse problem
  - From forward models to regularized inversion
- Combining models and learning for imaging
  - From PnP to RED using denoising neural nets
- **Scaling image formation to large problems**
  - Variants: PnP-SGD, On-RED, and BC-RED


# Motivation: optical tomographic microscopy replaces x-rays with the visible light

# Motivation: optical tomographic microscopy replaces x-rays with the visible light




volume of interest


# Motivation: optical tomographic microscopy replaces x-rays with the visible light




# Motivation: optical tomographic microscopy replaces x-rays with the visible light



# Motivation: optical tomographic microscopy replaces x-rays with the visible light




# Motivation: optical tomographic microscopy replaces x-rays with the visible light




coherent  
illumination

$$u_{\text{in}}^1(\mathbf{r}) = e^{j\langle \mathbf{k}_1, \mathbf{r} \rangle}$$


# Motivation: optical tomographic microscopy replaces x-rays with the visible light




# Motivation: optical tomographic microscopy replaces x-rays with the visible light




# Motivation: optical tomographic microscopy replaces x-rays with the visible light



# Motivation: optical tomographic microscopy replaces x-rays with the visible light




# Motivation: optical tomographic microscopy replaces x-rays with the visible light



$$u_{\text{in}}^\ell(\mathbf{r}) = e^{j\langle \mathbf{k}_\ell, \mathbf{r} \rangle}$$


$$\mathbf{y}_\ell$$

# Motivation: optical tomographic microscopy replaces x-rays with the visible light




**For each illumination the forward model is  
the (approximate) solution of the wave equation**

For each illumination the forward model is  
the (approximate) solution of the wave equation



For each illumination the forward model is the (approximate) solution of the wave equation


The Helmholtz equation for modeling object-light interactions



For each illumination the forward model is the (approximate) solution of the wave equation

The Helmholtz equation for modeling object-light interactions

$$(\Delta + k_b^2 I)u_{sc}(\mathbf{r}) = x(\mathbf{r})u(\mathbf{r}) \quad u(\mathbf{r}) = u_{in}(\mathbf{r}) + u_{sc}(\mathbf{r})$$




**For each illumination the forward model is the (approximate) solution of the wave equation**

The Helmholtz equation for modeling object-light interactions

$$(\Delta + k_b^2 I)u_{sc}(\mathbf{r}) = x(\mathbf{r})u(\mathbf{r}) \quad u(\mathbf{r}) = u_{in}(\mathbf{r}) + u_{sc}(\mathbf{r})$$

The Domain-integral formulation with the Green's function



For each illumination the forward model is the (approximate) solution of the wave equation

The Helmholtz equation for modeling object-light interactions


$$(\Delta + k_b^2 I) u_{sc}(\mathbf{r}) = x(\mathbf{r}) u(\mathbf{r}) \quad u(\mathbf{r}) = u_{in}(\mathbf{r}) + u_{sc}(\mathbf{r})$$

The Domain-integral formulation with the Green's function

$$u_{sc}(\mathbf{r}) = \int_{\Omega} g(\mathbf{r} - \mathbf{r}') x(\mathbf{r}') u(\mathbf{r}') d\mathbf{r}$$

nonlinear object-light coupling

$$g(\mathbf{r}) := \frac{e^{jk_b \|\mathbf{r}\|}}{4\pi \|\mathbf{r}\|}$$



For each illumination the forward model is the (approximate) solution of the wave equation


The Helmholtz equation for modeling object-light interactions

$$(\Delta + k_b^2 I) u_{sc}(\mathbf{r}) = x(\mathbf{r}) u(\mathbf{r}) \quad u(\mathbf{r}) = u_{in}(\mathbf{r}) + u_{sc}(\mathbf{r})$$

The Domain-integral formulation with the Green's function

$$u_{sc}(\mathbf{r}) = \int_{\Omega} g(\mathbf{r} - \mathbf{r}') x(\mathbf{r}') \boxed{u(\mathbf{r}') \mathrm{d}\mathbf{r}} \quad g(\mathbf{r}) := \frac{e^{jk_b \|\mathbf{r}\|}}{4\pi \|\mathbf{r}\|}$$

accounts for  
multi scattering



For each illumination the forward model is the (approximate) solution of the wave equation


The Helmholtz equation for modeling object-light interactions

$$(\Delta + k_b^2 I) u_{sc}(\mathbf{r}) = x(\mathbf{r}) u(\mathbf{r}) \quad u(\mathbf{r}) = u_{in}(\mathbf{r}) + u_{sc}(\mathbf{r})$$

The Domain-integral formulation with the Green's function

$$u_{sc}(\mathbf{r}) = \int_{\Omega} g(\mathbf{r} - \mathbf{r}') x(\mathbf{r}') u(\mathbf{r}') d\mathbf{r} \quad g(\mathbf{r}) := \frac{e^{jk_b \|\mathbf{r}\|}}{4\pi \|\mathbf{r}\|}$$

There are many approximations to solve this equation



For each illumination the forward model is the (approximate) solution of the wave equation

The Helmholtz equation for modeling object-light interactions

$$(\Delta + k_b^2 I) u_{sc}(\mathbf{r}) = x(\mathbf{r}) u(\mathbf{r}) \quad u(\mathbf{r}) = u_{in}(\mathbf{r}) + u_{sc}(\mathbf{r})$$


The Domain-integral formulation with the Green's function

$$u_{sc}(\mathbf{r}) = \int_{\Omega} g(\mathbf{r} - \mathbf{r}') x(\mathbf{r}') u(\mathbf{r}') d\mathbf{r} \quad g(\mathbf{r}) := \frac{e^{jk_b \|\mathbf{r}\|}}{4\pi \|\mathbf{r}\|}$$

There are many approximations to solve this equation

$$u_{sc}(\mathbf{r}) \approx H\{x, u_{in}\}(\mathbf{r})$$

(for each illumination)



**For many imaging inverse problems, the traditional batch data processing is suboptimal**

For many imaging inverse problems, the traditional batch data processing is suboptimal

Consider the data-fidelity of the following form

$$g(\mathbf{x}) = \frac{1}{L} \sum_{\ell=1}^L g_\ell(\mathbf{x}) = \frac{1}{2L} \sum_{\ell=1}^L \|\mathbf{y} - \mathbf{H}_\ell(\mathbf{x})\|_2^2$$

Sum of L data-fidelity terms

# For many imaging inverse problems, the traditional batch data processing is suboptimal

Consider the data-fidelity of the following form

$$g(\mathbf{x}) = \frac{1}{L} \sum_{\ell=1}^L g_\ell(\mathbf{x}) = \frac{1}{2L} \sum_{\ell=1}^L \|\mathbf{y} - \mathbf{H}_\ell(\mathbf{x})\|_2^2$$

Consider the complexity of computing  
the **full-batch gradient** and the **mini-batch gradient**

$$\nabla g(\mathbf{x}) = \frac{1}{L} \sum_{\ell=1}^L \nabla g_\ell(\mathbf{x})$$

Uses all the measurements

vs.

$$\hat{\nabla} g(\mathbf{x}) = \frac{1}{B} \sum_{b=1}^B \nabla g_{\ell_b}(\mathbf{x})$$


Uses a subset of measurements

**PnP-SGD enables to scale PnP-FISTA to a large number of tomographic measurements**

# PnP-SGD enables to scale PnP-FISTA to a large number of tomographic measurements

$$\begin{aligned} \mathbf{z}^k &\leftarrow \mathbf{s}^{k-1} - \gamma \nabla g(\mathbf{s}^{k-1}) \\ \mathbf{x}^k &\leftarrow \mathbf{D}_\sigma(\mathbf{z}^k) \\ \mathbf{s}^k &\leftarrow \mathbf{x}^k + ((q_{k-1} - 1)/q_k)(\mathbf{x}^k - \mathbf{x}^{k-1}) \end{aligned} \quad \text{PnP-FISTA}$$

$$\begin{aligned} \mathbf{z}^k &\leftarrow \mathbf{s}^{k-1} - \gamma \hat{\nabla} g(\mathbf{s}^{k-1}) \\ \mathbf{x}^k &\leftarrow \mathbf{D}_\sigma(\mathbf{z}^k) \\ \mathbf{s}^k &\leftarrow \mathbf{x}^k + ((q_{k-1} - 1)/q_k)(\mathbf{x}^k - \mathbf{x}^{k-1}) \end{aligned} \quad \text{PnP-SGD}$$



PnP-SGD uses only  $B \ll L$  measurements per iteration

# PnP-SGD enables to scale PnP-FISTA to a large number of tomographic measurements

$$\mathbf{z}^k \leftarrow \mathbf{s}^{k-1} - \gamma \nabla g(\mathbf{s}^{k-1}) \quad \text{PnP-FISTA}$$

$$\mathbf{x}^k \leftarrow \mathbf{D}_\sigma(\mathbf{z}^k)$$

$$\mathbf{s}^k \leftarrow \mathbf{x}^k + ((q_{k-1} - 1)/q_k)(\mathbf{x}^k - \mathbf{x}^{k-1})$$

$$\mathbf{z}^k \leftarrow \mathbf{s}^{k-1} - \gamma \hat{\nabla} g(\mathbf{s}^{k-1}) \quad \text{PnP-SGD}$$

$$\mathbf{x}^k \leftarrow \mathbf{D}_\sigma(\mathbf{z}^k)$$

$$\mathbf{s}^k \leftarrow \mathbf{x}^k + ((q_{k-1} - 1)/q_k)(\mathbf{x}^k - \mathbf{x}^{k-1})$$

**Theorem 1.** Run PnP-SGD for  $t \geq 1$  iterations under Assumptions 1-3 using a fixed step-size  $0 < \gamma \leq 1/L$  and a fixed minibatch size  $B = t$ . Then, we have

$$\mathbb{E} \left[ \frac{1}{t} \sum_{k=1}^t \|\mathbf{x}^{k-1} - \mathbf{P}(\mathbf{x}^{k-1})\|_2^2 \right] \leq \frac{C}{\sqrt{t}},$$

where  $C > 0$  is a constant.

Fixed point convergence similar to the traditional SGD

# PnP-SGD enables to scale PnP-FISTA to a large number of tomographic measurements

$$\mathbf{z}^k \leftarrow \mathbf{s}^{k-1} - \gamma \nabla g(\mathbf{s}^{k-1})$$

PnP-FISTA

$$\mathbf{x}^k \leftarrow \mathbf{D}_\sigma(\mathbf{z}^k)$$


$$\mathbf{s}^k \leftarrow \mathbf{x}^k + ((q_{k-1} - 1)/q_k)(\mathbf{x}^k - \mathbf{x}^{k-1})$$

$$\mathbf{z}^k \leftarrow \mathbf{s}^{k-1} - \gamma \hat{\nabla} g(\mathbf{s}^{k-1})$$

PnP-SGD

$$\mathbf{x}^k \leftarrow \mathbf{D}_\sigma(\mathbf{z}^k)$$


$$\mathbf{s}^k \leftarrow \mathbf{x}^k + ((q_{k-1} - 1)/q_k)(\mathbf{x}^k - \mathbf{x}^{k-1})$$



PnP-SGD enables fast regularized inversion in  
**optical tomography (OT)**

# PnP-SGD enables to scale PnP-FISTA to a large number of tomographic measurements

Experimental Fourier Ptychographic Microscopy (FPM) data



Using 60 (out of total 293) illuminations per iteration

**On-RED is a stochastic variant of GM-RED  
suitable for large-scale tomographic problems**

# On-RED is a stochastic variant of GM-RED suitable for large-scale tomographic problems

---

**Algorithm 1** GM-RED

```

1: input:  $\mathbf{x}^0 \in \mathbb{R}^n$ ,  $\tau > 0$ , and  $\sigma > 0$ 
2: for  $k = 1, 2, \dots$  do
3:    $\nabla g(\mathbf{x}^{k-1}) \leftarrow \text{fullGradient}(\mathbf{x}^{k-1})$ 
4:    $\mathbf{G}(\mathbf{x}^{k-1}) \leftarrow \nabla g(\mathbf{x}^{k-1}) + \tau(\mathbf{x}^{k-1} - \mathbf{D}_\sigma(\mathbf{x}^{k-1}))$ 
5:    $\mathbf{x}^k \leftarrow \mathbf{x}^{k-1} - \gamma \mathbf{G}(\mathbf{x}^{k-1})$ 
6: end for

```

---

**Algorithm 2** On-RED

```

1: input:  $\mathbf{x}^0 \in \mathbb{R}^n$ ,  $\tau > 0$ ,  $\sigma > 0$ , and  $B \geq 1$ 
2: for  $k = 1, 2, \dots$  do
3:    $\widehat{\nabla} g(\mathbf{x}^{k-1}) \leftarrow \text{minibatchGradient}(\mathbf{x}^{k-1}, B)$ 
4:    $\widehat{\mathbf{G}}(\mathbf{x}^{k-1}) \leftarrow \widehat{\nabla} g(\mathbf{x}^{k-1}) + \tau(\mathbf{x}^{k-1} - \mathbf{D}_\sigma(\mathbf{x}^{k-1}))$ 
5:    $\mathbf{x}^k \leftarrow \mathbf{x}^{k-1} - \gamma \widehat{\mathbf{G}}(\mathbf{x}^{k-1})$ 
6: end for

```

---

On-RED uses only  $B \ll L$  measurements per iteration

**Theorem 1.** Run GM-RED for  $t \geq 1$  iterations under Assumptions 1-3 using a fixed step-size  $0 < \gamma \leq 1/(L + 2\tau)$  and a fixed minibatch size  $B = t$ . Then, we have

$$\mathbb{E} \left[ \frac{1}{t} \sum_{k=1}^t \|\mathbf{G}(\mathbf{x}^{k-1})\|_2^2 \right] \leq \frac{C}{\sqrt{t}},$$

where  $C > 0$  is a constant.

Convergence similar to PnP-SGD

# On-RED is a stochastic variant of GM-RED suitable for large-scale tomographic problems

---

**Algorithm 1** GM-RED

```

1: input:  $x^0 \in \mathbb{R}^n$ ,  $\tau > 0$ , and  $\sigma > 0$ 
2: for  $k = 1, 2, \dots$  do
3:    $\nabla g(\mathbf{x}^{k-1}) \leftarrow \text{fullGradient}(\mathbf{x}^{k-1})$ 
4:    $\mathbf{G}(\mathbf{x}^{k-1}) \leftarrow \nabla g(\mathbf{x}^{k-1}) + \tau(\mathbf{x}^{k-1} - \mathbf{D}_\sigma(\mathbf{x}^{k-1}))$ 
5:    $\mathbf{x}^k \leftarrow \mathbf{x}^{k-1} - \gamma \mathbf{G}(\mathbf{x}^{k-1})$ 
6: end for

```

---

**Algorithm 2** On-RED

```

1: input:  $x^0 \in \mathbb{R}^n$ ,  $\tau > 0$ ,  $\sigma > 0$ , and  $B \geq 1$ 
2: for  $k = 1, 2, \dots$  do
3:    $\widehat{\nabla}g(\mathbf{x}^{k-1}) \leftarrow \text{minibatchGradient}(\mathbf{x}^{k-1}, B)$ 
4:    $\widehat{\mathbf{G}}(\mathbf{x}^{k-1}) \leftarrow \widehat{\nabla}g(\mathbf{x}^{k-1}) + \tau(\mathbf{x}^{k-1} - \mathbf{D}_\sigma(\mathbf{x}^{k-1}))$ 
5:    $\mathbf{x}^k \leftarrow \mathbf{x}^{k-1} - \gamma \widehat{\mathbf{G}}(\mathbf{x}^{k-1})$ 
6: end for

```


---

**Table 3. Optimized SNR for each test image in dB**

Algorithms ( $I = 6$ )	SGM ( $B = 1$ )	GM-RED (fixed 1)		On-RED ( $B = 1$ )		GM-RED (fixed 6)
Denoisers	—	BM3D	DnCNN*	BM3D	DnCNN*	DnCNN*
<i>Barbara</i>	27.37	26.04	26.15	30.95	31.50	32.59
<i>Boat</i>	27.68	26.90	27.53	31.65	32.61	33.17
<i>Lenna</i>	27.65	26.55	27.58	31.47	32.54	33.20
<i>Monarch</i>	27.51	24.76	26.34	29.66	31.31	32.63
<i>Parrot</i>	27.20	27.98	28.07	31.61	32.10	33.48
<i>Pepper</i>	27.08	26.14	25.85	30.29	31.39	32.58
<b>Average</b>	27.42	26.40	26.92	30.94	31.91	32.94

Phase retrieval from coded diffraction pattern (CDP) measurements

# On-RED is a stochastic variant of GM-RED suitable for large-scale tomographic problems



**BC-RED is a block-coordinate variant of GM-RED  
suitable for processing very large images**

# BC-RED is a block-coordinate variant of GM-RED suitable for processing very large images

---

**Algorithm 1** Block Coordinate Regularization by Denoising (BC-RED)

---

```

1: input: initial value  $\mathbf{x}^0 \in \mathbb{R}^n$ , parameter  $\tau > 0$ , and step-size  $\gamma > 0$ .
2: for  $k = 1, 2, 3, \dots$  do
3:   Choose an index  $i_k \in \{1, \dots, b\}$ 
4:    $\mathbf{x}^k \leftarrow \mathbf{x}^{k-1} - \gamma \mathbf{U}_{i_k} \mathbf{G}_{i_k}(\mathbf{x}^{k-1})$ 
      where  $\mathbf{G}_i(\mathbf{x}) := \mathbf{U}_i^\top \mathbf{G}(\mathbf{x})$  with  $\mathbf{G}(\mathbf{x}) := \nabla g(\mathbf{x}) + \tau(\mathbf{x} - \mathbf{D}(\mathbf{x}))$ .
5: end for



```

---

BC-RED can be faster  
than GM-RED

Download the code here:  
[github.com/wustl-cig/bcred](https://github.com/wustl-cig/bcred)

# BC-RED is a block-coordinate variant of GM-RED suitable for processing very large images



Download the code here:  
[github.com/wustl-cig/bcred](https://github.com/wustl-cig/bcred)

Sun *et al.*, “Block Coordinate Regularization by Denoising,”  
*Proc. NeurIPS*, Dec 2019

# BC-RED is a block-coordinate variant of GM-RED suitable for processing very large images

Table 1: Average SNRs obtained for different measurement matrices and image priors.

<b>Methods</b>	<b>Radon</b>		<b>Random</b>		<b>Fourier</b>	
	<b>30 dB</b>	<b>40 dB</b>	<b>30 dB</b>	<b>40 dB</b>	<b>30 dB</b>	<b>40 dB</b>
<b>PGM (TV)</b>	20.66	24.40	26.07	<b>28.42</b>	28.74	29.99
<b>U-Net</b>	<b>21.90</b>	21.72	16.37	16.40	22.11	22.11
<b>RED (TV)</b>	20.79	24.46	25.64	28.30	28.67	29.97
<b>BC-RED (TV)</b>	20.78	24.42	25.70	<b>28.40</b>	28.71	29.99
<b>RED (BM3D)</b>	21.55	<b>25.24</b>	26.46	27.82	28.89	29.79
<b>BC-RED (BM3D)</b>	21.56	25.16	26.52	27.89	28.85	29.80
<b>RED (DnCNN*)</b>	20.89	24.38	<b>26.53</b>	28.05	29.33	<b>30.32</b>
<b>BC-RED (DnCNN*)</b>	20.88	24.42	<b>26.60</b>	28.12	<b>29.40</b>	<b>30.39</b>

# To conclude

- We increasingly rely on implicit regularization using nonlinear operators, such as deep neural nets
- PnP and RED are a theoretically sound algorithm that can leverage denoising neural nets as priors
- For certain large-scale problems, it is beneficial to consider scalable PnP-SGD, BC-RED, and On-RED

# Computational Imaging Group (CIG) at Washington University in St. Louis (WashU)

## CONTACT INFO

Prof. Ulugbek Kamilov

Email: [kamilov@wustl.edu](mailto:kamilov@wustl.edu)

Personal Twitter: [@ukmlv](https://twitter.com/@ukmlv)

Web: <http://cigroup.wustl.edu>

Group Twitter: [@wustlcig](https://twitter.com/@wustlcig)



Support:



CCF-181391



point your camera  
get the slides



# Acknowledgements

- This material is based upon work supported by the National Science Foundation under Grant No. 1813910. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation.