

DUCT TYPE INDOOR UNIT

CE | ErP | RoHS | REACH



Flexible
installation



Eco-Friendly
Refrigerant



Dual
direction
of drainage



Ultra-low
noise design



Ultra-thin
design



WiFi
control



Healthy
filter option



Square outlet
grill option



Built-in
water pump



Comfort



Rapid
started



Energy
saving



Timer



Power-down
memory

Model		TCC-12D2HWH/DV(02)	TCC-18D2HWH/DV(02)	TCC-24D2HWH/DV(02)	TCC-30D2HWH/DV(02)	TCC-36D2HWH/DV(02)	TCC-42D2HWH/DV(02)	TCC-48D2HWH/DV7(02)	TCC-55D2HWH/DV7(02)
Declared cooling capacity	W	3770(600~4860)	5300(620~5580)	7030(2200~7500)	8800 (2230~9380)	10550(3080 ~ 12300)	12100(3520~13200)	14070(3520~15530)	16000((4100~17290)
Declared heating capacity	W	4000(700~5400)	5800(760~6100)	7900(2320~8350)	9380 (2700~9730)	11720(3280 ~ 13500)	13500(3810~14950)	16120(4100~18170)	18170(4400~20520)
SEER /SCOP declared	W/W	6.1/4.0	6.3/4.0	6.2/4.0	6.2/4.0	6.1/4.3	6.1/4.0	6.14.0	6.1/4.0
Energy Class		A++/A+	A++/A+	A++/A+	A++/A+	A++/A+	A++/A+	A++/A+	A++/A+
Annual energy consumption	Cooling	kwh/a	284	294	402	530	605	643	800
	Average	kwh/a	1475	1505	0	2540	2625	3205	4200
Moisture removal	Liters/h	1.5	1.5	2.00	2.60	3.60	4.20	4.80	5.40
Indoor sound pressure(S/H/M/L/Mute)	dB(A)	43/41/39/37/35	43/41/39/37/35	48/45/43/38/36	47/45/44/40/38	52/49/47/45/44	52/50/48/45/43	53/51/49/47/45	53/52/50/48/46
Indoor sound pressure	dB(A)	41	41	45	45	49	50	51	52
Outdoor sound pressure	dB(A)	52	52	54	56	57	58	60	58
Power supply		Indoor: 220~240V~/50Hz/1P , Outdoor: 220~240V~/50Hz/1P							
Power supply side		Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Voltage Range		176~265							Indoor: 176~265 , Outdoor: 304~458
Cooling Operating current	A	8.2(2.0 ~ 13.0)	8.2(2.0 ~ 13.0)	10.5(4.0 ~ 15.0)	12.1(4.0 ~ 16.5)	16.2(1.2 ~ 21.0)	19.5(1.28 ~ 21.91)	8.4 (2.2~12.0)	11.2(2.6~13.2)
Heating Operating current	A	8.6(1.8 ~ 11.0)	8.6(1.8 ~ 11.0)	11.5(4.2 ~ 14.0)	12.1.(4.2 ~ 15.5)	16.2(1.6 ~ 17.4)	17.7(1.81 ~ 18.71)	8.5(0.5~1.6)	11.0(2.3~13.2)
Max.current	A	13	13	15	16.5	21	21	12.0	12.0
Indoor air circulation Cooling/heating	m³/h	700/800	800/900	1350/1550	1600/1800	1900/2000	2200/2200	2300/2300	2300/2500
Outdoor air circulation	m³/h	2650	2650	3500	4000	5000	5000	5600	6000
Refrigerant type		R32							
External Static Pressure(Rated)	Pa	25	25	25	37	37	50	50	50
External Static Pressure(Range)	Pa	0~60	0~60	0~80	0~120	0~120	0~120	0~120	0~120
Connecting Pipe	Gas	Inches	3/8"	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"
	Liquid	Inches	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"
Application area	m (	20~35	20~35	27~45	35~60	39~71	50~95	50~95	55~105
Max. refrigerant pipe length	m	30	30	30	30	50	50	75	75
Max. difference in level	m	15	15	15	15	25	25	30	30
Operation temperature range	℃	16~31	16~31	16~31	16~31	16~31	16~31	16~31	16~31
Ambient temperature range	Outdoor	℃	Cooling:-15~58/Heating:-25~24						
	Indoor	℃	Cooling:17~32/Heating:0~30						
Net dimensions(W x H x D)	Indoor	mm	920×210×570	920×570×210	920×570×270	1140×710×270	1140×710×270	1400×720×250	1400x720x250
	Outdoor	mm	780×605×307	780×605×307	845×700×342	845×700×342	910×804×378	910×804×378	1010×858×436
Net / Gross weight	Indoor	kg	24/28	24/28	26/31	36/41	36/41	38/43	38/43
	Outdoor	kg	30/33	30/33	40/44	41/45	55/60	55/60	77/89
Packing dimensions (W x H x D)	Indoor	mm	1120x690x281	1120x690x281	1120x690x341	1341×830×341	1341×830×341	1632x827x298	1632x827x298
	Outdoor	mm	890×385×648	890×648×385	960×430×755	960×430×755	1022x860x480	1022x860x480	1135x970x530
Loading Capacity	20'/40'GQ/40'HQ		63/126/150	63/126/150	49/98/110	41/88/99	30/62/78	34/70/80	28/60/68