

*Log

1. R21-R24 : current sensing resistor
2. Valve Current = 64.39mA ~ 83.33mA
3. sensing volt = 0.321V ~ 0.416V(typ.0.35V)
4. resistor watt = $83.33^2 \times 2(\text{mA}) \times 5 = 34.72\text{mW}$
5. TBD will be fixed after test
6. R13-R20, D1-D8 is optional

Valve ID

Valve1 = V1

Valve2 = 2V1



Valve3 = 4V1

Valve4 = 8V1

Vave ID Max = 2.31V

Valve1+	1	J11
Valve1-	2	
Valve2+	3	
Valve2-	4	
Valve3+	5	
Valve3-	6	
Valve4+	7	
Valve4-	8	

Screw_Terminal_01x08



Sheet: /Actuator_Valve_Drive/
File: Actuator_Valve_Drive.kicad_sch




Title: Actuator_Valve_Drive

Size: A4 Date: 2022-03-28

KiCad E.D.A. kicad (6.0.0)

Rev: rev02

Id: 5/8



*FET Spec

Table 1 Key Performance Parameters

Parameter	Value	Unit
$V_{DS} @ T_{j,max}$	550	V
$R_{DS(on),max}$	0.38	Ω
I_D	14.1	A
$Q_{g,typ}$	24.8	nC
$I_{D,pulse}$	32.4	A
$E_{oss} @ 400V$	2.54	μJ

*Log

1. Pump current(typ.) : 700mA
2. Fault current : 700mA <
3. Pump voltage : 20.0V ~ 25.0V(-4V ~ 1V)
4. FET V_{ds} : $0.38 \times 0.7 = 0.27V$
5. Pump voltage error : -5% ~ +5%
6. Max sensing voltage : $24 \times 0.05 - 0.27 = 0.93V$
7. Max sensing resistor : $0.93/0.7 = 1.3ohm$
8. Pump Max peak current : 1.5A(from test)

Sheet: /Actuator_Pump_Drive/
 File: Actuator_Pump_Drive.kicad_sch

Title: Actuator_Pump_Drive

Size: A4 Date: 2022-03-31













KiCad E.D.A. kicad (6.0.0)

Rev: rev00

Id: 6/8

*Cylinder position sensor

■ 내부회로도




Sheet: /ExtSensor_Sig_process/
File: ExtSensor_Sig_process.kicad_sch

Title: ExtSensor_sig_process

Size: A4 Date: 2022-04-06
KiCad E.D.A. kicad (6.0.0)

Rev: rev00
Id: 7/8



Sheet: /ControllerPower/		
File: ControllerPower.kicad_sch		
Title: ControllerPower		
Size: A4	Date: 2022-03-29	Rev: rev00
KiCad E.D.A. kicad (6.0.0)		Id: 10/8