

Integrated Science Thesis Proposal

Evan Shapiro

Master's of Integrated Science, University of Colorado Denver

February 9, 2018

Contents

1	Abstract	1
2	Introduction	2
3	Motivation for Performing Study	3
3.0.1	Magnetically Confined Plasma as an Energy Source	6
3.0.2	Physics of Magnetically Confined Fusion	6
3.0.3	Transport Phenomenon in Fusion	6
4	Literature Review	6

1 Abstract

Plasma microturbulence is a leading candidate for the anomalous diffusion observed in modern tokamak experiments. Global gyrokinetic models have been shown to accurately predict the ion diffusivity, χ_i . Extreme-scale, fixed-flux supercomputing simulations are beginning to simulate modes of operation relevant to next-generation(ITER,DEMO) reactors. Using a surrogate model

to reduce computational expense, I conduct a predictive scan in ρ^{-1} , to ascertain whether or not the ion diffusivity χ_i scales in a Bohm or gyro-Bohm fashion, and analyze the sensitivity of χ_i to perturbation in the heating model in the *XGC* model.

2 Introduction

The energy and ion confinement properties of a magnetically confined plasma are critical to reaching a state of power balance in a fusion reactor. If power balance is not met then the alpha particle power heating from the plasma fusion reactions is not enough to overcome the losses due to Bremsstrahlung and thermal conduction by ions and electrons [?]. It is known that the ion diffusivity in Tokamak reactors stellarators has a time scale that can not be explained solely by Coulomb interactions [1]. It has been postulated that plasma turbulence is responsible for the non-Coulombic thermal conductivity, however due to the complexity of modeling turbulence other methods have been used to understand how the ion temperature gradient scales with reactor size.

Developing a theory and model of plasma turbulence would allow us to understand how ion diffusivity scales with reactor size, which is critically important when transitioning from a test reactor to an ITER or DEMO sized reactor. However, the computational complexity of such a task has encouraged clever dimensionless scaling arguments to be used to study the scaling behavior. Prior research [2] has focused on the scaling relationship between the ion thermal diffusivity, χ_i , and the dimensionless variable $\frac{\rho_i}{a}$, where ρ_i is the ion gyroradius, or Larmor radius, and a is the minor radius of a Tokamak reactor; it can be seen that $\frac{\rho_i}{a} \ll 1$.

Of interest is whether the ion diffusivity scaling is Bohm-like, or scales linearly with temperature, or gyro-Bohm like, scaling sublinearly with temperature.

Previous studies on the relationship between ion diffusivity and reactor size have been completed in a reduced scale geometry [2], leaving

The relationship between ion diffusivity, χ_i , and the dimensionless radius ρ_* is given by

$$\chi_i = (cT_e/|e|B)\rho_*^{x_p} F(v_*, \beta, q_\phi, T_e/T_i, \dots).$$

The first coefficient is the Bohm diffusivity function, where c is the speed of light in the plasma, T_e is the electron temperature e is the electron charge, and B is the perpendicular magnetic field. The second coefficient contains the dimensionless radius, where the exponent x_p determines the scaling of the ion diffusivity with respect to the dimensionless radius. The third coefficient is the dimensionless group formed by all of the relevant parameters.

In this thesis I want to determine the scaling behavior of χ_i with respect to ρ_* by performing a scan in ρ_* using a surrogate model. The reason for using a surrogate model is that the full-f gyrokinetic model that is used to model the behavior of the plasma is computationally expensive, requiring extreme scale HPC power, like the Titan supercomputer at Oak Ridge National Laboratories.

Most research on the scaling of ion heat diffusivity is concerned with determining the exponential relationship between, χ_i and $\chi_B\rho_*^n$. χ_B = Bohm diffusivity function if the on I am interested in studying the scaling behavior of the ion diffusivity with respect to ρ , as it has been established that the scaling can be Bohm like, or $\chi_i \propto \rho_*^0$, or The scaling properties of the ion diffusivity in a n, as if the diffusion scales in a Bohm (linear) fashion with respect to ρ_* then the chan

3 Motivation for Performing Study

The motivation for this project is tied in to the overall goals of the Partnership Center for High-Fidelity Boundary Plasma Simulation, which is working to understand the boundary physics of a magnetically confined plasma in a nuclear fusion reactor using high-fidelity simulations. [?]

For clarity, the boundary region in a fusion reactor is defined as extending 10% of the outer-minor radius in from the magnetic separatrix, through the open field line scrape off layer, out to the material walls. The separatrix is the point where the magnetic field lines cross, which in the case of the Tokamak is at the bottom of the toroid, while the scrape off layer (SOL) is defined as the plasma region that is characterized by open field lines, and is outside of the separatrix. The SOL absorbs most of the plasma exhaust and transports it along field lines to the divertor plates. The divertor plates are responsible for absorbing heat and ash produced by the plasma, minimizing contamination of the plasma, and protecting thermal and neutronic loads.

CHECK CITATION INSERT MAIN MAGNETIC FIELD LINE FIGURE HERE

The stability in the plasma boundary is critical to Tokamak operation, and thus the physics in the plasma boundary region must be understood before a fully functional fusion reactor can be built. To elucidate the importance of understanding plasma boundary physics, an example of a critical issue related to stable operation of a fusion reactor is outlined below.

Once a magnetically confined plasma reaches a heating threshold value the plasma transitions from a low-confinement mode (L-Mode) to a high-confinement mode (H-Mode). After L-H transition occurs, a steep pedestal in the plasma density develops in the plasma boundary region, as can be seen in figure 2.2. This transition brings a reduction in the radially directed electric field, as well as a reduction in the turbulence intensity, which in turn reduces heat transport. This reduction in turbulent transport leads to an increased heating in the ion core of the plasma by "a factor that is proportional to the temperature at the top of the pedestal." [?] The increased heating leads to a 2-3 fold increase in plasma power production, making the H-mode the desired operating mode for future fusion reactors.

Operating in H-mode requires a stable pedestal. However, the steep density gradient acts as a source of free energy for the magnetohydrodynamic plasma edge localized modes (ELM), [?] in which the pedestal repeatedly crashes, yielding bursts of plasma towards the divertor plates. A proposed solution to this problem is to use stochastic magnetic fields to stabilize steep gradient in the boundary region, and thus control the edge localized modes.

The Partnership seeks to understand the L-H transition, pedestal structure, and the requirements for ELM stability and control. The plasma behavior in the boundary region is non-Maxwellian, and has non-equilibrium characteristics, requiring a first principles, 5-D gyrokinetic model, that simulates multiscale edge Tokamak plasma physics. Simulations include: The code used (XGC), which is a particle in cell (PIC) code, requiring extreme high performance computing (HPC) to run a full plasma simulation.

One of the Modeling and simulating the magnetically confined plasma in the boundary region is incredibly important to progressing plasma research due to the difficulty of collecting data from inside a nuclear reactor.[?] The complexity of the XGC code requires computational resources of the scale of Titan Cray XK at Oak Ridge National Laboratory. To reduce the computational complexity to utilize surrogate methods to reduce the complexity of the models in order to more efficiently analyze the scaling of the ion diffusivity of the plasma. Constructing a surrogate model allows us to capture the primary behavior of the modeled process, and is sufficiently efficient for model validation and uncertainty propagation. [?]. To determine input parameters, boundary conditions and initial conditions, data from the C-Mod fusion reactor are analyzed in a probabilistic framework, in a process called model calibration.

[?] The boundary physics of a magnetically confined plasma within a reactor are tied to variety of parameters. The parameter of interest for this study is the ion diffusivity. As such, a bird's eye view of the current research being performed in the field of plasma physics will be presented. [?] This will be followed by an overview of the diffusion model that will be explored in this paper.

3.0.1 Magnetically Confined Plasma as an Energy Source

3.0.2 Physics of Magnetically Confined Fusion

3.0.3 Transport Phenomenon in Fusion

4 Literature Review

Literature Review for MIS Thesis Proposal Ralph C. Smith - Uncertainty Quantification

Determining the plasma size scaling of the ion diffusivity, and performing efficient sensitivity analysis on the ion diffusivity in the heating component of the XCG model, within a constructed surrogate model, will require a knowledge base in the following subjects.

Physics

A background in plasma physics, and the component of the XCG model that is used to model plasma heating and ion diffusivity. To support my physical understanding while completing this research I have identified the following references.

Plasma Physics and Fusion Reactors

Jeffrey P. Friedberg Plasma Physics and Fusion Energy

This textbook covers the physics of plasma fusion, its applications as an energy sources, the physical requirements to create an energy producing fusion reactor, and the designs requirements for fusion reactor with a toroidal geometry - the geometry of the ITER fusion reactor.

XCG Modeling

Dr. Wei-Lee from the Princeton Plasma Fusion Physics Laboratory has posted the lecture notes and homework assignments from a course on Theory and Modeling of Kinetic Plasmas on his website.

<http://w3.pppl.gov/~wwlee/>

This course contains the background information on gyrokinetic model that is being used to describe

the plasma boundary physics in the ITER Tokamak reactor.

Project Description

The project proposal from the Partnership Center for High-Fidelity Boundary Plasma Simulation provides the motivation for performing this research, as well as a reference list containing relevant literature that will be reviewed and cited as necessary.

Case Study to Understand Current Methods in Uncertainty Quantification

I am currently reviewing a paper referenced from the project proposal titled Improved profile fitting and quantification of uncertainty in experimental measurements of impurity transport coefficients using Gaussian process regression by Chilenski et al. to develop an understanding of the uncertainty quantification and parameter estimation pipeline.

Uncertainty Quantification

Performing the sensitivity analysis, and constructing surrogate models will require background knowledge in statistics, both Bayesian and frequentist error analysis, uncertainty quantification, and surrogate models. Two textbooks have been identified to support this work.

Uncertainty Quantification: Theory, Implementation, and Applications by Ralph C. Smith

Data Reduction and Error Analysis for the Physical Sciences by Phillip R. Bevington and D. Keith Robinson

References

- [1] C.C. Petty et al, “Gyroradius Scaling of Electron and Ion Transport,” *Physical Review Letters*, vol. 74, p. 4, June 1995.
- [2] Yasuhiro Idomura and Motoki Nakata, “Plasma size and power scaling of ion temperature gradient driven turbulence,” *AIP Physics of Plasmas*, vol. 21, p. 5, Feb. 2018.