

Setup

dplyr

select and filter

rename and mutate

Pipes

Setup 2.0

summarise

ggplot

geom_point

color and shape aesthetics

geom_histogram

Facets

Final plot

tidyverse exercise solutions

Kris Hong & Kim Dill-McFarland

version June 27, 2018

Setup

We will be working with the same data and packages as in the notes and main.R files.

```
library(tidyverse)
```

```
raw_data <- read_csv(file="data/Saanich_Data.csv",  
                     col_names=TRUE,  
                     na=c("", "NA", "NAN", "ND"))
```

```
dat <- raw_data
```

Because we will be manipulating the data further, first copy the data “dat” to practice data “pdat” so that what you do in the exercises does not impact the rest of the workshop.

```
pdat <- raw_data
```

dplyr

select and filter

Exercise. Using your pdat data:

1. select the Cruise, Date, Depth, PO4, and NO3 variables
2. filter the data to retain data on Cruise 72 where Depth is \geq to 0.1

Your resulting pdat object should be a 8x5 data frame.

```
# 1
pdat <- select(pdat, Cruise, Date, Depth, PO4, WS_NO3)

# 2
pdat <- filter(pdat, Cruise == 72 & Depth >= 0.1)

# Check dimensions
dim(pdat)
```

```
## [1] 8 5
```

rename and mutate

To start fresh, remake the pdat object.

```
pdat <- raw_data
```

Exercise. Using the practice data (pdat):

1. Select the Date, Depth and O2 variables from pdat using select
2. Rename the O2 variable to Oxygen using rename
3. Keep August observations where Oxygen is nonmissing using filter, months, and !is.na
4. Transform Oxygen from micromoles/L to micrograms/L using mutate (multiply Oxygen by 32)
5. Run the provided ggplot() code to create a scatterplot of Oxygen vs Depth

```
# 1
pdat <- select(pdat, Date, Depth, WS_O2)


# 2
pdat <- rename(pdat, Oxygen=WS_O2)

# 3
pdat <- filter(pdat, months(Date) == "August")

# 4
pdat <- mutate(pdat, Oxygen=Oxygen*32)
```

Plug this modified pdat data into a ggplot function.

```
# 5
ggplot(pdat, aes(x=Oxygen, y=Depth*1000)) +
  geom_point() +
  geom_smooth(method="loess", se=FALSE) +
  scale_y_reverse(limits=c(200, 0)) +
  labs(x=expression(O[2]*" "(mu*g/mL)),
       y="Depth (m)",
       title="Oxygen decreases with depth and is less variable at lower depths"
  )
```



Pipes

Again start fresh.


```
pdat <- raw_data
```

Exercise. Using your pdat data:

1. Rewrite your code from the previous exercise using pipes
2. Pipe your data into the ggplot function

```
# 1
pdat %>%
  select(Date, Depth, WS_O2) %>%
  rename(Oxygen=WS_O2) %>%
  filter(months(Date) == "August" & !is.na(Oxygen)) %>%
  mutate(Oxygen=Oxygen*32) %>%

# 2
ggplot(aes(x=Oxygen, y=Depth*1000)) +
  geom_point() +
  geom_smooth(method="loess", se=FALSE) +
  scale_y_reverse(limits=c(200, 0)) +
  labs(x=expression(O[2]*" "(mu*g/L)),
       y="Depth (m)",
       title="Oxygen decreases with depth and is less variable at lower depths"
  )
```



Setup 2.0

We will want to use cleaned-up data in the remaining exercises. So use the following to modify the `raw_data` and create a new `pdat` object.

```
pdat <-
  raw_data %>%
  select(Cruise, Date, Depth,
         Temperature, Salinity, Density,
         WS_O2, WS_NO3, WS_H2S) %>%
  filter(Date >= "2008-02-01") %>%
  rename(O2=WS_O2, NO3=WS_NO3, H2S=WS_H2S) %>%
  mutate(Depth=Depth*1000)
```

summarise

Exercise. Using your new, cleaned-up pdat data:

1. Calculate median, interquartile range, and sample size of Temperature by depth

```
pdat %>%
  group_by(Depth) %>%
  summarise(Median_Temperature=median(Temperature, na.rm=TRUE),
            IQR_Temperature=IQR(Temperature, na.rm=TRUE),
            n=n())
```

Depth <dbl>	Median_Temperature <dbl>	IQR_Temperature <dbl>	n <int>
10	10.024	4.2030	83
20	9.396	3.3075	83
40	9.101	2.0330	83
60	8.563	1.4185	83
75	8.480	0.9595	82
80	NA	NA	1
85	8.558	0.7590	82
90	8.599	0.7515	82
97	8.672	0.7050	82
100	8.696	0.6440	83

1-10 of 24 rows

Previous
1
2
3
Next

ggplot


geom_point

Exercise. Using your pdat data:


1. Investigate the relationship between O2 and H2S

2. Investigate the relationship between NO3 and H2S

```
# 1
pdat %>%
  ggplot(aes(x=O2, y=H2S)) +
  geom_point(size=1)
```



```
# 2
pdat %>%
  ggplot(aes(x=NO3, y=H2S)) +
  geom_point(size=1)
```




color and shape aesthetics

Exercise. Using your pdat data:

1. It may be difficult to differentiate between the different shapes in the previous plot so modify the following code to add colours to the shapes as well:

```
pdat %>%
  select(Cruise, Depth, O2, H2S) %>%
  filter(Cruise==72) %>%
  gather(key="Chemical", value="Concentration", -Cruise, -Depth) %>%

  ggplot(aes(x=Concentration, y=Depth, shape=Chemical, colour=Chemical)) +
  geom_point() +
  scale_y_reverse(limits=c(200, 0))
```




geom_histogram

Exercise. Using your pdat data:


1. Investigate the distribution of nitrate across all depths
2. Test out different values for the bins argument (“bins=”)

```
# 1
pdat %>%
  ggplot(aes(x=NO3)) +
  geom_histogram()
```

```
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```

```
# 2
pdat %>%
  ggplot(aes(x=NO3)) +
  geom_histogram(bins=50)
```




Facets

Exercise. Using your pdat data:

1. Filter to data at depths of 10, 60, 100 or 200
2. Plot Oxygen vs Nitrate faceted by Depth without providing arguments for dir or scales

```
pdat %>%  
  filter(Depth %in% c(10, 60, 100, 200)) %>%  
  
  ggplot(aes(x=O2, y=NO3)) +  
  geom_point(size=1) +  
  facet_wrap(~Depth, ncol=2)
```



Final plot

Setup a theme.

```
my_theme <-  
  theme_bw() +  
  theme(panel.grid.major=element_blank(),  
        panel.grid.minor=element_blank())
```

Save the two plots as objects: p1 and p2.

```
p1 <-  
  pdat %>%  
  gather(key="Key", value="Value", -Cruise, -Date, -Depth, factor_key=TRUE) %>%  
  
  ggplot(aes(x=Value, y=Depth)) +  
  geom_point(size=1) +  
  scale_y_reverse(limits=c(200, 0)) +  
  facet_wrap(~Key, ncol=2, dir="v", scales="free_x") +  
  my_theme +  
  labs(x="",  
        y="Depth (m)")  
  
p2 <-  
  pdat %>%  
  filter(!is.na(H2S)) %>%  
  arrange(H2S) %>%  
  
  ggplot(aes(x=O2, y=NO3, colour=H2S)) +  
  geom_point(size=2) +  
  my_theme +  
  labs(x="O2 in uM",  
        y="NO3 in uM") +  
  scale_colour_continuous(name="H2S in uM")
```

Use cowplot to create a multi-panel figure.

```
p <- cowplot::plot_grid(p1, p2, labels=c("A", "B"), rel_widths=c(2/5, 3/5))  
  
p
```

