

DOCTORAL PROGRAM IN ENGINEERING SCIENCES AT ITESO

ADAPTATIVE DISCOVERING ALGORITHM BASED ON NEURAL NETWORKS


Edgar-D. Ramirez-de-L.
Maria-del-P. Pozos-P.
Ivan Villalon-Turrubiates

Algorithm 5 - trainInputFunction.doc

May 15, 2018
Tlaquepaque, Mexico 45604

Doctoral Program in Engineering Sciences
ITESO (*Instituto Tecnológico y de Estudios Superiores de Occidente*)

No part of this document may be copied, translated, transcribed or entered in any form into any machine without written permission. Address inquiries in this regard to the authors or to the Chair of the Doctoral Program in Engineering Sciences at ITESO (dc@iteso.mx). Excerpts may be quoted for scholarly purposes with full acknowledgment of source. This document may not be lent or circulated without this cover page.



ADAPTATIVE DISCOVERING ALGORITHM BASED ON NEURAL NETWORKS

Edgar-D. Ramirez-de-L.
Maria-del-P. Pozos-P.
Ivan Villalon-Turrubiates

May 15, 2018

Doctoral Program in Engineering Sciences
ITESO (*Instituto Tecnológico y de Estudios Superiores de Occidente*)

Tlaquepaque, Mexico 45604
Tel +52 33 3669 3598
E-mail: dc@iteso.mx

Keywords *neural networks, deep learning, machine learning, classifiers, python*

Abstract

We present the Algorithm 5 (`trainInputFunction`) which is part of the Adaptative Discovering Algorithm based on Neural networks (ADAN algorithm).

Algorithm 5 `trainInputFunction`

Require: $features \neq \emptyset \wedge labels \neq \emptyset \wedge batchSize \neq \emptyset$

```
1:  $dataSet \leftarrow toSlices(features, labels)$   
2:  $dataSet \leftarrow shuffle(dataSet, 1000)$   
3:  $dataSet \leftarrow repeat(dataSet, \emptyset)$   
4:  $dataSet \leftarrow batch(dataSet, batchSize)$   
5: return  $dataSet$ 
```

Some important considerations about the Algorithm 5:

1. The method and implementation is basically the same as you can see in the Premade Estimators¹ guide. More precisely, as in `iris_data.py`². So, just to make it a little more clear, we will describe the functions in lines 1 to 4, and you can find more details in^{20,21}.

The `toSlices(tensors, labels)` function creates a data set whose elements are slices of the given tensors^{3,4}. Note that `labels` could be empty/null (`None` in Python).

`shuffle(dataSet, bufferSize)`, in line 2, is a function that randomly shuffles

¹ Premade Estimators, TensorFlow™. May 7, 2018, https://www.tensorflow.org/get_started/premade_estimators

² `models/iris_data.py`, TensorFlow™. May 7, 2018, https://github.com/tensorflow/models/blob/master/samples/core/get_started/iris_data.py

³ Tensors, TensorFlow™. May 7, 2018, https://www.tensorflow.org/programmers_guide/tensors

⁴ `tf.data.Dataset.from_tensor_slices`, TensorFlow™. May 7, 2018, https://www.tensorflow.org/api_docs/python/tf/data/Dataset#from_tensor_slices

the elements of the specified `dataSet`. In the implementation this is achieved thanks to `tf.data.Dataset.shuffle(buffer_size, seed=None, reshuffle_each_iteration=None)`⁵

The function `repeat(dataSet, count)` repeats the `dataSet` `count` times. For more details please consult the documentation for this function⁶.

Finally, in line 4, the `batch(dataSet, batchSize)` function, combines consecutive elements of the `dataSet` into batches from the size specified by `batchSize`. This is achieved thanks to `tf.data.Dataset.batch(batchSize)`⁷.

⁵ `tf.data.Dataset.shuffle`, TensorFlow™. May 7, 2018, https://www.tensorflow.org/api_docs/python/tf/data/Dataset#shuffle

⁶ `tf.data.Dataset.repeat`, TensorFlow™. May 7, 2018, https://www.tensorflow.org/api_docs/python/tf/data/Dataset#repeat

⁷ `tf.data.Dataset.batch`, TensorFlow™. May 7, 2018, https://www.tensorflow.org/api_docs/python/tf/data/Dataset#batch