

DOCTORAL PROGRAM IN ENGINEERING SCIENCES AT ITESO

ADAPTATIVE DISCOVERING ALGORITHM BASED ON NEURAL NETWORKS

Edgar-D. Ramirez-de-L.
Maria-del-P. Pozos-P.
Ivan Villalon-Turrubiates

Algorithm 2 - readSource.doc

May 15, 2018
Tlaquepaque, Mexico 45604

Doctoral Program in Engineering Sciences
ITESO (*Instituto Tecnológico y de Estudios Superiores de Occidente*)

No part of this document may be copied, translated, transcribed or entered in any form into any machine without written permission. Address inquiries in this regard to the authors or to the Chair of the Doctoral Program in Engineering Sciences at ITESO (dc@iteso.mx). Excerpts may be quoted for scholarly purposes with full acknowledgment of source. This document may not be lent or circulated without this cover page.



ADAPTATIVE DISCOVERING ALGORITHM BASED ON NEURAL NETWORKS

Edgar-D. Ramirez-de-L.
Maria-del-P. Pozos-P.
Ivan Villalon-Turrubiates

May 15, 2018

Doctoral Program in Engineering Sciences
ITESO (*Instituto Tecnológico y de Estudios Superiores de Occidente*)

Tlaquepaque, Mexico 45604
Tel +52 33 3669 3598
E-mail: dc@iteso.mx

Keywords *neural networks, deep learning, machine learning, classifiers, python*

Abstract

We present the Algorithm 2 (`readSource`) which is part of the Adaptative Discovering Algorithm based on Neural networks (ADAN algorithm).

Algorithm 2 `readSource`

Require: $args \neq \emptyset \wedge readArg('dataSource', args) \neq \emptyset$
1: $dataFrame \leftarrow loadData(readArg('dataSource', args))$
2: $label \leftarrow readArg('label', args)$
3: $randomizedDataFrame \leftarrow chooseRandomFeatures(args, dataFrame)$
4: $randomizedDataFrame \leftarrow concat(randomizedDataFrame, pop(dataFrame, label), 'columns')$
5: $(dfTraining, trainY), (dfTesting, testY), dfPredict, expected \leftarrow chooseRandomData(args, randomizedDataFrame)$
6: **return** $(dfTraining, trainY), (dfTesting, testY), dfPredict, expected$

For Algorithm 2 please consider the next:

1. The function `loadData(dataSource)` in line 1, will depend from the programming language and/or from the library to achieve this. In our case, like we said at the beginning of this document, we use Keras for this. In the file `data.py`¹ you will see the implementation for the function `loadData(dataSource)`. We don't include here because is a trivial process.

2. `concat(dataFrame, obj, concatBy)`, in line 4, like its name suggests, is a function that will concat the `dataFrame` with `obj` in the axis specified by `concatBy`.

¹ `adan/data.py`, The Authors. May 7, 2018, <https://github.com/EDario333/adan/blob/0.1.4/algorithm/data.py>

In the same line, you can see the `pop(dataFrame, 'serieName')` function, like its name suggests, it will pop from the `dataFrame` the serie (or the y axis) specified by `'serieName'`.

All this give us the next implementation, in Python: `randomized_df = pd.concat([randomized_df, df.pop(args.label)], 'columns')`