

RSA Algorithm Implementation in Python

Erikas Eigėlis

Vinius University Kaunas Faculty

Information Systems and Cyber Security (ISKS6)

Exponentiation by squaring

Description

- This method is based on the observation, that for a positive integer n we have:

$$x^n = \begin{cases} x (x^2)^{\frac{n-1}{2}}, & \text{if } n \text{ is odd} \\ (x^2)^{\frac{n}{2}}, & \text{if } n \text{ is even.} \end{cases}$$

- In python this is implemented by using recursive function, until the power is equal to 1

Python implementation

```
def pow_es(self, base, power):  
    # Raise to power by using exponentiation by squaring  
    # If power is equal to 1...  
    if power == 1:  
        # return base value (stop recursion cycle)  
        return base  
    # If power is even...  
    if power % 2 == 0:  
        # call same function with squared base half power  
        return self.pow_es(base * base, power / 2)  
    # If power is odd...  
    else:  
        # multiply base by value of same function with  
        # squared base and half of (power - 1) as arguments  
        return base * self.pow_es(base * base, (power - 1) / 2)
```

Finding inverse number

Description

- Finding inverse number (in this case the one that $q \bmod p = 1$) is achieved by checking if $xq \bmod p$ is equal to 1
- This is achieved by by incrementing x from 0 until such number is generated
- When d value is needed, the function looks like this:
 $q_inv(e, (p-1)*(q-1))$

Python implementation

```
def q_inv(q, p):  
    x = 0  
    # Do while xq%p is not equal to 1:  
    while x * q % p != 1:  
        # Increment x by one:  
        x += 1  
    return x
```

Chinese remainder algorithm

Description

- p and q are prime numbers used for key generation
- $d_p = d \bmod (p-1)$
- $d_q = d \bmod (q-1)$
- $q_{inv} = q^{-1} \bmod p$
- These values allow the recipient to compute exponentiation $m = c^d \bmod (pq)$ efficiently as follows:
 - $m_1 = c^{d_p} \bmod p$
 - $m_2 = c^{d_q} \bmod q$
 - $h = q_{inv}(m_1 - m_2) \bmod p$
 - Final result (m) is: $m = m_2 + hq$

Python implementation

```
def chinese_remainder(self, c, p, q, d):  
    dp = d % (p - 1)  
    dq = d % (q - 1)  
  
    qinv = self.q_inv(q, p)  
  
    m1 = self.pow_es(c, dp) % p  
    m2 = self.pow_es(c, dq) % q  
  
    h = qinv * (m1 - m2) % p  
  
    return m2 + h * q
```

Live showcase:

<https://isks6.pythonanywhere.com/rsa/>

View source code:

<https://github.com/EErikas/PythonCryptoExample>