

PyNeb_manual_9

June 4, 2020

```
[1]: import pyneb as pn
import numpy as np
import matplotlib.pyplot as plt
import time
```

```
[2]: # This is the AAN interface.
try:
    import ai4neb
except:
    !pip install -U git+https://github.com/morisset/AI4neb.git
    import ai4neb
```

1 Test Atom.getTemDen

```
[3]: O3 = pn.Atom('O',3)
# Set the Artificial Neuron Network verbosity to True:
O3.ANN_inst_kwargs['verbose'] = True
N2 = pn.Atom('N',2)
N2.ANN_inst_kwargs['verbose'] = True
S2 = pn.Atom('S',2)
S2.ANN_inst_kwargs['verbose'] = True
```

```
[4]: # Number of data points to test the ANN option speedup. 1,000 is good to see,
      ↪ what's happening. 10,000 starts to really rock.
N_rand = 1000
# Define some random values to test the
ratio = 150.+ 10*np.random.randn(N_rand)
den = 150.+ 10*np.random.randn(N_rand)
ratio_S2 = 1 + 0.1*np.random.randn(N_rand)
tem_S2 = 11000 + 2000 * np.random.randn(N_rand)
```

```
[5]: start = time.time()
resa = O3.getTemDen(ratio, den=1e2, wave1=5007, wave2=4363)

resb = O3.getTemDen(ratio, den=den, wave1=5007, wave2=4363)
resc = N2.getTemDen(ratio, den=den,
```

```

        to_eval = '(L(6584) + L(6548)) / L(5755)'
resd = S2.getTemDen(ratio_S2, tem=11000, wave1=6716, wave2=6731)

rese = S2.getTemDen(ratio_S2, tem=tem_S2, wave1=6716, wave2=6731)
end = time.time()
print(end-start)

```

18.869255304336548

```
[6]: pn.config.use_multiprocs()
```

```
[7]: start = time.time()
      resa = O3.getTemDen(ratio, den=1e2, wave1=5007, wave2=4363)

      resb = O3.getTemDen(ratio, den=den, wave1=5007, wave2=4363)
      resc = N2.getTemDen(ratio, den=den,
                          to_eval = '(L(6584) + L(6548)) / L(5755)',
      resd = S2.getTemDen(ratio_S2, tem=11000, wave1=6716, wave2=6731)

      rese = S2.getTemDen(ratio_S2, tem=tem_S2, wave1=6716, wave2=6731)
      end = time.time()
      print(end-start)

```

10.177392721176147

```
[8]: start = time.time()
      res2a = O3.getTemDen(ratio, den=1e2, wave1=5007, wave2=4363, method='ANN')

      res2b = O3.getTemDen(ratio, den=den, wave1=5007, wave2=4363, method='ANN')
      res2c = N2.getTemDen(ratio, den=den,
                          to_eval = '(L(6584) + L(6548)) / L(5755)',
                          method='ANN')
      res2d = S2.getTemDen(ratio_S2, tem=11000, wave1=6716, wave2=6731,
                          method='ANN', end_x=1e4)
      res2e = S2.getTemDen(ratio_S2, tem=tem_S2, wave1=6716, wave2=6731,
                          method='ANN', end_x=1e4)

      end = time.time()
      print(end-start)

```

Instantiation. V 0.17

Training set size = 30, Test set size = 0

Train data scaled. Log10 applied.

Test data scaled.

Training set size = 30, Test set size = 0

Training set size = 30, Test set size = 0

Regression Model SK_ANN

Training 2 inputs for 1 outputs with 30 data

```

RM trained, with 277 iterations. Score = 1.000
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
             beta_2=0.999, early_stopping=False, epsilon=1e-08,
             hidden_layer_sizes=(10, 10), learning_rate='constant',
             learning_rate_init=0.001, max_fun=15000, max_iter=20000,
             momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
             power_t=0.5, random_state=None, shuffle=True, solver='lbfgs',
             tol=1e-06, validation_fraction=0.1, verbose=False,
             warm_start=False)
Training time 0.1 s.
Test data scaled. Log10 applied.
Training set size = 30, Test set size = 1000
Predicting from 2 inputs to 1 outputs using 1000 data in 0.00 secs.
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 1 outputs with 900 data
RM trained, with 281 iterations. Score = 1.000
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
             beta_2=0.999, early_stopping=False, epsilon=1e-08,
             hidden_layer_sizes=(10, 10), learning_rate='constant',
             learning_rate_init=0.001, max_fun=15000, max_iter=20000,
             momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
             power_t=0.5, random_state=None, shuffle=True, solver='lbfgs',
             tol=1e-06, validation_fraction=0.1, verbose=False,
             warm_start=False)
Training time 0.2 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1000
Predicting from 2 inputs to 1 outputs using 1000 data in 0.00 secs.
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 1 outputs with 900 data
RM trained, with 508 iterations. Score = 1.000
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
             beta_2=0.999, early_stopping=False, epsilon=1e-08,
             hidden_layer_sizes=(10, 10), learning_rate='constant',
             learning_rate_init=0.001, max_fun=15000, max_iter=20000,
             momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,

```

```

        power_t=0.5, random_state=None, shuffle=True, solver='lbfgs',
        tol=1e-06, validation_fraction=0.1, verbose=False,
        warm_start=False)
Training time 0.4 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1000
Predicting from 2 inputs to 1 outputs using 1000 data in 0.00 secs.
Instantiation. V 0.17
Training set size = 30, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 30, Test set size = 0
Training set size = 30, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 1 outputs with 30 data
RM trained, with 182 iterations. Score = 1.000
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
              beta_2=0.999, early_stopping=False, epsilon=1e-08,
              hidden_layer_sizes=(10, 10), learning_rate='constant',
              learning_rate_init=0.001, max_fun=15000, max_iter=20000,
              momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
              power_t=0.5, random_state=None, shuffle=True, solver='lbfgs',
              tol=1e-06, validation_fraction=0.1, verbose=False,
              warm_start=False)
Training time 0.1 s.
Test data scaled. Log10 applied.
Training set size = 30, Test set size = 1000
Predicting from 2 inputs to 1 outputs using 1000 data in 0.00 secs.
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 1 outputs with 900 data
RM trained, with 1700 iterations. Score = 1.000
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
              beta_2=0.999, early_stopping=False, epsilon=1e-08,
              hidden_layer_sizes=(10, 10), learning_rate='constant',
              learning_rate_init=0.001, max_fun=15000, max_iter=20000,
              momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
              power_t=0.5, random_state=None, shuffle=True, solver='lbfgs',
              tol=1e-06, validation_fraction=0.1, verbose=False,
              warm_start=False)
Training time 1.2 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1000

```

Predicting from 2 inputs to 1 outputs using 1000 data in 0.00 secs.
2.01995587348938

```
[9]: # Compare the results
print(np.mean(resa/res2a), np.std(resa/res2a))
print(np.mean(resb/res2b), np.std(resb/res2b))
print(np.mean(resc/res2c), np.std(resc/res2c))
print(np.mean(resd/res2d), np.std(resd/res2d))
print(np.mean(rese/res2e), np.std(rese/res2e))
```

```
0.981179108818598 0.0015887091461342275
1.0019920062243979 0.00178459706723261
1.000210402665289 0.0016651336592158291
0.9896423314762055 0.01334863238699576
1.0020064355639797 0.004579351110900343
```

2 Test diagnostics.getCrossTemDen

```
[10]: N = 2000
rO3 = 0.0050 * (1 + 0.6*np.random.randn(N))
rN2 = 0.0080 * (1 + 0.6*np.random.randn(N))
rS2 = 1.5 * (1 + 0.7*np.random.randn(N))
```

```
[11]: diags = pn.Diagnostics()
```

```
[12]: # Normal way: looking for the point where both diagnostics coincide:
start = time.time()
tem, den = diags.getCrossTemDen('OIII 4363/5007', '[SII] 6731/6716', rO3, rS2)
tem2, den2 = diags.getCrossTemDen('NII 5755/6584', '[SII] 6731/6716', rN2,
    ↪rS2)
end = time.time()
print('time for classical method: {:.1f} s.'.format(end - start))
```

```
/Users/christophemorisset/Google Drive/Pro/PyNeb_devel/pyneb/core/diags.py:824:
RuntimeWarning: invalid value encountered in greater
    no_conv = ((abs(den_old - den) / den * 100) > tol_den) | ((abs(tem_old - tem)
/ tem * 100) > tol_tem)
time for classical method: 86.369073 s.
```

```
[13]: # Set up some parameters of the Regresor Method object
diags.ANN_inst_kwargs['random_seed'] = 43
#diags.ANN_inst_kwargs['use_log'] = False
diags.ANN_inst_kwargs['verbose'] = True

# Set up some parameters of the Analogic Neural Network
diags.ANN_init_kwargs['hidden_layer_sizes'] = (10, 30, 10)
```

```
diags.ANN_init_kwargs['activation'] = 'tanh'
diags.ANN_n_tem = 30
diags.ANN_n_den = 30
```

```
[15]: # Compute Te and Ne using the ANN. Print scoring at training
start = time.time()
temNN, denNN = diags.getCrossTemDen(['OIII] 4363/5007', '[SII] 6731/6716', r03,
    ↪rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)
print(diags.ANN.train_score)
temNN2, denNN2 = diags.getCrossTemDen(['NII] 5755/6584', '[SII] 6731/6716',
    ↪rN2, rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)
print(diags.ANN.train_score)
end2 = time.time()
print('time for ANN method: {:.1f} s.'.format(end2 - end))
```

```
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 2 outputs with 900 data
RM trained, with 5559 iterations. Score = 0.998
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
    beta_2=0.999, early_stopping=False, epsilon=1e-08,
    hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
    learning_rate_init=0.001, max_fun=15000, max_iter=20000,
    momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
    power_t=0.5, random_state=43, shuffle=True, solver='lbfgs',
    tol=0.0001, validation_fraction=0.1, verbose=False,
    warm_start=False)
Training time 6.9 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1765
Predicting from 2 inputs to 2 outputs using 1765 data in 0.00 secs.
[0.9982086401989643]
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 2 outputs with 900 data

/Users/christophemorriset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:522: RuntimeWarning:
```

```

invalid value encountered in log10
    X = np.log10(X)

RM trained, with 8624 iterations. Score = 0.998
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
              beta_2=0.999, early_stopping=False, epsilon=1e-08,
              hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
              learning_rate_init=0.001, max_fun=15000, max_iter=20000,
              momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
              power_t=0.5, random_state=43, shuffle=True, solver='lbfgs',
              tol=0.0001, validation_fraction=0.1, verbose=False,
              warm_start=False)

Training time 10.7 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1763
Predicting from 2 inputs to 2 outputs using 1763 data in 0.00 secs.
[0.9984161152279397]
time for ANN method: 55.007044 s.


/Users/christophemorisset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:522: RuntimeWarning:
invalid value encountered in log10
    X = np.log10(X)

```


```

[16]: # Plots comparing the results obtained by the classicla method and the ANN one
      # ANN is interpolating, while classicla method is looking for a zero.
      f, ((ax1, ax2), (ax3, ax4)) = plt.subplots(2, 2, figsize=(10,10))
      ax1.scatter(tem, (temNN-tem)/tem*100, c=np.log10(den))
      ax2.scatter(np.log10(den), (denNN-den)/den*100, c=tem)
      ax3.scatter(tem2, (temNN2-tem2)/tem2*100, c=np.log10(den2))
      ax4.scatter(np.log10(den2), (denNN2-den2)/den2*100, c=tem2);
      for ax in (ax1, ax2, ax3, ax4):
          ax.set_ylabel('Difference [%]')
          ax.set_ylim(-5, 5)

```



```
[17]: # Histograms of the differences. Not that bad indeed.
f, ((ax1, ax2), (ax3, ax4)) = plt.subplots(2, 2, figsize=(10,10))
ax1.hist((tem-temNN)/tem*100, bins=np.linspace(-4, 4, 100))
ax2.hist((den-denNN)/den*100, bins=np.linspace(-4, 4, 100));
ax3.hist((tem2-temNN2)/tem2*100, bins=np.linspace(-4, 4, 100))
ax4.hist((den2-denNN2)/den2*100, bins=np.linspace(-4, 4, 100));
for ax in (ax1, ax2, ax3, ax4):
    ax.set_xlabel('Difference [%'])
```

```
[18]: # Now we run 4 more ANN to make a mean of the 5 results obtained. Takes time,
      ↪but if one have 10s of thousands of data, it deserves it.
diags.ANN_inst_kwargs['random_seed'] = 42
temNNb, denNNb = diags.getCrossTemDen(' [OIII] 4363/5007', ' [SII] 6731/6716',
      ↪rO3, rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)
temNN2b, denNN2b = diags.getCrossTemDen(' [NII] 5755/6584', ' [SII] 6731/6716',
      ↪rN2, rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)
diags.ANN_inst_kwargs['random_seed'] = 44
temNNc, denNNc = diags.getCrossTemDen(' [OIII] 4363/5007', ' [SII] 6731/6716',
      ↪rO3, rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)
temNN2c, denNN2c = diags.getCrossTemDen(' [NII] 5755/6584', ' [SII] 6731/6716',
      ↪rN2, rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)
diags.ANN_inst_kwargs['random_seed'] = 45
```

```

temNNd, denNNd = diags.getCrossTemDen('['OIII'] 4363/5007', '['SII'] 6731/6716',
    ↳rO3, rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)
temNN2d, denNN2d = diags.getCrossTemDen('['NII'] 5755/6584', '['SII'] 6731/6716',
    ↳rN2, rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)
diags.ANN_inst_kwargs['random_seed'] = 46
temNNe, denNNe = diags.getCrossTemDen('['OIII'] 4363/5007', '['SII'] 6731/6716',
    ↳rO3, rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)
temNN2e, denNN2e = diags.getCrossTemDen('['NII'] 5755/6584', '['SII'] 6731/6716',
    ↳rN2, rS2, use_ANN=True, end_den=1e6, start_tem=3e3, limit_res=False)

```

Instantiation. V 0.17

Training set size = 900, Test set size = 0

Train data scaled. Log10 applied.

Test data scaled.

Training set size = 900, Test set size = 0

Training set size = 900, Test set size = 0

Regression Model SK_ANN

Training 2 inputs for 2 outputs with 900 data

```

/Users/christophemorisset/anaconda3/lib/python3.7/site-
packages/sklearn/neural_network/_multilayer_perceptron.py:470:
ConvergenceWarning: lbfgs failed to converge (status=1):
STOP: TOTAL NO. of f AND g EVALUATIONS EXCEEDS LIMIT.

```

Increase the number of iterations (max_iter) or scale the data as shown in:

```

    https://scikit-learn.org/stable/modules/preprocessing.html
    self.n_iter_ = _check_optimize_result("lbfgs", opt_res, self.max_iter)
/Users/christophemorisset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:513: RuntimeWarning:
invalid value encountered in log10
    X = np.log10(X)

```

RM trained, with 13405 iterations. Score = 0.998

```

MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
    beta_2=0.999, early_stopping=False, epsilon=1e-08,
    hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
    learning_rate_init=0.001, max_fun=15000, max_iter=20000,
    momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
    power_t=0.5, random_state=42, shuffle=True, solver='lbfgs',
    tol=0.0001, validation_fraction=0.1, verbose=False,
    warm_start=False)

```

Training time 17.7 s.

Test data scaled. Log10 applied.

Training set size = 900, Test set size = 1751

Predicting from 2 inputs to 2 outputs using 1751 data in 0.00 secs.

Instantiation. V 0.17

Training set size = 900, Test set size = 0

Train data scaled. Log10 applied.

```

Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 2 outputs with 900 data
RM trained, with 7852 iterations. Score = 0.998
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
              beta_2=0.999, early_stopping=False, epsilon=1e-08,
              hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
              learning_rate_init=0.001, max_fun=15000, max_iter=20000,
              momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
              power_t=0.5, random_state=42, shuffle=True, solver='lbfgs',
              tol=0.0001, validation_fraction=0.1, verbose=False,
              warm_start=False)
Training time 10.1 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1763
Predicting from 2 inputs to 2 outputs using 1763 data in 0.00 secs.
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 2 outputs with 900 data

/Users/christophemorriset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:513: RuntimeWarning:
invalid value encountered in log10
  X = np.log10(X)

RM trained, with 12997 iterations. Score = 0.999
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
              beta_2=0.999, early_stopping=False, epsilon=1e-08,
              hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
              learning_rate_init=0.001, max_fun=15000, max_iter=20000,
              momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
              power_t=0.5, random_state=44, shuffle=True, solver='lbfgs',
              tol=0.0001, validation_fraction=0.1, verbose=False,
              warm_start=False)
Training time 16.6 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1751
Predicting from 2 inputs to 2 outputs using 1751 data in 0.00 secs.
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.

```

```

Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 2 outputs with 900 data

/Users/christophemorriset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:513: RuntimeWarning:
invalid value encountered in log10
  X = np.log10(X)
/Users/christophemorriset/anaconda3/lib/python3.7/site-
packages/sklearn/neural_network/_multilayer_perceptron.py:470:
ConvergenceWarning: lbfgs failed to converge (status=1):
STOP: TOTAL NO. of f AND g EVALUATIONS EXCEEDS LIMIT.

Increase the number of iterations (max_iter) or scale the data as shown in:
  https://scikit-learn.org/stable/modules/preprocessing.html
  self.n_iter_ = _check_optimize_result("lbfgs", opt_res, self.max_iter)
/Users/christophemorriset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:513: RuntimeWarning:
invalid value encountered in log10
  X = np.log10(X)

RM trained, with 13177 iterations. Score = 0.999
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
             beta_2=0.999, early_stopping=False, epsilon=1e-08,
             hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
             learning_rate_init=0.001, max_fun=15000, max_iter=20000,
             momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
             power_t=0.5, random_state=44, shuffle=True, solver='lbfgs',
             tol=0.0001, validation_fraction=0.1, verbose=False,
             warm_start=False)

Training time 17.2 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1763
Predicting from 2 inputs to 2 outputs using 1763 data in 0.00 secs.
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 2 outputs with 900 data
RM trained, with 9122 iterations. Score = 0.998
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
             beta_2=0.999, early_stopping=False, epsilon=1e-08,
             hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
             learning_rate_init=0.001, max_fun=15000, max_iter=20000,
             momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,

```

```

        power_t=0.5, random_state=45, shuffle=True, solver='lbfgs',
        tol=0.0001, validation_fraction=0.1, verbose=False,
        warm_start=False)
Training time 11.3 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1751
Predicting from 2 inputs to 2 outputs using 1751 data in 0.00 secs.
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 2 outputs with 900 data

/Users/christophemorisset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:513: RuntimeWarning:
invalid value encountered in log10
  X = np.log10(X)

RM trained, with 9507 iterations. Score = 0.999
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
             beta_2=0.999, early_stopping=False, epsilon=1e-08,
             hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
             learning_rate_init=0.001, max_fun=15000, max_iter=20000,
             momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
             power_t=0.5, random_state=45, shuffle=True, solver='lbfgs',
             tol=0.0001, validation_fraction=0.1, verbose=False,
             warm_start=False)
Training time 12.2 s.
Test data scaled. Log10 applied.
Training set size = 900, Test set size = 1763
Predicting from 2 inputs to 2 outputs using 1763 data in 0.00 secs.
Instantiation. V 0.17
Training set size = 900, Test set size = 0
Train data scaled. Log10 applied.
Test data scaled.
Training set size = 900, Test set size = 0
Training set size = 900, Test set size = 0
Regression Model SK_ANN
Training 2 inputs for 2 outputs with 900 data

/Users/christophemorisset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:513: RuntimeWarning:
invalid value encountered in log10
  X = np.log10(X)

/Users/christophemorisset/anaconda3/lib/python3.7/site-
packages/sklearn/neural_network/_multilayer_perceptron.py:470:

```

ConvergenceWarning: lbfgs failed to converge (status=1):
STOP: TOTAL NO. of f AND g EVALUATIONS EXCEEDS LIMIT.

Increase the number of iterations (max_iter) or scale the data as shown in:

```
https://scikit-learn.org/stable/modules/preprocessing.html
self.n_iter_ = _check_optimize_result("lbfgs", opt_res, self.max_iter)
/Users/christophemorisset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:513: RuntimeWarning:
invalid value encountered in log10
X = np.log10(X)
```

RM trained, with 13818 iterations. Score = 0.999

```
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
             beta_2=0.999, early_stopping=False, epsilon=1e-08,
             hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
             learning_rate_init=0.001, max_fun=15000, max_iter=20000,
             momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
             power_t=0.5, random_state=46, shuffle=True, solver='lbfgs',
             tol=0.0001, validation_fraction=0.1, verbose=False,
             warm_start=False)
```

Training time 18.2 s.

Test data scaled. Log10 applied.

Training set size = 900, Test set size = 1751

Predicting from 2 inputs to 2 outputs using 1751 data in 0.00 secs.

Instantiation. V 0.17

Training set size = 900, Test set size = 0

Train data scaled. Log10 applied.

Test data scaled.

Training set size = 900, Test set size = 0

Training set size = 900, Test set size = 0

Regression Model SK_ANN

Training 2 inputs for 2 outputs with 900 data

RM trained, with 12894 iterations. Score = 0.998

```
MLPRegressor(activation='tanh', alpha=0.0001, batch_size='auto', beta_1=0.9,
             beta_2=0.999, early_stopping=False, epsilon=1e-08,
             hidden_layer_sizes=(10, 30, 10), learning_rate='constant',
             learning_rate_init=0.001, max_fun=15000, max_iter=20000,
             momentum=0.9, n_iter_no_change=10, nesterovs_momentum=True,
             power_t=0.5, random_state=46, shuffle=True, solver='lbfgs',
             tol=0.0001, validation_fraction=0.1, verbose=False,
             warm_start=False)
```

Training time 18.1 s.

Test data scaled. Log10 applied.

Training set size = 900, Test set size = 1763

Predicting from 2 inputs to 2 outputs using 1763 data in 0.00 secs.

```
/Users/christophemorisset/anaconda3/lib/python3.7/site-
packages/sklearn/neural_network/_multilayer_perceptron.py:470:
ConvergenceWarning: lbfgs failed to converge (status=1):
```





STOP: TOTAL NO. of f AND g EVALUATIONS EXCEEDS LIMIT.

Increase the number of iterations (max_iter) or scale the data as shown in:

```
https://scikit-learn.org/stable/modules/preprocessing.html
self.n_iter_ = _check_optimize_result("lbfgs", opt_res, self.max_iter)
/Users/christophemorisset/Google
Drive/Pro/AI4neb/ai4neb/Regressor/RegressionModel.py:513: RuntimeWarning:
invalid value encountered in log10
X = np.log10(X)
```

```
[19]: # Compute the median of the 5 runs.
temNNm = np.median(np.array((temNN, temNNb, temNNc, temNNd, temNNe)),0)
temNN2m = np.median(np.array((temNN2, temNN2b, temNN2c, temNN2d, temNN2e)),0)
denNNm = np.median(np.array((denNN, denNNb, denNNc, denNNd, denNNe)),0)
denNN2m = np.median(np.array((denNN2, denNN2b, denNN2c, denNN2d, denNN2e)),0)
```

```
[20]: # Histogram of the differences: even better now.
f, ((ax1, ax2), (ax3, ax4)) = plt.subplots(2, 2, figsize=(10,10))
ax1.hist((tem-temNNm)/tem*100, bins=np.linspace(-4, 4, 100))
ax2.hist((den-denNNm)/den*100, bins=np.linspace(-4, 4, 100));
ax3.hist((tem2-temNN2m)/tem2*100, bins=np.linspace(-4, 4, 100))
ax4.hist((den2-denNN2m)/den2*100, bins=np.linspace(-4, 4, 100));
for ax in (ax1, ax2, ax3, ax4):
    ax.set_xlabel('Difference [%]')
```



[]: