
Large-scale ligand-based virtual screening for SARS-CoV-2 inhibitors using deep neural networks

Markus Hofmarcher^{1 2 *} Andreas Mayr^{1 2 *} Elisabeth Rumetshofer^{1 2 *} Peter Ruch^{1 2 *} Philipp Renz^{1 2 *}
Johannes Schimunek^{1 2 *} Philipp Seidl^{1 2 *} Andreu Vall^{1 2 *} Michael Widrich^{1 2 *} Sepp Hochreiter^{1 2 *}
Günter Klambauer^{1 2 *}

Abstract

Due to the current severe acute respiratory syndrome coronavirus 2 (SARS-CoV-2) pandemic, there is an urgent need for novel therapies and drugs. We conducted a large-scale virtual screening for small molecules that are potential CoV-2 inhibitors. To this end, we utilized “ChemAI”, a deep neural network trained on more than 220M data points over 3.6M molecules from three public drug-discovery databases. With ChemAI, we screened and ranked one billion molecules from the ZINC database for favourable effects against CoV-2. We then reduced the result to the 30,000 top-ranked compounds, which are readily accessible and purchasable via the ZINC database. We provide these top-ranked compounds as library for further screening with bioassays at <https://github.com/ml-jku/sars-cov-inhibitors-chemai>.

Introduction. Due to the current world-wide crisis of SARS-CoV-2 virus infections, there is a strong need for new therapies. While many efforts are focused on repurposing existing drugs (Zhou et al., 2020; Wang et al., 2020; Ton et al., 2020), we suggest to test new molecules with potentially higher efficacy. To this end, we performed a large-scale ligand-based virtual screening run, which resulted in 30,000 potential SARS-CoV-2 inhibitors with favorable properties. We actively outreach to the scientific community to test these molecules and consider them as a custom-designed chemical library.

Most current virtual screens are structure-based and use docking methods (Chen et al., 2020; Huang et al., 2020; Haider et al., 2020; Wang et al., 2020; Fischer et al., 2020;

Chen et al., 2020; Ton et al., 2020; Senathilake et al., 2020; Ruan et al., 2020; Jin et al., 2020; Zhang et al., 2020) while one is ligand-based and uses a similarity-based approach (Zhu et al., 2020). The largest docking studies screen databases with sizes ranging from roughly 700M (Fischer et al., 2020) to 1.3 billion (Ton et al., 2020) molecules. We as well operate in this range by screening a collection of one billion molecules from the ZINC database.

Deep ligand-based virtual screening. ChemAI is a deep neural network trained to simultaneously predict a large number of biological effects (Mayr et al., 2018; Preuer et al., 2019). Concretely, the network is trained on a data set comprised ChEMBL (Gaulton et al., 2017), ZINC (Sterling & Irwin, 2015) and PubChem (Kim et al., 2016), and which is similar to the data set used by Preuer et al. (2018). The network, called “ChemAI”, predicts in total 6,269 biological outcomes, such as binding to targets, inhibitory or toxicity effects. The network was trained in a multi-task setting, in which data from other bioassays is used to enhance the predictive power for SARS-CoV inhibitory effects. Each modelled biological effect is represented by an output neuron of the neural network. We utilized a small set of output neurons associated with SARS-CoV inhibition and a set of output neurons associated with toxic effects to rank compounds.

We screen the ZINC database because it provides a large set of diverse molecules and offers a link to vendors such that those molecules can readily be bought and obtained physically. We downloaded roughly 1 billion molecules from ZINC and converted them to canonical SMILES (Weininger, 1988) using RDKit (Landrum, 2006). We then performed inference with the network ChemAI to obtain predictions for each of those 1 billion molecules.

Bioassays. The SARS-CoV-2 has two main proteases that are critical for its replication, these are the 3CLpro(3C-like protease) and PLpro(Papain Like Protease) encoded by the open reading frame (Macchiagodena et al., 2020). A compound that inhibits both proteases (Ledford, 2009; Collison, 2019) could be a promising drug candidate. The

*Equal contribution ¹ELLIS Unit at the LIT AI Lab, Johannes Kepler University Linz, Austria ²Institute for Machine Learning, Johannes Kepler University Linz, Austria. Correspondence to: Günter Klambauer <klambauer@ml.jku.at>.

Assay ID	Source	#inact	#act	Description
1706	PubChem	193637	269	QFRET-based assay for SARS-CoV 3C-like Protease
1879	PubChem	167	86	QFRET-based assay for SARS-CoV 3C-like Protease (confirmation)
485353	PubChem	215030	390	Yeast-based Assay for SARS-CoV PLP
652038	PubChem	493	135	Yeast-based Assay for SARS-CoV PLP (validation)

Table 1. Overview of the main biological effects considered for ranking the molecules of the virtual screen. “#inact” and “#actAll” report the number of actives and inactives in the training set. All assays are based on inhibition of proteins of SARS-CoV-1.

proteases are also strikingly similar to those in SARS-CoV-1 (Macchiagodena et al., 2020), which is also an implicit assumption by docking-based approaches. We therefore select two groups of assays of which one measures the inhibition of 3CLpro and the other the inhibition of PLpro (see Table 1). For each of those four assays, ChemAI possesses an output unit, which models the ability of small molecules to exhibit the effect measured by the assay. Thus, using the predictions by ChemAI, it is possible to rank compounds by their predicted ability to inhibit the two main proteases of SARS-CoV-1, which can be a proxy for the inhibitory potential for SARS-CoV-2.

Consensus ranking. We developed a compound library which is enriched for molecules with the ability to inhibit both proteases of the SARS-CoV-2. For scoring the multi-target effect, we calculated a consensus score for each molecule as the average rank of the predictions in each of the four selected assays (see Table 1). We then ranked all compounds by this consensus score. For each of the top-ranked compounds, we also calculated their minimal distance to actives in the training set to be able to identify novel chemical structures. We also report the number of potential toxic effects of a compound (Mayr et al., 2016).

We implemented the overall process as a two-step approach. In the first step, we reduced the ZINC database of 1 billion molecules to a smaller set, where we kept all molecules that exhibited some predicted activity on any of the four assays, i.e. at least one of the predictions had to reside in the top-1% quantile. In this way, we obtained an intermediate dataset of 5,672,501 molecules. For those molecules, the consensus score, the toxicity-flags and the distance to known actives were calculated. In the second step, we reduced the dataset to the top-ranked 30,000 molecules by the consensus score.

Results. With the abovementioned approach, we have assembled a library of potential inhibitors of SARS-Cov-2. For each compound, we report three metrics for each compound: a) predicted inhibitory effect of SARS-CoV proteases b) potential toxicities and c) distance to known actives. This led to a ranked list of compounds of which we provide the top 30,000 as a screening library. The top-ranked molecules are given in Table 2 and Figure 1.

We also checked whether molecules suggested by other publications can be confirmed by ChemAI. Overall, some suggested molecules show at least mild predicted activity against SARS-CoV (see Table 3).

Discussion. In this work, we presented the construction of a screening library of small molecules that are potential inhibitors of SARS-CoV-2. Our ligand-based approach uses a neural network trained to predict the outcomes of bioassays. From this multi-task models, four tasks have been selected to predicting the inhibitory potential against SARS-CoV-1. A consensus between these predictions was used to rank compounds from the ZINC database, of which the 30,000 top-ranked are reported.

The approach is limited by the predictive quality of the underlying machine learning method, evaluated via the area-under-ROC-curve leading to values in the range of 0.69 to 0.78. While these results are very promising, improved data quality, amount of data or other machine learning approaches could lead to increased predictive performance and hence library. We expect that the data for SARS-CoV-1 already has high predictive power for inhibitory effects of compounds on SARS-CoV-2. However, the current predictions can be further adjusted toward SARS-CoV-2 via transfer-learning and incorporating new data from SARS-CoV-2. In particular few shot learning may be utilized for the first measurements for SARS-CoV-2 which will adjust the multi-task model toward SARS-CoV-2

Availability The library of molecules is available at <https://github.com/ml-jku/sars-cov-inhibitors-chemai>.

Acknowledgements

Funding by the Institute for Machine Learning (JKU). All authors contributed equally to this work.

References

Chen, Y. W., Yiu, C.-P. B., and Wong, K.-Y. Prediction of the sars-cov-2 (2019-ncov) 3c-like protease (3cl pro) structure: virtual screening reveals velpatasvir, ledipasvir,




Figure 1. Graphical representation of the top-ranked molecules by ChemAI.

zinc_id	smiles	dist	score	tox
ZINC000254565785	<chem>CNC(=S)NN=Cc1c2ccccc2c(Cl)c2ccccc12</chem>	0.5455	0.8244	8
ZINC000726422572	<chem>C=C(Cl)COc1ccc(C(C)=NNC(=S)NCCc2ccccc2)cc1</chem>	0.5333	0.8232	7
ZINC000916265995	<chem>CNC(=S)NN=Cc1cc2cccc(C)c2nc1Cl</chem>	0.6111	0.8230	5
ZINC000916356873	<chem>N#CCc1cc(C=NNC(=S)NCCc2ccc(Cl)cc2)c2ccccc21</chem>	0.6377	0.8221	17
ZINC000806591744	<chem>O=c1c(Br)nn(Cc2cnc3ccccc3c2)c2ccccc12</chem>	0.7258	0.8215	11
ZINC000178971373	<chem>O=c1c(Br)nn(Cc2nc3ccccc3s2)c2ccccc12</chem>	0.7288	0.8211	8
ZINC000000155607	<chem>CSC(=S)N/N=C/c1ccc2cc3ccccc3cc2c1</chem>	0.3902	0.8204	4
ZINC000016317677	<chem>C=CCNC(=S)NNC(=O)Cn1c(COc2ccc(Cl)cc2)nc2ccccc21</chem>	0.7000	0.8197	4
ZINC000193073749	<chem>O=C(Cn1cccc(Br)c1=O)c1ccc2ccccc2c1</chem>	0.6667	0.8197	1
ZINC000769846795	<chem>O=c1c(Br)nn(Cc2ccc3ncccc3c2)c2ccccc12</chem>	0.6949	0.8195	9
ZINC000755523869	<chem>CN(N=Cc1nc2ccccc2c1Br)C(=S)NCc1ccccc1</chem>	0.6452	0.8194	4
ZINC000763345954	<chem>C=CCNC(=S)NN=Cc1nc2ccc(Cl)cc2n1C</chem>	0.6508	0.8194	5
ZINC000001448699	<chem>CSC(=S)N/N=C/c1nc(-c2ccc(Cl)cc2)n2ccccc12</chem>	0.6866	0.8192	4
ZINC000016940508	<chem>C/C(=N\NC(=S)NNC(=S)N(C)c1ccccc1)c1nccc2ccccc12</chem>	0.6721	0.8191	11
ZINC000005486767	<chem>C/C(=N/NC(=S)NNC(=S)N(C)c1ccccc1)c1nccc2ccccc12</chem>	0.6721	0.8191	11
ZINC000005527649	<chem>CSC(=S)N/N=C/c1ccc2ccccc2n1</chem>	0.6327	0.8187	6
ZINC000755497029	<chem>C=CCNC(=S)NN=Cc1nc2cc(Cl)ccc2n1C</chem>	0.6719	0.8186	5
ZINC000746495682	<chem>FC(F)(F)CNC(=S)NN=Cc1cn(Cc2ccccc2)c2ccccc12</chem>	0.5690	0.8186	15
ZINC000005719506	<chem>CN(N=C/c1ccc(Cl)cc1)C(=S)c1ccccc1</chem>	0.6818	0.8178	4
ZINC000002149503	<chem>S=C(NC1ccccc1)N/N=C/c1cn(CCOc2ccc(Br)cc2)c2ccccc12</chem>	0.5625	0.8175	13

Table 2. Top-ranked molecules found by ChemAI. All compounds have a predicted high activity on all four assays (column "score") and are relatively distant (column "dist") to current known inhibitors. Some of the presented molecules might exhibit a number of toxic effects (column "tox").

- and other drug repurposing candidates. *F1000Research*, 9, 2020.
- Collison, J. Two targets are better than one. *Nature Reviews Rheumatology*, 15(7):386–386, 2019.
- Fischer, A., Sellner, M., Neranjan, S., Lill, M. A., and Smieško, M. Inhibitors for novel coronavirus protease identified by virtual screening of 687 million compounds. 2020.
- Gaulton, A., Hersey, A., Nowotka, M., Bento, A. P., Chambers, J., Mendez, D., Mutowo, P., Atkinson, F., Bellis, L. J., Cibrián-Uhalte, E., et al. The chembl database in 2017. *Nucleic acids research*, 45(D1):D945–D954, 2017.
- Glantz-Gashai, Y., Meirson, T., Reuveni, E., and Samson, A. O. Virtual screening for potential inhibitors of Mcl-1 conformations sampled by normal modes, molecular dynamics, and nuclear magnetic resonance. *Drug Des Devel Ther*, 11:1803–1813, 2017.
- Haider, Z., Subhani, M. M., Farooq, M. A., Ishaq, M., Khalid, M., Khan, R. S. A., and Niazi, A. K. In silico discovery of novel inhibitors against main protease (mpro) of sars-cov-2 using pharmacophore and molecular docking based virtual screening from zinc database. 2020.
- Huang, A., Tang, X., Wu, H., Zhang, J., Wang, W., Wang, Z., Song, L., Zhai, M.-a., Zhao, L., Yang, H., et al. Virtual screening and molecular dynamics on blockage of key drug targets as treatment for covid-19 caused by sars-cov-2. 2020.
- Jin, Z., Du, X., Xu, Y., Deng, Y., Liu, M., Zhao, Y., Zhang, B., Li, X., Zhang, L., Duan, Y., et al. Structure-based drug design, virtual screening and high-throughput screening rapidly identify antiviral leads targeting covid-19. *bioRxiv*, 2020.
- Kim, S., Thiessen, P. A., Bolton, E. E., Chen, J., Fu, G., Gindulyte, A., Han, L., He, J., He, S., Shoemaker, B. A., et al. Pubchem substance and compound databases. *Nucleic acids research*, 44(D1):D1202–D1213, 2016.
- Landrum, G. RDKit: Open-source cheminformatics, 2006. URL <http://www.rdkit.org>.
- Ledford, H. One drug, two targets, 2009.
- Lim, L., Roy, A., and Song, J. Identification of a zika ns2b-ns3pro pocket susceptible to allosteric inhibition by small molecules including quercetin rich in edible plants. *bioRxiv*, 2016. doi: 10.1101/078543. URL <https://www.biorxiv.org/content/early/2016/10/01/078543>.

- Macchiagodena, M., Pagliai, M., and Procacci, P. Inhibition of the main protease 3cl-pro of the coronavirus disease 19 via structure-based ligand design and molecular modeling. *arXiv preprint arXiv:2002.09937*, 2020.
- Mayr, A., Klambauer, G., Unterthiner, T., and Hochreiter, S. Deeptox: toxicity prediction using deep learning. *Frontiers in Environmental Science*, 3:80, 2016.
- Mayr, A., Klambauer, G., Unterthiner, T., Steijaert, M., Wegner, J. K., Ceulemans, H., Clevert, D.-A., and Hochreiter, S. Large-scale comparison of machine learning methods for drug target prediction on chembl. *Chemical science*, 9(24):5441–5451, 2018.
- Preuer, K., Renz, P., Unterthiner, T., Hochreiter, S., and Klambauer, G. Fréchet chemnet distance: a metric for generative models for molecules in drug discovery. *Journal of chemical information and modeling*, 58(9):1736–1741, 2018.
- Preuer, K., Klambauer, G., Rippmann, F., Hochreiter, S., and Unterthiner, T. Interpretable deep learning in drug discovery. In *Explainable AI: Interpreting, Explaining and Visualizing Deep Learning*, pp. 331–345. Springer, 2019.
- Ruan, Z., Liu, C., Guo, Y., He, Z., Huang, X., Jia, X., and Yang, T. Potential inhibitors targeting rna-dependent rna polymerase activity (nsp12) of sars-cov-2. 2020.
- Senathilake, K., Samarakoon, S., and Tennekoon, K. Virtual screening of inhibitors against spike glycoprotein of 2019 novel corona virus: a drug repurposing approach. 2020.
- Sterling, T. and Irwin, J. J. Zinc 15–ligand discovery for everyone. *Journal of chemical information and modeling*, 55(11):2324–2337, 2015.
- Ton, A.-T., Gentile, F., Hsing, M., Ban, F., and Cherkasov, A. Rapid identification of potential inhibitors of sars-cov-2 main protease by deep docking of 1.3 billion compounds. *Molecular Informatics*, 2020.
- Wang, Q., Zhao, Y., Chen, X., and Hong, A. Virtual screening of approved clinic drugs with main protease (3clpro) reveals potential inhibitory effects on sars-cov-2. 2020.
- Weininger, D. Smiles, a chemical language and information system. 1. introduction to methodology and encoding rules. *Journal of chemical information and computer sciences*, 28(1):31–36, 1988.
- Wu, C., Liu, Y., Yang, Y., Zhang, P., Zhong, W., Wang, Y., Wang, Q., Xu, Y., Li, M., Li, X., Zheng, M., Chen, L., and Li, H. Analysis of therapeutic targets for sars-cov-2 and discovery of potential drugs by computational methods. *Acta Pharmaceutica Sinica B*, 2020. ISSN 2211-3835. doi: <https://doi.org/10.1016/j.apsb.2020.02.008>. URL <http://www.sciencedirect.com/science/article/pii/S2211383520302999>.
- Zhang, J.-J., Shen, X., Yan, Y.-M., Yan, W., and Cheng, Y.-X. Discovery of anti-sars-cov-2 agents from commercially available flavor via docking screening. 2020.
- Zhou, Y., Hou, Y., Shen, J., Huang, Y., Martin, W., and Cheng, F. Network-based drug repurposing for novel coronavirus 2019-ncov/sars-cov-2. *Cell Discovery*, 6(1): 1–18, 2020.
- Zhu, Z., Wang, X., Yang, Y., Zhang, X., Mu, K., Shi, Y., Peng, C., Xu, Z., et al. D3similarity: A ligand-based approach for predicting drug targets and for virtual screening of active compounds against covid-19. 2020.

ZINC-ID	Trivial-Name(s)	Canonical Smiles	Publications
ZINC00057060	Melatonin	<chem>COc1ccc2[nH]cc(CCNC(C)=O)c2c1</chem>	Zhou et al. (2020)
ZINC03869685	Meletin, Quercetin	<chem>O=c1c(O)c(-c2ccc(O)c(O)c2)oc2cc(O)cc(O)c12</chem>	Lim et al. (2016)
ZINC85537142	Aclarubicin	<chem>CC[C@@]1(O)C[C@H](O[C@H]2C[C@H](N(C)C)[C@H](O[C@H]3C[C@H](O)[C@H](O[C@H]4CCC(=O)[C@H](C)O4)[C@H](C)O3)[C@H](C)O2)c2c(cc3c(c2O)C(=O)c2c(O)cccc2C3=O)[C@H]1C(=O)OC</chem>	Senathilake et al. (2020)
ZINC03794794	Mitoxantrone	<chem>C1=CC(=C2C(=C1NCCNCCO)C(=O)C3=C(C=CC(=C3C2=O)O)O)NCCNCCO</chem>	Wang et al. (2020)
ZINC01668172	-	<chem>O=C(C[n+]1ccc2cccc2c1)c1ccc2ccc3ccccc3c2c1</chem>	Glantz-Gashai et al. (2017)
ZINC03830332	E155	<chem>C1=CC=C2C(=C1)C(=CC=C2S(=O)(=O)O)NN=C3C=C(C(=O)C(=NNC4=CC=C(C5=CC=CC=C54)S(=O)(=O)O)C3=O)CO</chem>	Senathilake et al. (2020)
ZINC14879972	Gar-936	<chem>CN(C)c1cc(NC(=O)CNC(C)(C)C)c(O)c2c1C[C@H]1C[C@H]3[C@H](N(C)C)C(O)=C(C(N)=O)C(=O)[C@@]3(O)C(O)=C1C2=O</chem>	Wu et al. (2020)
ZINC00001645	Magnolol	<chem>C=CCc1ccc(O)c(-c2cc(CC=C)ccc2O)c1</chem>	Wu et al. (2020)
ZINC00014036	Piceatannol	<chem>Oc1cc(O)cc(/C=C/c2ccc(O)c(O)c2)c1</chem>	Wu et al. (2020)
ZINC16052277	Doxycycline	<chem>C[C@H]1c2cccc(O)c2C(=O)C2=C(O)[C@]3(O)C(=O)C(C(=N)O)=C(O)[C@@H](N(C)C)[C@@H]3[C@@H](O)[C@@H]21</chem>	Wu et al. (2020)
ZINC3920266	Idarubicin	<chem>CC(=O)[C@]1(O)Cc2c(O)c3c(c(O)c2[C@@H](O[C@H]2C[C@H](N)[C@H](O)[C@H](C)O2)C1)C(=O)c1cccc1C3=O</chem>	Wu et al. (2020)

Table 3. Compounds suggested in related publications for potential activity against SARS-CoV-2 and which also exhibit at least mild predicted activity against and SARS-CoV proteases by ChemAI.