Mainstream Java

Handling Exceptions



```
URL myURL = new URL(someString);
//code that uses myURL
//e.g., connects to it and reads data
```

- Have code which might throw an exception
 - Example: MalformedURLException



```
try {
   URL myURL = new URL(someString);
   //code that uses myURL
   //e.g., connects to it and reads data
}
```

- Try-block:
 - Code that might throw an exception



```
try {
   URL myURL = new URL(someString);
   //code that uses myURL
   //e.g., connects to it and reads data
}
catch (MalformedURLException mfe) {
   //code to handle the error
}
```

- Catch block
 - Specifies what to do if exception is thrown



```
URL myURL = new URL(someString);
  //code that uses myURL
  //e.g., connects to it and reads data
}
catch (MalformedURLException mfe) {
  //code to handle the error
}
```

- Normal execution (no exception)
 - someString = "http://www.duke.edu"



```
URL myURL = new URL(someString);
//code that uses myURL
//e.g., connects to it and reads data
}
catch (MalformedURLException mfe) {
   //code to handle the error
}
```

- Normal execution (no exception)
 - someString = "http://www.duke.edu"



```
URL myURL = new URL(someString);
//code that uses myURL
//e.g., connects to it and reads data
}
catch (MalformedURLException mfe) {
   //code to handle the error
}
```

- Normal execution (no exception)
 - someString = "http://www.duke.edu"



```
try {
    URL myURL = new URL(someString);
    //code that uses myURL
    //e.g., connects to it and reads data
    catch (MalformedURLException mfe) {
        //code to handle the error
    }
```

- Normal execution (no exception)
 - someString = "http://www.duke.edu"



```
try {
  URL myURL = new URL (someString);
  //code that uses myURL
  //e.g., connects to it and reads data
catch (MalformedURLException mfe) {
   //code to handle the error
```

- Normal execution (no exception)
 - someString = "http://www.duke.edu"



```
URL myURL = new URL(someString);
  //code that uses myURL
  //e.g., connects to it and reads data
}
catch (MalformedURLException mfe) {
  //code to handle the error
}
```

- Exception is thrown
 - someString = "blahblahblah"



```
try {

INTERPORTED URL myURL = new URL(someString);
    //code that uses myURL
    //e.g., connects to it and reads data
}
catch (MalformedURLException mfe) {
    //code to handle the error
}
```

- Exception is thrown
 - someString = "blahblahblah"



```
try {
   URL myURL = new URL(someString);
   //code that uses myURL
   //e.g., connects to it and reads data
}
catch (MalformedURLException mfe) {
   //code to handle the error
}
```

- Exception is thrown
 - someString = "blahblahblah"



```
try {
   URL myURL = new URL(someString);
   //code that uses myURL
   //e.g., connects to it and reads data
}
catch (MalformedURLException mfe) {
   //code to handle the error
```

- Exception is thrown
 - someString = "blahblahblah"



```
try {
  URL myURL = new URL (someString);
  //code that uses myURL
  //e.g., connects to it and reads data
catch (MalformedURLException mfe) {
   //code to handle the error
```

- Exception is thrown
 - someString = "blahblahblah"



Handling Exceptions: Finally

```
try {
  URL myURL = new URL (someString);
  //code that uses myURL
  //e.g., connects to it and reads data
catch (MalformedURLException mfe) {
   //code to handle the error
 finally {
   //code to do whether exception or not
```

• Finally: always executed

