


Introduction to Graph Theory

Alberto Calderone




Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Seven Bridges of Königsberg



Leonhard Euler



The problem was to devise a walk through the city that would cross each bridge once and only once. Under the following conditions:

- 1) The islands could only be reached by the bridges
- 2) Every bridge once accessed must be crossed to its other end
- 3) The starting and ending points of the walk need not be the same


Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Seven Bridges of Königsberg

- The year 1736 can be considered the beginning of graph theory when EULER considered the Seven Bridges of Königsberg problem.
- 200 years later the first book on graph theory was written:
 - "Theorie der endlichen und unendlichen Graphen", by König in 1936.
- Since then, graph theory has developed into an extensive branch of mathematics, which has been applied to many problems in science and other areas.



Leonhard Euler




Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Seven Bridges of Königsberg



Leonhard Euler



The problem was to devise a walk through the city that would cross each bridge once and only once. Under the following conditions:


- 1) The islands could only be reached by the bridges
- 2) Every bridge once accessed must be crossed to its other end
- 3) The starting and ending points of the walk need not be the same

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Definition of Graph (Network)

A **graph** is a pair $G=(V,E)$ consisting of two sets:

- V is a set of elements called **Nodes** or **Vertices**
- E is a set of pairs (v_i, v_j) where $v_i \in V$ and $v_j \in V$.
These pairs are links between two elements called **Edges**



$$V = \{A; B; C; D\}$$


$$E = \{(A, B); (A, C); (B, C); (B, D); (C, D)\}$$

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Seven Bridges of Königsberg




Leonhard Euler



Solution: a graph is walkable without passing twice on the same edge if and only if all its nodes have an even number of connections, or if two of them have an odd number of connections; to travel a graph of this second type, it is necessary to start from one of the two nodes with an odd number of connections ending the walk on the other one.

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni


Protein Interactions Networks



Protein Interactions Networks


Simple Graph

EXAMPLE 1 (Friends) :
 $V = \{ \text{People living in Italy} \}$
 $E = \{ \text{Pairs of friends} \}$



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Food Chain Networks




Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Food Chain Networks


Directed Graph

EXAMPLE 2 (Mail) :
 $V = \{ \text{People living in Italy} \}$
 $E = \{ (x,y) : x \text{ sent a mail to } y \}$



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Signalling Networks




Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Signalling Networks


Signed Directed Graph

EXAMPLE 3 (Biological Signalling Networks) :
 $V = \{ \text{Proteins in a cell} \}$
 $E = \{ \text{Protein A activates/inactivates protein B} \}$



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni


Networks are Everywhere...



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Some Important Results


Enumeration: counting graphs meeting specified conditions.



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Some Important Results


Subgraphs, induced subgraphs: finding the largest complete subgraph, finding the largest edgeless induced subgraph.



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni


Some Important Results

Graph colouring: it is an assignment of labels traditionally called "colours" to elements of a graph subject to certain constraints.




Some Important Results

Route problems: weighted or unweighted path discovery, spanning trees.




Some Important Results

Network flow: maximum amount of flow passing from the source to the target.




Complex Networks

Network




Complex Network




Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Complex Networks

Network




Complex Network



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Graph Models



<http://160.80.34.9/elixir2015/>

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Activity: Describing Graphs


Nodes and edges Characteristics

- Definition of “Degree”
 - Definition of “Betweenness” (*)
 - Definition of “Transitivity” (*)


(*) Not easy

<http://160.80.34.9/elixir2015/>

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni



Definitions



Degree k_i = number of links connected to node i



Distance d_{ij} = shortest path length between node i and j




Diameter $D = \max \{ d_{ij} | i, j \in N \}$ N : all nodes in the network

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni



Definitions



$$\begin{array}{ll} \text{Transitivity} & c_i = \frac{2e_i}{k_i(k_i - 1)} \\ \text{or} \\ \text{Clustering} & e_i : \text{number of existing links (labeled in red) among the } k_i \text{ nodes that connect to node } i \\ \text{Coefficient} & \end{array}$$



Betweenness	$b_i = \sum_{ij} p_{ij}(i) / p_{ij}$	p_{ij} : number of shortest paths between i and j
Defined for Nodes and Edges		$p_{ij}(i)$: number of shortest paths between i and j going through node i

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Activity: Describing Graphs

Nodes and edges Characteristics

- Definition of "Degree"
- Definition of "Betweenness" (*)
- Definition of "Transitivity" (*)

Global characteristics

(*) Not easy



- Compare different graphs
- Find characteristics

<http://160.80.34.9/elixir2015/>

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Random Networks Model (Erdős-Rényi Model)



- 1) Starting from a set of n vertices
- 2) Give two random vertices there is a probability P that they are linked together



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Random Networks Characteristics (Erdős-Rényi Model)

- 1) High node degree => Short Average Path Length
- 2) Degree distribution follows Normal Distribution
- 3) Small Betweenness
- 4) High Transitivity





Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Small-World Networks Model

(Watts and Strogatz Model)

- 1) Generate a lattice
- 2) Nodes are initially linked to k closest neighbours
- 3) Apply a rewiring probability





Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Small-World Networks Characteristics

(Watts and Strogatz Model)

- 1) Small node degree => "Six-Degrees of Separation"
- 2) Degree distribution follows Poisson Distribution
- 3) Betweenness smaller than Scale-Free
- 4) Transitivity: smaller than Random, Higher than Scale-Free



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni


Scale-Free Networks

(Barabási-Albert Model)


- 1) Smallest node degree
- 2) Degree distribution follow Power-Law
- 3) Highest Betweenness
- 4) Transitivity: smallest

Scale-free refers to any function $f(x)$
That remains unchanged to within a multiplicative factor under a rescaling of x .
This means power-law since these are the only solutions to $f(ax)=bf(x)$.

Preferential Attachment: The rich gets richer



This is called "tree"





Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Natural Networks


(Biological Networks)

- 1) Small-World & Scale-Free
- 2) Small Node Degree, Short Path Length, Power-Law
- 3) Betweenness between Small-World and Scale-Free
- 4) Transitivity higher than Small-World and Scale Free
- 5) Average path length $\ln(\ln(n))$



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Communities (or Clusters)




The presence of communities in a graph is one of the most important features.

- For biologists to detect proteins with the same function
- For physicians to detect related diseases
- Communities are important for Amazon, to run their businesses

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Communities Discovery Algorithms




- Modularity - Edge-Betweenness Algorithm
modularity is the fraction of edges that fall within a given group minus the expected fraction if edges were distributed at random (*it is unable to detect small communities*)
Biological networks, including animal brains, exhibit a high degree of modularity

- Other Algorithms - e.g. Information Theory

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Network Motifs




Motifs can be seen as the smallest version of communities

Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Network Robustness

Complex systems tend to have a surprising degree of tolerance to errors (Robustness):


- Biological networks persist despite environmental noise, mutations, attacks ...
- Communication networks resist to malfunctions, hackers, nodes failure




Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Network Robustness

Preferential Attachment




Random




Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Network Robustness

Preferential Attachment




Random




Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Network Robustness

Homo Sapiens



Random Network



Scale-Free
Preferential Attachment



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni

Conclusions

- What is a graph/network
- Type of graphs
 - Simple, Directed, Signed
- Graph Algorithms Overview
- Graph Models
 - Random, Scale-Free, Small-World, Preferential attachment
- How to describe graphs: specific characteristics
 - Degree, Betweenness, Transitivity, Distance
- Complex Networks: Global Characteristics
- Networks Structure
 - Communities, Motifs
- Networks Robustness



Bioinformatics and Computational Biology Unit
Molecular Genetics Laboratory - University of Rome Tor Vergata - prof. Gianni Cesareni