

PHL245 Modern Symbolic Logic

© Tingfeng Xia

Fall 2019, modified on September 6, 2019

This work is licensed under a Creative Commons
“Attribution-NonCommercial-ShareAlike 4.0 In-
ternational” license.



Contents

1	Truth Tables	2
1.1	Summary.	2
1.2	Full truth tables	2

1 Truth Tables

1.1 Summary.

First we remark that we are here talking about binary operators, so they will have and only have two operands. We have the following to consider:

- **Logical OR** (\vee) is true when either one of the operands is true. It evaluates to false otherwise.
- **Logical AND** (\wedge) is true when both of the operands are true and false otherwise.
- **Implication** (\implies) is true in two cases. The first case is when the first operand is false and second case is when both operands are true.
- **Double implication, Iff** (\iff) is true when either both operands are true or when both operands are false.

1.2 Full truth tables

Example: ¹ evaluate $(P \wedge \neg Q) \vee R. \neg R \vee Q. \therefore \neg P \implies Q$. Notice that this is equivalent to evaluating

$$(((P \wedge \neg Q) \vee R) \wedge (\neg R \vee Q)) \implies \neg P \implies Q$$

and by staring at it we see this statement is valid and only valid when $(P, Q, R) \in \{(T, T, T), (T, F, F), (F, T, T)\}$, which has a non-null set of solution. Hence the statement is consistent.

¹This example was adapted from Scharer 4.4 EG3.