04 - Iteration Control Structures

For example:

Input	Result
20	1 2 4 5 10 20

Ex. No. : 4.1 **Date:**

Register No.: **Name:**

Factors of a number

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number).

```
n=int(input())
for i in range(1,n+1):
      if (n%i==0):
         print(i,end=“ ”)
```

For example:

Input	Result
292	1
1015	2
108	3
22	0

Ex. No. : 4.2 **Date:**

Register No.: **Name:**

Non Repeated Digit Count

Write a program to find the count of non-repeated digits in a given number N. The number will be passed to the program as an input of type int.
Assumption: The input number will be a positive integer number >= 1 and <= 25000.
Some examples are as below.
If the given number is 292, the program should return 1 because there is only 1 non--repeated digit '9' in this number
If the given number is 1015, the program should return 2 because there are 2 non-repeated digits in this number, '0', and '5'.
If the given number is 108, the program should return 3 because there are 3 non--repeated digits in this number, '1', '0', and '8'.
If the given number is 22, the function should return 0 because there are NO non--repeated digits in this number.

```
n=input()
m={}
for i in n :
        if i in m :
                m[i]+=1
p=0
for i in m.values():
         if i==1:
                  p=p+1
print(p)
```

Example1: if the given number N is 7, the method must return 2

Example2: if the given number N is 10, the method must return 1

For example:

Input	Result
7	2
10	1

Ex. No. : 4.3 **Date:**

Register No.: **Name:**

Prime Checking

Write a program that finds whether the given number N is Prime or not. If the number is prime, the program should return 2 else it must return 1.

Assumption: 2 <= N <=5000, where N is the given number.

```
n=int(input())
temp= 2
if n >= 2 and n <= 5000 :
    for i in range (2, n):
        if n% * i ==0 :
            temp= 1
             break
if temp=-1:
      print (1)
else:
      print(2)|
```

Input Format:

Integer input from stdin.

Output Format:

Perfect square greater than N.

Example Input:

10

Output:

16

Ex. No. : 4.4 **Date:**

Register No.: **Name:**

Next Perfect Square

Given a number N, find the next perfect square greater than N.

```
n=int(input())
m=0
for i in range (1, n) :
    if (i * i>n) :
        m =i* i
        break
print(m)
```

NOTE: Fibonacci series looks like –

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, . . . and so on.

i.e. Fibonacci series starts with 0 and 1, and continues generating the next number as the sum of the previous two numbers.

- first Fibonacci number is 0,
- second Fibonacci number is 1,
- third Fibonacci number is 1,
- fourth Fibonacci number is 2,
- fifth Fibonacci number is 3,
- sixth Fibonacci number is 5,
- seventh Fibonacci number is 8, and so on.

For example:

Input:

7

Output

8

Ex. No. : 4.5 **Date:**

Register No.: **Name:**

Nth Fibonacci

Write a program to return the nth number in the fibonacci series. The value of N will be passed to the program as input.

```
n=int(input())
temp= 0
a = 1
s = 0
for i in range (0, n) :
    s =temp+a
    a=temp
    temp= s
print(a)
```

Input Format:

Single Integer Input from stdin.

Output Format:

Yes or No.

Example Input:

175

Output:

Yes

Explanation

1^1 + 7^2 +5^3 = 175

Example Input:

123

Output:

No

For example:

Input	Result
175	Yes
123	No

Ex. No. : 4.6 **Date:**

Register No.: **Name:**

Disarium Number

A Number is said to be Disarium number when the sum of its digit raised to the power of their respective positions becomes equal to the number itself. Write a program to print number is Disarium or not.

```
n =int(input())
num = len(str(n))
p = num
q = n
r = 0
sum=0
for i in range(0,num):
    r = n% * 10
    sum = sum + r **p
    p = p - 1
    n =n//10
if um ==q :
   print("Yes")
else:
   print("No")
```

Sample Test Cases

Test Case 1

Input

4

Output

1234

Explanation:

as input is 4, have to take 4 terms.

1 + 11 + 111 + 1111

Test Case 2

Input

6

Output

123456

For example:

Input	Result
3	123

Ex. No. : 4.7 **Date:**

Register No.: **Name:**

Sum of Series

Write a program to find the sum of the series 1 +11 + 111 + 1111 + . . . + n terms (n will be given as input from the user and sum will be the output)

```
n=int(input())
sum = 1
C = 1
for i in range (1, n) :
    sum =sum * 10+1
    C = C + sum
print(C)
```

For example:

Input	Result
292	2
1015	3

Ex. No. : 4.8 **Date:**

Register No.: **Name:**

Unique Digit Count

Write a program to find the count of unique digits in a given number N. The number will be passed to the program as an input of type int.
Assumption: The input number will be a positive integer number >= 1 and <= 25000.
For e.g.
If the given number is 292, the program should return 2 because there are only 2 unique digits '2' and '9' in this number
If the given number is 1015, the program should return 3 because there are 3 unique digits in this number, '1', '0', and '5'.

```
n=int(input())
a =[ ]
while n >0:
    if n%10 not in a:
       a.append(n%10)
    n =n//10
print(len(a))
```

Input Format:

Single Integer input.

Output Format:

Output displays Yes if condition satisfies else prints No.

Example Input:

14

Output:

Yes

Example Input:

13

Output:

No

Ex. No. : 4.9 **Date:**

Register No.: **Name:**

Product of single digit

Given a positive integer N, check whether it can be represented as a product of single digit numbers.

```
n =int(input())
if( n%2 ==0 or n%3 ==0 or n%5 ==0 or n%7 ==0) :
    print (" Yes ")
else:
    print (" No ")
```

Input Format:

Single integer input.

Output Format:

Yes or No.

Example Input:

24

Output:

Yes

Example Input:

26

Output:

No

For example:

Input	Result
24	Yes

Ex. No. : 4.10 **Date:**

Register No.: **Name:**

Perfect Square After adding One

Given an integer N, check whether N the given number can be made a perfect square after adding 1 to it.

```
n=int(input())+1
a = 0
if(n==0 or n ==1) :
   a = 1
for i in range ( 2 ,(n//2)) :
      if (n==i*i) :
      a = 1
      break
if a ==1 :
      print("Yes")
else:
      print (" No ")
```