Technical configuration Schindler	Created by : I_PI_CRM Last change : GHEORGAD	Date: 31.10.2025 Date: 09.06.2026

Sales Order : 11915007 Page: 1
Equipment :
Project name: STONEYARD, BIRMINGHAM - PHASE 1

Sales men : 137054 Keith Docherty
Engineer :
Supervisor : 193732 Graham Whitehead
MDC contact : 20089465 Ansar Aboo Hameed

Address Sold-to party: Caddick Construction Limited
31 Temple Street
B2 5DB Birmingham

Address Ship-to party: Stoneyard, Birmingham - Phase 1
High Street
B9 4LS Birmingham

Configuration Text
The following characteristics with the material
940087 F3 EOS EU Sourcing
and position 200 were seized.

Characteristic description	Characteristic value
SD document category	Order
Configuration Status	Complete and Consistent
Building condition (Info)	dry
Equipment manufacturer	SCHINDLER
Elevator Name	L3 FF
Building Name	BLOCK F
Public Access (Info)	No
Type of Elevator Installation	New Elevator
Car Front Stainl.steel type	AISI 441
Group LOPs	LOP delivery with this lift
Communication options	Voice synthesizer on car
Communication options	Triphonie
Communication options	Remote Monitoring.
Communication options	Inductive loop
Control options	Pre-opening doors
Control options	Automatic return to main floor
Control options	Building management interface
Control options	STM Monitoring
Balancing of load	50.00 %
Machine room location	Machine room less
Height door drive above HT HTA	341 mm
Effective car area	2.24 m2
Drive system	Frequency controlled
Control system technology	Micro Processor
Control manufacturer	SCHINDLER
Landing door operation	Automatic
Landing door system	Hor. Centr. Sliding Door 2 Pan
Car buffer location	Pit
Engineering hours MDC	45.00 h
Engineering hours total	8.00 h

Total LSM hours set on 0 to 14	10.00 h
Local inst. time not Prod	0.00 h
Local installation time	250.50 h
Installation hours KG	219.90 h
Total installation hours	480.40 h
Travel hours	0.0
Project manager hours	41.00 h
SAIS inspector hours total	10.80 h
Opt: accessibl.space below pit	No
Lighting switch JHL type	RCBO_C10A_30_A
Option Pakages Selected	NONE
Option Pakages Upselling	NONE
TA/RM Connection type	Via mobile (wireless) CUBE
STM supplier	Megadyne
Gear ratio IW	1/1
Motor brake/winding type	PML145-K10-420
Communication functions	Remote monitoring
Communication functions	Inductive loop
Performance functions	Automatic releveling
Performance functions	Automatic return to main floo
Performance functions	Door pre-opening
Dedicated travel functions	Independ. service with parking
Supplementary functions	Auto.door closing with f.time
Supplementary functions	Building monitoring interface
Monitoring functions	Passenger release alt. landing
Intercom options	Car
Intercom options	Control
Building category	Apartments / Condominium
Balustrade Option	No
Balustrade Calculated	Yes
Braille	Not ordered
Opt: brand logo	Yes
Button technology	Mechanical push buttons
Code for car area calculation	EN_81-20:2020
Car light activation	Automatic
Car mirror locations	Rear
Opt: rear car wall with radius	No
Car size	FLEXI
Control function level	Level 2
Door flexibility level	Level 2
Decoration level	Level 2
Opt: emergency exit	No
Energy calculation	Show VDI+ISO calculation
Energy efficiency optimization	No
Max cust.deco.weight % GQ	30.00 %
Handrail location	Left wall
Handrail location	Right wall
Handrail location	Back wall
Handrail relevance	Yes, Standard
Opt: revolving handrail	No
Hoisting facilities	Hoisting hooks
Light in Hoistway Relevance	Yes

Opt: hoistway prep. removal	No
Installation method - Hoistway	Laser
Opt: ISO express zone	0
1way travel short circle ISO	14.625 m
Usage category ISO 25745-2	medium (300 trips per day)
Key types LOP	None
Lamp types LOP	None
Landing door category	Standard
Decoration of landing doors	Stainless steel
Hoistway wall type at landing	Closed with cut-out
LIP constellation	Arrows + pos. on all landings
Mirror relevance	Yes
Opt: only solid guide rails	Yes
Owner document. prepared by	Field operations
Material distribution by	Schindler
Pit ladder delivery	No Pit Ladder Required
Opt: pos indic.on all landings	Yes
Opt: pos. indic. main landing	No
Program scope mode	Based on car dimensions.
Ride quality	Medium
Second_COP_relevance	No
Opt: second car door lock	No
Special application level	Level 2
Travel demand class VDI	A
Specific travel demand VDI	0.35
Standby demand VDI	47 W
Standby demand class VDI	A
VDI usage category	Medium
Clear car height HKC	2,400 mm
Travel direction Indication	No
Arrival and Further travel Ind	Yes
CWT_Safety_Gear_Default	N
LIP Orientation	Vertical
LIP Mounting	Surface mounted
Starting nominal current INA	24.06 A
Mains distortion at JH and INN	0.99
Shared LOPs in Goup	No
CWT weight without filling mat	131 kg
Relevelling Relevance	Yes
Landing door lock optional	Latch lock EN81
Hoist. lighting switch type	RCBO C10A 30mA Type A
Car OPTIONS	Front and doors in stain.steel
Car OPTIONS	Light curtain on car entrance
Car OPTIONS	Mirror
Car OPTIONS	Handrail
Elevator model	1000_1600_1400_C2_900
Group LOP mounting	Surface vertical in wall
Landing door lock Type	01/C
Total Qty keys in COP 1	1
Weight for Custom Floor	95
Land. door lock cert number	ATV 616/5
Material of the Hoistway (Def.	Concrete

Technical configuration Schindler	Created by : I_PI_CRM Last change : GHEORGAD	Date: 31.10.2025 Date: 09.06.2026

Sales Order : 11915007 **Page: 4**
Equipment :
Project name: STONEYARD, BIRMINGHAM - PHASE 1

Opt: building inform. modeling	No
Tripping speed governor car	1.84 ... 2.15
Weight of add. custom deco	50.00 kg
Number of hoistway entrances	7
Car Weight use in INEX Install	833 kg
Language of owner manual	English
Type of owner manual	With maintenance instruction
VDI energy demand year	1,505.000
Group LOP Glass Color	Black
CAMOS Quantyty Error	1
Installing company	Schindler
EN81_71 Relevance	No
EN81_58 Relevance	Yes
EN81_72 Relevance	No
Car descent due to 1 person	1 mm
Clear car width incl. cladding	1,586 mm
Estimation of dismantling Cost	Not Required
1.Car entrance return BKF1	54 mm
EN81-70 Relevance	Yes
Guide Rail HMAIN	1,800 mm
LBLC_ES5_12_LastResultCode	0
Opt: media screen in car	No
Opt: third party fixtures	No
ISO Energy Efficiency	A
Main regulation code	EN81-20/50
Opt: customized rail length	No
Contract type	410
Opt: BR1 acc. to LWTG	No
Converter category	VAF0xx REGEN
EN81-73 Relevance	Yes
Category of car acc. EN 81-70	1 wheelchair + 1 person
Opt: basic residential requir.	No
Anual energy demand ISO25745-5	1,000 kwh
ISO Number Trips per Day	300
Idle power of the elevator ISO	69.58 W
Standby power after 30min ISO	47.14 W
Standby power after 5min ISO	47.14 W
Fixtures type COPH Info	Not Relevant
Fixtures type COPV Info	FI GS 300
Fixtures type LOP Info	FI GS 300
Fixtures type LIP Info	FI GS 300
LD Door Fire-Rating 1 Qty	7
LD Door Fire-Rating type 1	EN_81-58_E120
LD Door Finish 1 Qty	7
LD Door Finish 1	SS441_BRUS
FREIGHT_20	0
FREIGHT_40	0
LC Charges(USD)	0.000
HCOP on left side wall	No
Position of fan on car roof	No
ISO specific running reference	0.516200
ISO specific running average	0.561300

Perform.level idle power ISO	2
Perform.level standby30 ISO	1
LFKK	3,358 mm
AED category	No
JDC (call key switch) on COP	No
Resulting rope force FDR	15,758 N
Contact type	Not IP67 protection
Opt: maintenance space access	No
Floor Served 01	Y
Floor Served 02	Y
Floor Served 03	Y
Floor Served 04	Y
Floor Served 05	Y
Floor Served 06	Y
Floor Served 07	Y
Installation hours step 1	13.60 h
Installation hours step 2	13.40 h
Installation hours step 3	2.40 h
Installation hours step 4	15.10 h
Installation hours step 5	28.00 h
Installation hours step 6	35.40 h
Installation hours step 7	15.60 h
Installation hours step 8	12.80 h
Installation hours step 9	33.50 h
Installation hours step 10	10.70 h
Installation hours step 11	10.90 h
Installation hours step 12	25.40 h
Installation hours step 13	6.80 h
Installation hours step 14	6.30 h
Hoist. beam height in headroom	200.00 mm
Dist.hoist.facil.to HW ceiling	200.00 mm
Release version of ES	Rel.02.00
Remote removable hook	no
Opt: seimic req. for fishplate	No
Car floor design	Bare
Quantity mirror	1
Quantity handrail	3
Deco 3	Yes
Depth of landing door frame 01	60
Depth of landing door frame 02	60
Depth of landing door frame 03	60
Qty of MediaScreen Lobby	0
F55 max dynamic s	1,040
F57 max dynamic s	335
Perform.level standby5 ISO	1
Operation days per year	365 Days
Perform.level running ISO	1
Left entrance wall width BSW1	420 mm
Rigth entrance wall width BSW2	550 mm
Opt: basic residential pricing	No
Suspension traction media type	STM-PV50
Machine installation method	Catapult machine inst. tool

User information functions	Position indicator car 1
User information functions	Arrival gong on the landing
User information functions	In-service indicator
User information functions	Travel direction indicator ca
User information functions	Maintenance-work indicator
User information functions	Arrival & further travel Indi
User information functions	Voice signalization
Delivery groups quantity	1
Delivery group identification	Delivery Group 10
Delivery unit machine order	Standard
Del. unit machine add. TP	0.00
Del. unit machine to DG	Delivery Group 10
Del. unit fr. converter order	Standard
Del. unit fr. converter add TP	0.00
Del. unit fr. converter to DG	Delivery Group 10
Del. unit controller order	Standard
Del. unit controller add. TP	0.00
Del. unit controller to DG	Delivery Group 10
Del. unit COPV type 1 order	Standard
Del. unit COPV type 1 add. TP	0.00
Del. unit COPV type 1 to DG	Delivery Group 10
Del. unit LOP type 1 order	Standard
Delivery unit LOP type 1 QTY	1
Del. unit LOP type 1 add. TP	0.00
Del. unit LOP type 1 to DG	Delivery Group 10
Del. unit LOP type 2 order	Standard
Delivery unit LOP type 2 QTY	1
Del. unit LOP type 2 add. TP	0.00
Del. unit LOP type 2 to DG	Delivery Group 10
Del. unit LOP type 3 order	Standard
Delivery unit LOP type 3 QTY	5
Del. unit LOP type 3 add. TP	0.00
Del. unit LOP type 3 to DG	Delivery Group 10
Del. unit LIP type 1 order	Standard
Delivery unit LIP type 1 QTY	7
Del. unit LIP type 1 add. TP	0.00
Del. unit LIP type 1 to DG	Delivery Group 10
Del. unit hoist. info order	Standard
Del. unit hoist. info add. TP1	0.00
Del. unit hoist. info to DG	Delivery Group 10
Del. unit hoist. light order	Standard
Del. unit hoist. light add. TP	0.00
Del. unit hoist. light to DG	Delivery Group 10
Del. unit trav. cable order	Standard
Del. unit trav. cable add. TP	0.00
Del. unit trav. cable to DG	Delivery Group 10
Del. unit tract. media order	Standard
Del. unit tract. media add. TP	0.00
Del. unit tract. media to DG	Delivery Group 10
Del. unit brackets order	Standard
Del. unit brackets add. TP	0.00
Del. unit brackets to DG	Delivery Group 10

Del. unit car g. rails order	Standard
Del. unit car g. rails add. TP	0.00
Del. unit car g. rails to DG	Delivery Group 10
Del. unit cwt g. rails order	Standard
Del. unit cwt g. rails add. TP	0.00
Del. unit cwt g. rails to DG	Delivery Group 10
Del. unit fix points order	Standard
Del. unit fix points add. TP	0.00
Del. unit fix points to DG	Delivery Group 10
Del. unit mac. support order	Standard
Del. unit mac. support add. TP	0.00
Del. unit mac. support to DG	Delivery Group 10
Del. unit pit set order	Standard
Del. unit pit set add. TP	0.00
Del. unit pit set to DG	Delivery Group 10
Del. unit buffers order	Standard
Del. unit buffers add. TP	0.00
Del. unit buffers to DG	Delivery Group 10
Del. unit car g. sys. order	Standard
Del. unit car g. sys. add TP 1	0.00
Del. unit car g. sys. to DG	Delivery Group 10
Del. unit LD type 1 order	Standard
Delivery unit LD type 1 QTY	5
Del. unit LD type 1 add. TP	0.00
Del. unit LD type 1 to DG	Delivery Group 10
Del. unit LD type 2 order	Standard
Delivery unit LD type 2 QTY	1
Del. unit LD type 2 add. TP	0.00
Del. unit LD type 2 to DG	Delivery Group 10
Del. unit LD type 3 order	Standard
Delivery unit LD type 3 QTY	1
Del. unit LD type 3 add. TP	0.00
Del. unit LD type 3 to DG	Delivery Group 10
Del. unit car door 1 order	Standard
Del. unit car door 1 add TP 1	0.00
Del. unit car door 1 to DG	Delivery Group 10
Del. unit car struct. order	Standard
Del. unit car struct. add. TP	0.00
Del. unit car struct. to DG	Delivery Group 10
Del. unit car front 1 order	Standard
Del. unit car front 1 add. TP	0.00
Del. unit car front 1 to DG	Delivery Group 10
Del. unit car traction order	Standard
Del. unit car tract. add. TP 1	0.00
Del. unit car traction to DG	Delivery Group 10
Del. unit CWT fillers 1 order	Standard
Del. unit CWT fillers 1 add TP	0.00
Del. unit CWT fillers 1 to DG	Delivery Group 10
Del. unit CWT fillers 2 order	Standard
Del. unit CWT fillers 2 add TP	0.00
Del. unit CWT fillers 2 to DG	Delivery Group 10
Del. unit CWT frame order	Standard

Del. unit CWT frame add TP	0.00
Del. unit CWT frame to DG	Delivery Group 10
Del. unit cust order 1	Customized
Delivery unit CUST type 1 QTY	1
Del. unit cust add TP 1	0.00
Del. unit cust to DG 1	Delivery Group 10
Engraving number	$TMP
KnowledgeBaseVersion	LE_F3_EU Version 23.103w16
Product family	160
Product Category	ELG
KG / Customer / Country	Great Britain - Schindler Ltd.
Quotation- / Order type	Order registration
1 floor designation	0
2 floor designation	1
3 floor designation	2
4 floor designation	3
5 floor designation	4
6 floor designation	5
7 floor designation	6
Number of car entrances	1
Main landing	Landing at floor 1 on side 1
Car width BK	1,600 mm
Number of floors	7
Number of car entrances	1
Number of landing doors	7
Width car entrance BKE	900 mm
1.Car entrance return BKF1	350.0 mm
Hoistway width (BS)	2,150 mm
Type of cables	Halogen Free
Add. weight for car decoration	145 kg
Car buffer type	LSB16
Counterweight buffer type	LSB16
Car ceiling finish	Stainless steel
Car decoration line	Park Ave.
Car door detection	static Light curtain
Car front type	Front stonehenge
Car lighting	LED
Product Change Period CP	365
Frequency	50 Hz
Compensation chain	Not ordered
Control system	KS = collective selective
Type controller	Scalable Control
Control box position	connected to frame left
Country of installation	GB
Decoration corners	No
Designation within group	Elevator A
Drive side location	Right side
Energy efficiency class VDI	A
Fixtures type	FI GS 300
Finishing floor thickness	70 mm
Car weight GK	1,106 kg
Mass acting on car safety gear	2,110 kg

Rated load GQ	1000 kg
Floor to floor distance 1-2	3,450 mm
Floor to floor distance 2-3	2,925 mm
Floor to floor distance 3-4	2,925 mm
Floor to floor distance 4-5	2,925 mm
Floor to floor distance 5-6	2,925 mm
Floor to floor distance 6-7	2,925 mm
Car height HK	2,500 mm
Car door height HKE	2,000 mm
Height of Floor HKZ	33.0 mm
Travel height HQ	18.075 m
Depth of hoistway pit (HSG)	1,295 mm
HSG Type	Standard pit
Hoistway headroom (HSK)	4,821 mm
HSKType	Standard head
Reeving factor KZU	2
Landing door fixing	Anchor bolts (Upper and lower)
Machine room location	MRL Machineroomless
Main stop floor	1
Hoisting motor type	PML145-K
Number of car operating panels	1
Number of floors	7
Overspeed governor type car	GBP201
Overspeed governor type CWT	None
Packing type	Normal
Product	ES5
Installation method	Scaffoldless with hoisting dev
Seismic application	No
Hoistway wall	Concrete
Technical documentation lang.	English
Car depth TK	1,400 mm
Type of transport	Standard delivery
ZIP Key for transport price	B9
Hoistway depth (TS)	1,706 mm
Temporary Safety device rel.	No
Country key	GB
Postal Code	B9 4LS
Rated speed (VKN)	1.60 m/s
Starts per hour (ZKH)	180
Business zone	Zone EU
No. of suspens. ropes/belts ZZ	2
Height of CWT frame (HGR)	2,500 mm
No. of Buffers for Car ZPK	2
No. of Buffers for CW ZPG	1
Car guid.ax.to wellfrontw.TKSW	875.0 mm
Type of car safety gear	SA_GED_10
CCTV Interface	Not Ordered
Sourcing zone	Supply chain Europe
Group Name	BLOCK F FIREFIGHTING
Fire emergency service	BR1EU_2016
Alarm horn	No
Option: CWT safety gear	No

CAR RAIL TYPE	T75-3/B
Type of CWT guide rail	T75-3/B
Elevator standard	EN 81-20:2020
Year of production	2020
Year of installation	2026
Machine Room Type	Machine room less
TSD Switch	No
Temporary Safety device Pit	No
Width door BT	900 mm
Width door BT 1	900 mm
Width door BT 2	900 mm
Width door BT 3	900 mm
Accessibility code	EN 81-70:2021+A1:2022
LDU Floor identity	7.1
Car door operator (drive)	Varidor 15
Car door type	Door center opening, 2 panels
Handrail finish	St.steel AISI304 brushed
Car blocking device	No
Type of STM	STM-PV50
Opt: car door lock 1	Yes
Weight of counterweight GG	1,607 kg
Nominal motor output (PMN)	14.30 KW
Mains voltage lighting	230 V
Rated mains voltage	400 V
Reporting Company	Great Britain - Schindler Ltd.
Elevator system	ES5 (with STM up to 3.0 m/s)
Skirting finish	St.steel AISI304 brushed
Total length of STM	49.00 m
Handrail type	Not revolving
Opt: handrail with curved ends	Yes
Landing Door	DO WIV EU (Wittur Evo EU)
Car skirting shape	STRAIGHT
Car Type	CA PK 33
Car ceiling decoration	St.steel AISI441 brushed
Overtravel of car above	260.2 mm
Jump distance of car	90 mm
Overtravel of car below	245.2 mm
Buff.plate to buffer/plinthHKP	70 mm
Opt: common hoistway	No
Bracket distance calculation	Fixed distance
Opt: UCMP test tool	Yes
Fire fighter compliant	No
Market cluster	Market Cluster 5.1
Drive brake type	Type RSQ250_2X220
Incoterms delivered by SC EU	DAP W Thurrock
Maximum dist. bracket to brack	2,500 mm
BSR3 position from BK	460 mm
BSR4 position from BK	230 mm
TSR4 position from TK	731 mm
Nominal current install. INN	19.38 A
AC GSI main sensor variant	AC GSI 200 M. Sens. 2FS
Car buffer category	Hydraulic

CWT buffer category	Hydraulic
Opt: pit door	N
Letter of Credit Process	No
Release_Version_Machine	Rel.02
Landing_door sill extension	No
Opt: discount approved by SC	No
Sales discount [EUR]	0 EUR
Opt: certification holder 1	No
Opt: decoration frame for LOP	No
Opt: decoration frame for LIP	No
Main Floor with Green Ring	Ordered
Opt: CWT frame cover	No
Position of LOP	In the wall.
Accessibility compliance	Yes
Opt: change after pull process	No
Product line	F3
Thickness of front hoistway wa	200 mm
Thickness of rear hoistway wal	200 mm
Thickness of left hoistway wal	200.0 mm
Thickness of right hoistway wa	200.0 mm
BR activation	External contact
LBLC_ES5_12_LogKey	26-06-09-08-220-3EM
Material_of the hoistway	Concrete
LBLC system revision	0.000
Car side governor type	SA GBP 201
Add.Instal.hours for Report	0.00 h
Installation hours for Report	182.40 h
MDC hours for Report	45.00 h
Longest SC eng. lead time	0
Number of notified body	0041
Hoistway width (BS) min	2,113 mm
Shaft depth (TS) min	1,666 mm
Hoistway width (BS) max	2,948 mm
Shaft depth (TS) max	9,999 mm
Headroom max (HSK max)	9,999 mm
Well pit height max (HSG max)	2,800 mm
Headroom min (HSK min)	3,925 mm
Well pit height min (HSG min)	1,240 mm
Automatic Evac. Supply Device	0.000000 W
Automatic Evac. Supply Device	0.000000 W
Opt: LDU preassembled	No
Code for type examination	Not relevant
Product Application	Flexible
Elevator inspection code	Not relevant
Main switch JH variant	Miniature circuit break. C25A
Minimal car weight GKK	446 kg
Maximal car weight GKG	1,343 kg
Max. number of persons per car	13
Number of elevators in one grp	1
Control position	Attached to the left door jamb
Control location	Landing at floor 7 on side 1
Alarm type	Remote alarm ETMA

Ceiling type	Line
Car door finish	St.steel AISI441 brushed.
Car Side wall decoration	St.steel clad. AISI441 brushed
Car rear wall finish	St.steel cladd.AISI441 brushed
Car floor finish	Bare steel
Full height COP	Yes
Car front finish	St.steel AISI441 brushed
Fan	No
Display type COP 1	Dot Matrix High resolution
Car door sill	Aluminium
Land. door frame size (W x D)	120 mm x 60 mm
Landing door frame type	Basic / box frame
Elevator category	Person Elevator
Counterweight location	On the right side
Landing door finish 1	SS441_BRUS
Landing door finish 2	SS441_BRUS
Landing door finish 3	SS441_BRUS
Landings LD 1	Landing at floor 2 on side 1
Landings LD 1	Landing at floor 3 on side 1
Landings LD 1	Landing at floor 4 on side 1
Landings LD 1	Landing at floor 5 on side 1
Landings LD 1	Landing at floor 6 on side 1
Landings LD 2	Landing at floor 7 on side 1
Landings LD 3	Landing at floor 1 on side 1
Height CAR guide rail prof.HFP	62.00 mm
Configuration Type	All-New Configurator
Skirting design	Flush
LIP type	Fixtures FI GS 300
LOP type	FI_GS_300
Op: Car Deco 3.0 selected	No
Opt: PORT Included	No
Product name	Schindler 6000
Opt: split delivery	No
COP/CIM location 1	1
Opt: recessed door mounting	Yes
Landing door panel material 1	St.steel solid
Landing door panel material 2	St.steel solid
Landing door panel material 3	St.steel solid
Number of landing doors,side 1	7
Number of landing doors,side 2	0
Opt: card writer	No
Original change period	353
Framework agreement	No
CAMOS ID [Part1]	2EF4E5E331A7E24A
CAMOS ID [Part2]	87D457AE1BF2D090
CAMOS Model ID [Part1]	005056BBE96E1FE0
CAMOS Model ID [Part2]	ADCA14B20B90B1F5
CAMOS Group ID [Part1]	F098F7C90CDD254D
CAMOS Group ID [Part2]	A7CA3E12C2250ADF
CWT guide shoe type	Guide Shoe I10
Counterweight Types	GGM43_51
Filler material 2	High Density Concrete

Filler material 3	Steel
Filler material 4	CASTIRON
Height of CWT block 2	42 mm
Height of CWT block 3	20 mm
Height of CWT block 4	25 mm
Dist.CWT axis to car rail back	120 mm
Country language	English (United Kingdom)
Shipping document. language	English
Autom.evac.device batterypack	0
Width of counterweight (BG)	1,002 mm
Traction sheave pitch diameter	112 mm
Rated voltage motor UMN	340 V
Current on main switch JH	19.38 A
Guide rail length section 2	2,500 mm
Guide rail length section 3	1,055 mm
Guide rail length section 6	1,647 mm
Guide rail length section 2	2,500 mm
Guide rail length section 3	870 mm
Guide rail length section 6	1,642 mm
Fishplate qty for car	18 EA
REC-Panel	Intergrated
Guide rail ends 2	Male - Female
Guide rail ends 2	Male - Female
Guide rail ends 3	Female - Flat
Guide rail ends 3	Female - Flat
Guide rail ends 6	Male-Female
Guide rail ends 6	Male-Female
Guide rail quantity 1	0
Guide rail quantity 1	0
Guide rail quantity 2	16
Guide rail quantity 2	16
Guide rail quantity 3	2
Guide rail quantity 3	2
Guide rail quantity 4	0
Guide rail quantity 4	0
Guide rail quantity 5	0
Guide rail quantity 5	0
Guide rail quantity 6	2
Guide rail quantity 6	2
Depth of CWT blocks 2	155 mm
Depth of CWT blocks 3	155 mm
Depth of CWT blocks 4	155 mm
Type of load measuring system	AC LMF with 2 sensors
Position of pit ladder	Front left
Width of Counterweight Frame	1,002 mm
Fishplate qty for cwt	18 EA
Label language	English
Traveling cable length	35.83 m
Trafo Adapter	Not Ordered
Inertia IA (from 0.1 to 100)	3.2800
Car Cabinet (OKR)	Vertical
Counterweight position	right wall;center

Counterweight zone	CWT SIDE
Magnetic Band Length	23.000 m
Option: drilling in pit floor	Yes
Refuge space posture in Head	2 x Refuge Spaces Crouching
Refuge space posture in pit	1 x Refuge Space Laying
Option Travelling Cable	Not Ordered
Height of car buffer stand	328 mm
Height plinth undern. CWT HSS2	0 mm
Dist.left wall guide rail SF1	108 mm
Dist.right wall guide rail SF2	238 mm
Tip Up Seat Car	Not ordered
Mobile Communications Type	4G LTE
Emergency service NF type	None
CWT buffer stroke	175.2 mm
Car buffer stroke	175.2 mm
Height of car buffer HP	483.0 mm
Height of CWT buffer HP	483.0 mm
Distance Guides CW BGS	1,046 mm
Height car buffers, compr. HPE	307.8 mm
Height CWT buffers, compr. HPE	307.8 mm
Opt: frame in pit set	No
FF1G EXT	1,184 N
FF1G NO	434 N
FF2G EXT	799 N
FF2G NO	188 N
FF1 EXT	2,027 N
FF1 NO	668 N
FF2 EXT	1,033 N
FF2 NO	469 N
Car guid.trckc.CWTguid.ax TKG1	1,022.0 mm
Carguid.ax-CWTguid.trckc. TKG2	0 mm
Maintenance platform or not	No
Buffer distance underneath cwt	0
Buffer distance underneath car	864
Depth of counterweight (TG)	160 mm
Length of cable for KSS switch	15.000 m
OEM Policy	Not ordered
Tension force CAR governor rop	250 N
Temperature Sensor	Not Ordered
Number of BIOGIO	1
Power outlet type	Socket outlet K (British type)
Support for RESG	Not ordered
cbl length from JHSG1 to RESG	7.45 m
Insulation Pad	Without Insulation Pad
Main switch type	Min. Circuit Breaker
Print Sulfur Resistant Version	Not Ordered
Distance Salsis to OKR	5.000 m
Alternative Method for Safety	Ordered
Safety chain contacts	Jhsg1
Safety chain contacts	Car buffer contact KP
Safety chain contacts	2nd Car buffer contact KP
Safety chain contacts	Counterweight buf. contact KPG

Safety chain contacts	Slack Rope Speed Car KSSBV
Hand lamp	Controller
Porter Intercom	Not Ordered
CUBE release	Yes
Dist.CWT to buffer/plinth HGP	85 mm
Smoke seal for controlbox	No
Floor on fire function	Not Ordered
Rotation dir.mot.car upwords	Left
Cabinet fire kit	Ordered
Pit box type	Switch integrated
Floor Passing Chime	Not Ordered
Cabinet Glass Cover	Not Ordered
Reset for BR1 EN81-73	Not ordered
Cable for SPECI	Not Ordered
Ethernet switch	Not Ordered
Biometric pass	No
Intercom pit	No
Number of CANGIO	0
Distance cabinet to pit box	20.64 m
Vertical acceleration car	0.6 m/s2
Block calls to adjacent floor	Not Ordered
Switch JLBS	Ordered
Anti-burglar service	Not Ordered
Protection SIBS	Ordered
Protection SIBS Current	10 A
AAT plug	Ordered
Soft stop	Not Ordered
Push Button Earthquake Reset	Not Ordered
Current on light switch	10 A
JH = 63A Siemens	Not Ordered
Interfaces for Car	0
OKR position	Right
Quantity interface BS	0
Bank Service	Not Ordered
Stress Monitor Type	Bend Age
Floor Light Control	Not Ordered
Adapter Installation Trip Car	Ordered
Building Monitoring Service	Ordered
Type of Evacuation	None
Height control box	2,000 mm
Pulsed Elec. Brake Opening	Ordered
Gong on car	Not Ordered
Building sway / high wind	Not Ordered
Subgroup Control	Not Ordered
PSI interface	Not Ordered
Ese panel	Not Ordered
Intercom	Etma MR
3rd Party Parallel Voice	Not Ordered
Out of service function	Not ordered
Priority Travel	Not Ordered
Central alarm	Not ordered
Phase control device (RKPH)	Not ordered

Supply Module	Not ordered
On level indic. external(LUET)	Not Ordered
Water Detection Service	Not Ordered
Main Switch Maintenance JH1	Ordered
Car Preference Control	Not Ordered
Distance JH1 to VF	3.00 m
Interface LCUM	0
Telemonitoring	CUBE.
Attendant control function	Not Ordered
Direction of travel indicator	Ordered
Dist. Cabinet to VF	8.73 m
Manual car call cancelation	Not Ordered
Dist.cab. nearest up/low LP 1	6.15 m
Visitor control service	Not Ordered
Shaft Lighting	Switch and Lighting set
Independent service	with parking
Number of Cancpi	0
Distance cabinet to motor	11.07 m
Earthquake control service	Not ordered
Enforced Stop	Not Ordered
Build Interface Type	BIOGIO
Distance VF Motor	2.31 m
Distance JH to JH1	9.21
Cabinet door opening	Left hand
Overvolt. Protection	Not Ordered
Type of traveling cable fixati	Bracket
Voice language	English UK Female
Voice signalization delivery	Complete
Door mode if two access sides	Parallel
Connection to porter station	No
Transversal Beam Width TBW	25 mm
Thickn. weld.brack.plate left	0 mm
Thickn. weld.brack.plate rear	0 mm
Thickn. weld.brack.plate right	0 mm
Height CWT guide rail prof.HFP	62.00 mm
Hoistway height	24.191 m
Type of car buffer stand	STEEL
Air cond.	Not Ordered
Width of left part CWT frame	0 mm
Width of riight part CWT frame	0 mm
1.Car entrance return BKF2	350.0 mm
Distance between guides BKS	1,680 mm
Width of car guide rail head	10.0 mm
Width of guide rail head CWT	10.0 mm
Brake release device type	Not ordered
Landing door fire rating 1	EN 81-58 E120
Landing door fire rating 2	EN 81-58 E120
Landing door fire rating 3	EN 81-58 E120
Opt: Landing Door with LDU 1	No
Opt: Landing Door with LDU 2	No
Opt: Landing Door with LDU 3	No
Encoder category	SINCOS_ENDAT

Encoder plug type	Encoder plug type D_Sub
Motor frequency at VKN	45.5 Hz
Admissible braking torque	440 Nm
Width of CWT filler weight 2	986 mm
Width of CWT filler weight 3	986 mm
Width of CWT filler weight 4	986 mm
Filler density 2	4.20 kg/dm3
Filler density 3	7.85 kg/dm3
Filler density 4	6.70 kg/dm3
Min.Weight of CWT fller mat.2	594.00 kg
Min.Weight of CWT fller mat.3	901.10 kg
Total weight blocks type 4	0.00 kg
Opt: Landing Door Lateral Adj.	No
Landing door grout guard	No
Dust holes on landing door sil	No
Seismic category § EN 81-77	ad<1
Max.Height of CWT filler mat.2	1,008 mm
Max.Height of CWT filler mat.3	820 mm
Max.Height of CWT filler mat.4	0 mm
Number CWT filler weights 2	24
Number CWT filler weights 3	41
Number CWT filler weights 4	0
SALSIS fixation	fixation on car side
COP/CIM position 1	Side wall
Drop cable length	22.225 m
Handwinding device/interface	No interface, no handwinding
Type Shaft Light	LED strip (single strip) Id.57
Encoder cable length	2.31 m
Admis.radial force trac.sheave	25,000 N
Total static system mass (in..	2,736.00 kg
DF service	Not Ordered
Tie bracket qty	0
Height of CWT filler material	1,828 mm
Counterweight screen height	1,970 mm
Min. CWT screen top height	2,000 mm
Height of CWT attachments HGU	162 mm
CWT filling weight GGF	1,495 kg
Distance between pulley (LKR)	1,550 mm
Dist hoistway1-door sill (TSW)	35 mm
Dist hoistway2-door sill (TSW)	35 mm
Dist hoistway3-door sill (TSW)	35 mm
Motor output torque required..	183 Nm
Required RPM of motor	546
Number of LCUX	0
NGO quantity	0
Low standby	Not Ordered
Single Brake Arm Test Lever	Y
Dist landing to maint. platf.	0 mm
Fishplate type for cwt	Fishplate for T75 3B D10
Offset car guide rail axis	0 mm
Guide Rail System Type	Guide rail system MM GRS 513
Fishplate type for car	Fishplate for T75 3B D10

Supply power net type	TN-S (3L+PE+N)
COP faceplate finish 1	St.st.AISI304 hairline black
GB Tension Device Type CAR	TD203 car 59348350
Height of Safety System CAR	22.746 m
Length Oversp. Gov. rope CAR	47 m
Friction force of rope at SG	500.00
Cable length from LOP to LIP 1	1.9 m
Cable length from LOP to LIP 2	1.9 m
Cable length from LOP to LIP 3	1.9 m
Wiring type 1	FIGS Parallel with LIP
Wiring type 2	FIGS Parallel with LIP
Wiring type 3	FIGS Parallel with LIP
LIP Type	Arrows and Position
Glass display	Black
Inductive loop	Ordered
OKR position	Right wall; front
Sabbath Operation	No
Triphonie	Ordered
Masses CW suspension GGA	1,608 kg
Height of remov. CWT attachm.	150 mm
Height of counterweight yoke	220 mm
Height crosshead bottom HKJU	182 mm
Guide shoe type	Sliding guide shoe
Height upper yoke of car sling	110 mm
Sling type	SL33 (S5500)
Number of car fans	0
Fall protection wire Qty.	0
Type of car buffer stabilizer	No
Type of car buffer stabilizer	No
Cwt buffer location	Pit
Rough suface wall or not	No
Mechanical KNE	Not ordered
Shaft end (ETSL)	Not Ordered
Car fixpoint type	ES5.1&5.2 Car Fixpoint type 3
Height Handrail Top Edge	900.0 mm
Car fan category	NONE
Attendant box	No
Traction media type	STM
Braille type	None
Option: firefighter compliance	No
Overspeed govern. position car	Pos component rear left
Brand	Schindler
Opt: wall box 1	not Ordered
Opt: wall box 2	not Ordered
Opt: wall box 3	not Ordered
Lamp types 1	None
Lamp types 2	None
Lamp types 3	None
Button type 1	DE Up
Button type 2	DE Down
Button type 3	DE Down
Button type 3	DE Up

Fire code	No
Key locking system COP1	KABA Low Profile (1065)
Glass cover color LOP 1	Black
Glass cover color LOP 2	Black
Glass cover color LOP 3	Black
Glass cover color LIP	Black
Display type LOP 1	No
Display type LOP 2	No
Display type LOP 3	No
LOP mounting 1	Surface vertical in wall
LOP mounting 2	Surface vertical in wall
LOP mounting 3	Surface vertical in wall
Firefighter modules 1	None
Firefighter modules 2	None
Firefighter modules 3	None
Landing fire recall elements 1	None
Landing fire recall elements 2	None
Landing fire recall elements 3	None
Fixtures Design	Flush
Fixtures Design 1	Surface
Remote Monitoring	Yes
Car fan options	Not Ordered
Opt: wall box 1	No
Opt: arrival gong on the land1	Yes
Fixtures Variant LOP	Standard
Fixtures variant COP	Standard
Fixtures variant LIP	Standard
Blocking Of Side	Not Ordered
Width of car operating panel 1	250 mm
COP dedicated to 1	First access side
COP painted color 1	Unknown
Designation elements	No
Type of frequency converter	VAF025_480
Width BTF1 1	120.0 mm
Width BTF1 2	120.0 mm
Width BTF1 3	120.0 mm
Width BTF2 1	120.0 mm
Width BTF2 2	120.0 mm
Width BTF2 3	120.0 mm
Height door HT	2,000 mm
Height door HT 2	2,000 mm
Height door HT 3	2,000 mm
Landing egress device 1	No
Landing egress device 2	No
Landing egress device 3	Yes
Landing door wiring type 1	Standard cable
Landing door wiring type 2	Standard cable
Landing door wiring type 3	Standard cable
Height HTF 1	2,190 mm
Height HTF 2	2,190 mm
Height HTF 3	2,190 mm
Landing door type 1	Door center opening; 2 panels

Landing door type 2	Door center opening; 2 panels
Landing door type 3	Door center opening; 2 panels
Call Keys Position 1	Service Area
Anchor rail T bracket qty.	0
Anchor bolt T bracket qty.	0
Plate clamp Z brack qty	0
Plate clamp Ù bracket qty.	0
Chemical bolt qty.	0
Dist. car rail to Z-braket	600 mm
CWT rail anti snag guard QTY	0 EA
Button finish LOP	St.st.AISI304 hairline black
Cable pipe PIPE length	5.0 m
Opt: alarm device for Italy	No
Emergency power service (NS)	Not Ordered
Second OKR or SUET Box select	No
Cabinet Material	SS441_BRUS
Control box/LDU location	Cbox top floor, next t.door
Terminal Box on Car Roof (OKR)	OKR 3.0 Standing
intercom system	Yes
Card reader interface	Not Ordered
Height of car platform	80 mm
Height of Balustrade	700 mm
Car Toe Guard Height HKA	785 mm
Option: internal car ladder	No
Keyhole in emerg.exit for open	No
additional/balancing weight 2	0 kg
additional/balancing weight 4	0 kg
Vandal resistance category	No vandalism
Door installation template	Roller template
Car Apron Type	Apron fixed type EU
Front COP width on BKF1	0 mm
Front COP width on BKF2	0 mm
Front COP width on BKF3	0 mm
Front COP width on BKF4	0 mm
COP width on TKT1	250 mm
COP width on TKT2	0 mm
COP width on TKT3	0 mm
COP width on TKT4	0 mm
Oil Type for guiderail track	HLP68
Car wall/g-rail distance TK2	700.0 mm
Button finish COP 1	St.st.AISI304 hairline black
Button series COP 1	FI GS Standard Square
Car ceiling absorbing material	Not ordered
Emergency trap type	None
Height of TK beam	120 mm
additional/balancing weight 1	0 kg
additional/balancing weight 3	0 kg
total additional car weight	0 kg
Car_Door_Sill_Extension	No
COP_BKF1	No
COP_BKF2	No
COP_BKF3	No

COP_BKF4	No
COP quantity	1
damping pad	No
EMERGENCY LIGHT ON CEILING	No
Contact Bridging Car Apron	No
Platform type	Raster platform
Car Door RSE	No
Dist car front-center COP left	475 mm
Extension block 100	No
Extension block 200	No
Extension block 30	No
Extension block 50	No
Chicane for doors	No
COP Mounting type	FLUSH
Car door noise kit	No
Decoration frame LOP/LIP	No
Single Console Sill Support	No
LIP faceplate finish	Black glass
Landing door sill	Aluminium
Car door IP degree	IP21
Opt: Upright cover for glass	No
Car roof height	50 mm
Car buffer impact assembly BIA	No
Dist between top yoke and roof	50 mm
CAR guide shoe type	Guide Shoe I10
Number of car damping elem.	8
Additional weight on sling	0 kg
car isolation pulley	No
Pipe clamp CLAMP QTY	12 EA
LMS CABLE LENGTH	0.00 m
Installation elevation	<=2000 m
Opt: car jamb indic. in BKF1	No
Opt: car jamb indic. in BKF2	No
Opt: car jamb indic. in BKF3	No
Opt: car jamb indic. in BKF4	No
Type of indicator in car door	No
Evacuation landing No.1	Landing at floor 1 on side 1
BIOBUS interface request 1	No
BIOBUS interface request 2	No
BIOBUS interface request 3	No
Key types LOP 1	None
Key types LOP 2	None
Key types LOP 3	None
Opt: key switch extension 1	No
Opt: key switch extension 2	No
Opt: key switch extension 3	No
LOP Status indicator type 1	No
LOP Status indicator type 2	No
LOP Status indicator type 3	No
LOP Fixtures design 1	Surface
LOP Fixtures design 2	Surface
LOP Fixtures design 3	Surface

Button series LOP	FI GS Standard Square
Height of car damping	15 mm
Clip Design or not for support	Yes
Opt: KSSG contact	Yes
Car floor material	Bare steel
Front ending type of centre ha	Round
Height of car cupola (HKK)	500 mm
Front ending type of rear hand	Round
Rear ending type of rear handr	Straight
Diameter of handrail	40.0 mm
Front ending type of front han	Straight
Rear ending type of front hand	Round
Front ending type of rear hand	Round
Rear ending type of rear handr	Straight
Front ending type of front han	Straight
Rear ending type of front hand	Round
Rear ending type of centre han	Straight
Left ending type of rear handr	Straight
Right ending type of rear hand	Straight
Rear ending type of centre han	Straight
Front ending type of centre ha	Straight
Free space between car wall an	50 mm
Height of Skirting	58
Depth of car wall cladding sid	7.00 mm
Light curtain in car door	Cedes aesygard100 elements 36
noise reduction KIT	Ordered
LIN Status indicator type 1	Symbol
Landings 1	Landing at floor 1 on side 1
Landings 1	Landing at floor 2 on side 1
Landings 1	Landing at floor 3 on side 1
Landings 1	Landing at floor 4 on side 1
Landings 1	Landing at floor 5 on side 1
Landings 1	Landing at floor 6 on side 1
Landings 1	Landing at floor 7 on side 1
COP box size	Standard box 40mm
COP fixation type 1	Click Fixing
Opt: COP card reader box	No
Opt: COP voice announcer box 1	No
Sliding clip qty for CAR	22 EA
Sliding clip type for CAR	Sliding clip type SL3 (short)
Sliding clip qty for CWT	44 EA
Sliding clip type for CWT	Sliding clip type SL2
Car wall/g-rail distance TK1	700.0 mm
Height of 1st COP	2,332 mm
Key types COP 1	Independ. service with parking
Landing labels	None
Height of LD toe guard 1	260 mm
Height of LD toe guard 2	260 mm
Height of LD toe guard 3	260 mm
1H Width of car wall panel	350.0 mm
1L Width of car wall panel	350.0 mm
1R Width of car wall panel	350.0 mm

3H Width of car wall panel	900.0 mm
3L Width of car wall panel	450.0 mm
3R Width of car wall panel	700.0 mm
4L Width of car wall panel	0.0
4R Width of car wall panel	0.0 mm
5H Width of car wall panel	350.0 mm
5L Width of car wall panel	350.0 mm
5R Width of car wall panel	350.0 mm
6H Width of car wall panel	0.0 mm
Landings	Landing at floor 1 on side 1
Landings	Landing at floor 2 on side 1
Landings	Landing at floor 3 on side 1
Landings	Landing at floor 4 on side 1
Landings	Landing at floor 5 on side 1
Landings	Landing at floor 6 on side 1
Landings	Landing at floor 7 on side 1
Ov. governor rope diameter CAR	6.0 mm
Anti-snag guard. Z QTY	0 EA
Anti-snag guard. Omega QTY	0 EA
Anti-snag guard. L QTY	0 EA
Quantity of Ù brackets in Head	2 EA
Qty Z brackets f. SF1 in head	3 EA
Qty Z brackets f. SF1 in Pit	3 EA
Quantity of Ù brackets in Pit	3 EA
Quantity of Ù brackets in Trav	5 EA
Qty Z brackets f. SF1 in Trave	5 EA
Type Z-bracket SF1 at Head Pos	Z-AL16
type Omega Bracket in headroom	O-B L 1002 160 1
Type Z-bracket SF1 at Pit Pos	Z-AL16
type Omega Bracket in pit	O-B L 1002 160 1
Type Z-bracket SF1 at Trav Pos	Z-AL16
L-bracket qty head	1 EA
L-bracket type head	Family BL LBracket TG160/190 1
L-bracket qty TRAV	0 EA
L-bracket qty pit	0 EA
Opt:L Bracket connection plate	No
QTY:L Bracket connection plate	0 EA
Guide rail fixing head	Anchor bolts
Guide rail fixing pit	Anchor bolts
Guide rail fix at Travel Posi.	Anchor bolts
Upper Yoke Profile	P5
Car guide shoe insert quantity	0
Dist. CWT center to wall SG	118 mm
Ceiling until top yoke HKO	210 mm
Car damping device	Not ordered
Landing door IP degree	IP21
Landing SALSIS bracket	Yes
Toe guard Hong Kong	No
Land.door sill protection	Plastic
TK beam profille	TK Beam Profile No. 1
Upright profile	P1
Car front side 1	Entrance side 1

Opt: craneable packing	No
Building tolerance	-25 mm / +25 mm
Sandblasted sheave	Yes
Length oversp.gov.cable CAR	9.00 m
Type of el. recall control CAR	24 VDC + 82 W
Ov. governor plug type CAR	Harmonized (acc. J59501066)
Tension device disposition CAR	Right
Ov. governor base type CAR	MRL falling protect. 59500808
Ov. gov. rope coupl. type CAR	Short DZ6 GL12
Ov. governor rope type CAR	Seale 6x19S SFC 1770 B sZ
Ov. governor cover type CAR	Plastic cover 59500756
Type of el. remote reset CAR	No
Ov. governor retainer type CAR	ID 59500766 included in cover
KBV switch type CAR	2 normally closed
Depth of overspeed gover. CAR	113 mm
Pitch diameter of CWT pulley	150 mm
Type of CWT buffer stand	STEEL
Plinth protection	No
Car rail head # buffer center	408 mm
Timbers Qty.	0
LIP teach-in cable	Not ordered
Type of machine	PML145
Speed of motor r.p.m. (NMN)	546
PML145 Brake Winding	PML145-K10-420
Category of compensating means	N
Qty.reinfor.shims wall interf.	0 EA
Opt: reinforcement shims	No
Central Riser	Not Ordered
Side_Wall_Glass	N
Rear_wall_Glass	NO
Installation Zone	Zone EU
Neutral wire	Available
Depth of car door sill	45 mm
Qty emergency doors(interface)	0
Landing door closing means	Spring
Opt: landing door fire rating	Yes
Machine/CWT location	MRL side counterweight
Sill fixation tolerance	No
Car front sealing kit	No
Lamp on car	Not Ordered
Fall protection wire	No
Number of rear wall panels	3
Number of left wall panels	3
Door wiring	Door to door
Extension for lamp on car	Not Ordered
Shaft short headroom	No
Anchor bolt doors qty.	0
Decoration element	None
thickness car mirror rear	5 mm
Dist.TD rope to rail head(Car)	50.0 mm
Number of right wall panels	3
Slim sill	No

Anchor rail doors qty.	0
L. door cut out type LIP 1	No
L. door cut out type LIP 2	No
L. door cut out type LIP 3	No
Opt: short floor-to-floor d.1	No
Opt: short floor-to-floor d.2	No
Opt: short floor-to-floor d.3	No
L. door cut out type LOP 1	without
L. door cut out type LOP 2	without
L. door cut out type LOP 3	without
Door_Opt_Cut_Out_Type 1	No
Door_Opt_Cut_Out_Type 2	No
Door_Opt_Cut_Out_Type 3	No
Depth car door entrance TKA	110 mm
Handrail on left car wall	Parametric
Handrail on rear car wall	Parametric
Handrail on right car wall	Parametric
Bumper rails type	No
Maintenance hall relevance 1	No
Maintenance hall relevance 2	No
Maintenance hall relevance 3	No
type Omega Bracket at trav pos	O-B L 1002 160 1
Car suspension type	Bottom
Required motor output PME	10.46 KW
HTFO Value	190 mm
Drive Position	Right
Size of mirror on right car wa	No.
Size of mirror on left car wal	No.
Size of mirror on rear car wal	Half height full width
Car floor slip resist. rating	No classification
Opt. Landing unlocking key	Yes
Car door complete	DO VAR 15
HMI extension kit	Yes
Energy eff. class car door	Door Drive options: Normal
LIP mounting 1	Surface vertical in wall
Anti Snag Guard for Seismic	No
COP box size1	Standard box 40mm
COP box size2	No
COP box size3	No
COP box size4	No
Clear ceiling height in car..	100 mm
Position of car overspeed go.	160 mm
Drilling and Aligning Templ. S	No
Opt: emerg.stop switch machine	No
Required motor current IME	22.28 A
Balustrade left	NO
Balustrade rear	NO
Balustrade right	Fixed Balustrade EN81-20
balustrade extension	No
Opt: inverted car balustrade	No
Rear car wall material	St.Steel cladding
Side car walls material	St.Steel cladding

Motorfilter FEMH	Not ordered
Force of STM on car side FZ1	23,289 N
Force of STM on CWT side FZ2	23,837 N
Type car wall claddi mat. LEFT	St. steel AISI441 cladding
Type car wall claddi mat. REAR	Stainless steel AISI441
Type car wall claddi mat. RIGH	St. steel AISI441 cladding
Base material car walls REAR	Steel
Opt: T bracket	No
Hub width of pulley	62 mm
Opt: car wall skirting	Yes
Car installation set relevance	No
Cop Type	Fixtures FI GS 300
Thickn.rear car wall cladding	7.00 mm
Thickn.left car walls cladding	7.00 mm
Thickn.right car wall cladding	7.00 mm
Chain safety switch	No
Type of machine support	MRL_SIDE_TYPE_1
Car decoration reflection	Bright
Door pre-opening	Ordered
Depth 1. refuge space in head	500
TSR3 position from TK	34 mm
Type of intercom system ordere	ETMA MR
Opt: OMEGA CONNECTION PLATE	No
Rail backing plate qty	0 EA
HTFO Value 1	190.0 mm
HTFO Value 2	190.0 mm
HTFO Value 3	190.0 mm
Horizontal COP type	No
Qty of KIT CWT guide shim	0
Integrated safety gear or not	car safety gear not integrated
Code for baulstrade	EN_81-20:2020
Opt: service exit in car	No
Diameter Pulley Car DRKA	147 mm
Pulley susp. plate on top yoke	TY pulley susp. plate #No. 1
Release version car door	02
Height adapter for hang.ceilin	100.0 mm
Handicapped code	EN81-70 Permanent
STM MATERIAL	Polyurethane
TSD21 O bracket type	N
Qty_of_LIPs	7
Qty_of_LOPs	7
Balanced evacuation kit (BEK)	No
Anchor bolt type	AB for non-cracked wall (HSA)
Width BTF1	120.0 mm
Width BTF2	120.0 mm
Grout guard type	No
Option UCM Test Kit	No
LOP class 1	Main LOP
LOP class 2	Main LOP
LOP class 3	Main LOP
Dist between guiderail bracket	2,500 mm
LD cut-out for add. options 1	No

LD cut-out for add. options 2	No
LD cut-out for add. options 3	No
Opt: trapdoor maint. Platform	No
Opt: apron for car door	Yes
Short pit	No
sliding clip qty omega for car	20 EA
slid clip typ in omega for car	Sliding clip type SL3 (short)
Car door material	St Steel Solid
Opt: power supply AC/DC	No
Shims set quantity 1	0
Shims set quantity 2	0
Shims set quantity 3	0
Opt. LD Panel Protection 1	No
Opt. LD Panel Protection 2	No
Opt. LD Panel Protection 3	No
LIP class 1	Indicator LIP
Opt: reversing mirror	Not ordered
Landing door LOP cut out pos.1	Right
Landing door LOP cut out pos.2	Right
Landing door LOP cut out pos.3	Right
Distance center of guide rail	95
Dist. guide rail TD right end	605 mm
COP blind elements 1	0
Opt: short machine beam	No
Width of spacer	0 mm
Omega bracket family in head	B
Omega bracket family in pit	B
Omega bracket family in trav	B
Dist.from SG to bracket beam	120 mm
Designation of group in Bldng	2
Dist. CWT rail to car rail	190 mm
Height from top of car guide..	64 mm
Heigth 1. refuge space in pit	500 mm
Height of removable plinths ..	0 mm
Opt: handwheel surv. Contact	N
Contact located in the fixpo	Yes
Length of cable for KSSG switc	15.000 m
Length Motor Fixing	670 mm
Distance between the STMs, c..	430 mm
Distance between the 4 STMs	0 mm
Mat. of left car wall panel 1	Steel
Mat. of left car wall panel 3	Steel
Mat. of left car wall panel 5	Steel
Mat. of right car wall panel 1	Steel
Mat. of right car wall panel 3	Steel
Mat. of right car wall panel 5	Steel
Mat. of rear car wall panel 1	Steel
Mat. of rear car wall panel 3	Steel
Mat. of rear car wall panel 5	Steel
Mat. of rear car wall panel 6	Steel
Add. weight below car back	0 kg
Add. weight below car center	0 kg

car wall joint	No
Car walls color style	unicolor
Bluetooth Low Energy Interface	Ordered
Opt: car prot. external light	No
Landing door fixing type for b	N
Pad hook to hang temp protecti	No
COP hidden box type	Not ordered
Opt: add car st.wall stiffener	No
L-bracket family in head	B
Category of CWT guide shoes	Sliding guide shoe
Qty LOP elements per function	1
Safety gear imported from EU	No
Head Section Lateral Protectio	0 EA
LD telesc. profile qty duplex	0 EA
CAR rail Anti-snag guard QTY	0 EA
Base material car walls LEFT	Steel
Base material car walls RIGHT	Steel
Type of car buffer contact	Manual
Type of CWT buffer contact	Manual
Category of car guide rail	Machined
Length supp. bolt safety gear	253 mm
Opt: dust holes on CD sill	No
Sill loading	Standard
Cables from Cabinet to IOEE (C	3.00 m
Opt: corr. set car safety gear	No
Car Information Label 1st COP	Ordered
Width 1. refuge space in Pit	700
Width 1. refuge space in head	700
Width 2. refuge space in head	700
BSR1 pos. from left guide rail	552 mm
Depth 1. refuge space in pit	1,000
Depth 2. refuge space in head	500
TSR1 pos. from left guide rail	-500 mm
Disability sign 1	Yes
Disability sign 2	Yes
Disability sign 3	Yes
Opt: welded bracket plates	No
Opt: F-brackets	No
No. of refuge spaces in pit	1
Opt: frequency convert. Holder	No
Height 1. refuge space in head	1,000 mm
Height 2. refuge space in head	1,000 mm
Opt: tie brackets	No
Passenger Rel. on Alt. Landing	Release on the Next Floor
Special Public Transport Cable	Not Ordered
LD gong cut-out type 1	No
LD gong cut-out type 2	No
LD gong cut-out type 3	No
Width of bracket beam	250 mm
Car Information Panel 1	No
Button layout V 1	Customized (-3 ... 8)
Opt: firefighter key box 1	No

Gong	Not ordered
Height of#bracket beam	470 mm
Height of braket beam surface	0 mm
Type of hoistway light	LED strip (single strip)
Lamps Types 1	Emergency light in the COP
Opt: Landing Door w. LDU LIP 1	No
Opt: pit step	N
Opt: seamless car ceiling	No
Number of group floors	7
No. of refuge spaces in head	2
Width main control cabinet	295
Qty welded plates omega brack.	0
Qty welded plates L-bracket	0
Pit entrance side	On the front wall
Dist. hoistway to LD sill 1	35 mm
LOP faceplate finish 1	St.st.AISI304 hairline black
LOP faceplate finish 2	St.st.AISI304 hairline black
LOP faceplate finish 3	St.st.AISI304 hairline black
Separate power supplies	No
Double key types in the LOP 1	None
Double key types in the LOP 2	None
Double key types in the LOP 1	None
China Compulsory Certification	No
Opt: ACOPM name plate for CN	No
Position of car suspension	Bottom
Number of motor brakes	2
Opt: COP attendant box 1	No
Dist. from rail to magn. band	626 mm
Material of the hoistway head	Concrete
Material of the hoistway pit	Concrete
Material of the hoistway trav	Concrete
Build. toler. per hoistw. wall	0 mm / +35 mm
Opt: docking device	No
Opt: governor rope guide CAR	No
IP-degree of TD contact CAR	IP65
Car sill edge # car guide axis	810.0 mm
Soft stop type	Without
VF Location	Hoistway hall
Extension block 40	No
Dist. car door - land.door TKS	30 mm
Offset car entr.CL to car CL	0 mm
Coating of cwt pulleys	No
Access system connection 1	No
Dist. TD rope to rail head CAR	50.0 mm
Opt: Switch bypass KNE	No
Coating of car pulleys	No
Material of CWT pulley	Iron pulley
Display glass height	525 mm
Opt: finger protection (KTFP)	No
Rail mounting method, CWT side	Rail support is used
Rail mounting method, car side	Rail support is used
Original Brand Machine	No

CWT buffer impact material	Mixed
Dist. TD rope to rail axis CAR	160 mm
KSSBV-JHSG1 cable length	8.00 m
Opt: pit recall	Not Ordered
Release version of COPV	Rel.02
Material of car pulley	Iron pulley
Cutout on COP for card reader1	No
Opt: rear mid panel stst.mirr.	No
Cable length COP to OKR 1	6.6 m
Opt: Ethernet in car	No
Net load CWT rail base up dir	0 N
Net load car rail base up dir	0 N
Landing door cut out type LOP	without
Landing door cut out type LOP	without
Landing door cut out type LOP	without
LD cut-out for add. options	No
LD cut-out for add. options	No
LD cut-out for add. options	No
Opt: immediate call assignment	No
Packing material	Normal
SPH position in hoistway	Not required
Qty welded plates Z-bracket	0
Opt: fishplate shims	No
Opt: Z-bracket connect. plate	No
Opt: rail bracket shim Ù	No
Communication equipment type	ETMA PSTN
Special button 1	None
Opt: CBD Mainrtenance platform	No
Omega bracket conn. pl qty pit	0
Omega bracket conn. pl qty tra	0
Omega bracket conn. pl qty hea	0
Z-SF3 connection plate qty pit	0
Z-SF4 connection plate qty pit	0
Z-SF2 connection plate qty pit	0
Z-SF1 connection plate qty pit	0
Z-SF1 connect plate qty travel	0
Z-SF2 connect plate qty travel	0
Z-SF3 connect plate qty travel	0
Z-SF4 connect plate qty travel	0
Z-SF1 connect. plate qty head	0
Z-SF2 connect. plate qty head	0
Z-SF3 connect. plate qty head	0
Z-SF4 connect. plate qty head	0
Card reader module 1	No
Glass cover card reader	Black
Qty rail peces version 7 CAR	0
Qty rail peces version 8 CAR	0
Qty rail peces version 9 CAR	0
Qty rail peces version 10 CAR	0
Qty rail peces version 7 CWT	0
Qty rail peces version 8 CWT	0
Qty rail peces version 9 CWT	0

Qty rail peces version 10 CWT	0
Opt: CBD maint.platform deliv.	No
Height #underlayment on floor	70 mm
Quantity of KBF contacts	1
Opt: AED Battery Delivery	No
App. power autom. evac. suppl.	0 VA
Opt: callback module	No
Overspeed governor mountingCAR	On fixpoint
Qty. spacers for Omega	0
Length 1 bot. CWT rail L	2,500 mm
Height CWT shoe & supp.bearing	100 mm
Length 1 bot. CWT rail R	2,500 mm
Opt: CWT buffer impact assy	Yes
Total no. of traveling cables	1
Position of JHSG1 in hoistway	left wall;front
HGU_min	12.0 mm
Tolarance range for HGP	-20mm/0mm
Width of LOP 1	65 mm
Width of LOP 2	65 mm
Width of LOP 3	65 mm
FF1 max	2,027 N
FF1g max	1,184 N
FF2g max	799 N
Hoistway LED strip length	28.19 m
FF2 max	1,033 N
Opt: accessory box	No
Main voltage of Building	400 V
Quantity of M12 chem.bolt kits	0
Quantity of M16 chem.bolt kits	0
Qty M12 thin wall kit Z-bkt	0
Qty M12 thin wall kit Ù-bkt	0
Qty M12 thin wall kit L-bkt	0
Qty M16 thin wall kit Z-bkt	0
Opt:cracked concrete	No
Opt: double display	No
Opt: double display	No
Opt: double display	No
Opt: kit fall protection front	No
Opt: fall protection kit rear	No
Type fall protection kit front	Not required
Type: fall protection kit rear	Not required
Car clip family	SL
Landing door LIP cut-out pos1	Rear
Landing door LIP cut-out pos2	Rear
Landing door LIP cut-out pos3	Rear
Height vertical part toe gua01	260
Height vertical part toe gua02	260
Height vertical part toe gua03	260
Opt: LD on control landing1	No
Opt: LD on control landing2	Yes
Opt: LD on control landing	No
Qty M12 anchor bolts, L-brack.	4

Technical configuration Schindler	Created by : I_PI_CRM Last change : GHEORGAD	Date: 31.10.2025 Date: 09.06.2026

Sales Order : 11915007 Page: 32
Equipment :
Project name: STONEYARD, BIRMINGHAM - PHASE 1

Qty M12 anchor bolts, Ù-brack.	20
Qty M12 anchor bolts, Z-brack.	22
Qty M16 anchor bolts, L-brack.	0
Qty M16 anchor bolts, Ù-brack.	0
Qty M16 anchor bolts, Z-brack.	0
Qty M12 hook bolts f. brackets	0
Qty M16 hook bolts f. brackets	0
Qty M16 steel beam bkt bolts	0
Qty M12 steel beam bkt bolts	0
Opt: rope lubrication unit	No
ZBC function	No
ZBCE function	No
ZB1 function	No
ZB2 function	No
ZB3 function	No
Option: locking of floors	No
ZBE3 function	No
Drive Brake for ACOP UCMP	Yes
Size of display in COP 1	7 inch
CWT clip family	SL
Dest. indicator panel fixation	Clips
Height of CWT lower yoke	220 mm
Opt: hoistway wall ext. 50 mm	No
Opt: hoistway wall ext. 100 mm	No
Opt: hoistway wall ext. 200 mm	No
Dist. rail back to TZ center	0 mm
Hoistway lighting	Switch and lighting set
Position of JLBSSG in hoistway	left wall; front
Opt: original brand buffers	No
Height of CWT upper yoke	220 mm
Lop Landings 1	Landing at floor 1 on side 1
Lop Landings 2	Landing at floor 7 on side 1
Lop Landings 3	Landing at floor 2 on side 1
Lop Landings 3	Landing at floor 3 on side 1
Lop Landings 3	Landing at floor 4 on side 1
Lop Landings 3	Landing at floor 5 on side 1
Lop Landings 3	Landing at floor 6 on side 1
Min floor dist. same side	2,400
Rail buckling at ground level	38,252 N
Quantity of add tie brackets	0
Opt: JHSG1 bracket	No
Opt: pit ladder	Yes
Opt: maintenance step	No
Depth of car font wall	65 mm
Release version of car	Release 3
Opt: GB tripping speed reducer	Yes
Battery for control delivered	Supply Chain
Qty egress device per elevator	1
Opt: car buffer plinth protect	No
Option: AC GTW with UPS	No
Option: vision panel in landin	No
Option: vision panel in landin	No

Technical configuration Schindler	Created by : I_PI_CRM Last change : GHEORGAD	Date: 31.10.2025 Date: 09.06.2026

Sales Order : 11915007 **Page: 33**
Equipment :
Project name: STONEYARD, BIRMINGHAM - PHASE 1

Option: vision panel in landin	No
Opt: Bluetooth Low Energy	No
Opt: Bluetooth Low Energy	No
Opt: Bluetooth Low Energy	No
Constrat Frame LOP	No
display with QR Code for LOP	No
display with QR Code for LOP	No
display with QR Code for LOP	No
Number of ethernet link partne	2
LTSD21 Pit	2,140 mm
Category of LIP 1	Multifunctional
CWT side rail support type	RS V13 CWT
CAR side rail support type	RS V13 CAR
Opt: common machine room	No
Opt: hoist. access monitoring	No
Vert. car skirting allignment	With gap
Type of COP1 key switch box	No
Stat.force.susp.tract.shea.CWT	8,065 N
Opt: Car Safety gear from EU	No
Opt: CWT Safety gear from EU	No
Running clearance car SG	5.00 mm
SG wedge length on car	152 mm
Opt: fire control room	No
Opt: IG on car overspeed gov.	No
Type of Evacuation	None
SI-floor-sensor cable length	2.030 m
Power switch type (Car Door) 1	Normal switch on car door
Type of display on LIP	Dot matrix high resolution
DC voltage trav. cable on car	25.460 V
DC current in traveling cables	0.610 A
Indicator text color 1	Red
Building Code	No
Opt: further trav. indic. CD	Not ordered
Opt: output contactor box	No
Hoistway sectioning	Separ. pit/trav/head sections
Offs. car entr. 1 CL to car CL	0 mm
Option: USB-RS485 adapter	NO
Inverter input current IC1E	18.69 A
Car sill edge-car guide axis_1	810.0 mm
Opt: contact hoistw.end insp.U	No
Opt: contact hoistw.end insp.D	No
Off.travel.cabl.to car CL,TK-d	-350 mm
Opt: card reader sensor 1	No
Opt: card reader sensor 2	No
Opt: firesafe landing areas	No
Opt: fillers top metal cover	No
Cable length from LOP to LIP 1	1.9 m
AS-KTS-top cable length	3.81 m
Force on door sill	3,924 N
Opt: car wall lighting channel	No
Width of lighting channel	0 mm
AC GTW FXS Interface opt	Yes

Variant of LD AC GSI bracket	Standard
Base Code	EN_81-20
Brake Resistor box for VF	No
Opt: physical belt monitoring	No
Category of LOP 1	BIO Node for one elevator
Category of LOP 2	BIO Node for one elevator
Category of LOP 3	BIO Node for one elevator
Door Status After Evacuation	CLOSED
Opt: LD lock for low headroom	No