

=====			=====		
Modified order			No		
Supplier ID			=====		
Product Change Period			CP 369		
Sourcing zone			Supply chain Europe		
Installation Zone			Zone EU		
Country of installation			ES		
Product line			F3		
Elevator system			ES5 (with STM up to 3.0 m/s)		
Market cluster			Market Cluster 5.1		
Elevator system			Elevator system 5		
Elevator standard			EN 81-20:2020		
Code for type examination			Not relevant		
Technical document. lang.			Spanish		
Shipping document. language			Spanish		
Label language			Spanish		
Packing type			Normal		
Packing material			Normal		
Designation within group			Elevator A		
Elevator inspection code			Not relevant		

Guide Rail System Type	Guide rail system MM GRS 533
Hoistway sectioning	Separ. pit/trav/head sections
Counterweight Types	GM43 51
Counterweight position	left wall;center
Counterweight zone	CWT SIDE
Counterweight location	On the left side
Travel height HQ	48.320 m
Rated load GQ	1350 kg
Rated speed (VKN)	1.60 m/s
Hoistway width (BS)	2,501 mm
Width of counterweight (BG)	1,002 mm
Distance Guides CW BGS	1,046 mm
Dist.right wall guide rail SF2	172 mm
Dist. CWT center to wall SG	130 mm
Depth of counterweight (TG)	190 mm
Hoistway depth (TS)	2,300 mm
Machine Room Type	Mini machine room
Type of CWT guide rail	T75-3/B
CAR RAIL TYPE	T89/B
Seismic application	No
HSK type	Standard head
HSG Type	Standard pit
Height CWT guide rail prof.HFP	62.00 mm
Option: drilling in pit floor	Yes
No. of suspens. ropes/belts ZZ	4
Number of STM	4 EA
Option: CWT safety gear	No
Width of guide rail head CWT	10.0 mm
Height plinth undern. CWT HSS2	0 mm
Height of car buffer stand	648 mm
Depth of hoistway pit (HSG)	1,600 mm
Opt: KSSG contact	Yes
Length of cable for KSSG switc	8.000 m
Hoistway height	54.520 m
Category of compensating means	No
Dist.CWT axis to car rail back	145 mm
Dist.from SG to bracket beam	145 mm
Transversal Beam Width TBW	25 mm
Thickn. weld.brack.plate left	0 mm
Thickn. weld.brack.plate right	0 mm
Thickn. weld.brack.plate rear	0 mm
Sliding clip qty for CAR	90 EA
Sliding clip qty omega for car	90 EA
Sliding clip qty for CWT	180 EA
Sliding clip type for CAR	Sliding clip type SL3 (short)
Slid clip typ in omega for car	Sliding clip type SL3 (short)
Sliding clip type for CWT	Sliding clip type SL2
Fishplate qty for car	22 EA
Fishplate qty for cwt	22 EA
Fishplate type for cwt	Fishplate for T75 3B D10
Fishplate type for car	FP T89 D19A
FF1 max	3,216 N
FF2 max	1,638 N
FF1 NO	1,013 N
FF2 NO	750 N
FF1g max	1,210 N
FF2g max	138 N
FF1G NO	444 N
FF2G NO	44 N
Build. toler. per hoistw. wall	0 mm / +35 mm

Extension block 30	No	
Extension block 40	No	
Extension block 50	No	
Extension block 100	No	
Extension block 200	No	
Rail backing plate qty	0 EA	
Number of car entrances	1	
L-bracket qty head	0 EA	
L-bracket qty TRAV	0 EA	
L-bracket qty pit	0 EA	
Qty Z brackets f. SF2 in head	6 EA	
Type Z-bracket SF2 at Head Pos	Z-CH14	
Qty Z brackets f. SF2 in Trav	35 EA	
Type Z-bracket SF2 at Trav Pos	Z-CH14	
Qty Z brackets f. SF2 in Pit	4 EA	
Type Z-bracket SF2 at Pit Pos	Z-CH14	
Quantity of U brackets in Head	6 EA	
Type Omega Bracket in headroom	O-B H 1002 190 1	
Quantity of U brackets in Trav	35 EA	
Type Omega Bracket at trav pos	O-B H 1002 190 1	
Quantity of U brackets in Pit	4 EA	
Type Omega Bracket in pit	O-B H 1002 190 1	
Qty of KIT CWT guide shim	0	
Opt: T bracket	No	
Opt: tie brackets	No	
Fall protection wire	No	
Thickness of front hoistway wa	200 mm	
Thickness of rear hoistway wal	200 mm	
Thickness of left hoistway wal	200.0 mm	
Thickness of right hoistway wa	200.0 mm	
Material of the hoistway head	Concrete	
Material of the hoistway pit	Concrete	
Material of the hoistway trav	Concrete	
Opt:cracked concrete	Yes	
Guide rail fixing head	Anchor bolts	
Guide rail fix at Travel Posi.	Anchor bolts	
Guide rail fixing pit	Anchor bolts	
Anchor bolt type	for seismic application or cra	
Dist. car rail to Z-braket	910 mm	
Opt: OMEGA CONNECTION PLATE	No	
Opt:L Bracket connection plate	No	
Opt: Z-bracket connect. plate	No	
Opt: reinforcement shims	No	
Type of machine	PML145	
Omega bracket family in head	B	
Omega bracket family in trav	B	
Omega bracket family in pit	B	
Opt: fishplate shims	No	
Opt: rail bracket shim ù	No	
Opt: craneable packing	No	
Number of floors	10	
Height of Safety System CAR	55.748 m	
Opt: welded bracket plates	No	
Hoistway headroom (HSK)	4,600 mm	
Qty M12 anchor bolts, Z-brack.	90	
Qty M12 anchor bolts, U-brack.	180	
Qty M12 anchor bolts, L-brack.	0	
Qty M16 anchor bolts, Z-brack.	0	
Qty M16 anchor bolts, U-brack.	0	
Qty M16 anchor bolts, L-brack.	0	

Qty M12 hook bolts f. brackets 0

Qty M16 hook bolts f. brackets 0

Quantity of M12 chem.bolt kits 0

Quantity of M16 chem.bolt kits 0

Qty M12 thin wall kit Z-bkt 0

Qty M16 thin wall kit Z-bkt 0

Qty M12 thin wall kit U-bkt 0

Qty M12 thin wall kit L-bkt 0

Qty M12 steel beam bkt bolts 0

Qty M16 steel beam bkt bolts 0

Type of traveling cable fixati Bracket

Car clip family SL

CWT clip family SL

Clip Design or not for support Yes

Off.travel.cabl.to car CL,TK-d -500 mm

Car side governor type SA GBP 201

CWT buffer category Hydraulic

Car buffer category Hydraulic