

=====			No
Modified order			
Supplier ID			
=====			
Product Change	Period	CP	369
Sourcing zone			Supply chain Europe
Installation zone			Zone EU
Country of installation			ES
Product line			F3
Elevator system			ES5 (with STM up to 3.0 m/s)
Market cluster			Market Cluster 5.1
Elevator system			Elevator system 5
Elevator standard			EN 81-20:2020
Technical documentation	lang.		Spanish
Shipping document.	language		Spanish
Label language			Spanish
Packing type			Normal
Packing material			Normal
Designation within group			Elevator A
Code for type examination			Not relevant
Elevator inspection code			Not relevant

Guide Rail System Type	Guide rail system MM GRS 533
Counterweight Types	GGM43 51
Type of machine support	MR side type 2
Type of machine	PML145
Hoisting motor type	PML145-A
No. of suspens. ropes/belts ZZ	4
Number of STM	4 EA
Dist. CWT center to wall SG	130 mm
Travel height HQ	48,320 m
Rated speed (VKN)	1.60 m/s
Rated load GQ	1350 kg
Machine Room Type	Mini machine room
Opt: common machine room	No
Machine room width	2,501 m
Offset MR-shaft BS left(BO1)	0 mm
Right offset of MR to hoistway	0 mm
Machine room depth	2,300 m
Hoistway width (BS)	2,501 mm
Hoistway depth (TS)	2,300 mm
Pitch diameter of CWT pulley	150 mm
Traction sheave pitch diameter	112 mm
Opt: KSSG contact	Yes
Length of cable for KSSG switc	8,000 m
Option: CWT safety gear	No
Counterweight position	left wall:center
Counterweight zone	CWT SIDE
Counterweight location	On the left side
Type of car safety gear	Safety Gear GED 20
Car side governor type	SA GBP 201
Width of counterweight (BG)	1,002 mm
Depth of counterweight (TG)	190 mm
Type of CWT guide rail	T75-3/B
CAR RAIL TYPE	T89/B
Dist.right wall guide rail SF2	172 mm
Force of STM on car side FZ1	29,251 N
Force of STM on CWT side FZ2	28,726 N
HSKType	Standard head
HSG Type	Standard pit
Position of car overspeed go.	160 mm
Hoistway headroom (HSK)	4,600 mm
Type of STM	STM-PV40
Seismic application	No
Type of cables	PVC
Opt: craneable packing	No
Height CWT guide rail prof.HFP	62,00 mm
Length Motor Fixing	780 mm
Dist. CWT rail to car rail	190 mm
Height from top of car guide..	64 mm
Dist.from SG to bracket beam	145 mm
Width of spacer	0 mm
Distance between the STMs, c...	430 mm
Distance between the 4 STMs	80 mm
Opt: frequency convert. Holder	No
Opt:cracked concrete	Yes
Dist.CWT axis to car rail back	145 mm
Opt: emerg.stop switch machine	Yes
Opt: output contactor box	No
Framework agreement	No