

Material	59001034	COS Fix Points
Termin	18.06.2026	

===== Modifizierte Bestellung	===== Nein
Lieferanten-ID	
===== Product Change Period - CP	===== 369
Beschaffungszone	Supply chain Europe
Installationszone	Zone EU
Installationsland	DE
Produktlinie	F3
Elevator System (ES)	ES5 (mit STM bis zu 3,0 m/s)
Aufzugssystem	ES 5.1
GRP_ES	ES5
Aufzugsnorm	EN 81-20:2020
Sprache Technische Dokumente	Deutsch
Sprache Transport Dokumente	Deutsch
Sprache Bezeichnungsschild	Deutsch
Verpackungsart	Normal
Verpackungsmaterial	Normal
Bezeichnung innerhalb Gruppe	Aufzug A
Baumusterprüfnummer	nicht relevant
Aufzugsinspektionsverordnung	nicht relevant

Material 59001034 COS Fix Points
Termin 18.06.2026

Guide Rail System Type	Guide rail system MM GRS 513
Counterweight Types	GGM43_51
Machine Room Type	Machine room less
Force of STM on car side FZ1	32.342 N
Type of CWT guide rail	T75-3/B
CAR RAIL TYPE	T89/B
Type of STM	STM-PV40
Hoistway headroom (HSK)	4.100 mm
HSKType	Standard head
HSG Type	Standard Pit
No. of suspens. ropes/belts ZZ	4
Number of STM	4 EA
Contact located in the fixpo	Yes
Opt: KSSG contact	Yes
Length of cable for KSSG switc	30,000 m 40,00 m
Length of cable for KSS switch	30,000 m 40,00 m
Clip Design or not for support	Yes
Car side governor type	SA GBP 201
Option: CWT safety gear	No
Counterweight position	left wall;center
Counterweight zone	CWT SIDE
Counterweight location	On the left side
Dist. CWT center to wall SG	173 mm
Travel height HQ	20,400 m
Rated speed (VKN)	1,00 m/s
Rated load GQ	1350 kg
Hoistway width (BS)	2.500 mm
Hoistway depth (TS)	2.190 mm
Type of cables	PVC
Category of compensating means	No
Distance between the 4 STMs	80 mm
Type of machine	PML145
Hoisting motor type	PML145-A
Car fixpoint type	ES5.1&5.2 Car Fixpoint type 4
Type of machine support	MRL side type2
Opt: craneable packing	No
Dist. from rail to magn. band	626 mm
Overspeed govern. position car	Pos component front right
Type of load measuring system	AC LMF with 2 sensors
Framework agreement	No