

Guide Rail System Type	Guide rail system MM GRS 513
Material of the hoistway pit	Concrete
Type of machine	PML145
Travel height HQ	36,705 m
Rated load GQ	1800 kg
Rated speed (VKN)	2,00 m/s
Hoistway height	43,005 m
Hoistway width (BS)	2.260 mm
Width of counterweight (BG)	1.400 mm
Counterweight Types	GGM43 51
Counterweight zone	CWT SIDE
Counterweight location	On the left side
Counterweight position	left wall;center
Distance Guides CW BGS	1.444 mm
Category of compensating means	No
No. of suspens. ropes/belts ZZ	4
Number of SWR	
Number of STM	4 EA
Number of compensating rope.	
Number of compensating rope	
number compensating chain ZUK	
Rope diameter DZ	
Deflection pulley diameter DR	
Reeving factor KZU	2
Buffer distance underneath cwt	0
Chain/rope dis. underneath CWT	
Traction sheave pitch diameter	112 mm
Dist.left wall guide rail SF1	
Dist.right wall guide rail SF2	107 mm
Dist.right wall CWT rail SF3	
Dist. left wall CWT rail SF4	
Type of cables	PVC
Depth of hoistway pit (HSG)	1.800 mm
Dist. CWT center to wall SG	120 mm
Depth of counterweight (TG)	160 mm
Dist.CWT to buffer/plinth HGP	120 mm
Hoistway headroom (HSK)	4.500 mm
Height of CWT frame (HGR)	2.700 mm
Dist.CWT axis to car rail back	125 mm
Height plinth undern. CWT HSS2	35 mm
Height of car buffer stand	585 mm
No. of Buffers for CW ZPG	1
No. of Buffers for Car ZPK	1
Car weight GK	2.035 kg
Weight comp. rope tension dev.	
Height of buffers, fully exten	
Height of CWT buffer HP	776,0 mm
Height of car buffer HP	776,0 mm
Weight of counterweight GG	2.944 kg
Width of Counterweight Frame	1.400 mm
Diameter of compensating rope	
Contact located in the fixpo	
Opt: KSSG contact	Yes
Length of cable for KSSG switc	15,000 m
Opt: T bracket	No
Car guid.ax.to wellfrontw.TKSW	
Dist. car door - land.door TKS	30 mm
Car width BK	1.650 mm
Car depth TK	2.200 mm
Height of Safety System[HQB]	

Height of Safety System CWT	
Distance between guides BKS	1.730 mm
Buffer stroke HPH	
CWT buffer stroke HPH	
Car buffer stroke HPH	
CWT buffer stroke	282,7 mm
Car buffer stroke	282,7 mm
Height of buffers, compr. HPE	
Transversal Beam Width TBW	30 mm
Thickn. weld.brack.plate left	0 mm
Thickn. weld.brack.plate right	0 mm
Thickn. weld.brack.plate rear	0 mm
Type of CWT guide rail	T89/B
CAR RAIL TYPE	T127-1/B
Rope Type	
SWR category	
Seismic application	No
Option: CWT safety gear	No
Type of CWT safety gear	
Type of compensating chain	
Anti snag cable length	
CW safety gear modul	
Compensation chain length	
Chain guide type on CWT side	
Length of compensation chain	
Car side governor type	SA WOL 35M
Type of CWT overspeed governor	
HSKType	Reduced head
HSG Type	Standard pit
Height CWT guide rail prof.HFP	62,00 mm
Height CWT buffers, compr. HPE	489,0 mm
Height car buffers, compr. HPE	489,0 mm
Driling in pit floor allowed	
Option: drilling in pit floor	No
Installation method	
Opt: frame in pit set	No
Maintenance platform or not	No
Buffer distance underneath car	0
number of brakes	
Number of motor brakes	
Length of KSS switch	
Length of cable for KSS switch	
Guide rail oil need or not	
Oil Type for guiderail track	No
Machine Room Type	Machine room less
Width of counterweight guide r	
Bladewidth CWT-Guiderailtr.BFK	
Width of counterweight guide..	
Width of guide rail head CWT	16,0 mm
Installation Height of Chain	
Horizontal distance TZ	
Car guid.ax.to CWT guid.ax TKG	
Carguid.tr.c.CWTguid.tr.c TKG3	
Car guid.trckc.CWTguid.ax TKG1	1.079,0 mm
Carguid.ax-CWTguid.trckc. TKG2	0 mm
CWT guide shoe type	Guide shoe GSR 3 CWSS
CAR guide shoe type	Guide Shoe GSR 200 A
Category of CWT guide shoes	Roller guide shoe
Guide shoe type	Roller guide shoe
Pit maintenance trap door	

Material 59001045
COS Pit Set

Opt: trapdoor maint. Platform	No
Refuge space posture in pit	2 x Refuge Spaces Laying
refuge space type sticker pit	
Drive Position	Left side or left direction
MR cable routing	
Material of cable duct in MR	
Cable duct 100 length	
Cable duct 70 length	
Cable duct 60 length	
Instal acc 60 qty	
Horizontal bend 60 qty	
T bend 60 qty	
vertical bend 60 qty	
Qty install.accessor. duct 60	
Qty horiz. bends for duct 60	
Qty of T bends for duct 60	
Qty vertic.bends for duct 60	
Cable duct 120 length	
instal acc 120 qty	
horizontal bend 120 qty	
t bend 120 qty	
vertical bend 120 qty	
Qty install.accessor. duct 120	
Qty horiz. bends for duct 120	
Qty of T bends for duct 120	
Qty vertic.bends for duct 120	
Cable pipe PIPE length	
Pipe clamp CLAMP QTY	
Pvc cable DUCT length	
Corrugated conduit CONDUIT typ	
Corrugated conduit CONDUIT len	
Cable duct Ground wire WIRE le	
Cable duct fixture acc ACC QTY	
Qty fixation mat.cable ducts	
Car buffer plinth type	
Cwt buffer plinth type	
Type of car buffer stand	STEEL
Type of CWT buffer stand	STEEL
Car buffer type	SA OLE MLB20
Counterweight buffer type	SA OLE MLB20
Carbuffer stabilizer STABILIZE	
Cwtbuffer stabilizer STABILIZE	
Type of car buffer stabilizer	
Type of car buffer stabilizer	
Length car buffer stabilizer	
Length CWT buffer stabilizer	
Plinth beam len for car	
Plinth beam len for cwt	
M value for car	3.835,000 kg
M value for cwt	2.944,000 kg
Plinth protection	No
Opt: car buffer plinth protect	No
Chain safety switch	
Opt: comp. chain safety switch	
BKS Fixation	Yes
Opt: BGS fixation	Yes
Cwt buffer location	In the pit
Opt: counterweight screen	
Timbers Qty.	
Length of Edge Protector for	

Len of Edge Prot for sheetlmm	
Counterweight screen height	
Min. CWT screen top height	2.000 mm
Dist landing to maint. platf.	
Height guiding chain HGC	
Height of chain guide on CWT	
Maintenance hall relevance	
ASS3 Type	
Comp.rope tension device heigh	
Car rail head # buffer center	865 mm
FF1 EXT	
FF1 max	3.377 N
FF2 max	2.264 N
FF1 NO	1.153 N
FF2 NO	1.023 N
FF1g max	1.937 N
FF2g max	1.430 N
FF1G NO	852 N
FF2G NO	510 N
Opt:Steel buffer 57646894	
Opt:Steel buffer 57642513	
Steel buffer HSS2 & ZONE	
Tension device Type	
Tension device Type CAR	
Tension device Type CWT	
GB Tension Device Type CAR	TD203 Car 59348350
GB Tension Device Type CWT	
TSD Switch	No
Temporary safefy device type	
TSD position in hoistway	
Type of Traction Beam	
Position of oversp. gov. CWT	
Balanced evacuation kit (BEK)	Yes
Type of STM	STM-PV50
Opt: craneable packing	No
CWT buffer category	Hydraulic
Car buffer category	Hydraulic
Height of removable plinths ..	
No. of refuge spaces in pit	2
Heigth 1. refuge space in pit	500 mm
Heigth 2. refuge space in pit	500 mm
Width 1. refuge space in Pit	1.000
Width 2. refuge space in pit	1.000
Depth 1. refuge space in pit	700
Depth 2. refuge space in pit	700
Opt: pit door	N
Building tolerance	
Number of car entrances	2
Opt: pit ladder	Yes
Opt: pit step	
Net load at rail base up dir	
Net load car rail base up dir	0 N
Net load CWT rail base up dir	0 N
Opt: docking device	No
Sagging height of comp. chain	
Safety distance chain to pit	
Number of elevators in one grp	
Opt: CWT buffer impact assy	
CWT buffer impact material	
Hoisting motor type	PML145-A

Sourcing Zone - Machine
Rail buckling at ground level
Rail mounting method, CWT side Rail support is used
Rail mounting method, car side Rail support is used
Type of CWT guide rail base
CWT side rail support type RS V14 CWT
Type of CAR guide rail base
CAR side rail support type RS V14 CAR
Width door BT 1000 mm
Car sill edge # car guide axis 1.210,0 mm
Car sill edge-car guide axis_1 1.210,0 mm
Car sill edge-car guide axis_2 1.210,0 mm
Hor.dist.car entr.CL to car CL -75 mm
Dist. car entr. 1 CL to car CL -75 mm
Dist. car entr. 2 CL to car CL -75 mm
Height CAR guide rail prof.HFP 89,00 mm
Type of hoistway information
AC GSI main sensor variant
Drive brake type
SPH position in hoistway Not required
Position of JHSG1 in hoistway right wall;rear
Pit ladder type Foldable
Stop Button Bracket variant
Opt: JHSG1 bracket No
Distance wall to JHSG1 back
Tolarance range for HGP -20mm/0mm
Length 1 bot. CWT rail L
Length 1 bot. CWT rail R
Car wall/g-rail distance TK1 1.100,0 mm
Car wall/g-rail distance TK2 1.100,0 mm
HGU min
Height CWT shoe & supp.bearing
Maximum mass one buffer (GPZ2)
Type of machine support MRL_SIDE_TYPE_2
Disable configuration checks
Opt: CWT frame cover
LTSD21 Pit
Opt:cracked concrete Yes