## Homework 1 Sp25

- Due Feb 25 at 11:59pm
- Points 5
- Questions 5
- Available Feb 18 at 12am Feb 25 at 11:59pm
- Time Limit None
- Allowed Attempts 5

## Attempt History

	Attempt	Time	Score
KEPT	Attempt 5	44 minutes	5 out of 5
LATEST	Attempt 5	44 minutes	5 out of 5
	Attempt 4	78 minutes	4.67 out of 5
	Attempt 3	9 minutes	3.75 out of 5
	Attempt 2	12 minutes	3.75 out of 5
	Attempt 1	8,531 minutes	4 out of 5

## (!) Correct answers are hidden.

Score for this attempt: 5 out of 5 Submitted Feb 24 at 9:26pm This attempt took 44 minutes.

::

Question 1

1 / 1 pts

Suppose users share a 323 Mbps link. Also suppose each user requires 732 kbps when transmitting but each user transmits only 0.32 of the time.

Answer the following questions and for the final answer enter the answer like: Question 1a answer + Question 1b answer. For example, if for first part the answer is 10 and for second part is 256, please enter 266

- a- When circuit switching is used, how many users can be supported? each 1 Mbps is 1024 kbps
- b- Assume we want to use packet switching instead of circuit switching, suppose there are 9 users. Find the probability that at any given time,

exactly 7 users are transmitting simultaneously.

451.85

::


Question 2

1 / 1 pts

Which of the following statements are true regarding the comparison of packet switching and circuit switching? (Choose all that apply)

Circuit switching is more efficient than packet switching when handling bursty traffic, as it provides a constant dedicated bandwidth.

Packet switching can handle variable data rates more effectively, while circuit switching may waste resources when no data is being transmitted.
In packet switching, data is divided into packets that may take different routes to reach the destination, whereas in circuit switching, data follows a fixed route throughout the communication.
Packet switching generally offers lower latency compared to circuit switching due to the dedicated paths used in circuit switching.
Packet switching allows multiple users to share the same communication path simultaneously, while circuit switching requires a dedicated path for each communication.
Question 3
1 / 1 pts
Consider a client and a server connected through one router. Assume the router can start transmitting an incoming packet after receiving its first 69 bytes instead of the whole packet. Suppose that the link rates are 650 byte/s and that the client
transmits one packet with a size of 133 bytes to the server. What is the end-to-end
delay in seconds with 8 routers between the server and client? Assume the propagation, processing, and queuing delays are negligible.
1.05
Question 4
1 / 1 pts
Which of the following protocols are application layer protocols?
POP3
BGP
SSH
□ NAT
Question 5
1 / 1 pts
Suppose that there are 12 client-server pairs.
Denote Rs=63, Rc=47, and R=57 for the rates of the server links, client links, and network link. Assume all other links have abundant capacity and that there is no other traffic in the network besides the traffic generated by



Quiz Score: 5 out of 5