Research Architect for Coordinated AI Research

Technical white paper with an operational case study from the NWSW project

Brandon Santor
Creator and Principal Designer of Research Architect
October 31 2026

Executive summary

Research Architect provides an operating framework for human research teams working with AI. It helps design new work or organize an existing project around its retained evidence, decisions and constraints. The Architect proposes methods and feasible assignments; the accountable human chooses the design, authorities and consequential changes. A reviewed design becomes individual role kits with project instructions, selected methodological guidance, local helpers and continuity records. The New World Screwworm (NWSW) deployment supplied an active setting in which these mechanisms were used and refined. Its shared Library retains approved findings, methods, provenance, artifacts and use limits. The Hub alone publishes additions and corrections; Spokes and Ingestor read approved evidence directly within their permissions and return new contributions through the configured review process. [E5] [E6] [E11]

The documented results include creator-reported onboarding of eight people, verified remote exchanges, preservation of accumulated files during a live Hub upgrade and an isolated whole-project restore. The current RA 2.6.1 factory supplies executable setup-environment verification, review of the exact written plan before kit creation, scoped delivery and retained approval evidence. The October 27 publisher repair adds local incremental preparation, compatible Library retrieval and durable publication-evidence checks to future kits. Historical deployment results and software checks retain their separate dates and work units. [E1] [E2] [E7] [E10]

RA applies the established 10th man principle through guidance for challenging consensus, preserving dissent and recording reviewer independence. Selective retrieval and durable checkpoints support continuity without reloading the entire project on every prompt. Retained context measurements and research-workflow cases demonstrate particular operations and corrections. Whether these practices reliably reduce groupthink, improve scientific conclusions or lower total research cost remains to be tested. [12] [14] [E11] [E12] [E13]

Selected dated operational and release results [E1] [E2]

Capability	Documented result and scope
Onboarding	Eight people reported onboarded by the creator on October 16; one framework configurator.
Exchange records	262 unique transfer IDs in the October 16 inventory; individual receipts establish delivery.
Live upgrade continuity	701 exchange files preserved and rehashed during the October 13 Hub upgrade.
Project recovery	123,098 files verified in the original October 11 isolated restore exercise.
Release verification	171 offline tests passed on Windows; no model calls or remote transfers in that run.

This paper brings the engineering account to RA 2.6.1 while retaining the deployment case. Documented field operation includes Architect use in Codex and generated-kit operation across the reported Antigravity, Claude and Codex environments. RA requires a coding-capable agent workspace with persistent local files and code execution; any provider meeting those capabilities can qualify. The framework supplies usable software and coordination functions around existing models. Broader adoption and comparative research-quality effects remain questions for separate evaluation. [E7] [E8]

1 Introduction

AI-assisted research often spans several people, model sessions and collections of files. A useful answer becomes difficult to carry forward when the next session lacks its scope, supporting evidence, decisions or unresolved work. Teams also need to identify the current artifact, distinguish review from delivery and recover work after a session or machine changes.

Existing agent literature supplies useful design context. OpenAI describes models, tools and instructions as foundational components and discusses orchestration and guardrails. AutoGen demonstrates configurable conversations combining agents, tools and human input. Anthropic describes the coordination, evaluation and reliability work behind a deployed multi-agent research system. These sources inform the architectural context; their performance results are not evidence of RA performance. [1] [2] [3]

RA addresses the operating structure surrounding a research task. The Architect helps establish questions, assignments, methods, dependencies and review requirements. A compiler produces individual role kits and coordinated folders. Local helpers preserve state, inspect artifacts, prepare reviewed exchanges and support recovery. The selected coding-agent host supplies model inference and actual file/code access. These tools extend the workflow available to the agent without changing its model weights. Human operators retain responsibility for scientific judgments and consequential decisions. [E7]

2 System architecture

RA combines a reviewed project design, human-operated roles, persistent records and a shared project Library. Figure 1 separates Hub read/write access from Spoke and Ingestor read-only access. Only the Hub publishes additions and corrections. RA's scientific-methods collection supplies research guidance to the factory; the Library retains approved project findings for contextual reuse.

Each host installation needs its own tested startup, storage and transfer configuration. [E3] [E4] [E5] [E6]

Project design and role kits

The Hub issues bounded tasks, reviews contributions and validation results, obtains final human approval and uses its read/write Library authority to publish additions and corrections. Spokes conduct assigned work with their human operators, who accept and approve exact submissions. The Ingestor receives Hub-accepted work, validates it and reproduces results when needed, then returns its findings to the Hub. Generated kits carry these responsibilities, selected methods and continuity records. Generation does not grant remote access or establish scientific approval. [E6]

The Architect begins with the research question and the claim the team wants to support. It considers available observations, measurement limits, units of analysis, assumptions and appropriate checks. Its scientific-methods collection supplies guidance, worked examples and routes to original publications. Method recommendation requires assessing that guidance against the actual project; bibliographic availability or inclusion in a kit does not establish suitability. Consequential applications require inspecting the relevant original material and qualified human review. If the collection does not adequately cover a specialized method, the gap should remain explicit while additional project-specific guidance is researched and proposed for review. [E4] [E11]

The design also accounts for who has the expertise and time to conduct and review the work. The workload record includes available hours, methodological competence, deadlines, dependencies, anticipated rework and review burden. AI/runtime limits, such as tool availability, quotas, persistent storage and budget, enter the assessment when they affect feasibility. The Architect can recommend reassigning work, reducing scope, changing the schedule or obtaining focused specialist review. The human authority chooses the configuration; estimates retain uncertainty, and adding agents is not assumed to add useful capacity. [E11]

The human lead establishes project scope, decision authority, evidence-use boundaries and approval responsibilities with the team and applicable institutional requirements. Researchers remain responsible for their submissions and the access they control. The Hub coordinates work within those decisions; it does not acquire authority to expand access, change a study's consequential methods or accept a finding merely by recommending it. The Ingestor reports what it checked and reproduced, including unresolved discrepancies. Local software verifies defined technical conditions; qualified humans judge scientific adequacy and authorize consequential use. [E6] [E11]

Evidence boundaries have a research purpose. An item may be outside the agreed question, awaiting verification, restricted to a particular audience, or intentionally withheld until an independent first assessment is recorded. Such limits can protect confidentiality, preserve a valid comparison or prevent an unreviewed claim from becoming a shared assumption. Methodologically necessary information must not be concealed to manufacture a preferred result. The authorized human decides changes to these boundaries; the Hub records and implements the applicable scope, subject to actual host and storage permissions. [E11]

Research assignments, submissions, disagreements, proposed corrections and release decisions pass through the configured Hub routes. Approved Library lookups can occur directly. A participant's private conversation or local files become shared project evidence only when captured and delivered through an authorized route; the Hub does not automatically observe every device or conversation. [E6] [E11]

Local agent workspace and verified setup

RA and its kits operate in an agent environment that can access persistent local project files and execute code on the machine. Codex, Antigravity and Claude Code are examples, rather than a provider whitelist. Uploading a ZIP to ordinary browser-only chat or running code in a temporary sandbox does not establish the required working environment. Manual file exchange and recovery remain useful between suitable local workspaces. [E7] [E8]

After the environment and Python responses, a bounded preflight requires an agent file challenge, saved readback and a result from an independent Python process. The environment respondent explicitly confirms the actual local agent workspace and persistent host. Missing, stale or withdrawn evidence blocks later intake and all supported kit-generation routes. File/code access is machine-checked; physical locality and long-term host durability are human-confirmed. The same saved evidence is rechecked on resume and before publication without repeatedly launching the worker. [E7]

Model choices and operating costs

The Architect records the models and reasoning settings each operator can actually select, then recommends a default for each role. The plan includes the task rationale, expected cost tradeoff, available alternatives, switching conditions, an acceptance check and a retry limit. A single available model is valid; unavailable alternatives and unknown settings remain explicit. Recommendations based on documentation, operator experience or initial judgment are marked PROVISIONAL. MEASURED recommendations require comparable trial evidence and a dated reference. The compiler checks the record's structure and bindings, not the truth of a model-performance claim. [E11]

At runtime, an agent can recommend a stronger or lighter option under the recorded conditions. The human decides whether to switch, and actual access and provider permissions still apply. The agent reports its current model or reasoning setting only when the host exposes it or the operator confirms it. Routine integrity checks and diagnostics can run locally without another model call. Total cost assessment includes setup, review, failed attempts, saving and restoration; unavailable usage or billing remains unknown. Persistent local project storage does not imply local model inference: the selected host and provider determine where requests are processed and which material is transmitted. [E11]

Written plan and scoped delivery

The finalized design produces a shared-team PDF and a Hub PDF. The shared edition contains the permitted team context and explicitly selected coordinator sections; the Hub edition also carries its approved coordinator records and setup responsibilities. Role-specific handoffs preserve the storage, transport, permissions, model plan, owners and pending actions relevant to each recipient. Generation does not configure cloud accounts or grant permissions. [E7]

Before kits can be created, the accountable human must approve the exact bytes of both plan editions, bound to the configuration and source snapshot. Compilation copies those reviewed PDFs unchanged and attaches separate review receipts. Changed configuration, intake or plan artifacts require renewed review; explicit refusal blocks creation. Existing approval events remain in history. The current build also requires the verified setup-environment receipt, so recorded prose alone cannot satisfy the local-capability requirement. [E7]

Persistent context and source retrieval

Supported startup resolves the designated current checkpoint rather than choosing a directory by timestamp. Successor snapshots preserve their base and record changed state. The current generated startup uses selective retrieval: it selects the declared source scope for the requested intent, emits each required control once and replaces only exact repeated original lines with backward references. Before publication, it reconstructs every selected source byte and checks the source bindings. Original records remain available. The classic multipart path, with repeated governing controls, remains an explicit alternative. These controls preserve selected text and detect missing or altered parts; they do not establish that a model has understood or retained it. [E11] [E12]

Ordinary questions use bounded lookup of the relevant records. Routine message or diagnostic operations have scoped routes; resolving the current checkpoint or checking files on disk does not require emitting every file into the model's context. Within the same conversation, compact reuse is permitted only after fresh local source and selector checks and explicit confirmation that all required selected context was read and remains available. A saved index cannot prove that retention. A new session, context loss, uncertainty or a changed checkpoint, source, instruction, reader or sealed Library configuration requires renewed context output. Complete restoration is an explicit operation over its declared scope. [E11]

The active context window is the material available to the model for its current response. Project records persist outside that window. If the host condenses older messages or a researcher opens another conversation, restoration retrieves the current controls, state and task-relevant evidence from those records. RA does not enlarge the provider's context window, guarantee unlimited cumulative retention or reload the entire project at every prompt. It also does not retrain the model's neural-network weights when the team corrects a finding. Saved decisions, mistakes and their resolutions become retrievable project knowledge; their correct use still requires checking. [E11]

The persistence protocol calls for saving at meaningful milestones, review decisions, handoffs, session closure and before expected context loss. A researcher can ask, for example, "Save my spot, record what changed and what remains unresolved, and tell me exactly where to resume." This is a natural-language instruction to invoke the save workflow, not a universal hardcoded command or an automatic guarantee. The agent updates the research and workflow state, session handoff, index and changed linked records; it preserves the previous confirmed checkpoint, verifies the saved bytes and reports the exact resume point and pending work. A failed or partial save remains PENDING. "Resume from the saved checkpoint" then requires identity and version checks and reconciliation of intervening changes. Information left only in an unsaved conversation remains vulnerable, and closing a session does not close its research workstream. [E11]

Figure 6 gives a worked example of focused retrieval after required startup. An invented 437,112-character record remains in storage while a 2,450-character working context carries the current question, human decision, unresolved issue and exact source routes. Retrieving the relevant original passages brings that task input to 3,716 characters, before the answer is added. The answer retains the approved exclusion interval and the pending sensitivity check. Other questions can require other records. These illustrative counts do not measure RA restoration or show the entire archive compressed into a short summary. Exact duplicate removal during restoration and conditional reuse of already-retained context are separate mechanisms, described above and in the measured results. [E11] [E12]




Figure 1 Roles and Library authority. Teal arrows show Hub read/write access for additions and corrections. Dashed blue arrows show Spoke and Ingestor read-only access. Contributions return to the Hub; Figure 5 details review. [E3] [E4] [E5] [E6]

Shared Library and cumulative project knowledge

The shared Library retains approved project evidence and outputs. Researchers and agents inspect prior findings, methods and artifacts for reuse within their recorded scope. The Hub reads the collection and is its sole writer of additions and corrections. Spokes and Ingestor have read-only access. This supplies the shared-learning mechanism: agents retrieve and interpret versioned project knowledge, carrying provenance into new work. [E5] [E6]

Discovery preserves canonical artifact and version identities, original locations, dependencies, review status and correction relationships. Membership references let one canonical item appear in several collections without duplicating the research output. Extracted packages retain their relative paths and parent bindings. A Hub-published correction can be exposed through both the canonical record and its discovery routes, helping agents recognize which version and limitations apply. [E5]

The outward availability labels are Available in Library and Request from Hub. Already-approved files and verified aliases remain usable within their original scope without repeating approval; safe metadata for held work directs a request to the Hub. Shared views use reviewed audience selections and omit restricted internal records. The Library is distinct from RA's bundled scientific-methods collection: the former retains a team's evolving evidence and outputs, while the latter supplies reusable research guidance for configuring kits. [E4] [E5]

A researcher can discover reviewed catalog metadata for held work without receiving its payload or permission to use the finding. A request should identify the exact artifact and version, explain the research dependency and intended use, and retain audience and other relevant limits. The Hub

checks whether the item is located, cleared, still under review or unavailable. It can coordinate remaining checks and recommend prioritizing review or release; the human lead decides consequential changes to assignments, deadlines or access. In the inspected NWSW configuration, requests use the participant's existing Hub route and inform Brandon's review priorities. Fulfillment is not guaranteed, and restricted metadata or unlocated acquisition leads need not appear in shared discovery. This deployment illustrates the generic discovery/request capability; it does not establish a universal automatic prioritization queue. [E14]

Evidence review and decision traceability

The Hub defines a bounded task with scope, inputs, methods, artifacts and acceptance criteria. The Spoke performs it, and its human approves the exact submission. The Hub reviews and accepts it for Ingestor validation and any needed reproduction. The Ingestor returns checks, discrepancies and limits. The Hub obtains final human approval, publishes the exact version with its use scope, and verifies publication. Failed checks return for correction and repeat affected reviews. Other roles propose Library corrections; only the Hub applies and publishes them, preserving prior versions and decisions. [E6]

Human-agent discussions can preserve the decisions, alternatives, objections and reasoning behind an output. The supported reviewer-bundle helper binds supplied conversation files and their declared session coverage to the research package for Hub review. All relevant supplied discussion remains available as evidence; summaries do not replace the transcripts. The helper does not automatically capture every host message, tool call or attachment, so missing coverage must be declared. Transcripts stay in restricted review storage; publishing a research finding does not automatically disclose its raw conversations. [E6]

Applying the established 10th man principle

RA applies the established 10th man principle as a deliberate challenge to apparent consensus. The familiar formulation assigns someone to examine the possibility that the prevailing conclusion is wrong. Professional discussion uses the name, and the underlying practice of devil's advocacy has a longer history. In Psychology of Intelligence Analysis, the CIA's Center for the Study of Intelligence describes assigning a reviewer to develop a minority interpretation and expose assumptions behind competing views. RA adapts that approach to coordinated human-AI research; it does not claim to originate the principle. [12] [14]

RA preserves independent assessments through controlled evidence access. Under the governing workflow, a Spoke has no authorized access to another Spoke's output unless the Hub explicitly authorizes its release. An independent first assessment therefore precedes exposure to the other interpretation. The Hub records permitted disclosure and preserves initial assessments before comparison. Later authorized exposure changes the reviewer's recorded exposure status; it does not retroactively make the first assessment a consensus response. The accountable human decides whether to accept the work. Access separation supports independence, while human approval establishes the acceptance decision. [E6] [E11]

Operational awareness means knowing each agent's assignment, the evidence and interpretations it has seen, its authorized access, current decisions and conditions for stopping or escalating. The Hub coordinates that awareness through task, disclosure, handoff and review records. Review records identify the reviewer, exact artifact, material available or intentionally withheld, actual checks, disagreements and rationale. An exposed reviewer cannot later be described as blinded. These are governing instructions and record structures; the records must establish how the boundaries were

maintained in a particular operation. They do not create a universal technical access barrier across unrestricted host applications. [E6] [E11]

The responsible human and Hub define the challenge question, appropriate evidence access, reviewer or review mechanism, stopping conditions and decision authority. The reviewer tests credible alternatives and may conclude that the original result survives scrutiny. After an independent assessment, the Hub may authorize scoped comparison while preserving dissent for the human's final decision. A leading assignment, accidental disclosure or unauthorized access can compromise independence without a deliberate human decision to seek agreement. The process stops when the issue is resolved, available evidence cannot distinguish the alternatives or the authorized budget is exhausted; unresolved concerns remain visible. [E11]

For consequential findings, the governance guidance recommends qualified independent review or an appropriate challenge mechanism when feasible. If the Hub operator, contributor reviewer and final authority are the same person, the record must disclose that overlap. When another independent human is unavailable, the authorized human can proceed as documented self-review, recording checks, limitations, residual uncertainty and the actual decision, subject to applicable institutional requirements. The safeguards themselves need evaluation: both compliance with the procedure and its effect on error detection, evidence quality, cost and final decisions. Historical familiarity does not establish effectiveness in RA. [13] [E11]

Outside research and focused specialist review

A published study, agency dataset, external analysis or commissioned report can be brought forward by the lead, a researcher or the Hub within the project's authorized scope. The existing task, validation, review and publication mechanisms can carry that material through a bounded review. The team's responsible human authorizes its submission and intended use; this records the team's decision, not approval invented on behalf of the original authors. Original authorship, access restrictions and provenance remain attached. This route is an application of the existing mechanisms. The inspected package does not supply a separately verified universal outside-research importer or a completed end-to-end trial of arbitrary external intake. [E11]

The handoff needs the exact source and edition, citation or stable locator, relevant supplements, the specific claim or question to check, and available reproduction materials. Where applicable, those materials include data, code, parameters, environment requirements and expected outputs. Missing data, inaccessible methods and unresolved dependencies remain explicit. The Hub sets acceptance criteria within the approved task, the Ingestor reports checks and actual reproduced results, and the Hub obtains the required human decision before publishing an exact version and its permitted use. Reviewing citations and methods is different from reproducing results. If reproduction cannot be completed, the record must state not reproduced or blocked, with the reason; qualified evidence use may still be possible. [E6] [E11]

A focused outside specialist can review a method or finding without receiving a new Spoke kit. Using ordinary document-authoring tools, the Hub agent can prepare a readable packet containing the review question, exact versioned material, necessary project context, evidence and methods, known limitations and requested checks. Material deliberately withheld for an independent first pass is identified in the review record. The specialist's returned assessment records their identity, expertise relevant to the question, checks actually performed, conclusions, disagreement and any remaining conditions. The Hub preserves that return and routes consequential decisions to the authorized human. [E11]

RA supplies a review-record template and workflow guidance; a readable packet can be assembled from those records. PDF or Word export depends on the tools available in the host. A dedicated automatic specialist-packet exporter is not established by the inspected implementation, and sending a packet does not establish that the specialist read it or completed review. This limited consultation also avoids assuming that generating another kit solves the late-stage onboarding problem discussed in Section 7. [E11]

Versioned handoffs and recovery

Local helpers stage payloads, validate configured routes and retain receipts. Authorized host connectors perform remote transfer during active sessions. Preparation, delivery, reading, adoption, research acceptance and permitted downstream use remain distinct. Backup helpers verify selected project contents and captured external files, retain explicit recovery metadata and exercise restoration. Storage and transport configuration remain responsibilities of the deployment.

Diagnostics and repair coordination

The Doctor diagnoses the explicitly selected kit and its configured components. It leaves the sealed kit unchanged while writing external reports and diagnostic-operation records. Its seven scopes cover identity, context, storage, messages, Library, backup and recovery. Compact findings retain complete evidence through bounded continuation. A clean result establishes the checked technical state, rather than scientific approval, and diagnosis does not itself authorize repair. [E7]

The Hub can coordinate a repair and relay the configured human authority's actual, bounded instruction to a Spoke. The Spoke's agent performs permitted work locally, subject to its operator/host controls and the recovery tool's checks. RA supplies no general Hub-issued repair capability or remote-control channel. For example, lock recovery requires the inspected lock hash, the same host and a proven dead owner process. Checkpoint recovery retains its clean-base, review and publication requirements. This preserves practical maintenance coordination without treating a Hub message as a tool grant. [E7]

3 NWSW deployment

The NWSW project provided an operational case for RA-generated kits and a coordinating Hub. The creator reported onboarding eight people by October 16, 2026, while remaining the only person who had run or configured the Architect itself. This is evidence of participant onboarding in a creator-supported deployment, rather than eight independent framework configurations. [E1]

The creator also reports running the Architect in Codex with Astra and 6.1 High, using those supplied model/setting labels, and running generated kits in Antigravity, Claude and Codex. Early browser-chat use caused operational problems that required teammate migrations to suitable local coding-agent workspaces. These are field-use reports, distinct from the smaller scripted early-intake trials. A missing platform name in an older test report does not establish that no kit ran on that platform. [E8]

The Hub maintained exchanges, source routes, instructions and checkpoints while the team continued assigned work. The original case examined selected operational records from October 8 through October 16. Later technical returns, context measurements, research-workflow observations and Library records discussed here extend through October 30; source review for this paper was completed October 31. Each case retains its own observation date and evidence class. Historical quantities are not estimates of the current complete project. [E1] [E7] [E8] [E9] [E12] [E13] [E14]

Generic RA, the deployed NWSW coordination system and the independent NWSW Spatial Evidence Workbench are separate systems. The Workbench's web interface, database, spatial features and application tests are not capabilities or validation results of the RA distribution. The cases below describe operational review, correction and coordination in the customized Hub workflow. They do not publish contributor research payloads or establish that every generated kit automatically performs the same checks. [E13]

4 Operational results

File exchange and instruction continuity

The October 16 inventory recorded 98 incoming and 164 outgoing tickets with 262 unique transfer IDs. Tickets identify prepared exchanges; separate readback records support actual delivery. The October 8 repair distribution comprised 15 logical transfers and 30 remote objects. The October 13 distribution comprised 10 transfers and 20 remote files. The retained checks bound delivered objects to their intended destinations and bytes. [E1]

A complete versioned instruction was delivered through seven participant routes in October. Its register retained identity, version, supersession and observed delivery, with a subsequent report of retention and application. That report does not establish seven persistent installations. Later diagnostic returns and exported execution records strengthened evidence for participant-side setup and multipart restoration, while remaining distinct from independent observation of every device. [E1]

Continuity during engineering changes

The authorized October 13 Hub upgrade preserved and rehashed 701 exchange files, totaling approximately 1.66 GB. Its preceding exchange store and pointer remained unchanged. The post-activation exercise combined file-hash comparison with inventory checks and verified restoration records. This is a demonstrated preservation result for that upgrade, rather than a guarantee that arbitrary concurrent writers can be merged safely. [E1]

An October 15 native Windows context-repair fixture reconstructed a 466,824-character startup section through five resume parts and eight full-context parts. The largest part contained 189,188 characters under the unchanged 200,000-character ceiling. Checks included Unicode and CRLF reconstruction, repeated controls, missing or altered parts and later checkpoint restoration. These are synthetic engineering checks, separate from participant adoption. [E1]

Whole project backup and restoration

The October 11 capture covered 48 included Drive folders, 744 source files and 748 downloaded or exported artifacts, together with local project contents and dependencies. The original isolated restore verified 123,098 files totaling approximately 20.88 GB without using live sources. It materialized recorded dependencies and completed restored integrity and context checks. [E1]

A later authorized content amendment produced a separately documented backup inventory. It does not replace the historical restore result or authorize resurrection of excluded bytes. The deployment's two-copy rolling policy is project-specific; the reusable tools accept explicit retention configuration. Local backup and restore were evidenced, while actual offsite delivery was not established by the inspected capture records. [E1]

Shared Library implementation and publication recovery

The NWSW implementation established preserved holdings, a private census and evidence registers, immutable shared catalog generations, approved stored files and a pinned deployment graph. Readers follow the current designation through the deployment and relevant collection pages. This supports targeted discovery without scanning all research payloads or loading the full collection into model context. The implementation preserves prior versions and exact review bindings when registering reviewed additions and corrections. [E5]

The retained recovery completion records successful verification of the selected catalog, 58 convenience aliases and the status record, followed by guard release. Its final current-pointer observation was October 22, 2026 at 11:51 p.m. Central Daylight Time (October 23 at 04:51 UTC). Separate Hub activation completed at 12:30 a.m. CDT on October 23. These are completed, dated operational results. They establish the recorded publication and recovery outcome; contributor rollout and recipient reading remain separately tracked. [E5]

The October 27 incremental Library publication verified its shared index, navigation, status and normal guard closeout. Its final receipt records 741 selected metadata objects reused, 28 new metadata objects, nine changed aliases verified and 49 unchanged aliases retained. Reuse relied on dated baseline proof and pinned cached bytes, without a fresh full cloud audit. This demonstrates metadata reuse in that deployment; token costs were not measured. The receipt preserves original interrupted-controller qualifications. Participant adoption, scientific acceptance and standing unlock authority were unchanged. [E9]

Research review and coordination in deployed work

An October 29 package assessment found a submission describing a complete set of source records as available, while its retained original explicitly said that the complete roster or independent receiving ledger had not been obtained. The Hub's AI-assisted review identified the contradiction and produced a corrected reader that retained the missing-record qualification. Original packages and the correction lineage remained preserved. The contributor's guided review authorized the exact original submission, not subsequent Hub edits. Brandon separately authorized qualified descriptive use and existing-team Library publication; the release receipt records completed Library publication at 20:26 UTC on October 29. The additional NWSW adviser was an AI agent, not an independent human scientific reviewer. This was a documented correction and bounded release, not independent scientific validation or evidence of participant adoption. [E13]

An October 14 coverage correction separated observation dates from report preparation, final-report and download dates. It made source units and missing coverage explicit. Applying a historical observation cutoff to a later database did not reconstruct the database's historical contents or active statuses. Where the requested historical view could not be established, the corrected output displayed unavailable. Originals were retained, and that correction pass did not rerun the existing simulations or establish independent scientific acceptance. The observation concerns that dated pass; later project work retains its separate status. [E13]

An October 29 visualization correction addressed positive coloring in areas with zero source reports. Brandon authorized a corrected derivative of a contributor's original map, and the Hub with Codex assistance changed the display while preserving source records, dates, identifiers and geometry. Retained verification covers 25 movie frames and 475 county-interior pixel probes, plus 114 pixel probes across six additional temporal boundary dates. A relocated-export comparison also passed. The temporal checks concern dates, not geographic borders. This was rendering verification against

the pinned source, not independent corroboration of the underlying research; the receipt does not establish Library release. Credit for the original and the correction remains distinct. [E13]

An October 21-22 closure exchange distinguished the human's decision from its reported application. Brandon closed eight assignments and reserved reopening to later authorization. A received contributor-side report stated that the registry and workbook were saved, reloaded, refreshed and reloaded again, with all eight remaining complete, inactive and outside pending review. The Hub verified the received report's bytes. It did not inspect the contributor's workbook directly. The case supports recorded administrative closure and reported persistence while preserving history, not new scientific acceptance or a guarantee against later regressions. [E13]

An October 26 route repair found that a contributor's incoming folders had been omitted from configured Hub scans after an earlier repair incorporated only the outgoing route. Under the lead's instruction, the Hub added the existing research/status and restricted-review routes and their explicit bindings, preserved prior configuration entries and verified activation of the repaired checkpoint. No cloud-sharing change was required. A missing scan result therefore did not establish that the contributor had sent no work. The case demonstrates detection and repair of a configuration omission; it does not establish infallible routing or contributor adoption. [E13]

The retained-evidence audit completed on October 28 Central time classified 126 propositions: 58 as Establishes, six as Suggests, 12 as Consistent with and 50 as Does not show. These labels grade what the inspected evidence supports; Does not show does not mean false. The audit distinguished file enumeration and hashing from claim-level assessment, retained source references and uncertainty, and preserved its earlier baseline. Some checks reused retained evidence, and the inventory was not an atomic crawl of all live state. AI advisory review did not supply independent human validation, scientific acceptance or Library publication. [E13]

These episodes show what was checked, corrected, authorized or reported in particular operations. They do not estimate an error-prevention rate or demonstrate that RA improves scientific outcomes relative to a simpler workflow. Repeated reviews of the same package remain one episode rather than additional independent successes. The cases support evaluation questions about evidence traceability, source contradictions, date interpretation, operational state and review provenance. [E13]

5 Engineering improvements and release verification

Field operation exposed requirements for stable state selection, reliable Windows publication, growing context and recoverable exchanges. RA 2.1.0 distribution revision 2 ports reusable mechanisms into a separate package while preserving earlier source and deployed project history.

Capabilities in the inspected RA 2.1 distribution

Capability	Implemented mechanism
Current state selection	Verified designation, identity and manifest checks; invalid selectors stop affected work.
State publication	Separate successor snapshots, destination-local staging and expected-base checks.
Context continuity	Bounded retrieval and exact multipart restoration with repeated controls.
Exchange records	Configured local staging, version-bound receipts, idempotent repeats and guarded lock recovery.
Project recovery	Resumable capture, explicit retention, dependency materialization and standalone restore tools.

The October 16 release receipt records 171 passing offline regression tests in eleven groups on Windows and Python 3.12.10, with zero failures, errors or skips. Coverage included kit generation, checkpoints, context reconstruction, local exchange, affected evidence services, extracted-package generation and rebuilding, and backup recovery. The run made no model calls or remote transfers. A retained integrity comparison found all 278 recorded source hashes unchanged. [E2]

Instruction maintenance has a separate boundary. RA records stable IDs, complete versioned text, authority, applicability and explicit supersession. Routine Hub saves may append evidenced observations about an existing instruction, but cannot define or rewrite a rule. A new startup instruction requires reviewed reconfiguration and verification that the selected installation actually loads it. Delivered packages and acknowledgments alone do not establish fresh-session behavior.

The deployed Hub continued to evolve after the historical RA 2.1 package freeze. Later context and message improvements informed the reusable RA 2.3 implementation and remain in the current factory. In a retained repeated-context fixture, emitted prompt length fell from 773,391 to 119,362 characters, an 84.5664% reduction, with matching source hashes and complete reconstruction; confirmed same-conversation reuse emitted 277 characters. These are scenario-specific output measurements. Provider-token counts, billing and whole-task productivity are separate measures. [E1] [E7]

Measured reductions in returned context

The participant optimization report retained a controlled local replay against the same CP076 source checkpoint. The startup/resume comparison returned 1,346,562 characters before optimization and 160,808 afterward, an 88.0579% reduction. The unchanged subsequent-turn comparison returned 1,346,571 and 6,333 characters, respectively, a 99.5297% reduction. Cold replay used one context part instead of seven and eight logical reader calls instead of 59. These measurements include the protocols' complete stdout and the counted startup instructions; they are not tokenizer estimates or complete model-request sizes. [E12]

Retained comparison	Returned character counts and scope
Generic repeated-context fixture	773,391 to 119,362; 84.5664% reduction. Confirmed reuse emitted 277 characters.
Participant cold startup or resume	1,346,562 to 160,808; 88.0579% reduction in controlled local replay.
Participant unchanged subsequent turn	1,346,571 to 6,333; 99.5297% reduction in controlled local replay.
Hub message-workflow observation	113,239 to 9,149; 91.9206% reduction in returned tool-result characters across different workloads.

The participant replay verified selected-source reconstruction and preserved originals. Intent-based selection left historical material available for explicit retrieval. The replay was a local CLI measurement, not a fresh AI comprehension experiment; confirmation of retained model context remained a caller assertion. Provider framing, the surrounding conversation, cached input, generated responses, reasoning tokens and billed cost were outside its totals. Local source checks still perform work even when little text is emitted. The 6,333-character return does not mean the whole conversation or all provider input was that small. [E12]

The Hub comparison recorded 113,239 returned characters before the scoped message path and 9,149 afterward. It was a retrospective observational comparison in the same chat/model, with different checkpoints, histories, folder/object counts and closure work. It therefore cannot isolate the optimization's causal effect or be treated as an identical-input benchmark. The retained report preserves usage-counter definitions and unavailable evidence rather than converting character savings into a billing percentage. These three evidence settings, including the earlier generic fixture, remain separate and should not be pooled into a universal RA savings rate. [E12]

Current factory configuration and verification

The current factory is RA 2.6.1, with operational runtime 2.4.0 and scientific library 1.9. These identifiers distinguish kit preparation, operational helpers and methodological content. Manifests and startup text identify the delivered components. Factory updates carry forward the existing Library, context, backup and exchange mechanisms while adding configuration and delivery controls. Existing deployments and dated measurements retain their original identities. [E3] [E6] [E7]

New sessions use a persistent setup ledger with 43 baseline questions and additional required followups. Compact status identifies the pending item on each turn and after resume. Environment/Python answers require the separate verified preflight before later intake. Ordinary compilation then requires completed responses, explicit human preparation approval, the exact configuration binding and current review of both plan PDFs. Deferrals remain pending; changed decisions preserve history and reopen affected work. Build verification and each operator's walkthrough remain separate completion stages. Existing protocol-1 ledgers retain their 42-item catalog and historical approvals. [E3] [E6] [E7]

The RA 2.5 revision 1 verification exercised the changed question workflow, interrupted and stale-state paths, configuration binding and the extracted package. A synthetic four-role project compiled, each generated kit passed its consistency check and actual operator walkthroughs remained pending. Three teaching-runner defects were repaired: all-failed-project handling, infeasible sensitivity shifts and bounded duplicate-safe JSON input. Revision 2 changes release identification and documentation; its adjacent integrity receipt records only those changed-path checks. [E3]

The scientific collection contains 134 reference records and 38 local reference texts. Six targeted critical appraisals cover methodology, agent evaluation, failure analysis and computational reproducibility, with dependencies across 19 method routes. Complete runnable teaching cases address clustered workflow evaluation, nested model selection and target-population generalization. They pair declared plans, fixed data, analysis, diagnostics and bounded conclusions with applicability safeguards. Large source bodies remain retrievable on demand. These counts describe coverage and availability, rather than 134 completed full-paper reviews. [E3] [E4]

The reusable Library integration introduced in RA 2.3 remains in RA 2.6.1. Every generated role receives a configurable discovery client that verifies catalog revision, hashes, byte counts and audience, preserves complete matching metadata through continuation and prepares submission records for Hub review. The discovery client grants no write authority. Spokes and Ingestor have read-only Library access; the Hub has read/write authority and uses authorized tooling to publish additions and corrections. Earlier registration/discovery evidence is retained. Generating a kit does not install the NWSW backend or grant access to its holdings. [E3] [E5] [E6] [E7]

The opening invitation is the first required item in new protocol-2 sessions. Questions about setup remain pending until the human chooses to begin intake. Targeted compiler checks rejected 14 representative required-item omissions and preserved legacy ledgers and approvals. In a two-turn fresh-chat test using gpt-5.6-sol at low reasoning, the agent asked the invitation, explained approval and recorded a request for explanation as a deferral with zero answers. These results document early-intake behavior and structural gate enforcement. [E6]

The written-plan implementation was checked through eight focused test groups. The exact-PDF review gate was then exercised through eleven review-to-build groups and five refusal/renewal checks. Successful compilation copied the reviewed bytes while rendering was disabled; changed plan evidence blocked publication. Separate role-delivery checks verified local-runtime instructions in fresh Hub, Ingestor and Spoke kits and their resume context. These records establish the particular software paths exercised, rather than a new complete interview or independent team trial. [E7]

The current environment gate passed eight focused groups and six additional negative entry-point checks. Unsupported answers could not complete step 1, and missing evidence blocked readiness, approval, workflow-backed export and normal/draft/direct generation. Changed evidence, host/workspace drift, code failure or timeout and withdrawn confirmation remained blocked. One successful four-role build preserved the earlier configuration and PDF approval bytes; an interrupted-publication case stopped after capability evidence changed. These are synthetic engineering scenarios using real file/code execution. They are distinct from the field deployment and retain the underlying test receipts. [E7]

Incremental Library preparation and durable publication evidence

Future kits now include local tools for preparing an exact reviewed metadata delta against a pinned existing catalog. Unchanged objects are reused; an unchanged selection produces no candidate or upload actions. The preparer rejects stale or conflicting inputs and preserves the configured Library identity, storage root, audience and access policy. The Hub alone receives the publisher startup route, and the preparer command rejects other roles. A full holdings inventory, normalization or catalog rebuild is separate requested work; the preparer still validates the complete selected local metadata graph. [E10]

The compatible reader authenticates each object's original content revision separately from the selected catalog, retaining exact source-page provenance and complete records through page and

entry continuation. Existing strict readers remain supported; the new contract requires reviewed configuration. Metadata and delta envelopes are bounded to 22,000 UTF-8 bytes. Complete preparation reports retain upload and reuse lists while the default console response is bounded to 4,096 bytes. These controls bound transport without discarding the underlying evidence. [E10]

Receipt helpers preserve exact literal JSON through hash and length checks, exclusive storage, flushing and readback. Failed or denied persistence stops the operation. A local evidence check requires retained provider acknowledgment, downloaded-byte and destination/access proof, and existing scoped authority before saving its result. It performs no cloud write or lock release. The configured backend retains the owned writer guard, final current-pointer selection, readback and supported matching-token release. Repair-only authority remains bounded, and existing approvals and closed work remain in force. [E10]

Retained RA results record 19 publisher-specific test methods and one legacy-reader regression, including generated-kit delivery and Hub-only command behavior. Three later failure checks cover competing destinations, evidence changing after receipt storage and report-write failure. All stopped without returning success and retained recovery evidence. These local checks support the portable integration, separately from the deployed publication. [E9] [E10]

6 Research basis and methodological applicability

Multi-agent design requires explicit coordination and verification. Cemri and colleagues distinguish system-design, inter-agent alignment and task-verification failures. RA uses this taxonomy to examine pending questions, task drift and incomplete completion checks. Applying the taxonomy is an engineering interpretation, not evidence that RA shares the study's failure rates or has eliminated those failure modes. [4]

AI Agents That Matter argues for cost-aware evaluation, credible simpler baselines and holdouts matched to the intended generalization. RA adopts these considerations when planning comparisons: report the full retry policy and task denominator, and distinguish emitted characters from measured tokens and billed cost. The appraisal uses the explicitly identified 2024 author edition; it does not treat later publication as evidence of a new RA experiment. [5]

CORE-Bench evaluates computational reproduction using supplied code and data. Its inspected author version and separate journal publication identity are distinguished in the references. Reproducing an expected output is a useful verification target, but it does not independently establish the truth of a study's measurements or causal interpretation. RA therefore records file integrity, execution, operator rehearsal and scientific review separately. [6]

Preregistration guidance distinguishes prospective plans from choices made after seeing outcomes. RA's preparation approval concerns kit creation, not preregistration of a study. Applicable research plans should record timing, prior outcome exposure and deviations while preserving exploratory work under an accurate label. [7]

Clustered-inference guidance explains why observations within the same project or task group cannot automatically be counted as independent evidence. RA's workflow-evaluation case distinguishes all-attempt outcomes from completed-pair diagnostics; statistical inference must respect the design's independent units and few-cluster limits. The teaching case is an application of methodological principles, not a new empirical validation of them. [8]

Leakage analysis requires separation through preprocessing and evaluation, legitimate predictors and a test distribution that matches the scientific claim. RA's analysis-selection guidance carries these checks into model comparison. Nested selection or a held-out split does not repair inappropriate measurements or an unsupported target-population claim. [9]

FAIR principles emphasize identifiable, described and reusable research objects; practical scientific-computing guidance supports preserving raw inputs, processing records and change history. These sources inform RA's provenance and handoff design. RA's actual preservation and restore results are supported by its retained deployment receipts, not inferred from citing those principles. [10] [11] [E1]

The 10th man principle provides a recognizable description of deliberate challenge, while devil's advocacy and alternative analysis supply its methodological context. Heuer describes examining conflicting interpretations; Rieber and Thomason caution that intuitive confidence in analytic techniques can exceed the evidence for their effectiveness. The latter discuss mixed research on assigned devil's advocacy, including the possibility of reinforcing the original position. The professional use of the tenth-man label establishes its recognition, not a universally standardized protocol or a validated RA intervention. These sources support evaluating the safeguards rather than assuming that a named challenger guarantees better judgment. [12] [13] [14]

CONSENSAGENT examines agents reinforcing one another's responses in benchmark reasoning and evaluates a particular mitigation. Those findings motivate controlling exposure to others' conclusions. RA's governing workflow withholds other Spokes' outputs until Hub-authorized disclosure and retains assessments, dissent and human decisions. The benchmark does not show that direct cross-Spoke reinforcement occurred in RA. Shared sources or errors also do not become independent evidence merely because several agents repeat them. RA's access and review records support assessment of the actual exposure sequence; the effects of its safeguards require their own evaluation. [15] [E6] [E11]

7 Discussion and next phase

RA has supported continuing work across people, sessions and files. Role kits supplied assignments and governing context, checkpoints retained decisions and unresolved work, and verified exchanges made distribution traceable. The isolated restore established a recovery path. Operational defects supplied reproducible cases for the reusable package.

Scope and assurance

The evidence combines creator-reported deployment experience, retained execution receipts, recipient returns, synthetic software checks and observed model conversations. Reports of Architect and kit use across named hosts are part of that evidence. The smaller GPT-5.6-sol early-intake trials describe their own scripted scenarios; they are not an exhaustive history of live use. Each execution report supports the operation and measures it records. Further independent-lead or comparative evaluation adds evidence without negating those observed results. [E1] [E6] [E7] [E8]

File consistency does not authenticate authors or certify scientific validity. Human decisions remain distinct from technical checks, and local accounts and host configuration remain trust boundaries. Folder visibility alone does not establish research-use permission. Locks and selection checks do not form one transaction across uploads, designation and unrelated writers; cutover needs an idle window and reconciliation.

What is implemented and what remains to be evaluated

Capability or claim	Current evidence and remaining question
Selective context and continuity	Reader and checkpoint mechanisms are implemented; retained fixtures and local replay measure returned output. Reliable comprehension after restoration and total task cost need separate evaluation.
10th man safeguards	Controlled disclosure, independent initial assessments, preserved dissent and human acceptance are specified by governance instructions and review records. Actual exposure is established from the operation's records; comparative reduction of correlated errors has not been measured in RA trials.
Outside research and specialist review	Existing review mechanisms and templates support bounded use; packet preparation depends on host tools. A universal external importer and automatic specialist exporter are not established, and the composed route needs end-to-end trials.
Library discovery and requests	Generic clients support discovery; the configured NWSW catalog exposes reviewed held-item metadata and a request route. Automatic prioritization, guaranteed release and every participant's adoption are not established.
Research-workflow outcomes	Dated deployed cases document specific corrections and decisions. General improvements in scientific validity, time saved, error rates or cost per acceptable result require comparison.
Existing-project adoption and late expansion	Reviewed maintenance and compatibility procedures exist. Universal automatic migration and automatic readiness of a new participant/agent are not implemented.

Software checks, instructions and human decisions have different assurance limits. Code can reject an incorrect hash, stale version, missing required field or absent review binding in a supported path. Agent instructions direct source checking, dissent preservation and scoped conduct; their inclusion does not guarantee behavioral compliance. Host accounts and backend configuration determine actual access, while human review determines the scientific decision and authorized use. A clean technical report does not authenticate a human's identity or certify a conclusion. Assessment should identify which layer performed each check and whether the required procedure was actually followed. [E7] [E11]

Formal specification and testing of the outside-research route remain follow-up work. Such tests should cover exact-source intake, incomplete or inaccessible reproduction materials, prior reviewer exposure, a specialist's disagreement, qualified acceptance, refusal, and version changes after review. Tests should distinguish packet preparation, delivery, completed review and final human authorization. The present paper documents how existing mechanisms can be used; it does not report those proposed end-to-end scenarios as completed results. [E11]

Late-stage onboarding of participants and agents

Late-stage onboarding places separate demands on a new participant and their newly generated agent. The person must learn the project, while the agent must reconstruct the relevant decisions, terminology, evidence, dependencies and unresolved work. An experienced participant introducing a fresh agent still faces the agent's context gap. A role kit can contain supplied project context, but generating it does not automatically transfer the established team's accumulated working understanding.

This is a limitation of context transfer and assimilation in the AI technology on which RA depends. Shared Library access makes retained information available; it does not by itself establish that a new agent has selected, read, reconciled and understood the material needed for its assignment. While onboarding proceeds, the project continues producing and revising context. If relevant changes accumulate faster than the person and agent can assimilate them, a persistent catch-up backlog can develop. Loading more records is not equivalent to establishing current, usable understanding.

A useful analogy is giving a newcomer the first half of an examination's answers: access to correct outputs does not establish the ability to solve the remaining problems. RA can also preserve the relevant methods, rejected assumptions, mistakes and corrections, so its retained knowledge can be richer than an answer key. The limitation is whether the new person and agent retrieve, reconcile and correctly apply that history to unfamiliar work. No transfer of trained neural-network weights or automatic assimilation is implied. A focused external review, reassignment within the team or deliberate onboarding may be more feasible than immediate expansion; the lead decides based on the actual role and available capacity. [E11]

The lead and existing team must then supply explanations, identify authoritative records, resolve misunderstandings and verify the new pair's work. Existing agents may also spend context and inference resources assisting the newcomer. This diverts attention from established workstreams, can slow the team and can make late expansion impractical within the available time and cost budget. Adding a kit should therefore not be assumed to increase useful capacity. The severity depends on the role, project pace and completeness of retained reasoning; this is a technology and workflow limitation, not a measured claim that every late entrant can never become ready. Checkpoint restoration of an established workstream remains distinct from onboarding a new participant and agent.

Context and performance evaluation

Bounded retrieval and durable checkpoints provide practical control over working context. The documented fixture reductions establish lower emitted prompt volume in their tested scenarios. End-to-end evaluation should additionally count initialization, tool results, saving, restoration, retries and failures, with actual provider usage and billing where available. The paper does not convert character reductions into an unsupported token-cost or research-quality percentage. Comparable tasks, credible simpler baselines and claim-matched holdouts remain necessary for broader efficiency estimates. [5] [9] [E7]

Evaluation of the 10th man safeguards should retain initial and final assessments, evidence identities, the point of exposure to others' conclusions, reasons for revisions, the actual human decision and unresolved objections. On a suitable task sample, comparisons can examine missed errors, justified corrections, unsupported changes of opinion, correlated failures and review cost. Correct dissent and correct agreement both matter; counting objections or affirmative votes alone is inadequate. Checks of procedural compliance should be reported separately from checks of whether the accepted conclusion is supported. [E11]

Continuity trials should include fresh sessions, retained-context reuse, host compaction or equivalent context loss, changed checkpoints, interrupted saves and stale source bindings. Scoring should test application of the current decision and evidence, not only successful file reconstruction. Staffing and onboarding studies should measure the existing team's explanation and review effort as well as newcomer completion. These are proposed evaluation designs, not experiments completed by this paper revision. [E11] [E12]

Broader adoption

A useful next milestone is another project lead configuring a new team with documented support requirements. The reported cross-host operations provide field experience; systematic comparisons should identify the loaded startup guidance, selected checkpoint, complete restoration and behavior in fresh and resumed sessions. Existing-project adoption requires preserved state, compatibility checks, reviewed updates and deliberate cutover. Automatic migration across unrelated projects is a separate capability from the existing reviewed maintenance tools. [E7] [E8]

For an existing project, the preparation work begins by identifying its actual current state and preserving original records, exchanges, closed decisions and unresolved issues. The team maps existing people, methods, permissions and incoming/outgoing routes into the proposed operating structure. A separate candidate is checked for compatibility and exercised against the retained state before an authorized cutover. Delivered files, a new kit or a successful verifier do not establish installation or adoption on another person's machine. Existing maintenance tools support specific reviewed updates and schema migrations; organizing an arbitrary project remains deliberate project work rather than a one-click conversion. [E11]

The historical RA 2.1 case and current RA 2.6.1 factory remain development previews. Additional-lead adoption and systematic platform comparisons are distinct from the implemented setup gates, Library client, source retrieval and reported multi-host kit operation. Claims remain tied to their actual records and observation dates. [E1] [E7] [E8]

8 Conclusion

Research Architect has supported a creator-configured team with verified exchanges, preserved history and whole-project recovery. The current factory combines research-design guidance, human-reviewed preparation, selective context retrieval and versioned Library access with explicit review responsibilities. Deployed cases document source corrections, date qualifications, rendering checks and reconciliation of operational state. RA applies the established 10th man principle through challenge and review guidance whose compliance and effectiveness remain assessable questions. Retained measurements establish bounded output reductions in their respective scenarios. Further evaluation should test total costs, research-quality effects, external-intake workflows and adoption by additional leads while retaining each evidence class and its limits. [E1] [E7] [E8] [E11] [E12] [E13] [E14]

Visual guide from evidence to research design

RA draws on two complementary inputs. Published methodology explains how a design can support a claim; project evidence supplies the observations to which that design will apply. The Architect must assess their fit before selecting guidance for a kit. The compiler packages the resulting selection. It does not independently choose a scientifically valid study. [E3] [E4]




Figure 2 Published research and project evidence inform a reviewed design. Arrows show the intended reasoning and configuration flow, including scientific judgments that require agent and human review.

The scientific registry records source identities and availability. Local text is supplied where the retained collection permits it; other records point to an external original. Project data must be supplied or obtained through authorized project workflows. RA does not turn a bibliography into a dataset or treat technical integrity checks as scientific approval. The design should identify the question, independent units, measurement limits and relevant assumptions before a method is accepted. [8] [9] [10]

Visual guide tracing a cited method into a kit

Consider an illustrative evaluation with repeated task results within projects. The statistical guidance directs attention to dependence and independent units. Cameron and Miller provides relevant methodological grounding; the retained CLUSTER2015 appraisal identifies the original sections inspected and the limits of applying their guidance. This example explains a source route, not a newly conducted experiment. [8] [E4]




Figure 3 The STATISTICAL_ANALYSIS route includes the CLUSTER2015 source record and focused appraisal. The compiler carries selected guidance, a filtered index and provenance into generated kits. [E3] [E4]

For this source, the kit carries bibliographic metadata, an original-paper link and an RA-authored appraisal; it does not contain the full original paper. Other selected sources may have local full text. The knowledge reader supports targeted retrieval of local material, while consequential use requires inspection of the relevant original passages. Hashes establish which bytes were delivered. They do not establish that a model read the material or that clustered inference is suitable for the particular study. [8] [E4]

Visual guide questions and continuity

RA stores setup progress in a persistent ledger. Compact status identifies the pending question on each setup turn and after resume; clarification is not completion. After the environment/Python responses, actual capability evidence and local-host confirmation unlock later intake. The finalized design then produces the exact PDFs for human review. Only current environment evidence, completed requirements and the bound plan approval permit kit creation. Figure 4 shows these distinct gates and the subsequent walkthrough/resume stages. [E7]




Figure 4 Verified setup, exact plan review and continuity. File/code evidence and explicit local-host confirmation precede later intake. The human reviews both plan editions before kits are created from those unchanged bytes. Operator walkthroughs and saved-state restoration remain separate. Legacy approval history is preserved. [E7]

Preparation approval is bound to the exact configuration inputs and reviewed PDF identities. A separate environment receipt binds the setup workspace, current prerequisite answers, interpreter, machine and verification tools. Changes invalidate the affected evidence; attaching a capability receipt to unchanged approved records does not rewrite them. These controls enforce the supported preparation paths. They do not prove human comprehension, permanent host persistence or perfect instruction following by every model. The retained conversation trials and software checks remain separately scoped. [E6] [E7]

Visual guide sharing and reusing Library evidence

The Hub issues a bounded task; a Spoke performs it and obtains its human's approval. The Hub reviews and accepts the contribution for Ingestor validation and any needed reproduction. The Ingestor reports back, the Hub obtains final approval, and only the Hub publishes the approved finding. The Hub retains read/write access and alone publishes later corrections after the required reviews. Spokes and Ingestor discover and read approved evidence through read-only access. Figure 5 shows the required sequence. [E6]




Figure 5 Task, review, validation and Hub-only publication. The Hub has read/write authority and alone publishes additions and corrections; Spokes and Ingestor have read-only access. Human submission approval and final approval are separate decisions. Methods, artifacts, provenance and limits accompany the published finding. Conversation evidence supports restricted Hub review. [E6]

The deployed Hub's authorized backend verifies immutable catalog objects and deployment bindings before selecting CURRENT and reconciling convenience aliases. The reusable RA package supplies local delta preparation, compatible retrieval and durable evidence checks; generating a kit does not install that backend or grant cloud access. Writer guards, expected prior state and retained receipts support interrupted-operation recovery. Only the Hub publishes additions and corrections; other roles submit proposed corrections for review. The review sequence governs kit instructions, while each tool enforces its own checks. Human decisions and backend release authority remain separate from the local evidence result. [E5] [E6] [E9] [E10]

Visual guide focused context retrieval



Figure 6 Focused context and exact retrieval. Invented example; printed excerpts illustrate full example counts, not measured RA performance. [E11] [E12]

References

[1] OpenAI. (n.d.). A practical guide to building agents. OpenAI. Technical guide. Accessed October 23 2026.

[2] Wu Q, et al. (2024). AutoGen: Enabling Next-Gen LLM Applications via Multi-Agent Conversations. COLM 2024. Peer-reviewed conference paper. Accessed October 23 2026.

[3] Anthropic. (2025). How we built our multi-agent research system. Anthropic Engineering, June 13. Engineering report. Accessed October 23 2026.

[4] Cemri M, et al. (2025). Why Do Multi-Agent LLM Systems Fail?. NeurIPS 2025 Datasets and Benchmarks. peer-reviewed conference paper. DOI: 10.52202/085713-4082. Accessed October 23 2026.

[5] Kapoor S, Stroebl B, Siegel ZS, Nadgir N, Narayanan A. (2024). AI Agents That Matter. arXiv:2407.01502v1. Inspected author preprint; later journal publication in TMLR 2025. Published record: https://openreview.net/pdf?id=Zy4uFzMviZ. Accessed October 23 2026.

[6] Siegel ZS, Kapoor S, Nadgir N, Stroebl B, Narayanan A. (2026). CORE-Bench: Fostering the Credibility of Published Research Through a Computational Reproducibility Agent Benchmark. arXiv:2409.11363v2, revised June 22 2026. Inspected author version; published journal record in TMLR 2025. Published record: https://openreview.net/pdf?id=BsMMc4MEGS. Accessed October 23 2026.

[7] Nosek BA, Ebersole CR, DeHaven AC, Mellor DT. (2018). The preregistration revolution. Proceedings of the National Academy of Sciences of the United States of America. published journal article. DOI: 10.1073/pnas.1708274114. Accessed October 23 2026.

[8] Cameron AC, Miller DL. (2015). A Practitioner's Guide to Cluster-Robust Inference. Journal of Human Resources. published journal methodological article. DOI: 10.3368/jhr.50.2.317. Accessed October 23 2026.

[9] Kapoor S, Narayanan A. (2023). Leakage and the reproducibility crisis in machine-learning-based science. Patterns (New York, N.Y.). published journal article. DOI: 10.1016/j.patter.2023.100804. Accessed October 23 2026.

[10] Wilkinson MD, et al. (2016). The FAIR Guiding Principles for scientific data management and stewardship. Scientific data. published journal article. DOI: 10.1038/sdata.2016.18. Accessed October 23 2026.

[11] Wilson G, Bryan J, Cranston K, Kitzes J, Nederbragt L, Teal TK. (2017). Good enough practices in scientific computing. PLoS computational biology. published journal article. DOI: 10.1371/journal.pcbi.1005510. Accessed October 23 2026.

[12] Heuer RJ Jr. (1999). Psychology of Intelligence Analysis. Center for the Study of Intelligence, Central Intelligence Agency. Methodological monograph. Accessed October 31 2026.

[13] Rieber S, Thomason N. (2005). Creation of a National Institute for Analytic Methods. Studies in Intelligence 49(4). Methodological commentary. Accessed October 31 2026.

[14] Pelczar PD. (2025). The role of critical thinking. Australian Naval Institute, October 10; article heading From Analysis to Algorithms: Preserving the Art of Critical Thinking. Professional commentary; public introductory excerpt inspected. Accessed October 31 2026.

[15] Pitre P, Ramakrishnan N, Wang X. (2025). CONSENSAGENT: Towards Efficient and Effective Consensus in Multi-Agent LLM Interactions Through Sycophancy Mitigation. Findings of the Association for Computational Linguistics: ACL 2025, 22112-22133. Peer-reviewed conference paper; abstract and bibliographic record inspected for this revision. Accessed October 31 2026.

Primary RA evidence records

[E1] Santor B. NWSW operational case evidence register, October 8-22 2026. Retained private creator report, transfer inventories and readbacks, upgrade-preservation records, context fixtures and isolated-restore receipts. Reviewed locators and hashes are held in the editorial evidence manifest. These are primary project records, not independent peer-reviewed findings.

[E2] Santor B. Research Architect 2.1.0 distribution revision 2 release verification, October 16 2026. Retained offline regression and package-verification receipts: 171 tests; no model calls or remote transfers. The earlier editorial integrity comparison is retained without a new regression run.

[E3] Santor B. Research Architect 2.5.0 release notes and changed-path verification, October 23 2026. Distribution revision 1 records the new setup gate, runner repairs and extracted four-role project checks. Distribution revision 2 records release-label and citation changes. Exact archive identities and verification scopes accompany each release in its integrity receipt.

[E4] Santor B. Research Architect scientific library 1.9 source registry and six critical applicability appraisals, October 23 2026. Records source identity, actual inspected edition/sections and application limits. RA-authored synthesis is separate from the original publications.

[E5] Santor B. NWSW shared Library implementation, verified publication recovery and RA client integration records, October 22-23 2026. Maintained implementation manifest R2; recovered Library completion protocol 3; separate Hub activation receipt; and retained RA client registration/discovery test. The Library completion binds CURRENT, 58 aliases and the status record. These are primary engineering and operational records; local integration tests and deployed recovery are distinguished. Exact source hashes and private locators are retained in the editorial evidence manifest.

[E6] Santor B. Research Architect 2.5.1 implementation and verification records, October 23 2026. Versioned setup-workflow source and generated Hub, Spoke and Ingestor instructions; evidence-review and Library-client documentation; transcript-export implementation; retained compiler-omission, legacy-preservation and three-role delivery checks; and a recorded two-turn gpt-5.6-sol low-reasoning intake test. Source inspection establishes implemented controls and supplied instructions; test receipts establish the specific behaviors exercised. These records are distinct from the dated NWSW deployment evidence. File identities and verification scopes are retained with the release.

[E7] Santor B. Research Architect 2.3 through 2.6.1 implementation and scoped verification records, compiled October 25 2026. Retained context measurements, setup handoff and plan delivery checks, exact-PDF review and refusal tests, three-role instruction delivery, and the environment gate's eight focused groups and six negative entry-point checks. Release reports and hash-pinned receipts record each scope. These records retain their original verification scope.

[E8] Santor B. Creator account of runtime use and browser-host migrations, retained with RA 2.6.1 field-use documentation. Reports Architect use in Codex with Astra and 6.1 High, kit operation in Antigravity, Claude and Codex, and browser-chat problems requiring teammate migrations. Labels and outcomes are creator-reported field evidence; no controlled platform benchmark or new adoption rate is inferred.

[E9] Santor B. NWSW incremental Library publication and closeout evidence, October 27 2026. Retained source review and final release receipt record 741 selected metadata objects reused, 28 new metadata objects, nine changed aliases verified, 49 unchanged aliases retained and verified index, navigation, status and normal closeout. Dated reuse proof and original interrupted-controller qualifications remain explicit. Exact private locators and SHA256 pins are retained in the editorial evidence manifest. This is deployed engineering evidence, not a participant-adoption or scientific-quality study.

[E10] Santor B. Research Architect publisher integration and targeted verification records, October 27 2026. Retained source provenance, publisher operating contract, 19 publisher methods, one legacy-reader regression, three additional failure checks and archive-to-generated-Hub delivery records. The package carries local preparation, origin-aware reading and receipt checks; provider writes and controlled release remain backend responsibilities. Evidence records retain exact source and archive hashes.

[E11] Santor B. Research Architect 2.6.1 operating instructions and implementation source review, October 31 2026. Inspected project-design and workload guidance, governance and review templates, independent-evidence guidance, command routing, persistence and context procedures, model plans, and reviewed migration contracts. Exact local sources and SHA-256 pins are retained in the editorial evidence manifest. This establishes documented instructions, record structures and inspected implementation behavior, not universal compliance, a new runtime release or completed comparative trials. Outside-research intake and specialist packets are described as a composed use of existing mechanisms with stated implementation and testing limits.

[E12] Santor B. Retained participant context optimization report and Hub message-context comparison, held in the October 22 2026 integration assessment and inspected October 31. The participant report records controlled local CLI replays against the same CP076 sources; the Hub report records a retrospective observational workflow comparison. Units, counted output scope, differing workloads and unavailable measures remain explicit. These are separate from the generic repeated-context fixture. The editorial manifest pins the supplied report, retained comparison and their provenance. No historical replay or new model experiment was conducted for this revision.

[E13] Santor B. Retained NWSW Hub operational cases, October 14-29 2026, inspected October 31. Records cover source-claim correction and its bounded human-authorized release, date/coverage correction, visualization verification, a contributor-reported eight-assignment closure application, incoming-route repair, and a scoped evidence audit. Exact source identities, hashes, actors, dates, outcomes and limits are retained privately. AI review, human decisions, technical checks, sender reports and publication receipts are distinguished. These cases do not constitute independent scientific validation or comparative evidence that all RA deployments improve research quality.

[E14] Santor B. NWSW Library operating guide, reviewed metadata projection, request-route implementation and October 30 2026 catalog example, inspected October 31. Available in Library and Request from Hub preserve exact identities and distinct access/use states. Safe metadata disclosure is reviewed; requests inform the human lead's review priorities without guaranteeing fulfillment. The private editorial manifest pins the inspected guide, code and example. Generic client capability remains distinct from this deployment, and no new cloud audit, payload release or automatic priority scheduler is inferred.

Evidence availability

The public paper reports aggregate engineering observations and bounded operational case descriptions from retained deployment records, dated software receipts and creator accounts. Participant records and research payloads remain private. Exact locators, hashes, source-inspection scope and evidence classifications are retained for editorial review. External publications supply methodological context and terminology; RA's implementation and operational claims are supported by its own records. New references identify what was actually inspected, including a public excerpt and an abstract where full-text review was not undertaken. [E11] [E12] [E13] [E14]

Reading the engineering evidence

Results retain their dates and units. Transfer IDs count recorded exchanges; the isolated restore and context fixture establish their specific recovery and output results. Regression reports cover their named software paths. These observations support the operating mechanisms described here without forming an independent adoption rate or research-quality effect.

Future comparisons should freeze tasks, authorized evidence, runtime settings, stopping rules and grading criteria. Compare context strategies on the same tasks and include retries, failures and restoration work. Record actual usage when available and retain unavailable counters as unknown. Assess citations, uncertainty and unauthorized actions alongside completion. This is an evaluation plan. [5] [8] [9]

Prepared with AI-assisted source review and drafting. Brandon Santor configured the deployment and supplied the creator accounts. Execution records, recipient reports and independent evaluation retain their respective scopes.