

ELECTRIC MULTIROTOR DESIGN AND OPTIMIZATION

A Dissertation
Presented to
The Academic Faculty

by

Dmitry Bershadsky

In Partial Fulfillment
of the Requirements for the Degree
Doctor of Philosophy in the
School of Aerospace Engineering

Georgia Institute of Technology
August 2017

Copyright © 2017 by Dmitry Bershadsky

ELECTRIC MULTIROTOR DESIGN AND OPTIMIZATION

Approved by:

Professor Eric N. Johnson, Advisor
School of Aerospace Engineering
Georgia Institute of Technology

Professor Daniel Schrage
School of Aerospace Engineering
Georgia Institute of Technology

Professor Eric Feron
School of Aerospace Engineering
Georgia Institute of Technology

Professor Brian German
School of Aerospace Engineering
Georgia Institute of Technology

Dr. Phillip Jones
Founder
Scion UAS

Date Approved: 17 July 2017

ACKNOWLEDGEMENTS

I would like to thank my parents, grandparents, friends, my advisor Dr. Eric Johnson, the members of his UAVRF, namely Nimrod Rooz, Claus Christmann, Jack Mooney, Pierre Valdez, Steve Haviland, Lee Whitcher, Joshua Carnes, Eric Avari, Marc-Henri Bleu-Laine, Nick Willard, and Mitchell Sanders for their help with the work described in this document and the occasional pushes I needed to write about it. I would also like to thank Dr. Brian German, Dr. Daniel Schrage, Dr. Phillip Jones, Dr. Mark Costello, and Dr. Eric Feron for their time and insightful comments during both the proposal and defense.

TABLE OF CONTENTS

ACKNOWLEDGEMENTS	iii
LIST OF TABLES	vii
LIST OF FIGURES	ix
SUMMARY	xxvi
0.1 List of Symbols and Abbreviations	1
I INTRODUCTION	7
1.1 Motivation	7
1.2 Thesis organization	8
1.2.1 Contributions	8
II MULTIROTOR DESIGN CONSIDERATIONS, METHODS, AND ANALYSES	14
2.1 Background: multirotor electric propulsion system design considerations	14
2.1.1 Multirotor layout and naming convention	15
2.1.2 Motor	16
2.1.3 Propeller	18
2.1.4 Battery	19
2.1.5 Electronic Speed Controller	21
2.2 Selected propeller aerodynamic analysis methods	22
2.2.1 Momentum theory	22
2.2.2 Blade element momentum theory	23
2.2.3 Electrical modeling	26
2.3 Propulsion system sizing and design methods	28
2.4 Propulsion system configuration design methods	32
2.5 The need for a new framework, research questions	37
2.5.1 Mission-level questions	37
2.5.2 Task-level questions	45

III	A FRAMEWORK FOR MISSION-LEVEL ELECTRIC PROPULSION SYSTEM SIZING AND OPTIMIZATION	62
3.1	Propulsion system sizing and performance prediction	64
3.1.1	Optimizer flow	64
3.1.2	Mission definition	65
3.1.3	Power required calculation	68
3.2	Propulsion system component parameterization	74
3.2.1	Motor	74
3.2.2	ESC	76
3.2.3	Battery	77
3.2.4	Propeller	78
3.2.5	Structural	82
3.2.6	System Analysis	82
3.2.7	Analyzer hover time calculation	83
3.3	Range calculation, power required for cruise	85
3.3.1	MR chassis wind tunnel testing	87
3.3.2	Sensitivity analyses	93
3.3.3	Effects of temperature on battery performance	94
3.3.4	Other effects	95
3.3.5	Areas for improvement	96
3.3.6	Validation of analyzer algorithm	97
3.4	Application of the analysis and optimization algorithms	99
3.4.1	Case study for propulsion system optimization: <i>GTQ Mini</i>	99
3.4.2	Battery sizing case study: Eagle	104
3.4.3	Optimization with MST	105
3.4.4	Classical momentum theory method	109
IV	SYSTEM PHYSICAL CONFIGURATION	112
4.1	Achievable rates with coplanar and non-coplanar rotors	112
4.1.1	Authority analysis framework	114

4.1.2	Kinematics and dynamics modeling	118
4.1.3	Kinematics	119
4.1.4	Dynamics	122
4.1.5	Propulsion orientation configuration optimizer	125
4.1.6	Results and Validation	132
4.1.7	Power required for DFC cruise	139
4.1.8	Equivalent tilt of thrust vector for X6 DFC UAV	140
4.1.9	Maximum trimmed-hover attitudes	142
4.1.10	Thrust stand results	145
4.2	Configuration effects on rates	158
4.2.1	Quadrotors	159
4.2.2	Hexarotors	160
4.2.3	Octorotors, dodecadrotors	165
4.3	Optimization of X6 DFC UAV rotor configuration	165
4.3.1	Optimization: types 8, 9, 10 for 12-24-DOF optimization	167
4.3.2	Optimization: types 1, 2, and 4 for dihedral and motor tilt	168
4.3.3	Optimization: type 3 for wheelbase	171
4.3.4	Optimization: types 5, 6, 7 for 6-DOF optimization	174
V	CONCLUSIONS	178
5.1	Summary of contributions	184
5.2	Recommendations	186
APPENDIX A	— SELECTED ALGORITHMS	189
APPENDIX B	— ROTOR DYNAMICS AND WIND TUNNEL DATA	191
APPENDIX C	— DESIGN LOOKUP TABLES FOR ζ, ϵ	199
REFERENCES		341
VITA		353

LIST OF TABLES

1	Effects of temperature on Panasonic NCR18650B 3.4 Ah lithium ion cell voltage and capacity at 1C discharge	94
2	Flight time calculation validation survey, multiple vehicle types and respective reported and analyzer-predicted hover endurance	98
3	Drive optimizer outputs for <i>GTQ Mini</i> design.	101
4	Analyzer general system outputs for <i>GTQ Mini</i> at hover	102
5	Analyzer predictions from Table 4 compared to flight measurements for <i>GTQ Mini</i> in HOGE.	103
6	Calculated sensitivity analysis inputs for <i>GTQ Mini</i> at hover.	103
7	Sensitivity analysis outputs for <i>GTQ Mini</i> at hover	104
8	Calculated maximum range analysis outputs for <i>GTQ Mini</i> at various TAS.	104
9	Optimizer output for rubber propulsion system requirements for 140 minute hover, $d_b = 1$	106
10	Optimizer sizing prediction for long endurance vehicle. Rubber outputs compared to built vehicle.	106
11	Optimization problem for fixed-allocation controllers enforcing pure motion (a) and allowing impure motion (b) to maximize rates in 6 DOF	116
12	Array for k optimizer target maneuvers in Figure 33 to ensure positive and negative directions as well as hover are considered	117
13	Optimization <i>type</i> schedule for 1-24 DOF optimization of vehicle configuration. Each <i>type</i> has a different subset of free and number of design variables	129
14	Optimization options for vehicle configuration for each <i>type</i> : each <i>sub-type</i> has axis weights and dynamics purity constraints.	130
15	Predicted and measured inertia components of two vehicles	135
16	”Cobra” predicted and flight test rates. Italicized (angular) rates are not directly comparable as the controllers used are not identical. The flown controller asked for 10-20% of the available authority for the angular data: 10% in pitch, 15% in roll, 10% in yaw. Note that this roughly corresponds to the respective percentage of maximum pure rate in each direction, although this effect should not quite be linear .	137

17	Cobra predicted and flight test motor commands	137
18	Static tractor vs. pusher rotor configuration efficiency	153
19	Wake-wake interaction configuration; predicted geometric thrust ignoring aerodynamics compared to measured thrust	155
20	Comparative ground vs. ceiling effects on thrust at hub to ground/ceiling separation normalized by rotor diameter	156
21	Efficiency of Gemfan 6x4 propellers co-mounted, stacked on the same axle, CW + CW and CW + CCW	157
22	Design variables and corresponding GA optimizer design space for the X6 DFC UAV	166
23	Best design for <i>type 1</i> , <i>sub-type 6</i> optimization: $\Delta\%$ comparison to control vehicle in positive and negative directions of all 6 axes along with fitness score, average number of generations	168
24	Best design for <i>type 2</i> , <i>sub-type 3</i> (row 1) and 5 (row 2) optimization: $\Delta\%$ comparison to control vehicle in positive and negative directions of all 6 axes along with fitness score, average number of generations	170
25	Best design for <i>type 3</i> optimization (all <i>sub-types</i> have identical solution): $\Delta\%$ comparison to control vehicle in positive and negative directions of all 6 axes along with fitness score, average number of generations	174
26	Best design for <i>type 5</i> optimization: $\Delta\%$ comparison to control vehicle in positive and negative directions of all 6 axes along with fitness score, average number of generations, and number of generations to find optimal design	175
27	Best design for <i>type 6</i> , <i>sub-type 7</i> optimization: $\Delta\%$ comparison to control vehicle in positive and negative directions of all 6 axes along with fitness score, average number of generations	176
28	Best design for <i>type 7</i> , <i>sub-type 2</i> optimization: $\Delta\%$ comparison to control vehicle in positive and negative directions of all 6 axes along with fitness score, average number of generations	177

LIST OF FIGURES

1	Multirotor configurations: a) $+4$, b) $X4$, c) $+6$, d) $X6$, e) $Y6C$, f) $Y6C$ counter-rotating, g) $X8$, h) $X8C$. Red short arrows are thrust vector, green long arrows are right-handed rotation vector.	12
2	Multirotor configurations: i) $X6$ DFC $\zeta = 30^\circ, \epsilon = 15^\circ$, j) $Y6sC$, k) $+12$, l) $X12C$, m) $Y6C$ $\zeta = 30^\circ, \epsilon = 15^\circ$. Red short arrows are thrust vector, green long arrows are right-handed rotation vector.	13
3	NACA 0015 blade cross section at radial section r with local velocity V_l decomposed into axial and tangential directions	24
4	MST propulsion system electrical model.	26
5	The "standard $X6$ DFC" configuration referred to in this thesis. . .	47
6	MST overview and workflow. When referring to MST, the "Prop. param. optimization" direction in the figure is referred to as the "optimizer," and "segment perf. prediction" in the figure is referred to as the "analyzer"	63
7	Propulsion system parameter optimizer overview. Figure 8 shows the expanded version of this figure when the optimization objective is to minimize mass. Block A is described by section 3.1.3. The mission segments are like those shown in 9	66
8	Optimizer per-mission segment overall flowchart. This particular optimizer is set to find the lightest possible vehicle to accomplish the specified mission segment. See Figure 11 for more information on block B. Block C is found in Figure 12. Block D is described in Figure 10 . . .	67
9	Schematic mission profile for a remote delivery vehicle	68
10	Determining required thrust in steady state maneuver, used for block D in Figure 8	70
11	Find required RPM and torque to complete a mission segment for the set of propulsion system parameters, block B of Figure 8. These are used to calculate power required.	70
12	Find the propulsion system component masses given the electrical and mechanical requirements. Expansions of block A of Figure 7 and C of Figure 8	72
13	OR and IR K_v to mass relationship.	75
14	OR and IR K_v to mass relationship. OR H is the modified curve used for the analyzer and optimizer tools.	76

15	Masses of ESCs and their respective maximum amperage rating. . .	77
16	Battery masses for configurations between 2S and 6S. All batteries surveyed have 1P configuration.	78
17	Masses of propellers of various diameters composed of four materials.	79
18	Non-dimensionalized propeller blade chord at radial section r/R . Data shown from GWS Slowfly and DirectDrive propellers, extracted from [117]	79
19	Twist of GWS blades at $r/R = 0.6$ compared to indicated blade pitch, extracted from [117]	80
20	Blade twist at radial sections r/R for nine GWS Slowfly and Direct-Drive propellers, extracted from [117]	81
21	Simulated power required for cruise, <i>Eagle</i>	87
22	Simulated pitch angle required for cruise compared to classical calculations, <i>Eagle</i>	88
23	Configurations studied in wind tunnel, hobby multirotors made for acrobatics and racing: (a, left) 122 mm multirotor with flat vs (a, right) canopy, (b, left) 155 mm <i>Atom</i> chassis, (b, right) RTF 155 mm <i>Raiju</i> hexarotor, (c, left) 250 mm <i>H</i> frame <i>ZMR</i> vs (c, right) <i>X</i> frame <i>Shrike</i> , (d) 250 mm <i>ZMR</i> quadrotor with GoPro HD camera, (e, left) cased vs (e, right) uncased 5.8 GHz antenna. Thanks to Nick Willard for the photos.	89
24	TBS Vendetta 250 mm <i>H</i> frame aerodynamic data, with and without motors (no propellers)	92
25	Hoku 230 mm <i>X</i> frame aerodynamic data, RTF with and without an HD camera (no propellers)	93
26	MST analyzer deployed on public webpage [63]	99
27	<i>GTQ Mini Frobenius</i> 500 g autonomous multirotor	100
28	<i>Eagle</i> long endurance multirotor with 30x10.5" propellers	105
29	Battery parallel cell configuration selection at 6S with U8-16 100 K_v motor and 30x10.5 propellers. Simulated data.	107
30	Simulated lithium ion discharge dynamics for a flight lasting over two hours using 6S12P Panasonic 18650B cells.	108
31	Battery mass fraction and effect on ideal, relative hover time. Ideal Φ_b occurs at 2/3 GTOW. This matches that for an electric fixed wing as described by [44] and eVTOL by [47]	110

32	Approximate hover or flight endurance with battery fraction Φ_b for two dozen mainly hobby-grade, VTOL vehicles (a), (b) reported and calculated hover or flight endurance with battery fraction GTOW for two dozen mainly hobby-grade, VTOL vehicles.	111
33	Optimizer overview for selecting $\zeta, \epsilon, \lambda, l$	118
34	<i>X6</i> $\dot{q}$ design space, pure motion not enforced, M1 faulted	127
35	<i>X6</i> $\dot{q}$ design space, pure motion not enforced, no rotor faults	128
36	<i>X6</i> $\dot{q}$ design space, pure motion enforced, rotor faults: <i>M1</i> . Note loss of authority in $+\dot{q}$ direction	128
37	Design variables $\zeta, \epsilon, \lambda, l$ shown on a DFC <i>X6</i>	130
38	Simulated vs. measured static and dynamic thrust data for GWS 5x3 propeller, a) C_T , b) C_P , c) η . Differences mostly due to blade geometry. Measured data is extracted from [117]. These sized vehicles generally fly at advance ratio J of between 0 to 0.15, up to 0.34 for high performance racing multirotors using propellers of this size . . .	133
39	Predicted vs. measured static thrust data for GWS 5x3 propeller, a) T , b) RPM, c) P_e . This rotor is used for all vehicles described in this section unless otherwise noted.	134
40	<i>Cobra</i> DFC <i>X6</i> multirotor, $(\zeta, \epsilon) = (30^\circ, 0^\circ)$	136
41	Simulated power required for cruise, <i>Vulture</i>	139
42	Simulated pitch angle required for cruise, <i>Vulture</i>	140
43	Actuation authority in x_B and y_B as a function of ζ and ϵ , and mapping to equivalent thrust vector tilt, at hover	141
44	ζ and weight to maximum-thrust ratio effects on maximum trimmed-hover pitch angle for DFC <i>X6</i>	143
45	ζ and weight to maximum-thrust ratio effects on maximum trimmed-hover roll angle for DFC <i>X6</i>	144
46	Adjustable thrust stand to measure thrust, independent torque, current, voltage	146
47	Thrust stand torque load cell calibration	147
48	Thrust stand configuration for coaxial rotors	149
49	Co- vs. counter-rotating coaxial rotors at different hub-hub separations	150

50	Semi-coaxial configuration on thrust stand. Both rotors spin such that the wake airflow is aimed generally to the left, producing thrust generally to the right.	151
51	Semi-coaxial configuration (see Figure 2(j)) expected thrust in response to geometric angle compared to measured thrust including inter-rotor aerodynamics. Semi-coaxial configuration at 30° produces more thrust than the coaxial configuration at 0°	152
52	Thrust stand configuration to measure wake-wake interaction at 30° .	154
53	Tractor vs. pusher configuration rotor efficiency in ground and ceiling effect	156
54	1-DOF <i>X6</i> configuration optimization for rates, free $\epsilon(1)$	169
55	1-DOF <i>X6</i> configuration optimization for rates, free $\zeta(1)$ for <i>sub-types</i> 3 (a) and 5 (b)	170
56	Composite LUT for <i>X6</i> failures of rotors <i>M1</i> through <i>M3</i> , pure motion enforced	172
57	Composite LUT for <i>X6</i> failures of rotors <i>M1</i> through <i>M3</i> , pure motion not enforced	173
58	1-DOF <i>X6</i> configuration optimization for rates, free $l(1)$	175
59	6-DOF <i>X6</i> configuration optimization for rates, free $\lambda(6)$. Note extra l to decrease propeller strikes while optimizing.	176
60	6-DOF <i>X6</i> configuration optimization for rates, free $\epsilon(6)$	177
61	6-DOF <i>X6</i> configuration optimization for rates, free $\zeta(6)$. Note qualitative similarity to vehicle in Figure 55(b)	177
62	Dynamic response of U8-16 motor with T-motor 30x10.5 propeller, bang-bang inputs 0-50%, 50-100%, 0-100%, 100-0%, 50-0%	192
63	Dynamic response of U8-16 motor with T-motor 30x10.5 propeller with stepped inputs	192
64	Drag and lift coefficients for generic 450 mm <i>X</i> frame, no propellers .	193
65	Drag and lift coefficients for RTF ZMR 250 mm <i>X</i> frame, no propellers	193
66	Drag and lift coefficients for bare ZMR 250 mm <i>X</i> frame, no propellers	194
67	Drag and lift coefficients for TBS Vendetta 250 mm <i>H</i> frame [151] . .	194
68	Drag and lift coefficients for bare vs RTF Vendetta 250 mm <i>X</i> frame, no propellers	195
69	Drag and lift coefficients Shrike 250 mm <i>X</i> frame, no propellers . . .	195

70	Drag and lift coefficients for Hoku 250 mm X frame with and without HD camera, no propellers	196
71	Drag and lift coefficients for Atom 122 mm X frame with and without canopy, no propellers	196
72	Drag and lift coefficients for Charpu 210 mm X frame with and without HD camera, no propellers	197
73	Drag and lift coefficients for Alien 250 mm X frame, no propellers . .	197
74	Drag and lift coefficients for Alien 250 mm X frame with HD camera, no propellers	198
75	Drag and lift coefficients for Alien 250 mm X frame with 5.8 cased antenna, no propellers	198
76	$+4 \dot{p}$ design space, pure motion not enforced, M1 fault	200
77	$+4 \dot{p}$ design space, pure motion not enforced, no rotor faults	200
78	$+4 \dot{p}$ design space, pure motion enforced, M1 fault	201
79	$+4 \dot{p}$ design space, pure motion enforced, no rotor faults	201
80	$+4 \dot{q}$ design space, pure motion not enforced, M1 fault	202
81	$+4 \dot{q}$ design space, pure motion not enforced, no rotor faults	202
82	$+4 \dot{q}$ design space, pure motion enforced, M1 fault	203
83	$+4 \dot{q}$ design space, pure motion enforced, no rotor faults	203
84	$+4 \dot{r}$ design space, pure motion not enforced, M1 fault	204
85	$+4 \dot{r}$ design space, pure motion not enforced, no rotor faults	204
86	$+4 \dot{r}$ design space, pure motion enforced, M1 fault	205
87	$+4 \dot{r}$ design space, pure motion enforced, no rotor faults	205
88	$+4 \ddot{x}$ design space, pure motion not enforced, M1 fault	206
89	$+4 \ddot{x}$ design space, pure motion not enforced, no rotor faults	206
90	$+4 \ddot{x}$ design space, pure motion enforced, M1 fault	207
91	$+4 \ddot{x}$ design space, pure motion enforced, no rotor faults	207
92	$+4 \ddot{y}$ design space, pure motion not enforced, M1 fault	208
93	$+4 \ddot{y}$ design space, pure motion not enforced, no rotor faults	208
94	$+4 \ddot{y}$ design space, pure motion enforced, M1 fault	209

95	$+4 \ddot{y}$ design space, pure motion enforced, no rotor faults	209
96	$+4 \ddot{z}$ design space, pure motion not enforced, M1 fault	210
97	$+4 \ddot{z}$ design space, pure motion not enforced, no rotor faults	210
98	$+4 \ddot{z}$ design space, pure motion enforced, M1 fault	211
99	$+4 \ddot{z}$ design space, pure motion enforced, no rotor faults	211
100	$+6 \dot{p}$ design space, pure motion not enforced, M1 fault	212
101	$+6 \dot{p}$ design space, pure motion not enforced, no rotor faults	212
102	$+6 \dot{p}$ design space, pure motion enforced, no rotor faults	213
103	$+6 \dot{q}$ design space, pure motion not enforced, M1 fault	213
104	$+6 \dot{q}$ design space, pure motion not enforced, no rotor faults	214
105	$+6 \dot{q}$ design space, pure motion enforced, no rotor faults	214
106	$+6 \dot{r}$ design space, pure motion not enforced, M1 fault	215
107	$+6 \dot{r}$ design space, pure motion not enforced, no rotor faults	215
108	$+6 \dot{r}$ design space, pure motion enforced, no rotor faults	216
109	$+6 \ddot{x}$ design space, pure motion not enforced, M1 fault	216
110	$+6 \ddot{x}$ design space, pure motion not enforced, no rotor faults	217
111	$+6 \ddot{x}$ design space, pure motion enforced, no rotor faults	217
112	$+6 \ddot{y}$ design space, pure motion not enforced, M1 fault	218
113	$+6 \ddot{y}$ design space, pure motion not enforced, no rotor faults	218
114	$+6 \ddot{y}$ design space, pure motion enforced, no rotor faults	219
115	$+6 \ddot{z}$ design space, pure motion not enforced, M1 fault	219
116	$+6 \ddot{z}$ design space, pure motion not enforced, no rotor faults	220
117	$+6 \ddot{z}$ design space, pure motion enforced, no rotor faults	220
118	$X12C \dot{p}$ design space, pure motion not enforced, co-rotating, M1 fault	221
119	$X12C \dot{p}$ design space, pure motion not enforced, counter-rotating, M1 fault	221
120	$X12C \dot{p}$ design space, pure motion not enforced, co-rotating, no rotor faults	222
121	$X12C \dot{p}$ design space, pure motion not enforced, counter-rotating, no rotor faults	222

122	$X12C \dot{q}$ design space, pure motion not enforced, co-rotating, M1 fault	223
123	$X12C \dot{q}$ design space, pure motion not enforced, counter-rotating, M1 fault	223
124	$X12C \dot{q}$ design space, pure motion not enforced, co-rotating, no rotor faults	224
125	$X12C \dot{q}$ design space, pure motion not enforced, counter-rotating, no rotor faults	224
126	$X12C \dot{r}$ design space, pure motion not enforced, co-rotating, M1 fault	225
127	$X12C \dot{r}$ design space, pure motion not enforced, counter-rotating, M1 fault	225
128	$X12C \dot{r}$ design space, pure motion not enforced, co-rotating, no rotor faults	226
129	$X12C \dot{r}$ design space, pure motion not enforced, counter-rotating, no rotor faults	226
130	$X12C \ddot{x}$ design space, pure motion not enforced, co-rotating, M1 fault	227
131	$X12C \ddot{x}$ design space, pure motion not enforced, counter-rotating, M1 fault	227
132	$X12C \ddot{x}$ design space, pure motion not enforced, co-rotating, no rotor faults	228
133	$X12C \ddot{x}$ design space, pure motion not enforced, counter-rotating, no rotor faults	228
134	$X12C \ddot{y}$ design space, pure motion not enforced, co-rotating, M1 fault	229
135	$X12C \ddot{y}$ design space, pure motion not enforced, counter-rotating, M1 fault	229
136	$X12C \ddot{y}$ design space, pure motion not enforced, co-rotating, no rotor faults	230
137	$X12C \ddot{y}$ design space, pure motion not enforced, counter-rotating, no rotor faults	230
138	$X12C \ddot{z}$ design space, pure motion not enforced, co-rotating, M1 fault	231
139	$X12C \ddot{z}$ design space, pure motion not enforced, counter-rotating, M1 fault	231
140	$X12C \ddot{z}$ design space, pure motion not enforced, co-rotating, no rotor faults	232

141	$X12C \ddot{z}$ design space, pure motion not enforced, counter-rotating, no rotor faults	232
142	$X12 \dot{p}$ design space, pure motion not enforced, M1 fault	233
143	$X12 \dot{p}$ design space, pure motion not enforced, no rotor faults	233
144	$X12 \dot{q}$ design space, pure motion not enforced, M1 fault	234
145	$X12 \dot{q}$ design space, pure motion not enforced, no rotor faults	234
146	$X12 \dot{r}$ design space, pure motion not enforced, M1 fault	235
147	$X12 \dot{r}$ design space, pure motion not enforced, no rotor faults	235
148	$X12 \ddot{x}$ design space, pure motion not enforced, M1 fault	236
149	$X12 \ddot{x}$ design space, pure motion not enforced, no rotor faults	236
150	$X12 \ddot{y}$ design space, pure motion not enforced, M1 fault	237
151	$X12 \ddot{y}$ design space, pure motion not enforced, no rotor faults	237
152	$X12 \ddot{z}$ design space, pure motion not enforced, M1 fault	238
153	$X12 \ddot{z}$ design space, pure motion not enforced, no rotor faults	238
154	$X4 \dot{p}$ design space, pure motion not enforced, no rotor faults	239
155	$X4 \dot{p}$ design space, pure motion enforced, M1 fault	239
156	$X4 \dot{p}$ design space, pure motion enforced, no rotor faults	240
157	$X4 \dot{q}$ design space, pure motion not enforced, no rotor faults	240
158	$X4 \dot{q}$ design space, pure motion enforced, M1 fault	241
159	$X4 \dot{q}$ design space, pure motion enforced, no rotor faults	241
160	$X4 \dot{r}$ design space, pure motion not enforced, no rotor faults	242
161	$X4 \dot{r}$ design space, pure motion enforced, M1 fault	242
162	$X4 \dot{r}$ design space, pure motion enforced, no rotor faults	243
163	$X4 \ddot{x}$ design space, pure motion not enforced, no rotor faults	243
164	$X4 \ddot{x}$ design space, pure motion enforced, M1 fault	244
165	$X4 \ddot{x}$ design space, pure motion enforced, no rotor faults	244
166	$X4 \ddot{y}$ design space, pure motion not enforced, no rotor faults	245
167	$X4 \ddot{y}$ design space, pure motion enforced, M1 fault	245
168	$X4 \ddot{y}$ design space, pure motion enforced, no rotor faults	246

169	$X_4 \ddot{z}$ design space, pure motion not enforced, no rotor faults	246
170	$X_4 \ddot{z}$ design space, pure motion enforced, M1 fault	247
171	$X_4 \ddot{z}$ design space, pure motion enforced, no rotor faults	247
172	$X_6 \dot{p}$ design space, pure motion not enforced, M1 fault	248
173	$X_6 \dot{p}$ design space, pure motion not enforced, M2 fault	248
174	$X_6 \dot{p}$ design space, pure motion not enforced, M3 fault	249
175	$X_6 \dot{p}$ design space, pure motion not enforced, no rotor faults	249
176	$X_6 \dot{p}$ design space, pure motion enforced, M1 fault	250
177	$X_6 \dot{p}$ design space, pure motion enforced, M2 fault	250
178	$X_6 \dot{p}$ design space, pure motion enforced, M3 fault	251
179	$X_6 \dot{p}$ design space, pure motion enforced, no rotor faults	251
180	$X_6 \dot{q}$ design space, pure motion not enforced, M1 fault	252
181	$X_6 \dot{q}$ design space, pure motion not enforced, M2 fault	252
182	$X_6 \dot{q}$ design space, pure motion not enforced, M3 fault	253
183	$X_6 \dot{q}$ design space, pure motion not enforced, no rotor faults	253
184	$X_6 \dot{q}$ design space, pure motion enforced, M1 fault	254
185	$X_6 \dot{q}$ design space, pure motion enforced, M2 fault	254
186	$X_6 \dot{q}$ design space, pure motion enforced, M3 fault	255
187	$X_6 \dot{q}$ design space, pure motion enforced, no rotor faults	255
188	$X_6 \dot{r}$ design space, pure motion not enforced, M1 fault	256
189	$X_6 \dot{r}$ design space, pure motion not enforced, M2 fault	256
190	$X_6 \dot{r}$ design space, pure motion not enforced, M3 fault	257
191	$X_6 \dot{r}$ design space, pure motion not enforced, no rotor faults	257
192	$X_6 \dot{r}$ design space, pure motion enforced, M1 fault	258
193	$X_6 \dot{r}$ design space, pure motion enforced, M2 fault	258
194	$X_6 \dot{r}$ design space, pure motion enforced, M3 fault	259
195	$X_6 \dot{r}$ design space, pure motion enforced, no rotor faults	259
196	$X_6 \ddot{x}$ design space, pure motion not enforced, M1 fault	260
197	$X_6 \ddot{x}$ design space, pure motion not enforced, M2 fault	260

198	$X6 \ddot{x}$ design space, pure motion not enforced, M3 fault	261
199	$X6 \ddot{x}$ design space, pure motion not enforced, no rotor faults	261
200	$X6 \ddot{x}$ design space, pure motion enforced, M1 fault	262
201	$X6 \ddot{x}$ design space, pure motion enforced, M2 fault	262
202	$X6 \ddot{x}$ design space, pure motion enforced, M3 fault	263
203	$X6 \ddot{x}$ design space, pure motion enforced, no rotor faults	263
204	$X6 \ddot{y}$ design space, pure motion not enforced, M1 fault	264
205	$X6 \ddot{y}$ design space, pure motion not enforced, M2 fault	264
206	$X6 \ddot{y}$ design space, pure motion not enforced, M3 fault	265
207	$X6 \ddot{y}$ design space, pure motion not enforced, no rotor faults	265
208	$X6 \ddot{y}$ design space, pure motion enforced, M1 fault	266
209	$X6 \ddot{y}$ design space, pure motion enforced, M2 fault	266
210	$X6 \ddot{y}$ design space, pure motion enforced, M3 fault	267
211	$X6 \ddot{y}$ design space, pure motion enforced, no rotor faults	267
212	$X6 \ddot{z}$ design space, pure motion not enforced, M1 fault	268
213	$X6 \ddot{z}$ design space, pure motion not enforced, M2 fault	268
214	$X6 \ddot{z}$ design space, pure motion not enforced, M3 fault	269
215	$X6 \ddot{z}$ design space, pure motion not enforced, no rotor faults	269
216	$X6 \ddot{z}$ design space, pure motion enforced, M1 fault	270
217	$X6 \ddot{z}$ design space, pure motion enforced, M2 fault	270
218	$X6 \ddot{z}$ design space, pure motion enforced, M3 fault	271
219	$X6 \ddot{z}$ design space, pure motion enforced, no rotor faults	271
220	$X8C \dot{p}$ design space, pure motion not enforced, co-rotating, M1 fault	272
221	$X8C \dot{p}$ design space, pure motion not enforced, counter-rotating, M1 fault	272
222	$X8C \dot{p}$ design space, pure motion not enforced, co-rotating, no rotor faults	273
223	$X8C \dot{p}$ design space, pure motion not enforced, counter-rotating, no rotor faults	273

224	$X8C \dot{p}$ design space, pure motion enforced, counter-rotating, no rotor faults	274
225	$X8C \dot{q}$ design space, pure motion not enforced, co-rotating, M1 fault	274
226	$X8C \dot{q}$ design space, pure motion not enforced, counter-rotating, M1 fault	275
227	$X8C \dot{q}$ design space, pure motion not enforced, co-rotating, no rotor faults	275
228	$X8C \dot{q}$ design space, pure motion not enforced, counter-rotating, no rotor faults	276
229	$X8C \dot{q}$ design space, pure motion enforced, counter-rotating, no rotor faults	276
230	$X8C \dot{r}$ design space, pure motion not enforced, co-rotating, M1 fault	277
231	$X8C \dot{r}$ design space, pure motion not enforced, counter-rotating, M1 fault	277
232	$X8C \dot{r}$ design space, pure motion not enforced, co-rotating, no rotor faults	278
233	$X8C \dot{r}$ design space, pure motion not enforced, counter-rotating, no rotor faults	278
234	$X8C \dot{r}$ design space, pure motion enforced, counter-rotating, no rotor faults	279
235	$X8C \ddot{x}$ design space, pure motion not enforced, co-rotating, M1 fault	279
236	$X8C \ddot{x}$ design space, pure motion not enforced, counter-rotating, M1 fault	280
237	$X8C \ddot{x}$ design space, pure motion not enforced, co-rotating, no rotor faults	280
238	$X8C \ddot{x}$ design space, pure motion not enforced, counter-rotating, no rotor faults	281
239	$X8C \ddot{x}$ design space, pure motion enforced, counter-rotating, no rotor faults	281
240	$X8C \ddot{y}$ design space, pure motion not enforced, co-rotating, M1 fault	282
241	$X8C \ddot{y}$ design space, pure motion not enforced, counter-rotating, M1 fault	282
242	$X8C \ddot{y}$ design space, pure motion not enforced, co-rotating, no rotor faults	283

243	$X8C \ddot{y}$ design space, pure motion not enforced, counter-rotating, no rotor faults	283
244	$X8C \ddot{y}$ design space, pure motion enforced, counter-rotating, no rotor faults	284
245	$X8C \ddot{z}$ design space, pure motion not enforced, co-rotating, M1 fault	284
246	$X8C \ddot{z}$ design space, pure motion not enforced, counter-rotating, M1 fault	285
247	$X8C \ddot{z}$ design space, pure motion not enforced, co-rotating, no rotor faults	285
248	$X8C \ddot{z}$ design space, pure motion not enforced, counter-rotating, no rotor faults	286
249	$X8C \ddot{z}$ design space, pure motion enforced, counter-rotating, no rotor faults	286
250	$X8 \dot{p}$ design space, pure motion not enforced, M1 fault	287
251	$X8 \dot{p}$ design space, pure motion not enforced, no rotor faults	287
252	$X8 \dot{p}$ design space, pure motion enforced, M1 fault	288
253	$X8 \dot{p}$ design space, pure motion enforced, no rotor faults	288
254	$X8 \dot{q}$ design space, pure motion not enforced, M1 fault	289
255	$X8 \dot{q}$ design space, pure motion not enforced, no rotor faults	289
256	$X8 \dot{q}$ design space, pure motion enforced, M1 fault	290
257	$X8 \dot{q}$ design space, pure motion enforced, no rotor faults	290
258	$X8 \dot{r}$ design space, pure motion not enforced, M1 fault	291
259	$X8 \dot{r}$ design space, pure motion not enforced, no rotor faults	291
260	$X8 \dot{r}$ design space, pure motion enforced, M1 fault	292
261	$X8 \dot{r}$ design space, pure motion enforced, no rotor faults	292
262	$X8 \ddot{x}$ design space, pure motion not enforced, M1 fault	293
263	$X8 \ddot{x}$ design space, pure motion not enforced, no rotor faults	293
264	$X8 \ddot{x}$ design space, pure motion enforced, M1 fault	294
265	$X8 \ddot{x}$ design space, pure motion enforced, no rotor faults	294
266	$X8 \ddot{y}$ design space, pure motion not enforced, M1 fault	295
267	$X8 \ddot{y}$ design space, pure motion not enforced, no rotor faults	295

268	$X8 \ddot{y}$ design space, pure motion enforced, M1 fault	296
269	$X8 \ddot{y}$ design space, pure motion enforced, no rotor faults	296
270	$X8 \ddot{z}$ design space, pure motion not enforced, M1 fault	297
271	$X8 \ddot{z}$ design space, pure motion not enforced, no rotor faults	297
272	$X8 \ddot{z}$ design space, pure motion enforced, M1 fault	298
273	$X8 \ddot{z}$ design space, pure motion enforced, no rotor faults	298
274	$Y6C \dot{p}$ design space, pure motion not enforced, co-rotating, M1 fault	299
275	$Y6C \dot{p}$ design space, pure motion not enforced, counter-rotating, M1 fault	299
276	$Y6C \dot{p}$ design space, pure motion not enforced, co-rotating, no rotor faults	300
277	$Y6C \dot{p}$ design space, pure motion not enforced, counter-rotating, no rotor faults	300
278	$Y6C \dot{q}$ design space, pure motion not enforced, co-rotating, M1 fault	301
279	$Y6C \dot{q}$ design space, pure motion not enforced, counter-rotating, M1 fault	301
280	$Y6C \dot{q}$ design space, pure motion not enforced, co-rotating, no rotor faults	302
281	$Y6C \dot{q}$ design space, pure motion not enforced, counter-rotating, no rotor faults	302
282	$Y6C \dot{r}$ design space, pure motion not enforced, co-rotating, M1 fault	303
283	$Y6C \dot{r}$ design space, pure motion not enforced, counter-rotating, M1 fault	303
284	$Y6C \dot{r}$ design space, pure motion not enforced, co-rotating, no rotor faults	304
285	$Y6C \dot{r}$ design space, pure motion not enforced, counter-rotating, no rotor faults	304
286	$Y6C \ddot{x}$ design space, pure motion not enforced, co-rotating, M1 fault	305
287	$Y6C \ddot{x}$ design space, pure motion not enforced, counter-rotating, M1 fault	305
288	$Y6C \ddot{x}$ design space, pure motion not enforced, co-rotating, no rotor faults	306

289	$Y6C \ddot{x}$ design space, pure motion not enforced, counter-rotating, no rotor faults	306
290	$Y6C \ddot{y}$ design space, pure motion not enforced, co-rotating, M1 fault	307
291	$Y6C \ddot{y}$ design space, pure motion not enforced, counter-rotating, M1 fault	307
292	$Y6C \ddot{y}$ design space, pure motion not enforced, co-rotating, no rotor faults	308
293	$Y6C \ddot{y}$ design space, pure motion not enforced, counter-rotating, no rotor faults	308
294	$Y6C \ddot{z}$ design space, pure motion not enforced, co-rotating, M1 fault	309
295	$Y6C \ddot{z}$ design space, pure motion not enforced, counter-rotating, M1 fault	309
296	$Y6C \ddot{z}$ design space, pure motion not enforced, co-rotating, no rotor faults	310
297	$Y6C \ddot{z}$ design space, pure motion not enforced, counter-rotating, no rotor faults	310
298	$Y6sC \dot{p}$ design space, pure motion not enforced, co-rotating, M1 fault	311
299	$Y6sC \dot{p}$ design space, pure motion not enforced, counter-rotating, M1 fault	311
300	$Y6sC \dot{p}$ design space, pure motion not enforced, co-rotating, no rotor faults	312
301	$Y6sC \dot{p}$ design space, pure motion not enforced, counter-rotating, no rotor faults	312
302	$Y6sC \dot{p}$ design space, pure motion enforced, co-rotating, M1 fault	313
303	$Y6sC \dot{p}$ design space, pure motion enforced, counter-rotating, M1 fault	313
304	$Y6sC \dot{p}$ design space, pure motion enforced, co-rotating, no rotor faults	314
305	$Y6sC \dot{p}$ design space, pure motion enforced, counter-rotating, no rotor faults	314
306	$Y6sC \dot{q}$ design space, pure motion not enforced, co-rotating, M1 fault	315
307	$Y6sC \dot{q}$ design space, pure motion not enforced, counter-rotating, M1 fault	315
308	$Y6sC \dot{q}$ design space, pure motion not enforced, co-rotating, no rotor faults	316

309	$Y6sC \dot{q}$ design space, pure motion not enforced, counter-rotating, no rotor faults	316
310	$Y6sC \dot{q}$ design space, pure motion enforced, co-rotating, M1 fault . .	317
311	$Y6sC \dot{q}$ design space, pure motion enforced, counter-rotating, M1 fault	317
312	$Y6sC \dot{q}$ design space, pure motion enforced, co-rotating, no rotor faults	318
313	$Y6sC \dot{q}$ design space, pure motion enforced, counter-rotating, no rotor faults	318
314	$Y6sC \dot{r}$ design space, pure motion not enforced, co-rotating, M1 fault	319
315	$Y6sC \dot{r}$ design space, pure motion not enforced, counter-rotating, M1 fault	319
316	$Y6sC \dot{r}$ design space, pure motion not enforced, co-rotating, no rotor faults	320
317	$Y6sC \dot{r}$ design space, pure motion not enforced, counter-rotating, no rotor faults	320
318	$Y6sC \dot{r}$ design space, pure motion enforced, co-rotating, M1 fault . .	321
319	$Y6sC \dot{r}$ design space, pure motion enforced, counter-rotating, M1 fault	321
320	$Y6sC \dot{r}$ design space, pure motion enforced, co-rotating, no rotor faults	322
321	$Y6sC \dot{r}$ design space, pure motion enforced, counter-rotating, no rotor faults	322
322	$Y6sC \ddot{x}$ design space, pure motion not enforced, co-rotating, M1 fault	323
323	$Y6sC \ddot{x}$ design space, pure motion not enforced, counter-rotating, M1 fault	323
324	$Y6sC \ddot{x}$ design space, pure motion not enforced, co-rotating, no rotor faults	324
325	$Y6sC \ddot{x}$ design space, pure motion not enforced, counter-rotating, no rotor faults	324
326	$Y6sC \ddot{x}$ design space, pure motion enforced, co-rotating, M1 fault . .	325
327	$Y6sC \ddot{x}$ design space, pure motion enforced, counter-rotating, M1 fault	325
328	$Y6sC \ddot{x}$ design space, pure motion enforced, co-rotating, no rotor faults	326
329	$Y6sC \ddot{x}$ design space, pure motion enforced, counter-rotating, no rotor faults	326
330	$Y6sC \ddot{y}$ design space, pure motion not enforced, co-rotating, M1 fault	327

331	$Y6sC \ddot{y}$ design space, pure motion not enforced, counter-rotating, M1 fault	327
332	$Y6sC \ddot{y}$ design space, pure motion not enforced, co-rotating, no rotor faults	328
333	$Y6sC \ddot{y}$ design space, pure motion not enforced, counter-rotating, no rotor faults	328
334	$Y6sC \ddot{y}$ design space, pure motion enforced, co-rotating, M1 fault . .	329
335	$Y6sC \ddot{y}$ design space, pure motion enforced, counter-rotating, M1 fault	329
336	$Y6sC \ddot{y}$ design space, pure motion enforced, co-rotating, no rotor faults	330
337	$Y6sC \ddot{y}$ design space, pure motion enforced, counter-rotating, no rotor faults	330
338	$Y6sC \ddot{z}$ design space, pure motion not enforced, co-rotating, M1 fault	331
339	$Y6sC \ddot{z}$ design space, pure motion not enforced, counter-rotating, M1 fault	331
340	$Y6sC \ddot{z}$ design space, pure motion not enforced, co-rotating, no rotor faults	332
341	$Y6sC \ddot{z}$ design space, pure motion not enforced, counter-rotating, no rotor faults	332
342	$Y6sC \ddot{z}$ design space, pure motion enforced, co-rotating, M1 fault . .	333
343	$Y6sC \ddot{z}$ design space, pure motion enforced, counter-rotating, M1 fault	333
344	$Y6sC \ddot{z}$ design space, pure motion enforced, co-rotating, no rotor faults	334
345	$Y6sC \ddot{z}$ design space, pure motion enforced, counter-rotating, no rotor faults	334
346	Composite LUT for $X6$ failures of rotors $M1$ through $M3$, pure motion enforced	335
347	Composite LUT for $X6$ failures of rotors $M1$ through $M3$	335
348	Composite LUT for $X6$ failures of rotors $M1$ through $M3$	336
349	Composite LUT for $X6$ failures of rotors $M1$ through $M3$	336
350	Composite LUT for $X6$ failures of rotors $M1$ through $M3$	337
351	Composite LUT for $X6$ failures of rotors $M1$ through $M3$	337
352	Composite LUT for $X6$ failures of rotors $M1$ through $M3$, pure motion not enforced	338