

# Swift-Hohenberg Numerics - Testing with Chebfun

Edward McDugald

October 18, 2022

## 1 Operator Splitting for SH

- We have the PDE

$$w_t = -(1 + \nabla^2)^2 w + R w - w^3.$$

- We can break this into a linear part and a non-linear part,

$$W_t = L(w) + NL(w),$$

with

$$\begin{aligned} L(w) &= -(2\nabla^2 + \nabla^4)w \\ NL(w) &= (R - 1)w - w^3. \end{aligned}$$

- Basic procedure is as follows:

- (i) Let  $A = (-\nabla^4 - 2\nabla^2)$ . Consider the pair of PDEs

$$\begin{aligned} w_t &= A w \\ w_t &= (R - 1)w - w^3. \end{aligned}$$

- (ii) Handling the linear and nonlinear PDEs separately, we get the relations

$$\begin{aligned} w(t + \Delta t) &= \Delta t A w(t) + w(t) \\ \implies w(t + \Delta t) &\approx e^{A\Delta t} w(t). \end{aligned}$$

And for the nonlinear part,

$$w(t + \Delta t) \approx \Delta t [(R - 1)w(t) - w(t)^3] + w(t).$$

.

- (iii) Apply operator splitting (strang splitting) now

The code is implemented in python as follows:

```
def non_lin_rhs(w,R):
    return (R-1)*w - w**3

def integrateSH(w0,R,dt,nSteps,L):
    """
    :param w0: initial temperature surface
    :param R: bifurcation parameter- can be a constant, or of same shape as w0
    :param dt: time step length
    :param nSteps: number of time steps to take
    :param L: Length of square over which w0 is defined
    :return w0: time evolution of w0 at time 0+dt*nSteps
    Ideally, the size of w0 is fft friendly, ie 2^n x 2^n
    """
    print("Starting time integration of Swift Hohenberg")
    ny, nx = np.shape(w0)
    print("Dimensions of w0:", nx, ny)
    kx = (2.*np.pi/L)*sp.fft.fftfreq(nx,1./nx)
    ky = (2.*np.pi/L)*sp.fft.fftfreq(ny,1./ny)
    Kx, Ky = np.meshgrid(kx,ky)
    fourierLaplacian = -(Kx**2+Ky**2)
    A = -(fourierLaplacian*fourierLaplacian)-2*fourierLaplacian
    for i in range(0,nSteps):
        if i%100 == 0:
            print("step number:",i)
        w1 = np.real(sp.fft.ifft2(np.exp(A*.5*dt)*sp.fft.fft2(w0)))

        #rk4 version
        #k1 = dt*w1
        #k2 = dt*non_lin_rhs(w1+.5*k1, R)
        #k3 = dt*non_lin_rhs(w1+.5*k2, R)
        #k4 = dt*non_lin_rhs(w1+k3, R)
        #w2 = (k1+2*k2+2*k3+k4)/6 + w1

        #fwd euler version
        w2 = dt*((R-1)*w1-w1**3)+w1

        w0 = np.real(sp.fft.ifft2(np.exp(A*.5*dt)*sp.fft.fft2(w2)))
    return w0
```

## 2 Comparison with Chebfun

### 2.1 Chebfun vs Python 1

#### Chebfun 1 code

```
>> dom = [-16 16 -16 16]
>> tspan = [0 10];
>> S = spinop2(dom, tspan)
>> S.lin = @(u) -2*lap(u)-biharm(u)
>> R = .5
>> S.nonlin = @(u) (R-1)*u - u.^3;
>> u0 = 1/20*chebfun2(@(x,y) cos(x) + sin(2*x) + sin(y) + cos(2*y), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-5*pi).^2 + (y-5*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-5*pi).^2 + (y-15*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-15*pi).^2 + (y-15*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-15*pi).^2 + (y-5*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-10*pi).^2 + (y-10*pi).^2)), dom, 'trig');
S.init = u0;
>> u = spin2(S, 256, .1, 'plot', 'off');
>> plot(u), view(0,90), axis equal, axis off
>> saveas(gcf, '/Users/edwardmcdugald/Research/
convection_patterns_matlab/figs/sh_tsts_1018/cf1.pdf');
```

#### python 1 code

```
x = np.linspace(-16,16,256)
y = np.linspace(-16,16,256)
X,Y = np.meshgrid(x,y)
w0 = (1./20.)*(np.cos(X)+np.sin(2*X)+np.sin(Y)+np.cos(2*Y))
w0 = w0 + (np.exp(-((X-5*np.pi)**2 + (Y-5*np.pi)**2)))
w0 = w0 + (np.exp(-((X-5*np.pi)**2 + (Y-15*np.pi)**2)))
w0 = w0 + (np.exp(-((X-15*np.pi)**2 + (Y-15*np.pi)**2)))
w0 = w0 + (np.exp(-((X-15*np.pi)**2 + (Y-5*np.pi)**2)))
w0 = w0 + (np.exp(-((X-10*np.pi)**2 + (Y-10*np.pi)**2)))
dt = .1
R=.5
L=x[len(x)-1]-x[0]
nSteps = 100
W1 = integrateSH(w0,R,dt,nSteps,L)
fig1, ax1 = plt.subplots(nrows=1, ncols=1, figsize=(3,3))
ax1.imshow(W1)
```




Figure 1: Chebfun




Figure 2: Python

```
plt.savefig("/Users/edwardmcdugald/Research/
convection_patterns/code/figs/sh_num_tsts_1018/mySH1.pdf")
```

## 2.2 Chebfun vs Python 2

### chebfun 2 code

```
dom = [0 20*pi 0 20*pi];
tspan = [0 200];
S = spinop2(dom, tspan);
S.lin = @(u) -2*lap(u) - biharm(u);
r = 1e-2;
S.nonlin = @(u) (-1 + r)*u - u.^3;
u0 = 1/20*chebfun2(@(x,y) cos(x) + sin(2*x) + sin(y) + cos(2*y), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-5*pi).^2 + (y-5*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-5*pi).^2 + (y-15*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-15*pi).^2 + (y-15*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-15*pi).^2 + (y-5*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-10*pi).^2 + (y-10*pi).^2)), dom, 'trig');
S.init = u0;
plot(S.init), view(0,90), axis equal, axis off
```

```

u = spin2(S, 96, 2e-1, 'plot', 'off');
plot(u), view(0,90), axis equal, axis off
>> saveas(gcf, '/Users/edwardmcdugald/Research/
convection_patterns_matlab/figs/sh_tsts_1018/cf2.pdf');

```

## python 2 code

```

x = np.linspace(0,20*np.pi,96)
y = np.linspace(0,20*np.pi,96)
X,Y = np.meshgrid(x,y)
w0 = (1./20.)*(np.cos(X)+np.sin(2*X)+np.sin(Y)+np.cos(2*Y))
w0 = w0 + (np.exp(-((X-5*np.pi)**2 + (Y-5*np.pi)**2)))
w0 = w0 + (np.exp(-((X-5*np.pi)**2 + (Y-15*np.pi)**2)))
w0 = w0 + (np.exp(-((X-15*np.pi)**2 + (Y-15*np.pi)**2)))
w0 = w0 + (np.exp(-((X-15*np.pi)**2 + (Y-5*np.pi)**2)))
w0 = w0 + (np.exp(-((X-10*np.pi)**2 + (Y-10*np.pi)**2)))
fig, ax = plt.subplots(nrows=1, ncols=1, figsize=(3,3))
ax.imshow(w0)
dt = 2e-1
R= 1e-2
L=x[len(x)-1]-x[0]
nSteps = 1000
W2 = integrateSH(w0,R,dt,nSteps,L)
fig2, ax2 = plt.subplots(nrows=1, ncols=1, figsize=(3,3))
ax2.imshow(W2)
plt.savefig("/Users/edwardmcdugald/Research/
convection_patterns/code/figs/sh_num_tsts_1018/mySH2.pdf")

```

## 2.3 Chebfun vs Python 3

### chebfun 3 code

```

>> dom = [0 20*pi 0 20*pi];
tspan = [0 200];
S = spinop2(dom, tspan);
S.lin = @(u) -2*lap(u) - biharm(u);
>> u0 = 1/20*chebfun2(@(x,y) cos(x) + sin(2*x) + sin(y) + cos(2*y), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-5*pi).^2 + (y-5*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-5*pi).^2 + (y-15*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-15*pi).^2 + (y-15*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-15*pi).^2 + (y-5*pi).^2)), dom, 'trig');

```




Figure 3: Chebfun




Figure 4: Python

```
u0 = u0 + chebfun2(@(x,y) exp(-(x-10*pi).^2 + (y-10*pi).^2)), dom, 'trig');
S.init = u0;
>> r = 7e-1;
>> S.nonlin = @(u) (-1 + r)*u - u.^3;
>> u = spin2(S, 96, 2e-1, 'plot', 'off');
>> plot(u), view(0,90), axis equal, axis off
>> saveas(gcf, '/Users/edwardmcdugald/Research/
convection_patterns_matlab/figs/sh_tsts_1018/cf3.pdf');
```

### python 3 code

```
x = np.linspace(0,20*np.pi,96)
y = np.linspace(0,20*np.pi,96)
X,Y = np.meshgrid(x,y)
w0 = (1./20.)*(np.cos(X)+np.sin(2*X)+np.sin(Y)+np.cos(2*Y))
w0 = w0 + (np.exp(-((X-5*np.pi)**2 + (Y-5*np.pi)**2)))
w0 = w0 + (np.exp(-((X-5*np.pi)**2 + (Y-15*np.pi)**2)))
w0 = w0 + (np.exp(-((X-15*np.pi)**2 + (Y-15*np.pi)**2)))
w0 = w0 + (np.exp(-((X-15*np.pi)**2 + (Y-5*np.pi)**2)))
w0 = w0 + (np.exp(-((X-10*np.pi)**2 + (Y-10*np.pi)**2)))
dt = 2e-1
R= 7e-1
L=x[len(x)-1]-x[0]
```




Figure 5: Chebfun




Figure 6: Python

```
nSteps = 1000
W3 = integrateSH(w0,R,dt,nSteps,L)
fig3, ax3 = plt.subplots(nrows=1, ncols=1, figsize=(3,3))
ax3.imshow(W3)
plt.savefig("/Users/edwardmcdugald/Research/
convection_patterns/code/figs/sh_num_tsts_1018/mySH3.pdf")
```

### 3 Chebfun v Python 4

chebfun 4 code

```
>> dom = [0 20*pi 0 20*pi];
tspan = [0 200];
>> S = spinop2(dom, tspan);
>> S.lin = @(u) -2*lap(u) - biharm(u);
>> u0 = 1/20*chebfun2(@(x,y) cos(x) + sin(2*x) + sin(y) + cos(2*y), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-5*pi).^2 + (y-5*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-5*pi).^2 + (y-15*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-15*pi).^2 + (y-15*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-15*pi).^2 + (y-5*pi).^2)), dom, 'trig');
u0 = u0 + chebfun2(@(x,y) exp(-((x-10*pi).^2 + (y-10*pi).^2)), dom, 'trig');
```

```

S.init = u0;
>> r = 1e-1;
>> S.nonlin = @(u) (-1 + r)*u - u.^3;
>> u = spin2(S, 100, 2e-1, 'plot', 'off');
plot(u), view(0,90), axis equal, axis off
>> saveas(gcf, '/Users/edwardmcdugald/Research/
convection_patterns_matlab/figs/sh_tsts_1018/cf4.pdf');

```

## python 4 code

```

x = np.linspace(0,20*np.pi,100)
y = np.linspace(0,20*np.pi,100)
X,Y = np.meshgrid(x,y)
w0 = (1./20.)*(np.cos(X)+np.sin(2*X)+np.sin(Y)+np.cos(2*Y))
w0 = w0 + (np.exp(-((X-5*np.pi)**2 + (Y-5*np.pi)**2)))
w0 = w0 + (np.exp(-((X-5*np.pi)**2 + (Y-15*np.pi)**2)))
w0 = w0 + (np.exp(-((X-15*np.pi)**2 + (Y-15*np.pi)**2)))
w0 = w0 + (np.exp(-((X-15*np.pi)**2 + (Y-5*np.pi)**2)))
w0 = w0 + (np.exp(-((X-10*np.pi)**2 + (Y-10*np.pi)**2)))
dt = 2e-1
R= 1e-1
L=x[len(x)-1]-x[0]
nSteps = 1000
W4 = integrateSH(w0,R,dt,nSteps,L)
fig4, ax4 = plt.subplots(nrows=1, ncols=1, figsize=(3,3))
ax4.imshow(W4)
plt.savefig("/Users/edwardmcdugald/Research/convection_patterns/code/figs/sh_num_tsts_10

nSteps = 10000
W4b = integrateSH(w0,R,dt,nSteps,L)
fig4b, ax4b = plt.subplots(nrows=1, ncols=1, figsize=(3,3))
ax4b.imshow(W4b)
plt.savefig("/Users/edwardmcdugald/Research/convection_patterns/code/figs/sh_num_tsts_10

```

**ToDo: Compare Results with different initial value function** **ToDo: Compare results using RK4 instead of Fwd Euler** **ToDo: Add results of ellipse (with sigmoid)**






Figure 7: Chebfun




Figure 8: Python (using 1000 steps)




Figure 9: Chebfun




Figure 10: Python (using 10000 steps)