

Threat Research

New Zero-Day Exploit targeting Internet Explorer Versions 9 through 11 Identified in Targeted Attacks

April 27, 2014 | by [Xiaobo Chen](#), [Mike Scott](#), [Dan Caselden](#)

ZERO-DAY

Summary

FireEye Research Labs identified a new Internet Explorer (IE) zero-day exploit used in targeted attacks. The vulnerability affects IE6 through IE11, but the attack is targeting IE9 through IE11. This zero-day bypasses both ASLR and DEP. Microsoft has assigned CVE-2014-1776 to the vulnerability and released [security advisory](#) to track this issue.

Threat actors are actively using this exploit in an ongoing campaign which we have named "Operation Clandestine Fox." However, for many reasons, we will not provide campaign details. But we believe this is a significant zero day as the vulnerable versions represent about a quarter of the total browser market. We recommend applying a patch once available.

According to [NetMarket Share](#), the market share for the targeted versions of IE in 2013 were:

IE 9	13.9%
IE 10	11.04%
IE 11	1.32%

Collectively, in 2013, the vulnerable versions of IE accounted for 26.25% of the browser market. The vulnerability, however, does appear in IE6 through IE11 though the exploit targets IE9 and higher.

The Details

The exploit leverages a previously unknown use-after-free vulnerability, and uses a well-known [Flash exploitation technique](#) to achieve arbitrary memory access and bypass Windows' ASLR and DEP protections.

Exploitation

• Preparing the heap

The exploit page loads a Flash SWF file to manipulate the heap layout with the common technique [heap feng shui](#). It allocates Flash vector objects to spray memory and cover address `0x18184000`. Next, it allocates a vector object that contains a `flash.Media.Sound()` object, which it later corrupts to pivot control to its ROP chain.

• Arbitrary memory access

The SWF file calls back to Javascript in IE to trigger the IE bug and overwrite the length field of a Flash vector object in the heap spray. The SWF file loops through the heap spray to find the corrupted vector object, and uses it to again modify the length of another vector object. This other corrupted vector object is then used for subsequent memory accesses, which it then uses to bypass ASLR and DEP.

• Runtime ROP generation

With full memory control, the exploit will search for `ZwProtectVirtualMemory`, and a stack pivot (opcode `0x94 0xc3`) from NTDLL. It also searches for `SetThreadContext` in kernel32, which is used to clear the debug registers. This technique, may be an attempt to bypass protections that use hardware breakpoints, such as EMET's EAF mitigation.

With the addresses of the aforementioned APIs and gadget, the SWF file constructs a ROP chain, and prepends it to its RC4 decrypted shellcode. It then replaces the vtable of a sound object with a fake one that points to the newly created ROP payload. When the sound object attempts to call into its vtable, it instead pivots control to the attacker's ROP chain.

• ROP and Shellcode

The ROP payload basically tries to make memory at `0x18184000` executable, and to return to `0x1818411c` to execute the shellcode.

```
0:008> dds eax
```

```
18184100 770b5f58 ntdll!ZwProtectVirtualMemory
```

```
18184104 1818411c
```

```
18184108 ffffffff
```

```
1818410c 181840e8
```

```
18184110 181840ec
```

```
18184114 00000040
```

```
18184118 181840e4
```

Inside the shellcode, it saves the current stack pointer to `0x18181800` to safely return to the caller.

```
mov     dword ptr ds:[18181800h],ebp
```

Then, it restores the `flash.Media.Sound` vtable and repairs the corrupted vector object to avoid application



Email Updates

Information and insight on today's advanced threats from FireEye.

First Name Last Name

Email Address

Company Name

☐ Threat Research Blog

☐ FireEye Stories Blog

☐ Industry Perspectives Blog

Yes, I would like to receive communications from FireEye. Please read more about our [information collection and use](#).

SUBSCRIBE

SHARE



Recent Posts

09 Mar 2020

[Crescendo: Real Time Event Viewer for macOS >](#)

24 Feb 2020

[Ransomware Against the Machine: How Adversaries are Learning to Disrupt Industrial Production by Targeting IT and OT >](#)

20 Feb 2020

[M-Trends 2020: Insights From the Front Lines >](#)

RSS FEED: STAY CONNECTED



crashes.

```
18184123 b820609f06      mov     eax,69f6020h

18184128 90              nop

18184129 90              nop

1818412a c700c0f22169      mov     dword ptr [eax],offset Flash32_11_7_700_26!AdobeCPGetAPI+0x42ac00 (6921f2c0)

18184133 b800401818      mov     eax,18184000h

18184138 90              nop

18184139 90              nop

1818413a c700fe030000      mov     dword ptr [eax],3FEh ds:0023:18184000=3ffffff0
```

The shellcode also recovers the ESP register to make sure the stack range is in the current thread stack base/limit.

```
18184140 8be5      mov     esp,ebp

18184142 83ec2c      sub     esp,2Ch

18184145 90              nop

18184146 eb2c      jmp     18184174
```

The shellcode calls SetThreadContext to clear the debug registers. It is possible that this is an attempt to bypass mitigations that use the debug registers.

```
18184174 57              push    edi

18184175 81ec00500000      sub     esp,5E0h

1818417b c704241000001000      mov     dword ptr [esp],10010h

18184182 8d7c2404      lea     edi,[esp+4]

18184186 b9dc050000      mov     ecx,5DCh

1818418b 33c0      xor     eax,eax

1818418d f3aa      rep stos byte ptr es:[edi]

1818418f 54      push    esp

18184190 6afe      push    0FFFFFFFh

18184192 b8b308b476      mov     eax,offset kernel32!SetThreadContext (76b408b3)

18184197 ffd0      call    eax
```

The shellcode calls *URLDownloadToCacheFileA* to download the next stage of the payload, disguised as an image.

Mitigation

Using EMET may break the exploit in your environment and prevent it from successfully controlling your computer. **EMET versions 4.1 and 5.0 break (and/or detect) the exploit in our tests.**

Enhanced Protected Mode in IE breaks the exploit in our tests. EPM was introduced in IE10.

Additionally, the attack will not work without Adobe Flash. **Disabling the Flash plugin within IE will prevent the exploit from functioning.**

Threat Group History

The APT group responsible for this exploit has been the first group to have access to a select number of browser-based 0-day exploits (e.g. IE, Firefox, and Flash) in the past. They are extremely proficient at lateral movement and are difficult to track, as they typically do not reuse command and control infrastructure. They have a number of backdoors including one known as Pirpi that we previously discussed [here](#). CVE-2010-3962, then a 0-day exploit in Internet Explorer 6, 7, and 8 dropped the Pirpi payload discussed in this previous case.

As this is still an active investigation we are not releasing further indicators about the exploit at this time.

Acknowledgement: We thank Christopher Glyer, Matt Fowler, Josh Homan, Ned Moran, Nart Villeneuve and Yichong Lin for their support, research, and analysis on these findings.

< PREVIOUS POST

NEXT POST >

Company

Why FireEye?
Customer Stories
Careers
Certifications and Compliance
Investor Relations
Supplier Documents

News and Events

[Newsroom](#)
[Press Releases](#)
[Webinars](#)
[Events](#)
[Awards and Honors](#)
[Email Preferences](#)

Technical Support

[Incident?](#)
[Report Security Issue](#)
[Contact Support](#)
[Customer Portal](#)
[Communities](#)
[Documentation Portal](#)

FireEye Blogs

[Threat Research](#)
[FireEye Stories](#)
[Industry Perspectives](#)

Threat Map

[View the Latest Threats](#)

Contact Us

+1 877-347-3393

Stay Connected

