

```
// Disconnected environment
using System;
using System.Collections.Generic;
using System.ComponentModel;
using System.Data;
using System.Drawing;
using System.Linq;
using System.Text;
using System.Threading.Tasks;
using System.Windows.Forms;
using System.Data.SqlClient;
namespace ADO_3rd_program
    public partial class Form1 : Form
        public Form1()
        {
            InitializeComponent();
        SqlConnection conn = new SqlConnection("server= DESKTOP-
1GU2RS7\\SQLEXPRESS;integrated security=true;database=mkpit_sample1");
        DataSet ds = new DataSet();
        SqlDataAdapter da = null;
        SqlCommandBuilder cb = null;
        private void button1_Click(object sender, EventArgs e)
```

```
try
                da = new SqlDataAdapter("select * from student_info", conn);
                cb = new SqlCommandBuilder(da);
                da.Fill(ds, "student");
                dataGridView1.DataSource = ds.Tables["student"];
            }
            catch(Exception ee)
                MessageBox.Show(ee.ToString());
            }
            finally
                conn.Close();
            }
        }
        private void button2_Click(object sender, EventArgs e)
            try
            {
                da.Update(ds.Tables["student"]);
                MessageBox.Show("Records updated");
            catch (Exception ee)
                MessageBox.Show(ee.ToString());
            finally
            {
                conn.Close();
       }
    }
}
```