

# GiftList REST API

## Complete Endpoint Documentation

A comprehensive guide to the GiftList backend API

Built with PHP + MySQL + JWT Authentication

# Overview

- **Authentication:** Bearer Token (JWT)
- **Content-Type:** `application/json`
- **Total Endpoints:** 16

# Endpoint Categories

1. **Health** - GET /health - Server status check
2. **Authentication** - User registration and login
3. **Recipients** - Manage gift recipients
4. **Gifts** - Manage gifts for recipients



# Authentication Endpoints

## POST /auth/register

Description: Register a new user account

Authentication: **✗** Not Required

Request Body:

```
{  
  "name": "John Doe",  
  "email": "john@example.com",  
  "password": "password123"  
}
```

## POST /auth/register (continued)

Response (201 Created):

```
{
  "success": true,
  "data": {
    "id": 1,
    "name": "John Doe",
    "email": "john@example.com"
  }
}
```

cURL Example:

```
curl -X POST http://localhost:8000/auth/register \
  -H "Content-Type: application/json" \
  -d '{"name":"John Doe","email":"john@example.com","password":"password123"}'
```

# POST /auth/login

Description: Login and receive JWT token

Authentication: ✗ Not Required

Request Body:

```
{  
  "email": "john@example.com",  
  "password": "password123"  
}
```

# POST /auth/login (continued)

Response (200 OK):

```
{
  "success": true,
  "data": {
    "token": "eyJ0eXAiOiJKV1QiLCJhbGc...",
    "user": {
      "id": 1,
      "name": "John Doe",
      "email": "john@example.com"
    }
  }
}
```

# POST /auth/login - Example

## PowerShell:

```
Invoke-RestMethod -Uri "http://localhost:8000/auth/login" `
  -Method POST -ContentType "application/json" `
  -Body (@{email="john@example.com";password="pass123"}|ConvertTo-Json)
```



## GET /auth/me

**Description:** Get current authenticated user information

**Authentication:** ☒ Required

**Headers:**

```
Authorization: Bearer YOUR_JWT_TOKEN
```

Response (200 OK):


```
{  
  "success": true,  
  "data": {  
    "id": 1,  
    "name": "John Doe",  
    "email": "john@example.com",  
    "created_at": "2025-11-07 10:30:00"  
  }  
}
```



# Recipients Endpoints

## GET /recipients

**Description:** Get all recipients for the authenticated user

**Authentication:**  Required

Response (200 OK):

```
{
  "success": true,
  "data": [
    {
      "id": 1,
      "user_id": 1,
      "name": "Mom",
      "relationship": "Mother",
      "notes": "Birthday in June",
      "created_at": "2025-11-07 10:35:00"
    }
  ]
}
```

## GET /recipients/:id

**Description:** Get a specific recipient by ID

**Authentication:**  Required

**URL Parameters:**

- `id` (integer) - Recipient ID

Example: GET /recipients/1

Response (200 OK):

```
{
  "success": true,
  "data": {
    "id": 1,
    "user_id": 1,
    "name": "Mom",
    "relationship": "Mother",
    "notes": "Birthday in June",
    "created_at": "2025-11-07 10:35:00"
  }
}
```

# POST /recipients

Description: Create a new recipient

Authentication:  Required

Request Body:

```
{  
  "name": "Dad",  
  "relationship": "Father",  
  "notes": "Loves technology"  
}
```

Required Fields: name

Optional Fields: relationship, notes



## POST /recipients (continued)

Response (201 Created):

```
{
  "success": true,
  "data": {
    "id": 2,
    "user_id": 1,
    "name": "Dad",
    "relationship": "Father",
    "notes": "Loves technology",
    "created_at": "2025-11-07 10:40:00"
  }
}
```

# POST /recipients - Example

## PowerShell:

```
Invoke-RestMethod -Uri "http://localhost:8000/recipients" `
  -Method POST -Headers @{Authorization="Bearer $token"} `
  -ContentType "application/json" `
  -Body (@{name="Dad";relationship="Father"}|ConvertTo-Json)
```

## PUT /recipients/:id

Description: Update an existing recipient

Authentication:  Required

URL Parameters: `id` (integer)

Request Body (all fields optional):

```
{  
  "name": "Mom",  
  "relationship": "Mother",  
  "notes": "Birthday in June - loves gardening"  
}
```

Response (200 OK): Returns updated recipient object

## DELETE /recipients/:id

Description: Delete a recipient and all associated gifts

Authentication:  Required

URL Parameters: `id` (integer)

Example: `DELETE /recipients/1`

Response (200 OK):

```
{
  "success": true,
  "data": {
    "message": "Recipient deleted"
  }
}
```



# Gifts Endpoints

# GET /gifts

**Description:** Get all gifts for the authenticated user

**Authentication:**  Required

**Optional Query Parameters:**

- `recipientId` (integer) - Filter gifts by recipient

**Examples:**

- `GET /gifts` - All gifts
- `GET /gifts?recipientId=1` - Gifts for recipient 1

## GET /gifts (continued)

Response (200 OK):

```
{
  "success": true,
  "data": [
    {
      "id": 1,
      "recipient_id": 1,
      "name": "Garden Tools Set",
      "description": "Premium garden tools",
      "price": 89.99,
      "url": "https://example.com/product",
      "purchased": 0,
      "created_at": "2025-11-07 10:45:00"
    }
  ]
}
```

## GET /gifts/:id

Description: Get a specific gift by ID

Authentication:  Required

URL Parameters: `id` (integer)

Example: `GET /gifts/1`

Response (200 OK): Returns single gift object



## GET /recipients/:recipientId/gifts

**Description:** Get all gifts for a specific recipient

**Authentication:**  Required

**URL Parameters:** `recipientId` (integer)

**Example:** `GET /recipients/1/gifts`

**Response (200 OK):** Returns array of gift objects

# POST /gifts

Description: Create a new gift

Authentication:  Required

Request Body:

```
{  
  "recipient_id": 1,  
  "name": "Wireless Headphones",  
  "description": "Noise cancelling",  
  "price": 199.99,  
  "url": "https://example.com/headphones",  
  "purchased": 0  
}
```

Required Fields: recipient\_id , name

Optional Fields: description , price , url , purchased (0 or 1)

## POST /gifts (continued)

Response (201 Created):

```
{
  "success": true,
  "data": {
    "id": 2,
    "recipient_id": 1,
    "name": "Wireless Headphones",
    "description": "Noise cancelling",
    "price": 199.99,
    "url": "https://example.com/headphones",
    "purchased": 0,
    "created_at": "2025-11-07 10:50:00"
  }
}
```

## PUT /gifts/:id

Description: Update an existing gift

Authentication:  Required

URL Parameters: `id` (integer)

Request Body (all fields optional):

```
{  
  "name": "Wireless Headphones Pro",  
  "description": "Noise cancelling with case",  
  "price": 249.99,  
  "purchased": 1  
}
```

Response (200 OK): Returns updated gift object

# DELETE /gifts/:id

Description: Delete a gift

Authentication:  Required

URL Parameters: `id` (integer)

Example: `DELETE /gifts/1`

Response (200 OK):

```
{
  "success": true,
  "data": {
    "message": "Gift deleted"
  }
}
```