



Policy Enforcement Point Interface Control Document ***EOEPCA.ICD.xxx***

TVUK System Team

Version 1.0, 30/11/2020:

Policy Enforcement Point Interface Control Document

| | |
|--|---|
| 1. Introduction | 2 |
| 1.1. Purpose and Scope | 2 |
| 2. Overview | 3 |
| 3. Policy Enforcement Point Interfaces | 4 |
| 3.1. Endpoints | 4 |
| 3.1.1. PolicyEnforcement | 4 |
| 3.1.1.1. Proxy DELETE | 4 |
| 3.1.1.1.1. Description | 4 |
| 3.1.1.1.2. Parameters | 4 |
| 3.1.1.1.3. Return Type | 4 |
| 3.1.1.1.4. Responses | 5 |
| 3.1.1.1.5. Samples | 5 |
| 3.1.1.2. Proxy GET | 5 |
| 3.1.1.2.1. Description | 5 |
| 3.1.1.2.2. Parameters | 5 |
| 3.1.1.2.3. Return Type | 5 |
| 3.1.1.2.4. Responses | 5 |
| 3.1.1.2.5. Samples | 5 |
| 3.1.1.3. Proxy HEAD | 5 |
| 3.1.1.3.1. Description | 6 |
| 3.1.1.3.2. Parameters | 6 |
| 3.1.1.3.3. Return Type | 6 |
| 3.1.1.3.4. Responses | 6 |
| 3.1.1.3.5. Samples | 6 |
| 3.1.1.4. Proxy POST | 6 |
| 3.1.1.4.1. Description | 6 |
| 3.1.1.4.2. Parameters | 6 |
| 3.1.1.4.3. Return Type | 7 |
| 3.1.1.4.4. Responses | 7 |
| 3.1.1.4.5. Samples | 7 |
| 3.1.1.5. Proxy PUT | 7 |
| 3.1.1.5.1. Description | 7 |
| 3.1.1.5.2. Parameters | 7 |
| 3.1.1.5.3. Return Type | 7 |
| 3.1.1.5.4. Responses | 7 |
| 3.1.1.5.5. Samples | 8 |
| 3.1.1.6. Proxy PATCH | 8 |

| | |
|-----------------------------------|----|
| 3.1.1.6.1. Description | 8 |
| 3.1.1.6.2. Parameters | 8 |
| 3.1.1.6.3. Return Type | 8 |
| 3.1.1.6.4. Responses | 8 |
| 3.1.1.6.5. Samples | 8 |
| 3.1.2. Resources | 8 |
| 3.1.2.1. Resources GET | 8 |
| 3.1.2.1.1. Description | 9 |
| 3.1.2.1.2. Parameters | 9 |
| 3.1.2.1.3. Return Type | 9 |
| 3.1.2.1.4. Content Type | 9 |
| 3.1.2.1.5. Responses | 9 |
| 3.1.2.1.6. Samples | 9 |
| 3.1.2.2. Resources POST | 9 |
| 3.1.2.2.1. Description | 9 |
| 3.1.2.2.2. Parameters | 9 |
| 3.1.2.2.3. Body Parameter | 9 |
| 3.1.2.2.4. Return Type | 10 |
| 3.1.2.2.5. Content Type | 10 |
| 3.1.2.2.6. Responses | 10 |
| 3.1.2.2.7. Samples | 10 |
| 3.1.2.3. Resources DELETE | 10 |
| 3.1.2.3.1. Description | 10 |
| 3.1.2.3.2. Parameters | 10 |
| 3.1.2.3.3. Return Type | 10 |
| 3.1.2.3.4. Responses | 11 |
| 3.1.2.3.5. Samples | 11 |
| 3.1.2.4. Resource GET (ID) | 11 |
| 3.1.2.4.1. Description | 11 |
| 3.1.2.4.2. Parameters | 11 |
| 3.1.2.4.3. Return Type | 11 |
| 3.1.2.4.4. Content Type | 11 |
| 3.1.2.4.5. Responses | 11 |
| 3.1.2.4.6. Samples | 12 |
| 3.1.2.5. Resource HEAD (ID) | 12 |
| 3.1.2.5.1. Description | 12 |
| 3.1.2.5.2. Parameters | 12 |
| 3.1.2.5.3. Return Type | 12 |
| 3.1.2.5.4. Content Type | 12 |
| 3.1.2.5.5. Responses | 12 |
| 3.1.2.5.6. Samples | 12 |

| | |
|------------------------------------|----|
| 3.1.2.6. Resource PUT (ID) | 12 |
| 3.1.2.6.1. Description | 12 |
| 3.1.2.6.2. Parameters | 13 |
| 3.1.2.6.3. Body Parameter | 13 |
| 3.1.2.6.4. Return Type | 13 |
| 3.1.2.6.5. Responses | 13 |
| 3.1.2.6.6. Samples | 13 |
| 3.1.2.7. Resource PATCH (ID) | 13 |
| 3.1.2.7.1. Description | 13 |
| 3.1.2.7.2. Parameters | 13 |
| 3.1.2.7.3. Body Parameter | 14 |
| 3.1.2.7.4. Return Type | 14 |
| 3.1.2.7.5. Responses | 14 |
| 3.1.2.7.6. Samples | 14 |
| 3.1.3. API | 14 |
| 3.1.3.1. Swagger UI | 14 |
| 3.1.3.1.1. Description | 14 |
| 3.1.3.1.2. Parameters | 14 |
| 3.1.3.1.3. Return Type | 15 |
| 3.1.3.1.4. Responses | 15 |
| 3.1.3.1.5. Samples | 15 |
| 3.2. Models | 15 |
| 3.2.1. <i>NewResource</i> | 15 |
| 3.2.2. <i>Resource</i> | 15 |

EO Exploitation Platform Common Architecture
Policy Enforcement Point Interface Control Document
EOEPCA.ICD.xxx

| | |
|---|---|
| COMMENTS and ISSUES If you would like to raise comments or issues on this document, please do so by raising an Issue at the following URL https://github.com/EOEPCA/um-pep-engine/issues . | PDF This document is available in PDF format here . |
| EUROPEAN SPACE AGENCY CONTRACT REPORT The work described in this report was done under ESA contract. Responsibility for the contents resides in the author or organisation that prepared it. | TELESPAZIO VEGA UK Ltd 350 Capability Green, Luton, Bedfordshire, LU1 3LU, United Kingdom. Tel: +44 (0)1582 399000 www.telespazio-vega.com |

AMENDMENT HISTORY

This document shall be amended by releasing a new edition of the document in its entirety. The Amendment Record Sheet below records the history and issue status of this document.

Table 1. Amendment Record Sheet

| ISSUE | DATE | REASON |
|------------|------------|---------------------------|
| 0.1 | dd/mm/yyyy | Initial in-progress draft |

Chapter 1. Introduction

1.1. Purpose and Scope

This document presents the Policy Enforcement Point Interfaces for the Common Architecture. It serves as a complementary document to its corresponding Software Design Document.

Chapter 2. Overview

This Interface Control Document (ICD) is a companion to the System Design Document for the Policy Enforcement Point. The ICD provides a Building Block level specification of the interfaces exposed by the PEP to the rest of EOEPKA components.

Section [\[Interfaces\]](#)

Provides the interface specification of the Building Block.

Chapter 3. Policy Enforcement Point Interfaces

Abstract

*This OpenAPI Document describes the endpoints exposed by Policy Enforcement Point Building Block deployments.

 Using this API will allow to register resources that can be protected using both the Login Service and the Policy Decision Point and access them through the Policy Enforcement Endpoint.

 As an example this documentation uses |"proxy|" as the configured base URL for Policy Enforcement, but this can be manipulated through configuration parameters.*

3.1. Endpoints

3.1.1. PolicyEnforcement

3.1.1.1. Proxy DELETE

DELETE /proxy/{path}

Request to Back-End Service

3.1.1.1.1. Description

This operation propagates all headers

3.1.1.1.2. Parameters

Path Parameters

| Name | Description | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X |

Header Parameters

| Name | Description | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | - |

3.1.1.1.3. Return Type

-

3.1.1.1.4. Responses

Table 2. http response codes

| Code | Message | Datatype |
|------|------------------------------|----------|
| 200 | OK | <<>> |
| 401 | Unauthorized access request. | <<>> |

3.1.1.1.5. Samples

3.1.1.2. Proxy GET

GET /proxy/{path}

Request to Back-End Service

3.1.1.2.1. Description

This operation propagates all headers and query parameters

3.1.1.2.2. Parameters

Path Parameters

| Name | Description | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X |

Header Parameters

| Name | Description | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | - |

3.1.1.2.3. Return Type

-

3.1.1.2.4. Responses

Table 3. http response codes

| Code | Message | Datatype |
|------|------------------------------|----------|
| 200 | OK | <<>> |
| 401 | Unauthorized access request. | <<>> |

3.1.1.2.5. Samples

3.1.1.3. Proxy HEAD

HEAD /proxy/{path}

Request to Back-End Service

3.1.1.3.1. Description

This operation propagates all headers and query parameters

3.1.1.3.2. Parameters

Path Parameters

| Name | Description | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X |

Header Parameters

| Name | Description | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | - |

3.1.1.3.3. Return Type

-

3.1.1.3.4. Responses

Table 4. http response codes

| Code | Message | Datatype |
|------|------------------------------|----------|
| 200 | OK | <<>> |
| 401 | Unauthorized access request. | <<>> |

3.1.1.3.5. Samples

3.1.1.4. Proxy POST

POST /proxy/{path}

Request to Back-End Service

3.1.1.4.1. Description

This operation propagates all headers, query parameters and body

3.1.1.4.2. Parameters

Path Parameters

| Name | Description | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X |

Header Parameters

| Name | Description | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | - |

3.1.1.4.3. Return Type

-

3.1.1.4.4. Responses

Table 5. http response codes

| Code | Message | Datatype |
|------|------------------------------|----------|
| 200 | OK | <<>> |
| 401 | Unauthorized access request. | <<>> |

3.1.1.4.5. Samples

3.1.1.5. Proxy PUT

PUT /proxy/{path}

Request to Back-End Service

3.1.1.5.1. Description

This operation propagates all headers, query parameters and body

3.1.1.5.2. Parameters

Path Parameters

| Name | Description | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X |

Header Parameters

| Name | Description | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | - |

3.1.1.5.3. Return Type

-

3.1.1.5.4. Responses

Table 6. http response codes

| Code | Message | Datatype |
|------|------------------------------|----------|
| 200 | OK | <<>> |
| 401 | Unauthorized access request. | <<>> |

3.1.1.5.5. Samples

3.1.1.6. Proxy PATCH

PATCH /proxy/{path}

Request to Back-End Service

3.1.1.6.1. Description

This operation propagates all headers, query parameters and body

3.1.1.6.2. Parameters

Path Parameters

| Name | Description | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X |

Header Parameters

| Name | Description | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | - |

3.1.1.6.3. Return Type

-

3.1.1.6.4. Responses

Table 7. http response codes

| Code | Message | Datatype |
|------|------------------------------|----------|
| 200 | OK | <<>> |
| 401 | Unauthorized access request. | <<>> |

3.1.1.6.5. Samples

3.1.2. Resources

3.1.2.1. Resources GET

GET /resources

List all owned resources

3.1.2.1.1. Description

This operation lists all resources filtered by ownership ID. Ownership ID is extracted from the OpenID Connect Token

3.1.2.1.2. Parameters

Header Parameters

| Name | Description | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | - |

3.1.2.1.3. Return Type

array[[[resource](#)]]

3.1.2.1.4. Content Type

- application/json

3.1.2.1.5. Responses

Table 8. http response codes

| Code | Message | Datatype |
|------|---------|------------------------------------|
| 200 | OK | List[[resource]] |

3.1.2.1.6. Samples

3.1.2.2. Resources POST

POST /resources

Creates a new Resource reference in the Platform

3.1.2.2.1. Description

This operation generates a new resource reference object that can be protected. Ownership ID is set to the unique ID of the End-User

3.1.2.2.2. Parameters

3.1.2.2.3. Body Parameter

| Name | Description | Required |
|-------------|-----------------------------|----------|
| NewResource | NewResource | X |

Header Parameters

| Name | Description | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | - |

3.1.2.2.4. Return Type

[\[resource\]](#)

3.1.2.2.5. Content Type

- application/json

3.1.2.2.6. Responses

Table 9. http response codes

| Code | Message | Datatype |
|------|--------------|----------------------------|
| 200 | OK | [resource] |
| 401 | UNAUTHORIZED | <<>> |
| 404 | NOT FOUND | <<>> |

3.1.2.2.7. Samples

3.1.2.3. Resources DELETE

DELETE /resources/{resource_id}

Deletes an owned Resource Reference from the Platform

3.1.2.3.1. Description

This operation removes an existing Resource reference owned by the user.

3.1.2.3.2. Parameters

Path Parameters

| Name | Description | Required |
|-------------|--------------------|----------|
| resource_id | Unique Resource ID | X |

Header Parameters

| Name | Description | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | - |

3.1.2.3.3. Return Type

-

3.1.2.3.4. Responses

Table 10. http response codes

| Code | Message | Datatype |
|------|--------------|----------|
| 200 | OK | <<>> |
| 401 | UNAUTHORIZED | <<>> |
| 404 | NOT FOUND | <<>> |

3.1.2.3.5. Samples

3.1.2.4. Resource GET (ID)

GET /resources/{resource_id}

Retrieve a specific owned resource

3.1.2.4.1. Description

This operation retrieves information about an owned resource.

3.1.2.4.2. Parameters

Path Parameters

| Name | Description | Required |
|-------------|--------------------|----------|
| resource_id | Unique Resource ID | X |

Header Parameters

| Name | Description | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | - |

3.1.2.4.3. Return Type

[resource]

3.1.2.4.4. Content Type

- application/json

3.1.2.4.5. Responses

Table 11. http response codes

| Code | Message | Datatype |
|------|-----------|------------|
| 200 | OK | [resource] |
| 404 | NOT FOUND | <<>> |

3.1.2.4.6. Samples

3.1.2.5. Resource HEAD (ID)

HEAD /resources/{resource_id}

Retrieve a specific owned resource

3.1.2.5.1. Description

This operation retrieves information about an owned resource.

3.1.2.5.2. Parameters

Path Parameters

| Name | Description | Required |
|-------------|--------------------|----------|
| resource_id | Unique Resource ID | X |

Header Parameters

| Name | Description | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | - |

3.1.2.5.3. Return Type

[resource]

3.1.2.5.4. Content Type

- application/json

3.1.2.5.5. Responses

Table 12. http response codes

| Code | Message | Datatype |
|------|-----------|------------|
| 200 | OK | [resource] |
| 404 | NOT FOUND | <<>> |

3.1.2.5.6. Samples

3.1.2.6. Resource PUT (ID)

PUT /resources/{resource_id}

Updates an existing Resource reference in the Platform

3.1.2.6.1. Description

This operation updates an existing 'owned' resource reference.

3.1.2.6.2. Parameters

Path Parameters

| Name | Description | Required |
|-------------|--------------------|----------|
| resource_id | Unique Resource ID | X |

3.1.2.6.3. Body Parameter

| Name | Description | Required |
|----------|-----------------|----------|
| Resource | <i>Resource</i> | X |

Header Parameters

| Name | Description | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | - |

3.1.2.6.4. Return Type

-

3.1.2.6.5. Responses

Table 13. http response codes

| Code | Message | Datatype |
|------|--------------|----------|
| 200 | OK | <<>> |
| 401 | UNAUTHORIZED | <<>> |
| 404 | NOT FOUND | <<>> |

3.1.2.6.6. Samples

3.1.2.7. Resource PATCH (ID)

PATCH /resources/{resource_id}

Patches an existing Resource reference in the Platform

Currently, only support for this method is presented, and requires and functions the same as PUT.

3.1.2.7.1. Description

This operation updates an existing 'owned' resource reference.

3.1.2.7.2. Parameters

Path Parameters

| Name | Description | Required |
|-------------|--------------------|----------|
| resource_id | Unique Resource ID | X |

3.1.2.7.3. Body Parameter

| Name | Description | Required |
|----------|-----------------|----------|
| Resource | <i>Resource</i> | X |

Header Parameters

| Name | Description | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | - |

3.1.2.7.4. Return Type

-

3.1.2.7.5. Responses

Table 14. http response codes

| Code | Message | Datatype |
|------|--------------|----------|
| 200 | OK | <<>> |
| 401 | UNAUTHORIZED | <<>> |
| 404 | NOT FOUND | <<>> |

3.1.2.7.6. Samples

3.1.3. API

3.1.3.1. Swagger UI

/swagger-ui

3.1.3.1.1. Description

This operation accesses the API for the Policy Enforcement Point

3.1.3.1.2. Parameters

Path Parameters

| Name | Description | Required |
|------|-------------|----------|
| - | - | - |

Header Parameters

| Name | Description | Required |
|------|-------------|----------|
| - | - | - |

3.1.3.1.3. Return Type

-

3.1.3.1.4. Responses

Table 15. http response codes

| Code | Message | Datatype |
|------|---------|----------|
| 200 | OK | <<>> |

3.1.3.1.5. Samples

3.2. Models

3.2.1. NewResource

| Field Name | Required | Type | Description | Format |
|-----------------|----------|----------------------------------|---|--------|
| name | Y | String | Human readable name for the resource | - |
| description | Y | String | Human readable description of the resource | - |
| icon_uri | Y | String | Protected uri of the resource. | - |
| resource_scopes | Y | List of [string] | List of scopes associated with the resource | - |

3.2.2. Resource

| Field Name | Required | Type | Description | Format |
|-----------------|----------|----------------------------------|---|--------|
| ownership_id | Y | UUID | UUID of the Owner End-User | uuid |
| description | Y | UUID | Human readable description of the resource | uuid |
| name | Y | String | Human readable name for the resource | - |
| icon_uri | Y | String | Protected uri of the resource. | - |
| resource_scopes | Y | List of [string] | List of scopes associated with the resource | - |

<< End of Document >>