



***TELESPAZIO***

***a LEONARDO and THALES company***

Policy Enforcement Point Interface  
Control Document  
***EOEPCA.ICD.xxx***

TVUK System Team

Version 1.0, 30/11/2020:

# Policy Enforcement Point Interface Control Document

|  |   |
|--|---|
| 1. Introduction .....                        | 2 |
| 1.1. Purpose and Scope .....                 | 2 |
| 2. Overview .....                            | 3 |
| 3. Policy Enforcement Point Interfaces ..... | 4 |
| 3.1. Endpoints .....                         | 4 |
| 3.1.1. PolicyEnforcement .....               | 4 |
| 3.1.1.1. Proxy DELETE .....                  | 4 |
| 3.1.1.1.1. Description .....                 | 4 |
| 3.1.1.1.2. Parameters .....                  | 4 |
| 3.1.1.1.3. Return Type .....                 | 4 |
| 3.1.1.1.4. Responses .....                   | 5 |
| 3.1.1.1.5. Samples .....                     | 5 |
| 3.1.1.2. Proxy GET .....                     | 5 |
| 3.1.1.2.1. Description .....                 | 5 |
| 3.1.1.2.2. Parameters .....                  | 5 |
| 3.1.1.2.3. Return Type .....                 | 5 |
| 3.1.1.2.4. Responses .....                   | 5 |
| 3.1.1.2.5. Samples .....                     | 5 |
| 3.1.1.3. Proxy POST .....                    | 5 |
| 3.1.1.3.1. Description .....                 | 6 |
| 3.1.1.3.2. Parameters .....                  | 6 |
| 3.1.1.3.3. Return Type .....                 | 6 |
| 3.1.1.3.4. Responses .....                   | 6 |
| 3.1.1.3.5. Samples .....                     | 6 |
| 3.1.1.4. Proxy PUT .....                     | 6 |
| 3.1.1.4.1. Description .....                 | 6 |
| 3.1.1.4.2. Parameters .....                  | 6 |
| 3.1.1.4.3. Return Type .....                 | 7 |
| 3.1.1.4.4. Responses .....                   | 7 |
| 3.1.1.4.5. Samples .....                     | 7 |
| 3.1.2. Resources .....                       | 7 |
| 3.1.2.1. Resources GET .....                 | 7 |
| 3.1.2.1.1. Description .....                 | 7 |
| 3.1.2.1.2. Parameters .....                  | 7 |
| 3.1.2.1.3. Return Type .....                 | 7 |
| 3.1.2.1.4. Content Type .....                | 7 |
| 3.1.2.1.5. Responses .....                   | 7 |

|                                  |    |
|----------------------------------|----|
| 3.1.2.1.6. Samples .....         | 8  |
| 3.1.2.2. Resources POST .....    | 8  |
| 3.1.2.2.1. Description .....     | 8  |
| 3.1.2.2.2. Parameters .....      | 8  |
| 3.1.2.2.3. Body Parameter .....  | 8  |
| 3.1.2.2.4. Return Type .....     | 8  |
| 3.1.2.2.5. Content Type .....    | 8  |
| 3.1.2.2.6. Responses .....       | 8  |
| 3.1.2.2.7. Samples .....         | 8  |
| 3.1.2.3. Resources DELETE .....  | 9  |
| 3.1.2.3.1. Description .....     | 9  |
| 3.1.2.3.2. Parameters .....      | 9  |
| 3.1.2.3.3. Return Type .....     | 9  |
| 3.1.2.3.4. Responses .....       | 9  |
| 3.1.2.3.5. Samples .....         | 9  |
| 3.1.2.4. Resource GET (ID) ..... | 9  |
| 3.1.2.4.1. Description .....     | 9  |
| 3.1.2.4.2. Parameters .....      | 9  |
| 3.1.2.4.3. Return Type .....     | 10 |
| 3.1.2.4.4. Content Type .....    | 10 |
| 3.1.2.4.5. Responses .....       | 10 |
| 3.1.2.4.6. Samples .....         | 10 |
| 3.1.2.5. Resource PUT (ID) ..... | 10 |
| 3.1.2.5.1. Description .....     | 10 |
| 3.1.2.5.2. Parameters .....      | 10 |
| 3.1.2.5.3. Body Parameter .....  | 10 |
| 3.1.2.5.4. Return Type .....     | 11 |
| 3.1.2.5.5. Responses .....       | 11 |
| 3.1.2.5.6. Samples .....         | 11 |
| 3.1.3. API .....                 | 11 |
| 3.1.3.1. Swagger UI .....        | 11 |
| 3.1.3.1.1. Description .....     | 11 |
| 3.1.3.1.2. Parameters .....      | 11 |
| 3.1.3.1.3. Return Type .....     | 11 |
| 3.1.3.1.4. Responses .....       | 11 |
| 3.1.3.1.5. Samples .....         | 12 |
| 3.2. Models .....                | 12 |
| 3.2.1. <i>NewResource</i> .....  | 12 |
| 3.2.2. <i>Resource</i> .....     | 12 |

EO Exploitation Platform Common Architecture  
*Policy Enforcement Point Interface Control Document*  
EOEPCA.ICD.xxx

|   |   |
|---|---|
| <b>COMMENTS and ISSUES</b><br>If you would like to raise comments or issues on this document, please do so by raising an Issue at the following URL <a href="https://github.com/EOEPCA/um-pep-engine/issues">https://github.com/EOEPCA/um-pep-engine/issues</a> . | <b>PDF</b><br>This document is available in PDF format <a href="#">here</a> .   |
| <b>EUROPEAN SPACE AGENCY CONTRACT REPORT</b><br>The work described in this report was done under ESA contract. Responsibility for the contents resides in the author or organisation that prepared it.  | <b>TELESPAZIO VEGA UK Ltd</b><br>350 Capability Green, Luton, Bedfordshire, LU1 3LU, United Kingdom.<br>Tel: +44 (0)1582 399000<br><a href="http://www.telespazio-vega.com">www.telespazio-vega.com</a> |

## AMENDMENT HISTORY

This document shall be amended by releasing a new edition of the document in its entirety. The Amendment Record Sheet below records the history and issue status of this document.

*Table 1. Amendment Record Sheet*

| ISSUE      | DATE       | REASON                    |
|------------|------------|---------------------------|
| <b>0.1</b> | dd/mm/yyyy | Initial in-progress draft |

# Chapter 1. Introduction

## 1.1. Purpose and Scope

This document presents the Policy Enforcement Point Interfaces for the Common Architecture. It serves as a complementary document to its corresponding Software Design Document.

# Chapter 2. Overview

This Interface Control Document (ICD) is a companion to the System Design Document for the Policy Enforcement Point. The ICD provides a Building Block level specification of the interfaces exposed by the PEP to the rest of EOEPKA components.

## Section [\[Interfaces\]](#)

Provides the interface specification of the Building Block.

# Chapter 3. Policy Enforcement Point Interfaces

## Abstract

*This OpenAPI Document describes the endpoints exposed by Policy Enforcement Point Building Block deployments. <br> <br> Using this API will allow to register resources that can be protected using both the Login Service and the Policy Decision Point and access them through the Policy Enforcement Endpoint. <br> <br> As an example this documentation uses |"proxy|" as the configured base URL for Policy Enforcement, but this can be manipulated through configuration parameters.*

## 3.1. Endpoints

### 3.1.1. PolicyEnforcement

#### 3.1.1.1. Proxy DELETE

DELETE /proxy/{path}

Request to Back-End Service

##### 3.1.1.1.1. Description

This operation propagates all headers

##### 3.1.1.1.2. Parameters

###### Path Parameters

| Name | Description                  | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X        |

###### Header Parameters

| Name          | Description                          | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | -        |

##### 3.1.1.1.3. Return Type

-

#### 3.1.1.1.4. Responses

Table 2. http response codes

| Code | Message                      | Datatype |
|------|------------------------------|----------|
| 200  | OK                           | <<>>     |
| 401  | Unauthorized access request. | <<>>     |

#### 3.1.1.1.5. Samples

#### 3.1.1.2. Proxy GET

GET /proxy/{path}

Request to Back-End Service

##### 3.1.1.2.1. Description

This operation propagates all headers and query parameters

##### 3.1.1.2.2. Parameters

###### Path Parameters

| Name | Description                  | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X        |

###### Header Parameters

| Name          | Description                          | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | -        |

##### 3.1.1.2.3. Return Type

-

##### 3.1.1.2.4. Responses

Table 3. http response codes

| Code | Message                      | Datatype |
|------|------------------------------|----------|
| 200  | OK                           | <<>>     |
| 401  | Unauthorized access request. | <<>>     |

#### 3.1.1.2.5. Samples

#### 3.1.1.3. Proxy POST

POST /proxy/{path}



## Request to Back-End Service

### 3.1.1.3.1. Description

This operation propagates all headers, query parameters and body

### 3.1.1.3.2. Parameters

#### Path Parameters

| Name | Description                  | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X        |

#### Header Parameters

| Name          | Description                          | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | -        |

### 3.1.1.3.3. Return Type

-

### 3.1.1.3.4. Responses

Table 4. http response codes

| Code | Message                      | Datatype |
|------|------------------------------|----------|
| 200  | OK                           | <<>>     |
| 401  | Unauthorized access request. | <<>>     |

### 3.1.1.3.5. Samples

### 3.1.1.4. Proxy PUT

PUT /proxy/{path}

## Request to Back-End Service

### 3.1.1.4.1. Description

This operation propagates all headers, query parameters and body

### 3.1.1.4.2. Parameters

#### Path Parameters

| Name | Description                  | Required |
|------|------------------------------|----------|
| path | Path to the Back-End Service | X        |

## Header Parameters

| Name          | Description                          | Required |
|---------------|--------------------------------------|----------|
| Authorization | RPT Token generated through UMA Flow | -        |

### 3.1.1.4.3. Return Type

-

### 3.1.1.4.4. Responses

Table 5. http response codes

| Code | Message                      | Datatype |
|------|------------------------------|----------|
| 200  | OK                           | <<>>     |
| 401  | Unauthorized access request. | <<>>     |

### 3.1.1.4.5. Samples

## 3.1.2. Resources

### 3.1.2.1. Resources GET

GET /resources

List all owned resources

#### 3.1.2.1.1. Description

This operation lists all resources filtered by ownership ID. Ownership ID is extracted from the OpenID Connect Token

#### 3.1.2.1.2. Parameters

## Header Parameters

| Name          | Description         | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | -        |

### 3.1.2.1.3. Return Type

array[[resource]]

### 3.1.2.1.4. Content Type

- application/json

### 3.1.2.1.5. Responses

Table 6. http response codes

| Code | Message | Datatype                           |
|------|---------|------------------------------------|
| 200  | OK      | List[[ <a href="#">resource</a> ]] |

#### 3.1.2.1.6. Samples

#### 3.1.2.2. Resources POST

POST /resources

Creates a new Resource reference in the Platform

##### 3.1.2.2.1. Description

This operation generates a new resource reference object that can be protected. Ownership ID is set to the unique ID of the End-User

##### 3.1.2.2.2. Parameters

##### 3.1.2.2.3. Body Parameter

| Name        | Description                 | Required |
|-------------|-----------------------------|----------|
| NewResource | <a href="#">NewResource</a> | X        |

##### Header Parameters

| Name          | Description         | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | -        |

##### 3.1.2.2.4. Return Type

[\[resource\]](#)

##### 3.1.2.2.5. Content Type

- application/json

##### 3.1.2.2.6. Responses

Table 7. http response codes

| Code | Message      | Datatype                   |
|------|--------------|----------------------------|
| 200  | OK           | <a href="#">[resource]</a> |
| 401  | UNAUTHORIZED | <<>>                       |
| 404  | NOT FOUND    | <<>>                       |

##### 3.1.2.2.7. Samples

### 3.1.2.3. Resources DELETE

DELETE /resources/{resource\_id}

Deletes an owned Resource Reference from the Platform

#### 3.1.2.3.1. Description

This operation removes an existing Resource reference owned by the user.

#### 3.1.2.3.2. Parameters

##### Path Parameters

| Name        | Description        | Required |
|-------------|--------------------|----------|
| resource_id | Unique Resource ID | X        |

##### Header Parameters

| Name          | Description         | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | -        |

#### 3.1.2.3.3. Return Type

-

#### 3.1.2.3.4. Responses

Table 8. http response codes

| Code | Message      | Datatype |
|------|--------------|----------|
| 200  | OK           | <<>>     |
| 401  | UNAUTHORIZED | <<>>     |
| 404  | NOT FOUND    | <<>>     |

#### 3.1.2.3.5. Samples

### 3.1.2.4. Resource GET (ID)

GET /resources/{resource\_id}

Retrieve a specific owned resource

#### 3.1.2.4.1. Description

This operation retrieves information about an owned resource.

#### 3.1.2.4.2. Parameters

## Path Parameters

| Name        | Description        | Required |
|-------------|--------------------|----------|
| resource_id | Unique Resource ID | X        |

## Header Parameters

| Name          | Description         | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | -        |

### 3.1.2.4.3. Return Type

[resource]

### 3.1.2.4.4. Content Type

- application/json

### 3.1.2.4.5. Responses

Table 9. http response codes

| Code | Message   | Datatype   |
|------|-----------|------------|
| 200  | OK        | [resource] |
| 404  | NOT FOUND | <<>>       |

### 3.1.2.4.6. Samples

### 3.1.2.5. Resource PUT (ID)

PUT /resources/{resource\_id}

Updates an existing Resource reference in the Platform

#### 3.1.2.5.1. Description

This operation updates an existing 'owned' resource reference.

#### 3.1.2.5.2. Parameters

## Path Parameters

| Name        | Description        | Required |
|-------------|--------------------|----------|
| resource_id | Unique Resource ID | X        |

### 3.1.2.5.3. Body Parameter

| Name     | Description | Required |
|----------|-------------|----------|
| Resource | Resource    | X        |

## Header Parameters

| Name          | Description         | Required |
|---------------|---------------------|----------|
| Authorization | JWT or Bearer Token | -        |

### 3.1.2.5.4. Return Type

-

### 3.1.2.5.5. Responses

Table 10. http response codes

| Code | Message      | Datatype |
|------|--------------|----------|
| 200  | OK           | <<>>     |
| 401  | UNAUTHORIZED | <<>>     |
| 404  | NOT FOUND    | <<>>     |

### 3.1.2.5.6. Samples

## 3.1.3. API

### 3.1.3.1. Swagger UI

/swagger-ui

#### 3.1.3.1.1. Description

This operation accesses the API for the Policy Enforcement Point

#### 3.1.3.1.2. Parameters

##### Path Parameters

| Name | Description | Required |
|------|-------------|----------|
| -    | -           | -        |

##### Header Parameters

| Name | Description | Required |
|------|-------------|----------|
| -    | -           | -        |

#### 3.1.3.1.3. Return Type

-

#### 3.1.3.1.4. Responses

Table 11. http response codes

| Code | Message | Datatype |
|------|---------|----------|
| 200  | OK      | <<>>     |

#### 3.1.3.1.5. Samples

## 3.2. Models

### 3.2.1. *NewResource*

| Field Name      | Required | Type                             | Description                                 | Format |
|-----------------|----------|----------------------------------|---|--------|
| name            | Y        | String                           | Human readable name for the resource        | -      |
| description     | Y        | String                           | Human readable description of the resource  | -      |
| icon_uri        | Y        | String                           | Protected uri of the resource.              | -      |
| resource_scopes | Y        | List of <a href="#">[string]</a> | List of scopes associated with the resource | -      |

### 3.2.2. *Resource*

| Field Name      | Required | Type                             | Description                                 | Format |
|-----------------|----------|----------------------------------|---|--------|
| ownership_id    | Y        | UUID                             | UUID of the Owner End-User                  | uuid   |
| description     | Y        | UUID                             | Human readable description of the resource  | uuid   |
| name            | Y        | String                           | Human readable name for the resource        | -      |
| icon_uri        | Y        | String                           | Protected uri of the resource.              | -      |
| resource_scopes | Y        | List of <a href="#">[string]</a> | List of scopes associated with the resource | -      |

<< End of Document >>