

Reusing this material





This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License.

https://creativecommons.org/licenses/by-nc-sa/4.0/

This means you are free to copy and redistribute the material and adapt and build on the material under the following terms: You must give appropriate credit, provide a link to the license and indicate if changes were made. If you adapt or build on the material you must distribute your work under the same license as the original.


Note that this presentation contains images owned by others. Please seek their permission before reusing these images.

Partners









Natural Environment Research Council





Recap on parallelism



- Two main types of parallelism
- Shared memory parallelism
 - Single node
 - Mainly thread based
 - Single program generates set of workers (threads)
- Distributed memory parallelism
 - Can work inside a node but also enables parallelisation across nodes
 - Mainly uses message passing programming approaches (i.e. MPI)
 - Workers are individual processes (program)
 - Collaborate to reduce runtime/host large amounts of data

Parallelism in Python

epcc

- Python has a number of built in options for parallelisation
- threading library
 - Create python threads (workers) from functions
 - Can .start() and .join() them import threading

```
def thread_function(name):
    ...

if __name__ == "__main__":

    threads = list()
    for index in range(3):
        x = threading.Thread(target=thread_function, args=(index,))
        threads.append(x)
        x.start()

for index, thread in enumerate(threads):
        thread.join()
```

- Python global interpreter lock (GIL) restricts parallelism
 - An create many threads, but only one executes at a time, regardless of available hardware

Parallelism in Python

epcc

- multiprocessing library
 - Enables generation of multiple process workers
 - Not restricted by the GIL
- Can create Process, similar to Thread:

```
from multiprocessing import Process

def f(name):
    print('hello', name)

if __name__ == '__main__':
    p = Process(target=f, args=('bob',))
    p.start()
    p.join()
```

Share data between processes using Queues or Pipes
 from multiprocessing import Process, Queue
 def f(q):
 q.put([42, None, 'hello'])
 if __name__ == '__main__':
 q = Queue()
 p = Process(target=f, args=(q,))
 p.start()
 print(q.get()) # prints "[42, None, 'hello']"
 p.join()

```
from multiprocessing import Process, Pipe
def f(conn):
    conn.send([42, None, 'hello'])
    conn.close()
if __name__ == '__main__':
    parent_conn, child_conn = Pipe()
    p = Process(target=f, args=(child_conn,))
    p.start()
    print(parent_conn.recv()) # prints "[42, None, 'hello']"
    p.join()
```

Parallelism in Python



- Multiprocessing in Python is more suited to distributed or concurrent rather than parallel computing
 - Communication mechanisms aren't as high performance
 - Don't map on to high performance interconnects
- Implicit parallelism
 - numpy provide access to parallel blas libraries
 - scipy can interface with other parallel maths libraries
- Native code interfacing
 - Call C/Fortran/C++/etc... code from Python to provide some parallel functionality
- mpi4py
 - Direct message passing interface for Python
 - https://github.com/EPCCed/archer2-python/tree/master/lectures/dev-mpi4py