

Disclaimer

If the user has the same measurement made with different techniques or made on different specimen points the most accurate measurement must be used. Make sure that all these columns have the same length except for Test_Date and Specimen_name. In the downloaded folder a .csv example file is prepared.

CSV data table, Quasi Static with fracture

Column name	Description	Unit	Data type
Test_Date	day of the test	[-]	YYYY-MM-DD
Load	Load measured by the machine	[N]	float
u	Average displacement measured along main axis	[mm]	float
v	Average displacement measured along secondary axis	[mm]	float
exx	Average strain measured along main axis	[-]	float
eyy	Average strain measured along secondary axis	[-]	float
exy	Average shear strain	[-]	float
Crack_length	Crack length measurement	[mm]	float
Specimen_name	Name of the specimen	[-]	string

Table 1: CSV data table_QuasiStatic_fracture

Mandatory field

- Load
- Crack_length
- one between: u, and exx
- Specimen_name

Considerations

Make sure that:

- . is used as decimal separator
- , is used as list separator

For changing it in Excel, the procedure is:

1. Click **File**.
2. Click **Options**.
3. Click **Advanced**.
4. Insert . as **Decimal separator**.

For changing pc settings, follow these steps:

1. Open the computer **Control Panel**.
2. Select **Change date, time, or number formats**.
3. Click on **Additional settings**.
4. Change the **List separator** to comma (',').