

# Project 2 on Machine Learning

## Text classification

### Team Yoor

Sergei Volodin<sup>1</sup>, Baran Nama<sup>1</sup>, and Omar Mehio<sup>1</sup>

<sup>1</sup>EPFL

{sergei.volodin,baran.nama,omar.mehio}@epfl.ch

**Abstract**—A classification dataset consisting of Tweets is being studied. First, the data is thoroughly explored using visual aids. Several basic Natural Language Processing methods are applied. Results are evaluated using cross-validation. Model overview is given and the best model is chosen.

#### I. INTRODUCTION

This paper investigates into improving the quality of sentiment analysis on Tweets dataset [4]. It consists of  $N_1 = N_2 = 1250000$  positive/negative tweets, each of them representing a message in English and numerical alphabet  $\Sigma$  with no longer than 140 characters. This way, each of  $N = N_1 + N_2 = 2500000$  tweets is assigned to one of the classes  $\mathcal{C} = \{:(, :)\}$ . The task is to minimize the classification error. In other words, if  $\mathcal{D} = \{(x_n, y_n)\}_{n=1}^N$  is the dataset with tweets  $x_i \in \Sigma^*$  being messages and  $y_n \in \mathcal{C}$  being class labels, the goal is to train a classifier  $f: \Sigma^* \rightarrow \mathcal{C}$  which minimizes the loss function  $l(y, \hat{y}) = [y \neq \hat{y}]$ .

The task of sentiment analysis of tweets was thoroughly studied [2], [3]. Several techniques were applied, mostly consisting of two steps. First, the words are converted to dense vectors using Glove, word2vec, cbow or skip-gram models. After that, the resulting word vectors are used to construct features for the whole tweet. At the end, the vector is feeded into a classifier, such as SVM or Logistic Regression. Two latter steps might be replaced with a neural network accepting variable-length input such as RNN or CNN. Moreover, the embeddings themselves might be trained using backpropagation while training the classifier.

Claim: it is possible to find a model which fits the data better than the current state-of-the-art using expert knowledge on the Tweets dataset.

- 1) What is the data (preprocessed tweets [4]) +
- 2) What are we trying to do? Get the best classification score, compared to the state-of-the-art [?]
- 3) Overview of data, diagrams of features, feature selection, feature augmentation
- 4) Methods and their choice (glove, word2vec, cnn, rnn, cbow, skip-gram) because of the problem statement: classify variable-length arrays of sparse one-hot vectors with local structure (text)

Next sections describe in details our approaches and compare them to various baselines.

#### II. MODELS AND METHODS

This paragraph describes the data being studied. Tweets are short messages no longer than 140 characters long [1]. The table I represents a few examples from the small dataset. Being considered an informal way of communication, tweets often contain misspelled words and letter repetitions, grammatical and other writing mistakes. Besides plain text with punctuation, tweets also contain hashtags, two types of tags, *user* and *url*, which are tokens for replaced user mentions and URL links, respectively. In addition, tweets sometimes contain emoticons. Despite the fact that objects in the training dataset mostly comply with its classes, some tweets cannot be determined as positive/negative even by a human (appear neutral). Moreover, some of the tweets are clearly mislabeled in the training data. Dataset contains repeating tweets.

- 1) Dataset and loss
- 2) State of the art description
- 3) Baseline: glove.
- 4) Preprocessing: stemming, word variants, hashtag removing, ...
- 5) Word2Vec
- 6) CNN
- 7) RNN

#### III. RESULTS

The following models were considered: *aba*, *caba*, the best one is *aba*. This (does not) correspond to already conducted experiments [99, 98, 97]. Our contribution consists of running *method* with *xxx* modified with *yyy* and this does (not) give an improvement of 0.01231%

#### IV. DISCUSSION

Our experiments lack *zzz*, which can be improved by doing also *ttt*

#### V. SUMMARY

We have shown that it is possible to predict tweets using *aba* better than state-of-the-art.

Class	Id	Message	Comment
:(	171	<user> 5k i could cry i'm so unfit !	User tag
:(	99804	if i feel like this tomorrow i'm going to the er	Contraction, missed comma
:)	524	its the weekend ! ! <user> s coming home andddd <user> s baby shower , excitedddd	Letter repetitions
:)	99615	<user> aren't you just an adorable granny <url>	URL tag
:)	443	<user> :d :d :d :d :d wish jocelyn had a twitter . #kudos for her too .	Hashtag, emoticons
:)	468	retweet if you was born in the 90 ' s ! #90's babies	Grammar mistake
:(	14	<user> i'm white . #aw	Appear neutral to human
:(	99594	<user> <user> <user> they're there tonight ! ! !	Does appear positive negative

Table I  
EXAMPLES OF TWEETS IN THE SMALL DATASET

## REFERENCES

- [1] Twitter
- [2] Go, Alec, Lei Huang, and Richa Bhayani. "Twitter sentiment analysis." Entropy 17 (2009): 252.
- [3] Kouloumpis, Efthymios, Theresa Wilson, and Johanna D. Moore. "Twitter sentiment analysis: The good the bad and the omg!" Icwsm 11.538-541 (2011): 164.
- [4] Competition and data downloads on kaggle.com