Orion PCB node overview



Author: Vincent Nguyen

EPFL Xplore

Sheet: /
File: orion_pcb.kicad_sch

Title: Orion PCB Node Overview

Size: A4	Date:	**Rev: 3**
KiCad E.D.A. kicad 7.0.1		Id: 1/11

MCU (STM32H750VBT6)

GPIO, UART, SPI, TIMERS, I2C, ADC



Debug



Status LEDs (user-controlled)



Buses

I2C

UART

SPI

GPIO



QUADSPI



5V power source status



Power inputs, reset, boot



Reset and boot

Author: Vincent Nguyen

EPFL Xplore

Back to overview

Sheet: /MCU/		
File: MCU.kicad_sch		
Title: MCU		
Size: A3	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.1		Id: 2/11

USB to UART bridge



Author: Vincent Nguyen

EPFL Xplore

Back to overview

Sheet: /USB to UART Bridge/
File: USB_UART.kicad_sch

Title: USB to UART Bridge

Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.1		Id: 3/11

Power path



Switching converter connector



Author: Vincent Nguyen

EPFL Xplore

Back to overview

Sheet: /Power connectors/
File: POWER_CONNECTORS.kicad_sch

Title: External Connectors and Power Path

Size: A5	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.1		Id: 4/11

RS232 Transceivers

UART4, USART8



UART3, UART5



Maximum speed is 250 kb/s if using RS232 transceiver

Jumpers

UART4, USART8



USART3, UART5



To use TTL voltage levels, short ALL of the jumpers
for both nodes, for the corresponding UART buses.

Activity LEDs

UART4, USART8



UART3, UART5

Activity LEDs don't need to be very bright.
We choose If = 1.7 mA
R = (3.3 V − 2 V)/(2 mA) = 765 Ohm
Closest standard resistor −> 768 Ohm

Author: Vincent Nguyen

EPFL Xplore

Back to overview

Sheet: /Node to node connectors/
File: NODE_CONNECTORS.kicad_sch

Title: RS232 UART Node to Node Connectors

Size: A3	Date:	Rev:
KiCad E.D.A. kicad 7.0.1		Id: 5/11

Quad-SPI external flash memory



Author: Vincent Nguyen

EPFL Xplore

Back to overview

Sheet: /Flash memory/
File: FLASH.kicad_sch

Title: External Flash Memory

Size: A5	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.1		Id: 6/11

Test points, power flags



Mounting holes

H701 MountingHole
H702 MountingHole
H703 MountingHole
H704 MountingHole
H705 MountingHole
H706 MountingHole
H707 MountingHole
H708 MountingHole

Logos

Xplore
EPFL
maxon
APCO TECHNOLOGIES
ELCA

Author: Vincent Nguyen

EPFL Xplore

Back to overview

Sheet: /Mechanical elements, testpoints, logos/
File: MECHANICAL_TP_LOGO.kicad_sch

Title: Mechanical Elements and Test Points

Size: A5	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.1		Id: 7/11

Node to Hat connectors







Author: Vincent Nguyen

Back to overview

EPFL Xplore

Sheet: /Node to hats connections/
File: NODE_TO_HATS.kicad_sch

Title: Hat Connectors and Delocalized Connectors

Size: A5	Date:	Rev:
KiCad E.D.A. kicad 7.0.1		Id: 8/11

Hat connector



Author: Vincent Nguyen

EPFL Xplore

Back to overview

Sheet: /Node to hats connections/Hat connector circuit1/
File: HAT_CONNECTOR.kicad_sch

Title: Hat Connector

Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.1		Id: 9/11

Hat connector



Author: Vincent Nguyen

EPFL Xplore

Back to overview

Sheet: /Node to hats connections/Hat connector circuit2/
File: HAT_CONNECTOR.kicad_sch

Title: Hat Connector

Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.1		Id: 10/11

Hat connector



Author: Vincent Nguyen

EPFL Xplore

Back to overview

Sheet: /Node to hats connections/Hat connector circuit3/
File: HAT_CONNECTOR.kicad_sch

Title: Hat Connector

Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.1		Id: 11/11