

EPS - Datasheet

Series EPS/PV

This AC/AC converter series EPS/PV from EPS Power Supply is a cost-effective solution to meet the requirements of frequency conversion, voltage regulation and stabilization, especially for high power applications.

Output powers from 10000VA at 33A to 150000VA at 1250A are available. The voltage setting is infinitely variable up to max. 300V 1-phase and optionally with a separate AC output of 400V or 600V. The frequency can also be set from 45-120Hz, or optionally separately up to 500Hz or 840Hz, via the TFT touch panel.

The frequency converters enable a high-dimensioned output that can supply all load types (resistive, inductive and capacitive) with a perfect sinusoidal output waveform. The converters are used wherever electrical devices are operated with different sinusoidal voltages and frequencies that deviate from the standard. This range of voltage and frequency converters is a powerful and cost-effective alternative to AC sources for laboratory use. To protect the device under test, a soft start as well as OVP, UVP, OCP and OTP are integrated as standard.

For automated tests, there is an Ethernet, RS485 and RS232 interface as standard and an optional analog interface. Curves with ramp or step functions can be programmed here.

Optionally, the devices can be overloaded by 200% for 2 seconds.

Energy Efficiency: Latest new technology, High efficiency

Scope of delivery:
Converter
Operation Manual

EPS/PV100TS-FB AC/AC Frequency Converter



EPS/PV 100

General data

Technology	Switching
Mains	380VAC 3ph + N/PE +/-15% (optional 480V)
Input frequency	47-63Hz
Power factor	>=85%
Display	TFT Touch panel 7"
Voltage resolution	+/- 0,1V
Voltage accuracy	0,5% fs 4d
Voltage Stability Mains	~1%
Current Accuracy	0,5% fs+4d
Power Accuracy	1% fs +6d
Overheat protection	Standard
Protection class	IP20
Cooling	Fan
Operation temperature	0°C - 45°C
Design	Cabinet
Standards	2014-35/80-EU, EN61000-6-2/4, EN61558-1
Memory	6 Profiles

Interfaces

RS232 Interface	Standard (SCPI)
RS485 Interface	Standard (ModBus)

Technical data

Series EPS/PV**Technical data**

Output Voltage	150V/300V AC (L-N)
Output Voltage 2	120V/240V AC (L-N)
Output Current 2	800A/400A(1000/500A)
Output Power	100000 VA
Input Voltage	24 VDC (21-32V)
Crest factor	≥ 3
Distortion	$\geq 3\%$
Output Frequency	45-120Hz
Frequency Accuracy	$\pm 0,02\%$ fs
Efficiency	$> 85\%$
Dimensions in mm (WxHxD)	1178 x 1900 x 1200
Weight	980
Order code	400327

Options

Option 1	Overload (200%, 2s, 150% 5s, 125% 15s) EPS/V-OL
Option 2	Frequency 100Hz/120Hz/200Hz/240Hz/400Hz EPS/BV-xH

Subject to modification without notice, errors and omissions excepted

EPS Stromversorgung GmbH
Electronic Power Supplies
Alter Postweg 101, 86159 Augsburg/Germany
Tel.: +49 (0) 821 570451-0
E-mail: sales@eps-germany.de
www.eps-germany.de