

Model: FTP 3K-U/M3P-3U7/19XA-U9278**COSD: XXXX****Summary description: 1.5kVA Industrial Quality Frequency Converter
Universal AC to 3-phase 115Vac (L-N) 400Hz****Customer Name: EPS /Germany****Customer Part Number: Same as above****Product description:**

This rugged, AC/AC frequency converter system uses field proven, microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage. The frequency converter is built with internal power modules. Three CAP 1200 modules convert the input voltage to an internal DC voltage, which feeds the three MSI 1500 AC output modules. The built-in fans provide sufficient airflow for operation without de-rating to the specified temperature. The high frequency conversion enables a compact construction, low weight and high efficiency. The unit has full electronic protection. The input and output are filtered for low noise. The use of components with established reliability results in high MTBF. The unit is manufactured at our plant under strict quality control.

Special Features: Conformal coating, 19" rackmount, +70C, Alarm, Ruggedizing (requested)

SPECIFICATIONS**Input Voltage**

95-264Vac universal, 47-63 Hz

Input current: 38Arms max.

Power Factor meets EN61000-3-2, -12

Input Protection

Inrush current limiting

Varistor

Internal safety fuse links

Lower voltage than the specified minimum will not damage the unit

Isolation

2250Vdc Input to chassis

Output neutrals are connected to chassis internally

Standards

Designed to meet EN 62368-1

EMI

EN 55032 Class A with margins

Output Voltage

3-phase 115Vac (L-N) / 400Hz

8.7Ams continuous per phase

All output neutrals are internally connected to chassis

Output Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Line/Load Regulation

± 6% from no load to full load

Load Crest Factor

2 at 90% load

Output Noise

High frequency ripple is better than 500mVrms (20MHz BW)

Output Overload Protection

Thermal shutdown with automatic recovery in case of continuous overload or insufficient airflow.

Output Overvoltage Protection

By internal supply voltage limiting at 140Vac on output

Operating Temperature Range

0°C to +70°C

Temperature Drift

0.05% per °C over operating temperature range

Efficiency

80% at full load

Cooling

By built-in high quality fans

Environmental Protection

Basic ruggedizing

Conformal coating

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

Indicators

None

Control Input

None

Alarm Output

Output Fail Alarm

Form C contacts

Package/Dimensions (WxHxL)

3U7: 432 x 132 x 432mm

(19" x 5.2" x 17")

19" rackmount

Weight

13kg (28.5 lbs)

Connections

Input: Terminal block Phoenix 125A

Output: Terminal block Phoenix FRONT

Alarm: PHOENIX 3-pole 2.5-V/SA 10

RoHS Compliance

Compliant

Warranty

Two years subject to application within good engineering practice
Contamination related failures and shipping cost excluded

Originated by TS/kv	Date August 20, 2026
Updated by TS/ma	Drawing No./ Rev. SCD U9278A1
Approved by TS	ABSOPULSE ELECTRONICS LTD.

This document is the property of Absopulse Electronics Ltd. Its contents are proprietary and may neither be copied, reproduced, nor its contents disclosed to others without prior written agreement from Absopulse Electronics Ltd.