## Our Topic

AMIT DHOMNE

#### PDA (pushdown automaton)


AMIT DHOMNE

# Pushdown Automaton (PDA)


A Pushdown Automaton is a nondeterministic finite state automaton (NFA) that permits ε-transitions and a stack.

#### Pushdown Automaton -- PDA


#### Input String





## **Initial Stack Symbol**





#### The States


















$\boldsymbol{\mathcal{C}}$
h
e
\$














$\boldsymbol{\mathcal{C}}$
b
h
e
\$

$$\begin{array}{cccc}
 & a, & b \to \lambda \\
\hline
 & q_1
\end{array}$$













h
e
\$










No Change

b
h
e
\$


#### Non-Determinism




These are allowed transitions in a Non-deterministic PDA (NPDA)


#### NPDA: Non-Deterministic PDA

#### Example:




#### Execution Example: Time 0







#### **Input**




\$


#### **Input**






Time 3










a


 $\boldsymbol{a}$ 


 $\boldsymbol{a}$ 

\$




#### **Input**







$$a, \lambda \to a \qquad b, a \to \lambda$$


$$q_0 \qquad \lambda, \lambda \to \lambda \qquad q_1 \qquad b, a \to \lambda \qquad \lambda, \$ \to \$$$







#### **Input**








#### **Input**



\$



### The Language of PDA

A string is accepted if there is a computation such that:

· All the input is consumed

The last state is a final state

At the end of the computation, we do not care about the stack contents

# **ANY**QUESTION

???????



## THE

# **END**