

**Data Fetching**

Get Certified & Job Ready
Sponsored · aifortechies.in

**Visit site**

SSR, SSG & ISR in Next.js | Sigma Web Development Course - Tutorial #133


30K views 9mo ago Sigma Web Development Course - Web ...more



CodeWithHarry 8.41M

Join


1.2K

**Share****Remix****Download**

Comments 242



Vote for ultimate java and C++ course with DSA



Next: Environment Variables in Next.js | Sigma...



Today's Special • 6/8



Ghar pohochne ki tension
side karo

SSR



Server-Side Rendering

SSG



Static Site Generation

ISR



Incremental Static Regeneration



Get Certified & Job Ready
Sponsored · aifortechies.in



Visit site

SSR, SSG & ISR in Next.js | Sigma Web Development Course - Tutorial #133

30K views 9mo ago Sigma Web Development Course - Web ...more



CodeWithHarry 8.41M

Join




1.2K



Share



Remix




Download

Comments 242



A Vote for ultimate java and C++ course with DSA



Next: Environment Variables in Next.js | Sigma...



Today's Special • 6/8



Ghar pohochne ki tension
side karo

EXPLORER

SSR-SSG-ISR

- .next
- app
 - fonts
 - ★ favicon.ico
 - # globals.css
 - JS layout.js
 - JS page.js
- node_modules
- .eslintrc.json
- .gitignore
- jsconfig.json
- JS next.config.mjs
- package-lock.json
- package.json
- JS postcss.config.mjs
- README.md
- JS tailwind.config.js

OUTLINE

TIMELINE

TASK EXPLORER

JS page.js

README.md

```
23 ## SSR - Server Side Rendering
24 This is default behaviour
25
26 ## SSG - Static Site Generation
27 Any content which does not have network calls is a static page by default
28
29 ## ISG or ISR
30 fetch in next.js caches the response
31 However, there are exceptions, fetch requests are not cached when:
32
33 Used inside a Server Action.
34 Used inside a Route Handler that uses the POST method.
35
36
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

Import trace for requested module:

```
./app/page.js
  o Compiling /_error ...
  ✓ Compiled /_error in 1032ms (753 modules)
GET / 200 in 80ms
```



EXPLORER

SSR-SSG-ISR

- .next
- app
 - fonts
 - ★ favicon.ico
 - # globals.css
 - JS layout.js
 - JS page.js
- node_modules
- .eslintrc.json
- .gitignore
- jsconfig.json
- next.config.mjs
- package-lock.json
- package.json
- postcss.config.mjs
- README.md
- tailwind.config.js

OUTLINE

TIMELINE

TASK EXPLORER

JS page.js

README.md

```

30 fetch in next.js caches the response
31 To opt out use:
32 ...
33 export const dynamic = 'force-dynamic';
34 ...
35 However, there are exceptions, fetch requests are
   not cached when:
36
37 - Used inside a Server Action.
38 - Used inside a Route Handler that uses the POST
   method.
39
40

```

Preview README.md

fetch in next.js caches the response To opt out use:

```
export const dynamic = 'force-dynamic';
```

However, there are exceptions, fetch requests are not cached when:

- Used inside a Server Action.
- Used inside a Route Handler that uses the POST method.

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

powershell

```

L o /_not-found 873 B 88 kB
+ First Load JS shared by all 87.1 kB
  {
    chunks/117-9d7f1cd31c438fde.js 31.6 kB
    chunks/fd9d1056-aa94ea5c2eabf904.js 53.6 kB
    other shared chunks (total) 1.86 kB
  }

o (Static) prerendered as static content
f (Dynamic) server-rendered on demand

PS C:\Users\iitia\Downloads\Sigma Web Development Course\Sigma-Web-Dev-Course\Video 133\ssr-

```



Subscribe

Environment



Get Certified & Job Ready
Sponsored · aifortechies.in



Visit site


Environment Variables in Next.js | Sigma Web Development Course - Tutorial #134

22K views 9mo ago Sigma Web Development Course - Web ...more



CodeWithHarry 8.43M

Join



909



Share



Remix



Download

Comments 166



Add a comment...



Next: Styled JSX and other ways to Style in Nex...



Today's Special · 5/6



- EXPLORER
- ENVIRONMENT-VARIABLES
- > .next
 - > app
 - > node_modules
 - ⚙ .env
 - 🔗 .eslintrc.json
 - 🔗 .gitignore
 - {} jsconfig.json
 - JS next.config.mjs
 - {} package-lock.json
 - {} package.json
 - JS postcss.config.mjs
 - 📖 README.md
 - JS tailwind.config.js

⚙ .env


```
1 ID=harry
2 SECRET=harry123456
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
✓ Compiled in 136ms (545 modules)
  Reload env: .env
✓ Compiled in 88ms (545 modules)
  Reload env: .env
✓ Compiled in 110ms (545 modules)
  Reload env: .env
✓ Compiled in 101ms (545 modules)
```




Subscribe



```
.env JS page.js X
app > JS page.js > Home
1 import Image from "next/image";
2
3 export default function Home() {
4   console.log("The id is: ", process.env.ID);
5   console.log("The id is: ", process.env.SECRET);
6   return (
7     <div>
8       Hey this is home
9     </div>
10  );
11 }
12
```

```
Import trace for requested module:
./app/page.js
GET / 500 in 18ms
✓ Compiled /_not-found in 228ms (742 modules)
The id is: harry
⚠ Fast Refresh had to perform a full reload. Read more: https://nextjs.org/docs/messages/fast-refresh-reload
GET / 200 in 183ms
✓ Compiled /favicon.ico in 126ms (346 modules)
```






```
.env JS page.js X
app > JS page.js > ...
1 import Image from "next/image";
2
3 export default function Home() {
4   console.log("The id is: ", process.env.ID)
5   console.log("The secret is: ", process.env.SECRET)
6   return (
7     <div>
8       Hey this is home. The id is {process.env.ID} and secret is {process.env.SECRET}
9     </div>
10  );
11 }
12
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
node + - [ ] [ ] ... ^ X
o Compiling /_not-found ...
✓ Compiled /_not-found in 183ms (773 modules)
The id is: harry
The secret is: harry123456
⚠ Fast Refresh had to perform a full reload. Read more: https://nextjs.org/docs/messages/fast-refresh-reload
GET / 200 in 189ms
GET /favicon.ico 200 in 15ms
[ ]
```





```
.env JS page.js X
app > JS page.js > ...
1 "use client"
2 import Image from "next/image";
3
4 export default function Home() {
5   // console.log("The id is: ", process.env.ID)
6   // console.log("The secret is: ", process.env.SECRET)
7   return (
8     <div>
9       Hey this is home. The id is {process.env.ID} and secret is {process.env.SECRET}
10    </div>
11  );
12 }
13
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
node
GET / 200 in 189ms
GET /favicon.ico 200 in 15ms
✓ Compiled in 260ms (751 modules)
The id is: harry
The secret is: harry123456
✓ Compiled in 380ms (750 modules)
✓ Compiled in 141ms (750 modules)
```



- EXPLORER
- ENVIRONMENT-VARIABLES
- > .next
 - ▼ app
 - > fonts
 - ★ favicon.ico
 - # globals.css
 - JS layout.js
 - JS page.js
 - > node_modules
 - gear .env
 - eslintrc.json
 - .gitignore
 - jsconfig.json
 - JS next.config.mjs
 - package-lock.json
 - package.json
 - JS postcss.config.mjs
 - info README.md
 - JS tailwind.config.js

gear .env

```
1 NEXT_PUBLIC_ID=harry
2 SECRET=harry123456
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

✓ Compiled in 2.2s (768 modules)
✓ Compiled in 166ms (750 modules)
✓ Compiled in 260ms (751 modules)
GET / 200 in 81ms
✓ Compiled /favicon.ico in 173ms (344 modules)
GET /favicon.ico 200 in 243ms
✓ Compiled in 150ms (781 modules)



EXPLORER

ENVIRONMENT-VARIABLES

- > .next
- > app
 - > fonts
 - ★ favicon.ico
 - # globals.css
 - JS layout.js
 - JS page.js
- > node_modules
- gear .env
- eslintrc.json
- .gitignore
- jsconfig.json
- JS next.config.mjs
- package-lock.json
- package.json
- JS postcss.config.mjs
- info README.md
- JS tailwind.config.js

```
.env JS page.js X
app > JS page.js > Home
1  "use client"
2  import Image from "next/image";
3
4  export default function Home() {
5    // console.log("The id is: ", process.env.ID)
6    // console.log("The secret is: ", process.env.SECRET)
7    return (
8      <div>
9        Hey this is home. The id is {process.env.NEXT_PUBLIC_ID} and secret is
10       {process.env.SECRET}
11     </div>
12   );
13 }
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

node + - [] [] ... ^ X

```
✓ Compiled in 2.2s (768 modules)
✓ Compiled in 166ms (750 modules)
✓ Compiled in 260ms (751 modules)
GET / 200 in 81ms
✓ Compiled /favicon.ico in 173ms (344 modules)
GET /favicon.ico 200 in 243ms
✓ Compiled in 150ms (781 modules)
```



- EXPLORER
- ENVIRONMENT-VARIABLES
- > .next
 - ▼ app
 - > fonts
 - ★ favicon.ico
 - # globals.css
 - JS layout.js
 - JS page.js
 - > node_modules
 - ⚙ .env
 - \$.env.local
 - ⚙ .eslintrc.json
 - 📁 .gitignore
 - { } jsconfig.json
 - JS next.config.mjs
 - { } package-lock.json
 - { } package.json
 - JS postcss.config.mjs
 - 📖 README.md
 - JS tailwind.config.js

.env

\$.env.local

```
1 NEXT_PUBLIC_ID=rohan
2 SECRET=rohan3456
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
node
```

```
GET /favicon.ico 200 in 53ms
GET /favicon.ico 200 in 5ms
✓ Compiled in 318ms (559 modules)
GET / 200 in 80ms
GET /favicon.ico 200 in 15ms
GET / 200 in 84ms
GET /favicon.ico 200 in 6ms
```



- Using Pages Router
Features available in /pages
- Using Stable Version
v14.2.15

- Getting Started
 - Installation
 - Project Structure
- Building Your Application
 - Routing
 - Rendering
 - Data Fetching
 - Styling
 - Optimizing
 - Configuring

- TypeScript
- ESLint
- Environment Variables
- Absolute Imports and Module Path Aliases
- src Directory
- MDX
- AMP
- Babel

Building Your Application > Configuring > Environment Variables

Environment Variables

Examples

Next.js comes with built-in support for environment variables, which allows you to do the following:

- Use `.env.local` to load environment variables
- Bundle environment variables for the browser by prefixing with `NEXT_PUBLIC_`

Loading Environment Variables

Next.js has built-in support for loading environment variables from `.env.local` into `process.env`.

```
.env.local

1 DB_HOST=localhost
2 DB_USER=myuser
3 DB_PASS=mypassword
```

This loads `process.env.DB_HOST`, `process.env.DB_USER`, and `process.env.DB_PASS` into the Node.js environment automatically allowing you to use them in [Next.js data](#)

On this page

- Loading Environment Variables
 - Referencing Other Variables
- Bundling Environment Variables for the Browser
 - Runtime Environment Variables
- Default Environment Variables
- Environment Variables on Vercel
- Test Environment Variables
- Environment Variable Load Order
- Good to know
- Version History

Managed Next.js (Vercel) →



Subscribe



@next/env package.

Using Pages Router
Features available in /pages

Using Stable Version
v14.2.15

Getting Started

Installation

Project Structure

Building Your Application

Routing

Rendering

Data Fetching

Styling

Optimizing

Configuring

TypeScript

ESLint

Environment Variables

Absolute Imports and Module
Path Aliases

src Directory

MDX

AMP

Babel

```
1 // The below can be used in a Jest global setup file or similar for your test
2 import { loadEnvConfig } from '@next/env'
3
4 export default async () => {
5   const projectDir = process.cwd()
6   loadEnvConfig(projectDir)
7 }
```

Environment Variable Load Order

Environment variables are looked up in the following places, in order, stopping once the variable is found.

1. process.env
2. .env.\${NODE_ENV}.local
3. .env.local (Not checked when NODE_ENV is test.)
4. .env.\${NODE_ENV}
5. .env

For example, if NODE_ENV is development and you define a variable in both .env.development.local and .env, the value in .env.development.local will be used.

Good to know: The allowed values for NODE_ENV are production, development and test.

On this page

Loading Environment Variables

Referencing Other Variables

Bundling Environment Variables
for the Browser

Runtime Environment
Variables

Default Environment Variables

Environment Variables on Vercel

Test Environment Variables

Environment Variable Load
Order

Good to know

Version History

Managed Next.js (Vercel)


Scroll to top

Next.js CONF 24

Join us virtual or live on
October 24

Get Tickets






Styled JSX and other ways to Style in Next.js | Sigma Web Development Course - Tutorial...

28K views 9mo ago Sigma Web Development Course - We ...more



CodeWithHarry 8.43M

Join



952



Share



Remix



Download

Comments 211



finally harry remember this course is pending

Invest Right, Invest Now

₹0

Commission on
Mutual Funds

₹0

Account Opening
And Maintenance
Charges



Top Rated
Mutual Funds




Ready-made
Mutual Fund Baskets



SIPs starting
at ₹100



Upstox: Explore upcoming IPO




End of playlist

Today's Special • 5/5



Install




```
JS page.js # globals.css 3 JS layout.js X
app > JS layout.js > RootLayout
1 import localFont from "next/font/local";
2 import "./globals.css";
3
4 const geistSans = localFont({
5   src: "./fonts/GeistVF.woff",
6   variable: "--font-geist-sans",
7   weight: "100 900",
8 });
9 const geistMono = localFont({
10  src: "./fonts/GeistMonoVF.woff",
11  variable: "--font-geist-mono",
12  weight: "100 900",
13 });
14
15 export const metadata = {
16   title: "Create Next App",
17   description: "Generated by create next app".
```

PROBLEMS 3 OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
▲ Next.js 14.2.15
- Local:      http://localhost:3000

✓ Starting...
✓ Ready in 1644ms
o Compiling / ...
✓ Compiled / in 2.9s (546 modules)
GET / 200 in 3244ms
✓ Compiled in 340ms (254 modules)
o Compiling /favicon.ico ...
```





```
JS page.js  X  # Home.module.css


app > JS page.js > Home
1  import Image from "next/image";
2  import styles from "../styles/home.module.css"
3
4  export default function Home() {
5    return (
6      <div className={styles.red}>
7        Hey
8      </div>
9    );
10 }
11
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
▲ Next.js 14.2.15
- Local:      http://localhost:3000

✓ Starting...
✓ Ready in 1644ms
o Compiling / ...
✓ Compiled / in 2.9s (546 modules)
GET / 200 in 3244ms
✓ Compiled in 340ms (254 modules)
o Compiling /favicon.ico ...
```





```
JS page.js # Home.module.css X
styles > # Home.module.css > .red
1 body{
2   background-color: green;
3 }
4
5 .red{
6   color: red;
7 }
```




PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
▲ Next.js 14.2.15
- Local: http://localhost:3000

✓ Starting...
✓ Ready in 1644ms
o Compiling / ...
✓ Compiled / in 2.9s (546 modules)
GET / 200 in 3244ms
✓ Compiled in 340ms (254 modules)
o Compiling /favicon.ico ...
```

Ln 7, Col 2 (21 selected) Spaces: 4 UTF-8 CRLF CSS



```
JS page.js app JS page.js ...\about X # Home.module.css
app > about > JS page.js > [About]
1 import React from 'react'
2
3 const About = () => {
4   return (
5     <div className='container'>
6
7       <h1>This is about me</h1>
8       <p>Hey I am a good boy</p>
9
10      <style ></style>
11    </div>
12  )
13 }
14
15 export default About
```


PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

▲ Next.js 14.2.15
- Local: http://localhost:3000

✓ Starting...
✓ Ready in 1644ms
o Compiling / ...
✓ Compiled / in 2.9s (546 modules)
GET / 200 in 3244ms
✓ Compiled in 340ms (254 modules)
o Compiling /favicon.ico ...

← Space





```
JS page.js app JS page.js ...\about X # Home.module.css
app > about > JS page.js > [About]
1 import React from 'react'
2
3 const About = () => {
4   return (
5     <div className='container'>
6
7       <h1>This is about me</h1>
8       <p>Hey I am a good boy</p>
9
10      <style jsx>{`
11        .container{
12          background-color: red;
13          color: black;
14        }
15      `}
16    </style>
17  </div>
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
▲ Next.js 14.2.15
- Local:      http://localhost:3000

✓ Starting...
✓ Ready in 1644ms
o Compiling / ...
✓ Compiled / in 2.9s (546 modules)
GET / 200 in 3244ms
✓ Compiled in 340ms (254 modules)
o Compiling /favicon.ico ...
```



EXPLORER

STYLES-IN-NEXTJS

- .next
- app
 - about
 - JS page.js
 - fonts
 - ★ favicon.ico
 - # globals.css
 - JS layout.js
 - JS page.js
- node_modules
- styles
 - # Home.module.css
- .eslintrc.json
- .gitignore
- jsconfig.json
- JS next.config.mjs

JS page.js app JS page.js ...\about X # Home.module.css

```
1 "use client"
2 import React from 'react'
3
4 const About = () => {
5   return (
6     <div className='container'>
7
8       <h1>This is about me</h1>
9       <p>Hey I am a good boy</p>
10
11       <style jsx>{`
12         .container{
13           background-color: red;
14           color: black;
15         }
16       `}
17     </style>
18   )
19 }
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

▲ Next.js 14.2.15
- Local: http://localhost:3000

✓ Starting...
✓ Ready in 1644ms
o Compiling / ...
✓ Compiled / in 2.9s (546 modules)
GET / 200 in 3244ms
✓ Compiled in 540ms (254 modules)
o Compiling /favicon.ico ...



Next.js USE Space CLIENT

Ln 1, Col 12 Spaces: 4 UTF-8 CRLF () JavaScript

Subscribe

← Back to Blog

Thursday, March 28th 2019

Styling Next.js with Styled JSX

Posted by

[Styled JSX](#) is a CSS-in-JS library that allows you to write encapsulated and scoped CSS to style your components. The styles you introduce for one component won't affect other components, allowing you to add, change and delete styles without worrying about unintended side effects.


Getting started

Next.js includes Styled JSX by default, so getting started is as simple as adding a `<style jsx>` tag into an existing React element and writing CSS inside of it:

```
pages/index.js

1 function Home() {
2   return (
3     <div className="container">
4       <h1>Hello Next.js</h1>
5       <p>Let's explore different ways to style Next.js apps</p>
6     </div>
7   )
8 }
```





```
JS page.js app JS page.js ...\about X # Home.module.css
app > about > JS page.js > [e] About
1  "use client"
2  import React from 'react'
3
4  const About = () => {
5    return (
6      <div>
7
8        <div className='container'>
9
10         <h1>This is about me</h1>
11         <p>Hey I am a good boy</p>
12
13         ..... I <style jsx global>{`
14         .container{
15           background-color: red;
16           color: green;
17         }
18         `}
19         </style>
20       </div>
21       <div className="container">
22         Hey I am good
23       </div>
24     </div>
25   )
26 }
27
28 export default About
```