



IMqttClientWrapper + callbackAdapter() : IMqttClientCallbackAdapter* + client(): Client& connect(char*) : bool connected(): bool disconnect(): void # IMqttClientWrapper() -s_mqttClientWrapper + ~IMqttClientWrapper() IMqttClientWrapper(IMqttClientWrapper&) operator =(IMqttClientWrapper&) : IMqttClientWrapper& processMessages(): bool publish(char*, char*) : unsigned char setCallbackAdapter(IMqttClientCallbackAdapter*): void state(): elMqttClientState stateStr() : char* subscribe(char*) : unsigned char unsubscribe(char*) : unsigned char

PubSubClientWrapper

- m_callbackAdapter: IMqttClientCallbackAdapter*
- m_client: Client&
- m_pubSubClient: PubSubClient*
- s_pubSubClientWrapper: PubSubClientWrapper*
- + callbackAdapter(): IMqttClientCallbackAdapter*
- + client() : Client&
- + connect(char*) : bool
- connected(): bool
- disconnect(): void
- operator = (PubSubClientWrapper&) : PubSubClientWrapper&

+s_pubSubClientWrapper

- processMessages(): bool
- publish(char*, char*): unsigned char
 PubSubClientWrapper(Client&, char*, unsigned short int)
- ~PubSubClientWrapper()
- PubSubClientWrapper()
 PubSubClientWrapper(PubSubClientWrapper&)
- setCallbackAdapter(IMqttClientCallbackAdapter*): void
- + state(): elMqttClientState
- + subscribe(char*) : unsigned char
- unsubscribe(char*) : unsigned char

IMqttClientCallbackAdapter -m_callbackAdapter # IMqttClientCallbackAdapter() ~IMqttClientCallbackAdapter() messageReceived(char*, unsigned char*, unsigned int): void PubSubClientCallbackAdapter m_trPortMqttRx: DbgTrace_Port* + messageReceived(char*, unsigned char*, unsigned int) : void operator =(PubSubClientCallbackAdapter&) : PubSubClientCallbackAdapter& PubSubClientCallbackAdapter() ~PubSubClientCallbackAdapter() PubSubClientCallbackAdapter(PubSubClientCallbackAdapter&)