Assembly Oral & Practical Questions

1. PSP is a 256 byt's long (T/F)

2. Arr db 1, 2, 3, 4 Mov dl, arr[1] What is the adressing mode used in the previous instruction?

3.If u have an instruction of size 16 bit and address size of 12 bit , how many operation supported by that system

4. @data and @model are predefined symbols in assembly T/F

5.What is the difference between the short and near >> short 8 byte but near 16 byte

6.The command program G is used to name a program." --> F

7.what are the registers used for indirect addressing: SI, DI, BP, BX

8.program loader uses the NEAR procedure as the procedure entry to the program (true,false)

9.Bios contains a set of services “t”

10.For initializing the offset for a reg Answer : A&B

11.If the R/M is register the MOD = 11 ? T OR F

12.what is the difference between JA, JG? One for unsigned, one for signed

13The first instruction to be excuted is ffff0h(t/f)

14.The difference between far and near A- near access only 16-bit address and far access 32-bit B- near access only 8-bit address and far access 16-bit

Practical:

1.Write a program that check even number within this array 2, 4, 6, 7 and print them .. Output : 246

2.To create an array of six elements of {5,4,3,2,6,8} and two empty arrays , i named even and other odd Put even number in its array and odd numbers in its array And after u finish ,print each array on a line having ' , ' between them

3.read two numbers from user and show the result and the reminder

4.Write a program that: 1- accepts two numbers from the users and put them in X and Y variables 2- divide X by Y and save the result in Z 3- print out wether Z is an odd or even number

5.Print the first 10 alphabetical letters

6.Convert "COMPUTER" to "computer"