

** mcq وبوينتس من محاضره 1 ل 6 ولكن التلخيص للمحاضرات ع اللينك دا

**

<https://drive.google.com/drive/folders/152ANDnPkojZzQsHyph525bGt3hvxOmfd>



Week (1)

*MCQ *

1. refers to software in which the source code is freely available for others to view, amend and adapt.
 - a. Free software
 - b. Open source
 - c. Freeware
2.the software is freely accessible and can be freely used, changed, improved, copied and distributed by all who wish to do so. And no

payments are needed to be made for FREE SOFTWARE.

1. Free software
2. Open source
3. Freeware

3.can be downloaded from the internet_for various different purposes. And may not come with the source code.

1. Free software
2. Open source
3. Freeware

4. software that come with source code

1. Free software
2. Open source
3. Freeware

5. is software, which is made available with the right to redistribute copies

1. Free software
2. Open source
3. [shareware](#)

6. Free software is the S/w which permit redistribution but not modification and their Source Code is not available? (T/[F](#))

7.is a non-profit corporation dedicated to managing and promoting the Open Source definition by certifying products.

1. FLOSS
2. GNU
3. [OSI](#)

8. is the software that is neither open nor freely available. Its use is regulated and modification is either forbidden or requires special permission by the supplier.

1. GNU
2. FSF
3. [Proprietary S/W](#)
4. W3C

9. It is responsible for producing the software standards for world wide web.

1. GNU
2. FSF
3. [W3C](#)

10. It promotes the development and use of free software. It is a non- profit organization.

1. [FSF](#)
2. GNU

3. W3C

11. **Standards**: are those for which users have to buy license to use them. These are also known as or standards.

1. Open
2. Proprietary

12. Grants permission to use a copyrighted work

1. Licenses
2. Contract

13. It is used to store and play digital music.

1. FLAC
2. OGG
3. ODF

14. A is the contract between the software owner and the licensee defining terms of use of software
(Software license)

15. Must have three things: **Offer,**

Acceptance, Consideration

1. License

2. Contract

16. One of properties of open source is free redistribution of software (T/F)

17. The opposite of **copyright**.
(copyLeft)

18. is used to protect intellectual property (including software) from being copied or distributed

1. [copyLeft](#)
2. copyright

19. there are two kinds of copyleft: According to its strength ([Strong & weak copyLeft](#))

20. it can be licensed **under other licenses**, even **closed-source** licenses.

1. Strong copyLeft
2. [Weak copyLeft](#)

21. when products usually can be mixed with closed-source software, or software with a totally open-source license.

1. [Permissive license](#)
2. Strict license.

22. when you cannot **mix** strong licensed software with closed-source.

1. Permissive license

2. [Strict license.](#)

23. GPL is copyleft and very License

1. [Strong, strict](#)

2. Strong, permissive

3. Weak, strict

4. Weak, permissive

24. MIT is License

1. [permissive](#)

2. weak

3. strong

4. strict

25. Non-copyleft for and licenses .

1. [MIT & Apache](#)

2. MIT & GPL

3. GPL & Apache

26. Popular project (GPL).....

1. Node.js

2. [Inkscape](#)
3. Spring Framework
4. GNU Aspell

27. MPL is copyLeft

1. Strong
2. [Weak](#)
3. Strict

28. BSD license is(Non-[copyLeft](#))

29. record changes to a file or set of files over time so that you can recall specific versions later ([Version control system](#))

30. Create a new repository in the current directory.

1. \$git commit -m
2. \$git clone
3. [\\$git init](#)

31.Files in the working directory that are not tracked

1. `$git status`
2. `$git commit -m`
3. `$git clone`

32. create a copy (repository) in current directory.

1. \$git commit -m
2. \$git clone
3. \$git init

33. File modifications not yet staged for commit

1. `$git status`
2. `$git commit -m`
3. `$git clone`

* * * * *

Week (2)

////////Git Commands //////////

Git init - > دا معناه انه هيتعامل مع الفولدر اللي محدده ف **terminal** ع انه **Repository**

Git add filename - > هتضيف الفايل اللي ع جهازك لل **staging** (ولكن لسه مترفعش)

Git commit -m 'msg' - > هترفع الملف علي **local repo**. وبتديله مسدج عشان يعرف التعديل اللي حصل عالملف دا بمسج معينه

Git checkout -b branchName - > تنفيذ السطر دا هيكريت برانش جديد وينقلك عليه ف

خطوه واحده

Git merge master branchName - > هتدمج 2 branches بس الاول تروح ع

Git log - > يعرض ال **history** لتعديلات الملفات وكمان معاها **checksum** فايده ال

checksum (ببقي ارقام وحروف جمب بعضها) انك لما تحب ترجع لفيرجن قديم هتقدر توصله من

الارقام دي.. كمان ال **log** هيعرض التاريخ والوقت بتاع التعديل ع الملفات ومين للي عدل



34. is a way to style text on the web. You control the display of the document

1. Github
2. [Markdown](#)
3. CSS

35. It will display all the visible files within the directory that you are currently in

1. Pwd
2. Who
3. [ls](#)

36. A fancy way of asking the computer to display information about where you are and what directory you are currently working in

1. [Pwd](#)
2. Who
3. ls

37. This will display information about the current user i.e. You!

1. Pwd
2. Whoami
3. ls

38. This will display information about who is logged on, both yourself and others.

1. Who
2. Ls
3. pwd

39. This will provide you with the manual for the given command

1. Man
2. Keyword
3. Pwd

40. This will list the files in a reverse alphabetical order

1. [Ls-r](#)
2. Ls-h
3. Ls-t

41. This list will be based on the size order

1. Ls-t
2. Ls-R
3. [Ls-S](#)

42. This list will list them chronologically based on the last access date

1. Ls-t
2. Ls-h
3. [Ls-tu](#)

43. This list will include the content of subdirectories

1. Ls-h
2. Ls-tu
3. Ls-R
4. Ls-r

44. this will make the list human readable
format for example the size would be 1.0MB instead
of 1004638

1. Ls-r
2. Ls-h
3. Ls-S

45. This will list all the files and/or
subdirectories with detailed information such as file
size, date modified etc

1. Ls-l
2. Ls-h
3. Ls-a

46. This will sort the list into a chronological order based on modification time.

1. `ls-t`
2. `ls-l`
3. `ls-a`

47. This will list all of the files in the directory including the hidden dot files.

1. `ls-t`
2. `ls-l`
3. `ls-a`

48. would display all files including hidden in the long format human readable.
`(ls-alh)`

49. Root directory.

1. `Bin`
2. `Etc`
3. `/`

4. .

50. Contain all system related configuration files

1. Usr

2. Etc

3. Bin

51. Contain the executable programmer for the OS.

1. Usr

2. Etc

3. Bin

52. Contain all libraries, the installed programs by user

1. Media

2. Root

3. Usr

53. Home directory of the root user.

1. Root

2. Bin

3. Home

54. For mounting removal media e.g. hard drive, CD_Rom

1. Media

2. Bin

3. Root

4. home

55. information about system resources.

1. /home

2. /root

3. /media

4. `/proc`

56. to one level up the tree.

1. `Cd ..`

2. `Cd ~`

3. `Cd &`

57. to the home directory

1. `Cd ..`

2. `Cd *`

3. `Cd ~`

58. this creates a new directory within the current working directory.

1. `rmdir`

2. `mkdir`

3. `rm -r`

59. Remove directory, the flag on this command will make it so there is user interaction, i.e. the computer will ask for confirmation

1. r
2. i
3. m

60. This will remove the named directory, It must be within the current working directory

1. `rmdir`
2. `mkdir`
3. `rm -r`

61. this command will along remove with its contents

1. `rm-r`
2. `rm-i`

62. This will move the file to a new location

1. `mv filename1 filename2`
2. `cp filename1 filename2`

63. the combination will remove all files within the directory and ask for confirmation for each file within

1. `rm-ir`
2. `rm-i`
3. `rm-r`

64. This will make a copy of the file under the

1. `mv filename1 filename2`
2. `cp filename1 filename2`

65. is used to match a single character.

1. `?`
2. `*`
3. `#`

66. is used to match multiple character.

1. `*`

2. %

3. ?

67.permission bits

1. 8

2. 5

3. 10

4. 15

68. To delete read permission from all (file name= file1)

1. Chmod a-r file1

2. Chmod o-r file1

3. Chmod g-r file1

4. Chmod a+r file1

69. To add read and write permission from user and file name is (file1)

1. Chmod u-rw file1
2. Chmod u-rx file1
3. Chmod u+rw file1
4. Chmod u+wx file1

70. chmod g-rwx →

1. **rw**x----**rw**x
2. **rw**x**rw**x----
3. ----**rw**x**rw**x

71. (-) equal

1. **File**
2. Directory

72. (d) equal

1. File
2. **Directory**

73. For changing permissions use
command (chmod)
74. Bit 1 (leftmost) →.....
1. owner's permissions (read, write, and execute)
 2. world's permissions (read, write, and execute)
 3. group's permissions (read, write, and execute)
 4. file type
75. Bit 2-4 →
1. owner's permissions (read, write, and execute)
 2. world's permissions (read, write, and execute)
 3. group's permissions (read, write, and execute)
 4. file type
76. Bit 5-7 →
1. owner's permissions (read, write, and execute)
 2. world's permissions (read, write, and execute)
 3. group's permissions (read, write, and execute)

4. file type

77. Bit 8-10 →

1. owner's permissions (read, write, and execute)
2. world's permissions (read, write, and execute)
3. group's permissions (read, write, and execute)
4. file type

* * * * *

Week (3)

<<<POINTS IN THIS CHAPTER >>>

- **Bash shell programming examples :**

- # 1. #! /bin/sh

```
read -p "enter your name: " first last
```

```
echo "First name: $first"
```

```
echo "Last name: $last"
```

اول حاجه هتظهر عند تنفيذ الكود دا ادخل اسمك ومديني 2param
 هتدخل ال first=x last=y ... وعند الطباعة بتقوله \$first echo
 فهيطبعك اللي دخلته x y

Parameter	Meaning
\$0	Name of the current shell script
\$1-\$9	Positional parameters 1 through 9
\$#	The number of positional parameters
\$*	All positional parameters, "\$*" is one string
\$@	All positional parameters, "\$@" is a set of strings
\$?	Return status of most recently executed command
\$\$	Process id of current process

2. % set tim bill ann fred

من الجدول اللي فوق جاوب علي \$* , \$1 , \$# وهكذا

- 1) % echo \$* → tim bill ann fred
(result)
 - 2) % echo \$# → 4 (result)
 - 3) % echo \$1 → tim (result)
 - 4) % echo \$3 \$4 → ann fred
(result)
-

3. #!/bin/bash

```
read -p "Enter calls handled:" CHandle
read -p "Enter calls closed: " CClose
if [[ "$CHandle" -gt 150 || "$CClose" -gt
50 ]]
then
    echo "You are entitled to a bonus"
else
    echo "You get a bonus if the calls"
    echo "handled exceeds 150 or"
    echo "calls closed exceeds 50"
fi
```

المثال يطبق if condition & relational operator .. ان الكونديشن هنا
مقارنه بين رقمين فاستخدم -gt كمان خد بالك من ال || or عشان وجودها
زود 2brackets [[]]

4. #!/bin/bash

ChildRate=3

```

AdultRate=10
SeniorRate=7
read -p "Enter your age: " age
case $age in
    [1-9]|[1][0-2]) # child, if age 12 and
younger
        echo "your rate is" '$'$ChildRate.00" ;;
        # adult, if age is between 13 and 59
inclusive
    [1][3-9]|[2-5][0-9])
        echo "your rate is" '$'$AdultRate.00" ;;
    [6-9][0-9])    # senior, if age is 60+
        echo "your rate is"
'$'$SeniorRate.00" ;;
esac

```

المثال تطبيق ع case statement & case pattern .. ان اول حاجه اليوزر يدخل السن ويدخل جوه switch case .. اول كيس.. ان لو العمر من سنه لغايه 12 هيطبع ال child rate =3\$ وهكذا

5. #!/bin/bash

```
COUNTER=0
```

```
while [ $COUNTER -lt 10 ]
```

do

echo The counter is \$COUNTER

let COUNTER=\$COUNTER+1

done

مثال بسيط ع while loop ... خد بالك بان قفله ال while بتبقي ب
done .. و do جواها بتكتب الاكواد اللي هتتنفذ ف حاله ان
شرط while بتروو

6. #!/bin/bash

اراي فيها الارقام دي

for i in 7 9 2 3 4 5

do

echo \$i

done

مثال بسيط بيوضح فكره ال forloop وشكل كتابتها قريه من
foreach

7. #! /bin/bash

select var in alpha beta gamma

do

echo \$var

done

1) alpha

2) beta

3) gamma

#? 2

beta

#? 4

#? 1

alpha

Select بتطبع للي بعد ..in فلما قولتله echo \$var
 فطبع 3param للي هما (alpha beta gamma)
 وكمان مترقمين زي للي فالجدول عاليين ... ولو قولتله
 2 فهيطبعك البارميتر للي واخذ رقم 2 وهو beta... اما
 لما ادبتله 4 واخر رقم فالباراميترز هوا 3 فمرجعش
 حاجه ...

Relational Operators

Meaning	Numeric	String
Greater than	-gt	
Greater than or equal	-ge	
Less than	-lt	
Less than or equal	-le	
Equal	-eg	= or ==
Not equal	-ne	!=
str1 is less than str2		str1 < str2
str1 is greater str2		str1 > str2

String length is greater than zero		-n str
String length is zero		-z str

78. A script is file containing a series of commands in linux.

1. [Shell](#)
2. Java

79. Shell scripts need permission to be able to run

1. write
2. [execution](#)
3. read

80. execute line by line and stop when find an error.

1. [Interpreter](#)

2. Compiler

81.are interpreted by another programs
(Shell scripts)
82. ./ mean execute shell script ? (T/ F)
83. All positional parameters, is one string
1. \$0
 2. \$*
 3. \$@
84. Positional parameters 1 through 9
1. \$0
 2. \$1-\$9
 3. \$#
85. Process id of current process
1. \$\$
 2. \$#

3. \$*

86. The number of positional parameters

1. \$#

2. \$@

3. \$*

87. Name of the current shell script

1. \$*

2. \$0

3. \$?

88. Return status of most recently executed
command

1. \$*

2. \$@

3. \$?

89. All positional parameters, is a set of strings

1. \$*
2. \$\$
3. @\$

90. terminate if condition by.....

1. fi
2. Endif
3. break

91. else if in if condition bash (elif)

92. greater than in relational operator for numeric ...

1. -gt
2. >

93. greater than in relational operator for string ...

1. -gt
2. >

94. And(&&), or (| |) must be enclosed within

..... ([[]])

95. Exit 1 mean (ان حصل ايرور زيها زي ريتيرن)

96. Break = in shell

1. ,,

2. &&

3. ;;

97. Command control,and list control

..... ,..... .

1. While, until and for... in, select

2. for... in, select and While, until

98. To execute commands in “command-list” as long as “expression” evaluates to false

1. For loop

2. While loop

3. until

99. To execute commands in “command-list”
as long as “expression” evaluates to true

1. For loop
2. While loop
3. Until

100. Terminate of switch case by

1. Break
2. Esac
3. escape

101. To execute commands as many times as
the number of words in the “argument-list”.

1. For loop
2. While loop
3. until

102. Constructs simple menu from word list

103. Allows user to enter a number instead of a word

- ## Week (5)

104. ([wordpress](#)) It's free and open source software based on html & php

105. WordPress started as just a system.
(blogging)

106. There are thousands of and available to transform your site into almost anything you can imagine. (plugins and themes)

107. is a discussion or informational site published on the World Wide.

1. Themes
2. Blogs
3. plugin

108. The element allows the content manager or author, to manage the content from a Web site without needing the expertise of a Webmaster.

1. CMA
2. CDA
3. CDM

109. The element uses and compiles that information to update the Web site.

1. CMA
2. CDA
3. CDM

110. Wordpress is ([Content Management System \(CMS\)](#)) And([open source](#)) software and search engine([optimized](#))
111. A – static and Use it for content that doesn't change (About Us, Locations, etc).
1. [Pages](#)
 2. Widget
 3. Posts
112. A single entry and use it for time sensitive content (Fraud Alert, Promotional item, etc)
1. Pages
 2. Widget
 3. [posts](#)
113. Areas of content you can add to your site without code knowledge.

1. plugins
2. [Widget](#)
3. posts

114. Code that adds additional functionality to your website

1. [plugins](#)
2. Widget
3. Posts

115. Allows users to organize their content for easy access

1. themes
2. [Categories](#)
3. Media library

116. A plugin created by Web services which: Adds calculators, rateboards, membership links, external link warnings, online banking logins.

1. [Site control](#)

2. Forms

3. themes

117. Contains all uploaded files (images, documents, etc).

1. Forms

2. Themes

3. [Media library](#)

118. The style/layout of your site.

1. Forms

2. [Themes](#)

3. Media library

119. are files that work together to create the design and functionality of a WordPress Site

1. Forms

2. Media library

3. Themes

120. Job of includes anything related to WordPress. It includes: WordPress Set Up and Configuration, WordPress Upgrades, Plugin Installation and Customization, Theme Installation and Customization, WordPress Troubleshooting, WordPress Security.

1. Wordpress consultant

2. Wordpress website webmaster

3. Theme developer

121. A is a person responsible for maintaining one or many websites. may include:
Maintaining websites for clients and businesses,

Ensure the web servers, hardware and software are operating accurately, Design WordPress websites.

1. Wordpress consultant
2. Wordpress website webmaster
3. Theme developer

122. A is someone who writes content.

1. Plugin developer
2. Blogger
3. Theme developer

123. is the act of writing a post. (blogging)

124. UI developer : similiary uses: emphasis on scripting languages like JavaScript and emphasis on HTML and CSS.

1. Less, more
2. More, less
3. Less, less

125. Organized around category but
..... has no category and stand alone.

1. Pages, posts
2. Posts, pages
3. Themes, posts
4. Posts, plugin

126. You should have no more than - tags per
entry.

1. 1-7
2. 2-5
3. 3-10

127. PHP is a Typed Language

1. Loosly
2. Loosless

128. The PHP function returns the data type and value. ([var_dump](#))

129. In php operator that equal exponential??

1. &&
2. ^^
3. [**](#)
4. %%

130. - loops through a block of code as long as the specified condition is true.

1. [While](#)
2. Do.. while
3. Foreach
4. For

131. - loops through a block of code a specified number of times.

1. While

2. Do.. while

3. Foreach

4. For

132. - loops through a block of code for each element in an array.

1. While

2. Do.. while

3. Foreach

4. For

133. loops through a block of code once, and then repeats the loop as long as the specified condition is true.

1. While

2. Do.. while

3. Foreach

4. For

134. Organizing around posts can also improve your
.....

135. are also known as instance.

1. Class
2. [object](#)

136. This is also called a base class or
super class.

1. [Parent class](#)
2. Child class

137.: This is an object oriented concept where
same function can be used for different purposes.

1. [Polymorphism](#)
2. Inheritance
3. Overloading

138. Any representation of data in which the implementation details are hidden

1. Encapsulation
2. Data abstraction
3. Inheritance

139. Fopen() function, It requires two arguments, one is and the second one is of the file.

1. Filename, mode of the file
2. Filename, length of the file

140. Refers to a special type of function which will be called automatically whenever there is an object formation from a class.

1. Encapsulation
2. Destructor
3. Constructor

141. If an attempt to open a file fails then **fopen()** returns a value of otherwise it returns a which is used for further reading or writing to that file.
1. False, file pointer
 2. False, file length
 3. True, file pointer
142. After making a changes to the opened file it is important to close it with the function.
1. Fclose()
 2. Fopen()
 3. Fread()
143. The **fclose()** function requires a as its argument and then returns **true** when the closure succeeds or **false** if it fails.
1. File length
 2. File pointer

144. : Refers to a special type of function which will be called automatically whenever an object is deleted or goes out of scope.

1. Destructor
2. Constructor
3. Encapsulation

145. Once a file is opened using **fopen()** function it can be read with a function called

1. Fread()
2. Fsize()
3. Fclose()

146. Fread() function requires two arguments. These must be the and the expressed in bytes

1. File pointer, file length
2. file length, file pointer

147. The file's length can be found using the()
function which takes the as its argument
and returns the size of the file expressed in bytes.

1. `Filesize(), file name`
2. `Filesize(), file pointer.`

148. `Fwrite()` , This function requires two arguments
specifying a and that is to be
written.

1. File size, string of data
2. `File pointer, string of data`

149. Optionally a third integer argument in `fwrite()`
function can be included to specify(`specify
the length of the data to write.`) If the third argument
is included, writing would stop after
(`the specified length has been reached.`)

150.() function is used to read the contents of the file.

1. fgets()
2. [readfile\(\)](#)
3. feof()

151. The() function is useful for looping through data of unknown length.

1. fgets()
2. readfile()
3. [feof\(\)](#)

152. After a call to the() function, the file pointer has moved to the next line.

1. [fgets\(\)](#)
2. fgetc()
3. feof()

153. The() function is used to read a single character from a file.

1. fgetc()
2. fgetc()
3. feof()

* * * * *

Week (6) part 1

154. – determine appearance & behavior

1. Plugins
2. Themes
3. Widgets

155. –add functionality

1. Plugins
2. Themes
3. Widgets

156. – insert content / features into specific area on the page.

1. Plugins
2. Themes
3. [Widgets](#)

157. Used to display pages, blog indexes, individual blog posts, and custom post types
For each item, retrieve and display: the_title, the_excerpt, the_content, the_category, the_author, the_date.

1. [Wordpress loop](#)
2. Header
3. sidebar

158. The PHP code of any plugin consists of a combination of one or more WordPress and one or more functions.

1. Callback, hooks

2. Hooks, callback

159. What wordpress core? All folders and files outside of the wp-content directory including:..... , and(Root, WP-includes, WP-admin)
160. Where is the Code for Plugins and themes Stored?
(wp-content → plugins “folder” && Wp-content → themes “folder”).
161. There are two kinds of hooks:..... And
(action, filter)
162. Augment, modify or change information BEFORE it is displayed on the screen.
1. Action
 2. Filter

163. This code usually adds content to a site or changes the way a given action is performed

1. [Action](#)
2. Filter

164. plugins that currently running

1. Inactive
2. Drop-in
3. [Active](#)
4. Must-use

165. These are loaded automatically and can only be deactivated by removing the plugin from the directory.

1. Inactive
2. Drop-in
3. Active
4. [Must-use](#)

166. type of plugin That are specifically named PHP files.(install.php, maintenance.php, Db.php)

1. Inactive
2. Drop-in
3. Active
4. Must-use

167. plugins that are installed but not active. No code from the plugin is executed.

1. Inactive
2. Drop-in
3. Active
4. Must-use

168. A is a small block that can be dragged into (typically a sidebar or footer) in a WordPress theme.

- a. Theme

169. Widget code can be added to your WordPress website in two ways:
1. Upload the widget code as a, or
 2. Add the widget code to the functions.php file in
 - a
 - a. Theme, plugin
 - b. plugin, theme

Week (6) part 2

170. are electronic snapshots taken of a scene or scanned from documents, such as photographs, manuscripts, printed texts, and artwork.

- a. Digital image
- b. Moving image

171. is sampled and mapped as a grid of dots or(pixels). Each pixel is assigned a value (black, white, shades of gray or color), which is represented in binary code (zeros and ones).

- a. Digital image
- b. Moving image

172. is typically a movie ([film](#)) or [video](#), including [digital video](#). It could also be an animated display

- a. Digital image
- b. Moving image

173._is also used in the broader sense of any two-dimensional figure such as a map, a graph, a pie chart, or an abstract painting.

- a. Digital image
- b. Moving image
- c. Image

174.: is an artifact, that has a similar appearance to some subject - usually a physical object or a person.

- a. Digital image
- b. Moving image
- c. Image

175. is a numeric representation (normally binary) of a 2-D image. Depending on whether the image resolution is fixed, it may be of vector or raster type.

- a. Digital image
- b. Moving image
- c. Image

176. images have a finite set of digital values, called picture elements or pixels.

a. Raster

b. Vector

177. The digital image contains a number of columns and rows of pixels. (fixed)

178. are the smallest individual element in an image, holding quantized values that represent the brightness of a given color at any specific point.

a. Pixels

b. images

179.: is a digital image that has only two possible values for each pixel.

a. Gray scale

b. Binary

c. color

180. images resulted from mathematical
.....

a. Gray scale

b. Binary

c. Vector

181. : is an image in which the value of each
pixel is a single sample, that is, it carries only intensity
information.

a. Gray scale

b. Binary

c. Color

182. : is a digital image that includes color
information for each pixel.

a. Gray scale

b. Binary

c. color

183. In mathematical terms, a vector consists of point that has both and
(direction and length)

184. for example, in the case of a billboard with text
(.....) and photographs (.....).

a. vector, raster

b. raster, vector

185. Graphic Software programs, which can be broadly grouped intoeditors
(vector graphics)

186. Often, both raster and vector elements will be combined in one image? ((T/F))

187. : Simply, saved as a single file that includes a low resolution preview inside of it, allowing some programs to display a preview on the screen(vector or raster)

- a. PDF
- b. EPS
- c. WMF

188. GIMP is graphic editor??

- a. Raster
- b. Vector

189. : used to represent documents in a manner independent of application software, hardware, and operating system. (vector or raster)

- a. PDF
- b. EPS
- c. WMF

190. is a compression method (in most cases)
(.....) compression. (vector or raster)

- a. JPEG, loosely
- b. TIFF, loosely

191. : are intended to be
between applications and may contain both [vector](#)
[graphics](#) and raster components.

- a. PDF
- b. EPS
- c. WMF

192. format is a flexible format that normally saves
8 bits or 16 bits per color (red, green, blue) for 24-bit
and 48-bit totals.

- a. TIFF
- b. JPEG
- c. WebP

193. ... is limited to an 8-bit palette, or 256 colors.

- a. TIFF
- b. GIF
- c. BMP

194. or **[xml file]**: is an [XML](#)-based [vector image format](#) for two-dimensional graphics that has support for interactivity and animation.

- a. SVG, VML
- b. SVG, PNG
- c. TIFF, VML

195. file format was created as the free, open-source successor to the GIF. Supports true color (16 million colors).

- a. BMP
- b. PNG
- c. TIFF

196. The SVG specification is an
developed by the [World Wide Web Consortium](#)
(W3C) since 1999.
([open standard](#))
197. is a new image format that uses
compression. It was designed by Google to reduce
image file size to speed up web page loading
- a. [Webp, loosely](#)
 - b. Webp, lossless
198. files are **uncompressed**, hence they are
large; the advantage is their simplicity and wide
acceptance in Windows programs.
- a. [BMP](#)
 - b. TIFF
 - c. BNG
 - d. GIF

199. **JPEG ..** (New JPEG standard based on Microsoft HD Photo)
(XR)

200. Crusial in image editing.
(selection in image editing)

201. Categories of Selection Tools:,,
.....,,

(* Predefined shapes

* Lasso

* By color

* By painting with a brush

* By drawing an outline around the area)

#####END