

COMPUTER ARCHITECTURE EXAM 2025 (تخلفات)

Choose the correct answer:

1.	_____ called a 1-bit monochrome image since it contains no color.							
	a)	Gray image	b)	Binary image	c)	RGB image	d)	CMY images
2.	By reducing the sound wave sample rate the amount of data you need to store is							
	a)	reduced	b)	increased	c)	compressed	d)	decoded
3.	In assembly languages the _____ register is used for looping							
	a)	AX	b)	BX	c)	CX	d)	DX
4.	The binary equivalent of (233) ₁₀ is							
	a)	00100101	b)	11101001	c)	00101100	d)	10101010
5.	_____ is the time interval between the request for information and the access to the first bit of that information.							
	a)	Cycle Time	b)	Latency	c)	Access Type	d)	Throughput
6.	Which of the following instruction cannot be in octal program?							
	a)	823	b)	1010	c)	231	d)	530
7.	All of the following are reserved words in assembly language except							
	a)	SIZE	b)	FAR	c)	MODEL	d)	PAGE
8.	In _____ bus set-up is faster than other transmissions, so well suited for applications where messages are generated at irregular intervals							
	a)	Synchronous	b)	Semi-synchronous	c)	Asynchronous	d)	System
9.	_____ is the time elapsed from the start of a read operation to the start of a subsequent read.							
	a)	Cycle Time	b)	Latency	c)	Access Type	d)	Throughput
10.	_____ is employed to hold temporarily the right-hand instruction from a word in memory.							
	a)	IBR	b)	IR	c)	MBR	d)	IMR
11.	Which of the following registers, keep track of the program instructions stored in memory?							
	a)	Accumulator	b)	Address Register	c)	Program Counter	d)	Index Register
12.	In assembly languages _____ register contains machine instructions to be executed							
	a)	CS	b)	DS	c)	SS	d)	SI
13.	Which of the following is a valid label name							
	a)	@FLDD	b)	?FLDD	c)	\$FLDD	d)	All of the above
14.	The hexadecimal equivalent of (125) ₁₀ is							
	a)	7D	b)	D7	c)	77	d)	DD
15.	Which of the following is not a typical assembly language instruction?							
	a)	ADD	b)	MOV	c)	IF	d)	SHRD

16.	In Assembly explain the program's purpose.							
	a)	Identifiers	b)	Directives	c)	Comments	d)	Labels
17.	_____ type indicates the boundary on which the segment is to begin.							
	a)	Alignment	b)	Combine	c)	Class	d)	data
18.	In Assembly _____ explain the program's purpose.							
	a)	They are machine-independent						
	b)	They are easier to read than high-level language programs						
	c)	They are faster and more efficient than high-level language programs						
	d)	They are harder to debug than high-level language programs						
19.	Which of the following operations is/are performed by the ALU?							
	a)	Data manipulation	b)	Exponential	c)	Square root	d)	All of the above
20.	_____ is employed to hold the instruction from an I/O device.							
	a)	CS	b)	I/OAR	c)	IMR	d)	I/OBR
21.	Processor bandwidth determines how many instructions per second the processor can execute.							
	a)	True	b)	False	c)	All of the above	d)	None of the Above
22.	In STROBE signal, slave reads on falling edge							
	a)	True	b)	False	c)	All of the above	d)	None of the Above
23.	Asynchronous bus is slightly more complex and expensive than synchronous							
	a)	True	b)	False	c)	All of the above	d)	None of the Above
24.	Data Bus is bi-directional so that it allows data flow in both directions along the wires							
	a)	True	b)	False	c)	All of the above	d)	None of the Above
25.	External Interrupts are known as traps and their causes could be due to some illegal operation or the erroneous use of data.							
	a)	True	b)	False	c)	All of the above	d)	None of the Above
26.	In Daisy Chain the poll could be implemented with the help of a separate command line for example TESTI/O.							
	a)	True	b)	False	c)	All of the above	d)	None of the Above
27.	Linking involves converting the OBJ module to an .EXE machine code module							
	a)	True	b)	False	c)	All of the above	d)	None of the Above
28.	Operands Control the way a source program assembles and lists							
	a)	True	b)	False	c)	All of the above	d)	None of the Above
29.	USB 2.0 - is capable of supporting a transfer rate of up to 480 Mbps							
	a)	True	b)	False	c)	All of the above	d)	None of the Above

30.	Control Bus: carries the signals relating to the control and co-ordination of the various activities across the computer							
	a)	True	b)	False	c)	All of the above	d)	None of the Above
31.	In Signed Integers, if highest bit is 1 then it indicates that the number is							
	a)	Positive	b)	Negative	c)	does not matter	d)	invalid
32.	Which of the following is a typical assembly language instruction							
	a)	PAGE	b)	ASSUME	c)	RET	d)	ENDP
33.	In memory reference instructions, the Opcode part is _____ bits?							
	a)	8	b)	10	c)	11	d)	12
34.	These types of interrupts generally come from external input/output devices							
	a)	Software Interrupts	b)	External Interrupts	c)	Internal Interrupts	d)	Trap Interrupts
35.	A small amount of storage available as part of a digital processor							
	a)	ROM	b)	RAM	c)	Registers	d)	Hard disk
36.	which of the following instructions cannot have operands							
	a)	MUL	b)	RET	c)	SHRD	d)	INC
37.	image a pixel represented by one bit							
	a)	Gray scale	b)	RGB	c)	Binary	d)	Gif
38.	An image on the seven segments can be represented by _____ bits.							
	a)	4 bits	b)	7 bits	c)	8 bits	d)	16 bits
39.	describes what the computer does.							
	a)	Data communication	b)	Computer Hardware	c)	Computer organization	d)	Computer architecture
40.	employed to hold, the least significant bits of the product as multiplication proceeds, and the quotient from division							
	a)	Accumulator	b)	Instruction Register	c)	Multiplier Quotient	d)	Stack Pointer

(إِنَّ اللَّهَ وَمَلَائِكَتَهُ يُصَلُّونَ عَلَى النَّبِيِّ يَا أَيُّهَا الَّذِينَ آمَنُوا صَلُّوا عَلَيْهِ وَسَلِّمُوا تَسْلِيمًا)