

GENERAL SPECIFICATIONS

SPEC



2

Model	YFS200U	
Spark Plug: Type/Manufacture	For USA and Oceania B8ES/NGK, W24ES/NIPPON DENSO For Canada and S. Africa BP8ES/NGK	
Spark Plug Gap	0.7 ~ 0.8 mm (0.028 ~ 0.032 in)	
Clutch Type:	Wet, Multiple-disc	
Transmission: Primary Reduction System Primary Reduction Ratio Secondary Reduction System Secondary Reduction Ratio Transmission Type Operation Gear Ratio: 1st 2nd 3rd 4th 5th 6th	Helical Gear 71/22 (3.227) Chain Drive 40/13 (3.077) Constant Mesh 6-Speed Left Foot Operation 34/11 (3.091) 31/14 (2.214) 25/15 (1.667) 20/16 (1.250) 19/18 (1.056) 19/21 (0.905)	
Chassis: Frame Type Caster Angle Trail Tread (Standard): Rear Front Toe-in	Steel Tube Frame 9° 40 mm (1.57 in) 780 mm (30.7 in) 820 mm (32.3 in) 0 ~ 10 mm (0 ~ 0.39 in)	
Tire: Type Size: Front Rear	Tubeless AT21 x 7 – 10 AT21 x 10 – 8	
Tire Pressure (Cold Tire): Recommended Minimum Maximum	Front	Rear
	30 kPa (0.30 kg/cm ³ , 4.3 psi)	25 kPa (0.25 kg/cm ³ , 3.6 psi)
	27 kPa (0.27 kg/cm ³ , 3.8 psi)	22 kPa (0.22 kg/cm ³ , 3.1 psi)
	33 kPa (0.33 kg/cm ³ , 4.7 psi)	28 kPa (0.28 kg/cm ³ , 4.0 psi)
Brake: Front Brake Type Front Brake Operation Rear Brake Type Rear Brake Operation	Drum Brake Right Hand Operation Single Disc Brake Right Foot Operation	