

CHASSIS

Model	YFS200U
Steering System:	
Lock to Lock Angle	40°
Left	40°
Right	
Front Suspension:	
Shock Absorber Travel	90 mm (3.54 in)
Suspension Spring Free Length	226.6 mm (8.93 in)
Spring Rate	
K1	30.0 N/mm (3.0 kg/mm, 168 lb/in)
K2	35.0 N/mm (3.5 kg/mm, 196 lb/in)
Stroke	
K1	0 ~ 46.7 mm (0 ~ 1.84 in)
K2	46.7 ~ 112.2 mm (1.84 ~ 4.42 in)
Optional Spring	No.
Rear Suspension:	
Shock Absorber Travel	80 mm (3.15 in)
Spring Free Length	245 mm (9.65 in)
Spring Rate	
K1	45.0 N/mm (4.5 kg/mm, 252 lb/in)
K2	80.0 N/mm (8.0 kg/mm, 448 lb/in)
Stroke	
K1	0 ~ 55.0 mm (0 ~ 2.17 in)
K2	55.0 ~ 105.0 mm (2.17 ~ 4.13 in)
Optional Spring	No.
Swingarm:	
Free Play Limit	< 1.0 mm (0.04 in) > at swingarm end
Side Clearance	Move swingarm and side to side. 0.4 ~ 0.7 mm (0.016 ~ 0.027 in) at swingarm pivot
Front Wheel:	
Type	Panel Wheel
Rim Size	10 x 5.5 AT
Rim Material	Steel
Rim Runout Limit < Vertical >	< 2.0 mm (0.08 in) >
< Lateral >	< 2.0 mm (0.08 in) >
Rear Wheel:	
Type	Panel Wheel
Rim Size	8 x 8.0 AT
Rim Material	Steel
Rim Runout Limit < Vertical >	< 2.0 mm (0.08 in) >
< Lateral >	< 2.0 mm (0.08 in) >
Drive Chain:	
Type/Manufacturer	520V6/DAIDO
No. of Links	92
Chain Free Play	30 ~ 40 mm (1.18 ~ 1.57 in)
Front Drum Brake:	
Type	Leading, Trailing
Brake Drum Inside Diameter	110 mm (4.33 in)
< Limit >	< 111 mm (4.37 in) >
Lining Thickness	4.0 mm (0.16 in)
< Limit >	< 2.0 mm (0.08 in) >
Shoe Spring Free Length	50.5 mm (1.99 in)