







MAINTENANCE SPECIFICATIONS

ENGINE

Model	YFS200U
Cylinder Head: < Warp Limit > 	< 0.03 mm (0.0012 in) > * Lines indicate straightedge measurement.
Cylinder: Bore Size < Taper Limit > < Out of Round Limit >	66.00 ~ 66.02 mm (2.598 ~ 2.599 in) < 0.08 mm (0.003 in) > < 0.05 mm (0.002 in) >
Piston: Piston Size "D" Measuring Point "H" Piston Off-Set Piston-to-Cylinder Clearance Oversize 1st 2nd 	65.965 ~ 66.000 mm (2.597 ~ 2.598 in) 10 mm (0.39 in) 0 mm (0 in) 0.035 ~ 0.040 mm (0.0014 ~ 0.0016 in) 66.25 mm (2.608 in) 66.50 mm (2.618 in)
Piston Ring: Sectional Sketch  Top Ring 2nd Ring End Gap (Installed) Side Clearance	Keystone B = 1.2 mm (0.047 in) T = 2.8 mm (0.110 in) Keystone B = 1.2 mm (0.047 in) T = 2.8 mm (0.110 in) 0.20 ~ 0.35 mm (0.008 ~ 0.014 in) 0.20 ~ 0.35 mm (0.008 ~ 0.014 in) 0.03 ~ 0.05 mm (0.0012 ~ 0.0020 in) 0.03 ~ 0.05 mm (0.0012 ~ 0.0020 in)
Crankshaft:  Crank Width "A" < Runout Limit "C" > Big End Side Clearance "D" Big End Radial Clearance "E" Small End Free Play "F"	57.90 ~ 57.90 mm (2.280 ~ 2.281 in) < 0.03 mm (0.0012 in) > 0.4 ~ 0.7 mm (0.016 ~ 0.028 in) 0.021 ~ 0.035 mm (0.0008 ~ 0.0014 in) 0.8 ~ 1.0 mm (0.031 ~ 0.039 in)