




Model	YFS200U
Ballancer: Ballancer Drive Method	Gear
Clutch: Friction Plate Thickness/Quantity < Wear Limit > Clutch Plate Thickness/Quantity < Warp Limit > Clutch Spring Free Length/Quantity Clutch Spring Minimum Length Clutch Housing Radial Clearance Clutch Release Method < Push Rod Bending Limit >	2.92 ~ 3.08 mm (0.115 ~ 0.121 in)/7 pcs. < 2.8 mm (0.110 in) > 1.05 ~ 1.35 mm (0.041 ~ 0.053 in)/5 pcs. < 0.05 mm (0.002 in) > 32.5 mm (1.28 in)/5 pcs. 30.0 mm (1.18 in) 0.015 ~ 0.049 mm (0.0006 ~ 0.0019 in) Inner push, Cam push < 0.15 mm (0.006 in) >
Transmission: < Main Axle Runout Limit > < Drive Axle Runout Limit >	< 0.08 mm (0.003 in) > < 0.08 mm (0.003 in) >
Shifter: Type	Cam Drum and Guide Bar
Kick Starter: Kick Starter Type Kick Clip Friction Force	Kick and Mesh Type P = 0.8 ~ 1.2 kg (1.8 ~ 2.6 lb)
	
Air Filter Oil Grade:	Foam-Air-Filter Oil or SAE 10W30 SE
Carburetor: Type/Manufacturer/Quantity I.D. Mark Main Jet (M.J.) Main Air Jet (M.A.J.) Jet Needle-clip Position (J.N.) Needle Jet (N.J.) Cutaway (C.A.) Pilot Outlet (P.O.) Pilot Jet (P.J.) Bypass 1 (B.P. 1) Pilot Air Screw (P.A.S.) Valve Seat Size (V.S.) Starter Jet (G.S.) Float Height (F.H.) Fuel Level (F.L.) Engine Idling Speed	VM26SS/MIKUNI/1 2XJ 00 # 220 ϕ 0.7 5J22-2 P-6 (# 345) 2.0 0.6 # 32.5 0.8 x 3.75 1 and 1/2 turns out ϕ 2.8 # 45 20.0 ~ 21.5 mm (0.79 ~ 0.85 in) 0.5 ~ 1.5 mm (0.02 ~ 0.06 in) 1,450 ~ 1,550 r/min