

CHASSIS

FRONT WHEEL AND FRONT BRAKE

- | | |
|------------------------|----------------|
| ① Cam lever | ⑪ Wheel hub |
| ② Wear indicator plate | ⑫ Collar |
| ③ Brake shoe plate | ⑬ Plain washer |
| ④ Oil seal | ⑭ Cotter pin |
| ⑤ O-ring | |
| ⑥ Camshaft | |
| ⑦ Spring | |
| ⑧ Brake shoe | |
| ⑨ Bearing | |
| ⑩ Spacer collar | |

TIRE AIR PRESSURE		
COLD TIRE PRESSURE	FRONT	REAR
STANDARD	30 kPa (0.30 kg/cm ² , 4.3 psi)	25 kPa (0.25 kg/cm ² , 3.6 psi)
MINIMUM	27 kPa (0.27 kg/cm ² , 3.8 psi)	22 kPa (0.22 kg/cm ² , 3.1 psi)
MAXIMUM	33 kPa (0.33 kg/cm ² , 4.7 psi)	28 kPa (0.28 kg/cm ² , 4.0 psi)

A	TIRE SIZE: AT21 x 7-10
B	WHEEL RUNOUT LIMIT VERTICAL: 2.0 mm (0.08 in) LATERAL: 2.0 mm (0.08 in)
C	TIRE WEAR LIMIT: 3.0 mm (0.12 in)

D	BRAKE DRUM INSIDE DIAMETER: < WEAR LIMIT >: 111 mm (4.37 in)
E	BRAKE SHOE THICKNESS: < WEAR LIMIT >: 2.0 mm (0.08 in)

9 Nm (0.9 m•kg, 6.5 ft•lb)

