FASTHUB SOLUTIONS LIMITED
business@fasthub.co.tz
P.O.Box: 31206 Dar es salaam
Call: 0800 712 354 **"Toll Free"**
www.fasthub.co.tz

Fasthub Bulk SMS Gateway API

Documentation

Request to SMS Gateway from Third Party

Method: POST **Headers:** `Content-Type: application/json`

Payload:

```
{
    "auth": {
        "client_id": string,
        "client_secret": string
    },
    "messages": [
        {
            "text": string,
            "msisdn": string,
            "source": string,
            "reference": string
        }
    ]
}
```

Field	Description	Type
`auth`	Authentication credentials	Object
- `client_id`	Client ID for authentication	String
- `client_secret`	Client secret for authentication	String
`messages`	List of messages to be sent (maximum 50)	Array
- `text`	Content of the message	String
- `msisdn`	Recipient's phone number	String
- `source`	Source of the message (senderId)	String
- `reference`	Reference identifier for the message (min length 20 chars)	String

Response from SMS Gateway to Third Party Application

Headers: `Content-Type: application/json`

```
{
    "status": Boolean,
    "message": string,
    "data": Object
}
```

Field	Description	Type
`status`	Status of the response	Boolean
`message`	Description or additional information	String
`data`	Data payload	Object

Callback from SMS Gateway to Third Party Application

If a third-party API client has set up a callback endpoint for status delivery and has activated callbacks on the FastHub SMS Gateway, the final status of SMS messages will be transmitted through the preconfigured endpoint.

Endpoint : [the end point you set to the portal for callbacks]

Method: POST **Headers:** `Content-Type: application/json`

Payload:

```
{
    "statuses":[
        {
            "status": string,
            "reference": string,
            "description": string,
            "msisdn": string
        }
    ]
}
```

Field	Description	Type
`statuses`	List of status objects	Array
- `status`	Status of the message	String
- `reference`	Unique reference identifier for the message	String
- `description`	Description of the status	String
- `msisdn`	Recipient's phone number	String

Response from third-party application

```
{
    "status": string
}
```

Field	Description	Type
`status`	Status information eg. Ok	String