Information and Coding Theory

University of Chinese Academy of Sciences Fall 2023

Kewei Lv, Liping Wang

Homework 1019

Chenkai GUO

2023.10.22

1. 第一题

(1) 由题可得:
$$\bar{D} = E[d(x_i, x_i)] = p \cdot 0 \cdot 1 + (1-p) \cdot p \cdot 1 + (1-p) \cdot (1-q) \cdot 0 = (1-p)q$$

(2) 当
$$D_{\min}$$
 时, $R(D)$ 取最大值,此时 $q=0,\bar{D}=0$

$$R(D)_{\text{max}} = H(X) = -p \log p - (1-p) \log(1-p)$$

(3) 当
$$D_{\text{max}}$$
 时, $R(D)$ 取最小值,此时 $q=1,\bar{D}=(1-p)$

$$R(D)_{\min} = H(Y) - H(Y|X) = 0$$

2. 第二题

$$D_{\min} = \sum_{i=1}^{2} p(x_i) \min_{j} d(x_i, x_j) = 0$$

最小允许失真度的试验信道为:
$$\begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \end{pmatrix}$$

3. 第三题

(1) 由题可得:
$$D_{\min} = \sum_{i=1}^{2} p(x_i) \min_{j=1}^{2} d(x_i, x_j) = 0$$

信道转移概率矩阵为: $\begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \end{pmatrix}$

(2) 最小允许失真度的试验信道为:
$$P_D = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \end{pmatrix}$$

$$R(D_{\min}) = H(X) = -(0.4 \log 0.4 + 0.6 \log 0.6) = 0.970$$

(3)
$$D_{\max} = \max(0.4p(y_2|x_1) + 0.2p(y_3|x_1) + 0.6p(y_1|x_2) + 0.3p(y_3|x_2)) = 1$$
,此时信

道转移概率矩阵为:
$$\begin{pmatrix} 0 & 1 & 0 \\ 1 & 0 & 0 \end{pmatrix}$$