

ETCE / IoT-Mining SS24 Exercise – 3

Published on: 29.04.2024

Deadline: 06.05.2024 – 14:00 pm

Do you have any questions? Contact us via email etce-etce@tu-clausthal.de

Task(s):

Task 1: The goal of this LCA exercise is to compare the water consumption of washing dishes: manually using a sink vs a dishwasher, to determine which consumes less.

- We (simplisticly) assume that a dishwasher at full load requires ~11 litres of water to
 perfectly clean 20 dishes, 20 glasses and 20 pieces of cutlery. We do this to obtain
 comparative results. We have further standardized the scope of this (unscientific) LCA:
 - o Functional Unit: 20 dishes, 20 glasses and 20 pieces of cutlery cleaned.
 - o Reference Flow: Amount of water consumed (in Liters)
- Your main task is to collect LCI data, and determine "How much water do you consume to perfectly clean 20 dishes, 20 glasses and 20 pieces of cutlery?" We denote this target value by X.

Steps:

- 1. Compute the *Flow Rate (f)* of your tap using a timer:
 - Grab an empty cup which has a known maximum capacity (or a graduated measuring cup). We assume this maximum capacity is *c liters*. Remember to compute this in liters and not milliliters.
 - 2. Turn on your kitchen tap until the flow of water is indicative of what you use to clean dishes. Be sure to take note of the exact position of the tap, perhaps by using a marker on your tap.
 - 3. With the tap open in this position, use a timer to determine the number of seconds (*t*) required for the cup to fill to it's maximum capacity.
 - 4. Compute the Flow Rate (f) = c / t Liters per second.





- For this exercise you will only wash dishes under running tap water, and we divide
 this system into individual unit processes; one each for washing a dish, a glass and
 an item of cutlery, For each of these unit processes, we collect data.
 - 1. Wash 1 dish, while using a timer to count how much time the water is flowing. Ensure that you use the same tap position as used when computing the flow rate, and that you measure the time in seconds.
 - 2. Repeat this process for at 2-3 dishes (possibly of different sizes and levels of dirtyness) and compute the average time required. We denote this average time by T_d .
 - 3. Repeat steps 1 and 2 for glasses and cutlery, computing T_g and T_c respectively.
 - 4. To relate the data collected to the functional unit of "20 dishes, 20 glasses and 20 pieces of cutlery cleaned", compute $X = (T_d + T_g + T_c) * 20 * f$ Liters

Submission instructions

- Document every step in the process of computing *X* and submit your results as a (single) PDF file on Moodle:
 - 1. What were the exact calculations that you used to compute your personal flow rate?
 - 2. What were the exact calculations that lead you to the values of T_d , T_q , and T_c
 - 3. What the final result of your LCI, the final value of X.
 - 4. How can you change/modify the method of manually cleaning dishes, in order to consume less water?
- **BONUS:** If you have a dishwasher, try to determine how much water it consumes for a full load.

