[7] Power - Connectors

DESIGN NOTE:
It's best to power the controller through the male connector to always have a female connector at the end of the chain.



CHASSIS
MP2
XT60PW-F
J2
2
1
MP1



CHASSIS
MP2
XT60PW-M
J3
2
1
MP1

VBAT_IN

Q12
FDMS86163P
5
1
4

Q10
FDMS86163P
5
1
4

VBAT_OUT

+VBAT

R83
100k

D23
BZT52C15

D2
SMBJ60A

R84
220k

GND

DESIGN NOTE:
Do not hot-plug when powered!

DESIGN NOTE:
Do not exceed absolute maximum ratings! Maximum input voltage is 48V (13S).

LAYOUT NOTE:
Place TVS diodes near input power connectors.

LAYOUT NOTE:
Keep sufficient clearance between power nets according to IPC-2221/IEC60664-1

Comments:	Company: ETH Robotics Club		Variant: PRELIMINARY	Git Hash: 1a83c5d
	Board Name: ETHRC Motor Controller		Project Name: BLDC Motor Controller	
Sheet Title: Power - Connectors	File Name: Power - Connectors.kicad_sch	Designer: Masiar Etemadi	Date: 2023-12-31	Revision: + (Unreleased)
Sheet Path: /Project Architecture/Power - Connectors/		Reviewer:	Size: A4	Sheet: 7 of 20